

# PACIFIC SURVEYS

## SONIC VELOCITY VARIABLE DENSITY

Job No.

15004

Company WDC EXPLORATION & WELLS

Well TW-2

Field FORD DRY LAKE

County RIVERSIDE State CA

Location:

1/4 Mile N of 10 Fwy @ Wileys Well Road  
GPS: N33o 36.748' W114o 54.485'

Other Services:  
LL3/GR  
ELOG  
DIL/DEV  
CAL

Sec.

Twp.

Rge.

Permanent Datum G.L.  
Log Measured From G.L. 0'  
Drilling Measured From G.L.

Elevation  
above perm. datum

K.B.  
D.F.  
G.L.

Date 12-04-09

Run Number ONE

Depth Driller 1835'

Depth Logger 1840'

Bottom Logged Interval 1840'

Top Log Interval 30'

Casing Driller 11" @ 40'

Casing Logger 40'

Bit Size 10.625" @ 1240'

Type Fluid in Hole BENTONITE 10" @ 1835'

Density / Viscosity NA

pH / Fluid Loss NA

Source of Sample PIT

Rm @ Meas. Temp 4.90 @ 77F

Rmf @ Meas. Temp 3.90 @ 77F

Rmc @ Meas. Temp NA

Source of Rmf / Rmc MEAS

Rm @ BHT NA

Time Circulation Stopped 4 HOURS

Time Logger on Bottom 0520 pm

Max. Recorded Temperature NA

Equipment Number PS-1

Location LA

Recorded By Ozman Trad

Witnessed By Nat Beal

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

**DOCKET**  
**09-AFC-8**

DATE 12/18/09

RECD. 12/21/09

Database File: 15004.db  
Dataset Pathname: wdc/well/run1/snc3  
Presentation Format: SLT  
Dataset Creation: Fri Dec 04 21:08:18 2009 by Log Warrior Version 6.6  
Charted by: Depth in Feet scaled 1:600

|     |                  |     |            |     |                       |      |     |                       |      |
|-----|------------------|-----|------------|-----|-----------------------|------|-----|-----------------------|------|
| 240 | DT (usec/ft)     | 40  | ITT (msec) | 500 | Variable Density 5 ft | 1600 | 500 | Variable Density 5 ft | 1600 |
| 20  | Gamma-Ray (GAPI) | 220 |            | 0   | RI 1.3 (Ohm-m)        | 25   |     |                       |      |







