

| DOCKETED | | | | | | |
|------------------|----------------------------------------|--|--|--|--|--|
| Docket Number: | 21-SPPE-01 | | | | | |
| Project Title: | CA3 Backup Generating Facility-Vantage | | | | | |
| TN #: | 240157 | | | | | |
| Document Title: | CA3DC PCC Drawing Set Rev3 - Part II | | | | | |
| Description: | N/A | | | | | |
| Filer: | Scott Galati | | | | | |
| Organization: | DayZenLLC | | | | | |
| Submitter Role: | Applicant Representative | | | | | |
| Submission Date: | 10/28/2021 10:25:36 AM | | | | | |
| Docketed Date: | 10/28/2021 | | | | | |


















| | Description | Date |
|---|-----------------------|-----------|
| 1 | ISSUED FOR 100% SD | 07-16-202 |
| 2 | ISSUED FOR 100% DD | 08-26-202 |
| D | Issued for PCC Review | 10-25-202 |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |

2590 WALSH AVENUE SANTA CLARA, CA 95051 APN: 216-28-112

ISSUED FOR PCC REVIEW

Landscape Planting Plan





CITY OF SANTA CLARA ARBORIST NOTES

I. GENERAL

- No cutting of any part of city trees, including roots, shall be done without securing approval and direct supervision from the city arborist or arborist employed by city (408-615-3080).
- 2. No cutting of any part of private trees, including roots, shall be done without direct supervision of an international society of arboriculture (ISA) certified arborist.
- 3. When construction occurs within the drip line of existing trees, contractor shall pile the soil on the side away from the tree. When this is not possible, place soil on plywood, tarp, or 4"-5" thick bed of mulch. This is to help prevent cutting into the soil surface when the backhoe or tractor blade refills the trench.
- 4. Refill open trenches quickly within hours of excavation when they occur within the drip line of existing trees. If this is not possible and the weather is hot, dry, or windy, contractor must keep root ends moist by covering them with wet burlap. If the temperature is 80°f or greater, the burlap must be inspected every hour and re-wet as necessary to maintain a constant cool moist condition. If the temperature is below 80°, the burlap must be inspected every four hours and re-wet as necessary to maintain a constant cool moist condition. Small roots can dry out and die in 10-15 minutes. Larger roots can succumb in an hour or less under unfavorable weather conditions.
- 5. When roots 2" or larger are required to be cut, shovel by hand near the roots and prune the roots with an industry-approved pruning tool. Roots that are accidentally broken should be pruned two inches from the damaged end. Crushed or torn roots are more likely to allow decay to begin. Sharply cut roots produce a flush of new roots helping the tree to recover from its injury.
- 6. Contractor shall notify the city arborist or arborist employed by city 72 hours in advance of any work requiring digging around or within the drip line of existing trees.
- 7. A clear system of flagging must be provided around trees within 20' of the proposed grading. Contractor shall secure approval of such system from the city arborist or arborist employed by city.
- 8. Materials, equipment, temporary buildings, fuels, paints and other construction items shall not be placed within the drip line of existing trees.

Page 1 of 4



CITY OF SANTA CLARA ARBORIST NOTES

9. Fence all trees to be retained to completely enclose the <u>tree protection zone</u> prior to demolition, grubbing or grading. Fencing shall be placed at the drip line of existing trees or, if possible, 1.5 times the radius of the drip line out from the trunk of the tree. A warning sign shall be prominently displayed on each fence. The sign shall be a minimum of 8.5"x11" and clearly state "warning – <u>tree protection zone</u> this fence shall not be removed without approval from the city arborist/project arborist". Fences shall be 6-foot tall chain link or

equivalent, as approved by the city arborist or arborist employed by city. Fences shall remain until all grading and construction work is completed. In addition, wrap all trees with straw waddle up to the first main branch, and then wrap snow fencing around the waddle on all trees in the construction zone to protect them from bark damage caused by the work.

- 10. No trenching shall be done within the drip line of existing trees without the approval of the city arborist or arborist employed by city. Open trenching in the root zone of a public tree is prohibited except in cases where the trenching falls outside the drip line of the tree involved. Exceptions may be allowed if, in the opinion of the city arborist or arborist employed by city, the impact of trenching on the tree will be negligible.
- 11. Any cutting of existing roots of city trees shall be done with approved light equipment under the direct supervision of the city arborist or arborist employed by city. Any cutting of existing roots of private trees shall be done with approved equipment under the direct supervision of an ISA certified arborist.
- 12. Grading should not create drainage problems for trees by channeling water into them, or creating sunken areas.
- 13. All grading within the drip line of city trees shall be done with approved light equipment under the direct supervision of the city arborist or arborist employed by city. All grading within the drip line of private trees shall be done with approved equipment under the direct supervision of an ISA certified arborist. The original grade at the base of existing trees shall not be modified. If a grade increase is necessary, dry wells should be used.
- 14. When trenching is allowed, the contractor must first cut roots with a vermeer root cutter prior to any trenching to avoid tugging or pulling of roots.
- 15. Trees that are determined to be removed by the city arborist or arborist employed by city due to an unforeseen circumstance during construction shall be replaced by the

Page 2 of 4



CITY OF SANTA CLARA ARBORIST NOTES

contractor. The city arborist or arborist employed by city shall determine the replacement specie, size, quantity, and spacing.

- 16. Place 4"-5" thick mulch around all existing trees (out to their drip line) that are to be retained prior to any construction. This will help maintain moisture under the tree within the fencing area.
- 17. Bore pits are not allowed within the drip line of any tree.

II. BORING

Where there is insufficient space to bypass the drip line by trenching adjacent to all existing trees in excess of 5" DBH, the installation must be made by boring. The beginning and ending distance of the bore from the face of the tree in any direction is determined by the diameter of the tree as specified by the accompanying table:

| When the tree dia | meter at 4⅓ feet is: | Trenching will be replaced by boring at this minimum distance from the face of the tree in any direction: | | |
|-------------------|----------------------|-----------------------------------------------------------------------------------------------------------------|------|--|
| 0-2 | inches | 1 | foot | |
| 3-4 | inches | 2 | feet | |
| 6-9 | inches | 5 | feet | |
| 10-14 | inches | 10 | feet | |
| 15-19 | inches | 12 | feet | |
| over 19 | inches | 15 | feet | |

| Tree diameter | (minimum) depth of bore |
|-------------------|-------------------------|
| 9 inches or less | 2.5 feet |
| 10-14 inches | 3.0 feet |
| 15-19 inches | 3.5 feet |
| 20 inches or more | 4.0 feet |

III.TREE PROTECTION

Contractor shall tag and identify existing trees which are to remain within the
project limits and on the public right-of-way prior to start of work. Protect all tagged
trees at all times from damage by the work. Treatment of all minor damage to tagged
trees shall be performed by an ISA certified arborist or other personnel approved by
the city arborist or arborist employed by city. If a tagged tree is permanently

Page 3 of 4




CITY OF SANTA CLARA ARBORIST NOTES


disfigured or killed as a result of the work, contractor shall remove the tree, including its roots, from the site and replace each removed tree with an equal-sized tree. If such replacement is not possible, the contractor shall reimburse to the tree owner the amount listed in the table below. The city arborist or arborist employed by city shall be the sole judge of the condition of any tree. Contractor shall provide regular watering of existing landscaping within the construction area through the construction period.

2. Contractor shall pay the tree owner the value of existing trees to remain that died or were damaged because of the contractor's failure to provide adequate protection and maintenance. The payment amount shall be in accordance with the following schedule of values, using "tree caliper" method established in the most recent issue of the "guide for establishing values of trees and other plants", prepared by the council of tree and landscape architects.

| 7 | inches | \$ 2,400 | |
|-----------|-------------------|-----------|--|
| 8 | inches | \$ 3,400 | |
| 9 | inches | \$ 4,400 | |
| 10 | inches | \$ 5,200 | |
| 11 | inches | \$ 6,200 | |
| 12 | inches | \$ 7,200 | |
| 13 | inches | \$ 8,200 | |
| 14 | inches | \$ 9,200 | |
| 15 | inches | \$ 10,000 | |
| 16 | inches | \$ 11,000 | |
| 17 | inches | \$ 12,000 | |
| 18 inc | hes and over: | | |
| Add for e | each caliper inch | \$ 1,200 | |

Page 4 of 4





TREE PROTECTION FENCE

TREE PROTECTION NOTES

PROTECT EXISTING TREES SHOWN ON PLAN TO REMAIN BY FOLLOWING THESE INSTRUCTIONS.

- I. THE GRADE BETWEEN THE DRIPLINE AND ROOT CROWN OF THE TREES SHALL NOT BE CUT AND CAN BE FILLED BY ONLY 3 INCHES, EXCEPT WITHIN 5'-O" OF THE TRUNK WHERE THE GRADE SHALL NOT BE DISTURBED.
- 2. IRRIGATION AND RAIN WATER SHALL BE ABLE TO DRAIN AWAY FROM THE ROOT CROWN OF THE TREES.
- 3. DO NOT DRIVE OR PARK VEHICLES WITH IN THE DRIPLINE AREA OF THE TREES UNLESS NECESSARY TO DO PAVING CONSTRUCTION. IF THERE HAS BEEN ANY VEHICULAR TRAFFIC WITHIN THE DRIPLINE, THE GROUND SHALL BE SCARIFIED BY HAND TO A DEPTH OF 12 INCHES TO DE-COMPACT.
- 4. DO NOT ALLOW CONTRACTORS TO DUMP WASTE CONCRETE, PLASTER, ETC. UNDER DRIPLINE OF TREES. DO NOT ALLOW PAINTERS OR OTHER TO CLEAN EQUIPMENT UNDER DRIPLIN OR UPHILL OF EXISTING TREES WHERE NATURAL DRAINAGE WOULD CAUSE WASTE TO RUN WITHIN DRIPLINE. DO NOT ALLOW ANY WASTE TO BE DUMPED IN SOIL ON SITE.
- 5. TREES SHALL NOT BE PRUNED WITHOUT THE WRITTEN PERMISSION OF THE LANDSCAPE ARCHITECT OR ARBORIST.
- 6. IF IT IS NECESSARY TO PRUNE OR CUT ANY ROOTS LARGER THAT I INCH IN DIAMETER, THE ROOTS SHALL BE CUT CLEANLY AND ROOT SEALED. WHERE EXCAVATION IS REQUIRED AROUND TREES (FOR WALL, PAVING, ETC.) THE REPLACED SOIL SHALL BE 1/3 SOIL AMENDMENT AND 1/3 NATIVE SOIL.
- 7. NO IRRIGATION SHALL BE INSTALLED WITHIN 5'-O" OF THE TRUNK. NO SPRAY SHALL HIT THE TRUNKS OF TREES. ALL TRENCHING WITHIN THE DRIPLINE WILL BE DONE BY HAND. ALL PIPING SHALL RUN PERPENDICULAR TO THE TRUNK WITHIN THE DRIPLINE EXCEPT AT FACE OF CURB, PLANTER OR PAVING.

OWNER



ARCHITECT
SHEEHAN
NAGLE
HARTRAY

ARCHITECTS

SHEEHAN NAGLE HARTRAY ARCHITECTS 130EastRandolph Street, Suite 3100 CHICAGO, IL 60601 MEP ENGINEER





STRUCTURAL ENGINEER

CIVIL ENGINEER





PRORESTRUCTION PROPERTY OF THE PROPERTY OF THE

| 2 1 No. | Issued for PCC Review ISSUED FOR 100% DD ISSUED FOR 100% SD Description | 10-25-202 08-26-202 07-16-202 |
|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|
| 2 | ISSUED FOR 100% DD | |
| U | Issued for PCC Review | 10-25-20 |
| D | | |
| | | |
| | | |
| | T. Control of the Con | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |

VANTAGE CA31

2590 WALSH AVENUE SANTA CLARA, CA 95051 APN: 216-28-112

ISSUED FOR PCC REVIEW

Existing Tree Protection Notes and Details

L1.2

SCALE: AS NOTED

© 2018 SHEEHAN NAGLE HARTRAY ARCHITECTS, LTD.

5

Exhibit 2 - 2590 Walsh Avenue Inventory Matrix

| Tag# | Botanical Name | Common Name | DBH (inches) | Health Rating | Structure Rating | Condition | Disposition | Suitability f Preservation |
|------|-------------------------|-----------------|--------------|---------------|------------------|-----------|-------------|-------------------------------|
| 1 | Fraxinus uhdei | Evergreen Ash | 2 | Excellent | Excellent | Excellent | Preserve | High |
| 2 | Fraxinus uhdei | Evergreen Ash | 2 | Excellent | Excellent | Excellent | Preserve | High |
| 3 | Fraxinus uhdei | Evergreen Ash | 2 | Excellent | Excellent | Excellent | Preserve | High |
| 4 | Fraxinus uhdei | Evergreen Ash | 2 | Excellent | Excellent | Excellent | Preserve | High |
| 5 | Fraxinus uhdei | Evergreen Ash | 2 | Excellent | Excellent | Excellent | Preserve | High |
| 6 | Fraxinus uhdei | Evergreen Ash | 2 | Excellent | Excellent | Excellent | Preserve | High |
| 7 | Fraxinus uhdei | Evergreen Ash | 34 | Fair | Fair | Fair | Preserve | Moderat |
| 8 | Fraxinus uhdei | Evergreen Ash | 34 | Fair | Fair | Fair | Preserve | Moderat |
| 9 | Fraxinus uhdei | Evergreen Ash | 2 | Excellent | Excellent | Excellent | Preserve | High |
| 10 | Fraxinus uhdei | Evergreen Ash | 2 | Excellent | Excellent | Excellent | Preserve | High |
| 11 | Fraxinus uhdei | Evergreen Ash | 2 | Excellent | Excellent | Excellent | Preserve | High |
| 12 | Fraxinus uhdei | Evergreen Ash | 2 | Excellent | Excellent | Excellent | Preserve | High |
| 13 | Sequoia sempervirens | Coastal Redwood | 28 | Excellent | Excellent | Excellent | Preserve | High |
| 14 | Sequoia sempervirens | Coastal Redwood | 30 | Excellent | Excellent | Excellent | Preserve | High |
| 19 | Liquidambar styraciflua | Sweetgum | 28 | Good | Good | Good | Preserve | Modera |
| 20 | Liquidambar styraciflua | Sweetgum | 24 | Good | Fair | Good | Preserve | Modera |
| 21 | Sequoia sempervirens | Coastal Redwood | 24 | Excellent | Excellent | Excellent | Preserve | High |
| 22 | Liriodendron tulipifera | Tulip Tree | 28 | Excellent | Excellent | Excellent | Preserve | High |
| 23 | Sequoia sempervirens | Coastal Redwood | 40 | Excellent | Excellent | Excellent | Preserve | High |
| 24 | Sequoia sempervirens | Coastal Redwood | 14 | Excellent | Excellent | Excellent | Preserve | High |
| 25 | Liriodendron tulipifera | Tulip Tree | 26 | Excellent | Good | Excellent | Preserve | High |
| 26 | Liriodendron tulipifera | Tulip Tree | 26 | Excellent | Good | Excellent | Preserve | High |
| 27 | Liquidambar styraciflua | Sweetgum | 12 | Good | Fair | Good | Preserve | Modera |

| Tag# | Botanical Name | Common Name | DBH (inches) | Health Rating | Structure Rating | Condition | Disposition | Suitability for |
|------|-------------------------|-----------------|--------------|---------------|------------------|-----------|---------------------------------------|-----------------|
| 28 | Liquidambar styraciflua | Sweetgum | 13 | Good | Fair | Good | Preserve | Moderate |
| 29 | Liriodendron tulipifera | Tulip Tree | 10 | Fair | Good | Fair | Remove Based On Conflicts With Layout | Moderate |
| 30 | Liriodendron tulipifera | Tulip Tree | 10 | Fair | Good | Fair | Remove Based On Conflicts With Layout | Moderate |
| 31 | Sequoia sempervirens | Coastal Redwood | 40 | Excellent | Excellent | Excellent | Remove Based On Conflicts With Layout | High |
| 32 | Sequoia sempervirens | Coastal Redwood | 40 | Excellent | Excellent | Excellent | Remove Based On Conflicts With Layout | High |
| 33 | Sequoia sempervirens | Coastal Redwood | 40 | Excellent | Excellent | Excellent | Remove Based On Conflicts With Layout | High |
| 34 | Sequoia sempervirens | Coastal Redwood | 40 | Excellent | Excellent | Excellent | Remove Based On Conflicts With Layout | High |
| 35 | Liquidambar styraciflua | Sweetgum | 10 | Good | Fair | Good | Remove Based On Conflicts With Layout | Moderate |
| 36 | Sequoia sempervirens | Coastal Redwood | 40 | Excellent | Excellent | Excellent | Remove Based On Conflicts With Layout | High |
| 37 | Sequoia sempervirens | Coastal Redwood | 40 | Excellent | Excellent | Excellent | Remove Based On Conflicts With Layout | High |
| 38 | Sequoia sempervirens | Coastal Redwood | 40 | Excellent | Excellent | Excellent | Remove Based On Conflicts With Layout | High |
| 39 | Liquidambar styraciflua | Sweetgum | 10 | Good | Fair | Good | Remove Based On Conflicts With Layout | Moderate |
| 40 | Sequoia sempervirens | Coastal Redwood | 26 | Excellent | Excellent | Excellent | Preserve | High |
| 41 | Sequoia sempervirens | Coastal Redwood | 30 | Excellent | Excellent | Excellent | Preserve | High |
| 42 | Fraxinus uhdei | Evergreen Ash | 26 | Fair | Fair | Fair | Preserve | Moderate |
| 43 | Fraxinus uhdei | Evergreen Ash | 26 | Fair | Fair | Fair | Preserve | Moderate |
| 44 | Fraxinus uhdei | Evergreen Ash | 26 | Fair | Fair | Fair | Preserve | Moderate |
| 45 | Fraxinus uhdei | Evergreen Ash | 26 | Fair | Fair | Fair | Preserve | Moderate |
| 46 | Fraxinus uhdei | Evergreen Ash | 26 | Fair | Fair | Fair | Preserve | Moderate |
| 48 | Fraxinus uhdei | Evergreen Ash | 26 | Fair | Fair | Fair | Preserve | Moderate |
| 49 | Fraxinus uhdei | Evergreen Ash | 26 | Fair | Fair | Fair | Preserve | Moderate |
| 50 | Fraxinus uhdei | Evergreen Ash | 26 | Fair | Fair | Fair | Preserve | Moderate |
| 51 | Fraxinus uhdei | Evergreen Ash | 26 | Fair | Fair | Fair | Preserve | Moderate |
| 52 | Fraxinus uhdei | Evergreen Ash | 26 | Fair | Fair | Fair | Preserve | Moderate |

| | | | | | | | | professional tree manager |
|-------|-------------------------|-----------------|--------------|---------------|------------------|-----------|---------------------------------------|---------------------------------|
| Tag # | Botanical Name | Common Name | DBH (inches) | Health Rating | Structure Rating | Condition | Disposition | Suitability for Preservation |
| 53 | Sequoia sempervirens | Coastal Redwood | 18 | Excellent | Excellent | Excellent | Preserve | High |
| 54 | Sequoia sempervirens | Coastal Redwood | 14 | Excellent | Excellent | Excellent | Preserve | High |
| 55 | Sequoia sempervirens | Coastal Redwood | 18 | Excellent | Excellent | Excellent | Preserve | High |
| 59 | Pyrus kawakamii | Evergreen Pear | 14 | Good | Good | Good | Remove Based On Conflicts With Layout | Moderate |
| 60 | Pyrus kawakamii | Evergreen Pear | 14 | Dead | Dead | Dead | Remove Based On Conflicts With Layout | Low |
| 61 | Ceratonia siliqua | Carob | 6 | Good | Good | Good | Remove Based On Conflicts With Layout | Low |
| 62 | Ceratonia siliqua | Carob | 12 | Poor | Poor | Poor | Remove Based On Conflicts With Layout | Low |
| 63 | Sequoia sempervirens | Coastal Redwood | 36 | Good | Excellent | Good | Remove Based On Conflicts With Layout | High |
| 64 | Sequoia sempervirens | Coastal Redwood | 34 | Good | Excellent | Good | Remove Based On Conflicts With Layout | High |
| 65 | Sequoia sempervirens | Coastal Redwood | 30 | Good | Excellent | Good | Remove Based On Conflicts With Layout | High |
| 66 | Liquidambar styraciflua | Sweetgum | 10 | Good | Good | Good | Remove Based On Conflicts With Layout | Moderate |
| 67 | Liquidambar styraciflua | Sweetgum | 6 | Good | Good | Good | Remove Based On Conflicts With Layout | Moderate |
| 69 | Liquidambar styraciflua | Sweetgum | 10 | Good | Good | Good | Remove Based On Conflicts With Layout | Moderate |
| 70 | Liquidambar styraciflua | Sweetgum | 6 | Good | Good | Good | Remove Based On Conflicts With Layout | Moderate |
| 71 | Liquidambar styraciflua | Sweetgum | 8 | Good | Good | Good | Remove Based On Conflicts With Layout | Moderate |
| 72 | Liquidambar styraciflua | Sweetgum | 12 | Good | Good | Good | Remove Based On Conflicts With Layout | Moderate |
| 73 | Liquidambar styraciflua | Sweetgum | 12 | Good | Good | Good | Remove Based On Conflicts With Layout | Moderate |
| 74 | Liquidambar styraciflua | Sweetgum | 14 | Good | Good | Good | Remove Based On Conflicts With Layout | Moderate |
| 75 | Liquidambar styraciflua | Sweetgum | 8 | Good | Good | Good | Remove Based On Conflicts With Layout | Moderate |
| 76 | Liquidambar styraciflua | Sweetgum | 12 | Good | Good | Good | Remove Based On Conflicts With Layout | Moderate |
| 77 | Sequoia sempervirens | Coastal Redwood | 36 | Good | Excellent | Good | Remove Based On Conflicts With Layout | High |
| 78 | Sequoia sempervirens | Coastal Redwood | 36 | Good | Excellent | Good | Remove Based On Conflicts With Layout | High |
| 79 | Sequoia sempervirens | Coastal Redwood | 34 | Good | Excellent | Good | Remove Based On Conflicts With Layout | High |
| 80 | Sequoia sempervirens | Coastal Redwood | 36 | Good | Excellent | Good | Remove Based On Conflicts With Layout | High |

| Suitability for Preservation | Disposition | Condition | Structure Rating | Health Rating | DBH (inches) | Common Name | Botanical Name | Tag# |
|---------------------------------|---------------------------------------|-----------|------------------|---------------|--------------|------------------|-------------------------|------|
| Low | Remove Based On Conflicts With Layout | Fair | Fair | Fair | 20 | Carob | Ceratonia siliqua | 82 |
| Low | Remove Based On Conflicts With Layout | Fair | Fair | Fair | 8 | Sweetgum | Liquidambar styraciflua | 84 |
| Low | Remove Based On Conflicts With Layout | Fair | Fair | Fair | 8 | Sweetgum | Liquidambar styraciflua | 86 |
| Low | Remove Based On Conflicts With Layout | Fair | Fair | Fair | 8 | Sweetgum | Liquidambar styraciflua | 87 |
| Moderate | Remove Based On Conflicts With Layout | Good | Good | Good | 12 | Tulip Tree | Liriodendron tulipifera | 88 |
| Moderate | Remove Based On Conflicts With Layout | Good | Good | Good | 12 | Tulip Tree | Liriodendron tulipifera | 89 |
| High | Remove Based On Conflicts With Layout | Excellent | Excellent | Excellent | 32 | Coastal Redwood | Sequoia sempervirens | 90 |
| High | Remove Based On Conflicts With Layout | Excellent | Excellent | Excellent | 14 | Coastal Redwood | Sequoia sempervirens | 91 |
| High | Remove Based On Conflicts With Layout | Excellent | Excellent | Excellent | 28 | Coastal Redwood | Sequoia sempervirens | 91 |
| High | Remove Based On Conflicts With Layout | Excellent | Excellent | Excellent | 30 | Coastal Redwood | Sequoia sempervirens | 92 |
| Low | Remove Based On Conflicts With Layout | Fair | Fair | Fair | 8 | Purpleleaf Plum | Prunus cerasifera | 95 |
| High | Preserve | Excellent | Excellent | Excellent | 12 | Coastal Redwood | Sequoia sempervirens | 96 |
| High | Preserve | Excellent | Excellent | Excellent | 8 | Coastal Redwood | Sequoia sempervirens | 97 |
| High | Remove Based On Conflicts With Layout | Excellent | Excellent | Excellent | 14 | Coastal Redwood | Sequoia sempervirens | 98 |
| High | Remove Based On Conflicts With Layout | Excellent | Excellent | Excellent | 14 | Coastal Redwood | Sequoia sempervirens | 99 |
| High | Remove Based On Conflicts With Layout | Excellent | Excellent | Excellent | 16 | Coastal Redwood | Sequoia sempervirens | 100 |
| High | Remove Based On Conflicts With Layout | Good | Excellent | Good | 14 | Coastal Redwood | Sequoia sempervirens | 101 |
| High | Remove Based On Conflicts With Layout | Excellent | Good | Excellent | 28 | Coastal Redwood | Sequoia sempervirens | 102 |
| High | Remove Based On Conflicts With Layout | Excellent | Excellent | Excellent | 32 | Coastal Redwood | Sequoia sempervirens | 103 |
| High | Remove Based On Conflicts With Layout | Excellent | Excellent | Excellent | 20 | Blackwood Acacia | Sequoia sempervirens | 104 |
| High | Remove Based On Conflicts With Layout | Excellent | Excellent | Excellent | 32 | Coastal Redwood | Sequoia sempervirens | 105 |
| High | Remove Based On Conflicts With Layout | Excellent | Excellent | Excellent | 32 | Coastal Redwood | Sequoia sempervirens | 106 |
| High | Remove Based On Conflicts With Lavout | Evcellent | Evcellent | Evcellent | 36 | Coastal Redwood | Seguaia sempervirens | 107 |

| Suitability for Preservation | Disposition | Condition | Structure Rating | Health Rating | DBH (inches) | Common Name | Botanical Name | Tag# |
|---------------------------------|---------------------------------------|-----------|------------------|---------------|--------------|-----------------|-------------------------|------|
| Hìgh | Remove Based On Conflicts With Layout | Excellent | Excellent | Excellent | 13 | Evergreen Pear | Pyrus kawakamii | 109 |
| High | Remove Based On Conflicts With Layout | Excellent | Excellent | Excellent | 4 | Crapemyrtle | Lagerstroemia indica | 110 |
| Hìgh | Remove Based On Conflicts With Layout | Excellent | Excellent | Excellent | 4 | Crapemyrtle | Lagerstroemia indica | 111 |
| High | Remove Based On Conflicts With Layout | Excellent | Excellent | Excellent | 4 | Crapemyrtle | Lagerstroemia indica | 112 |
| Moderate | Remove Based On Conflicts With Layout | Good | Fair | Good | 10 | Sweetgum | Liquidambar styraciflua | 113 |
| High | Preserve | Excellent | Excellent | Excellent | 6 | Coastal Redwood | Sequoia sempervirens | 114 |
| Moderate | Remove Based On Conflicts With Layout | Good | Good | Good | 6 | Tulip Tree | Liriodendron tulipifera | 115 |
| Low | Remove Based On Conflicts With Layout | Fair | Fair | Fair | 2 | Laurel | Laurus noblis | 116 |
| High | Remove Based On Conflicts With Layout | Excellent | Excellent | Excellent | 18 | Coastal Redwood | Sequoia sempervirens | 120 |
| Low | Remove Based On Condition | Poor | Poor | Poor | 36 | Monterey Pine | Pinus Radiata | 1113 |
| Low | Remove Based On Condition | Dead | Dead | Dead | 36 | Monterey Pine | Pinus Radiata | 1114 |
| Low | Remove Based On Condition | Poor | Poor | Poor | 24 | Black Walnut | Juglan nigra | 1115 |
| Low | Remove Based On Condition | Dead | Dead | Dead | 36 | Monterey Pine | Pinus Radiata | 1116 |



ARCHITECT SHEEHAN NAGLE HARTRAY ARCHITECTS

SHEEHAN NAGLE HARTRAY ARCHITECTS 130East Randolph Street, Suite 3100 CHICAGO, IL 60601 MEP ENGINEER





STRUCTURAL ENGINEER

PEOPLES ASSOCIATES STRUCTURAL ENGINEERS 408-957-9220 • www.pase.com San Jose, California Pleasanton, California

CIVIL ENGINEER





| No. | Description | Date |
|-----|-----------------------|-----------|
| 1 | ISSUED FOR 100% SD | 07-16-202 |
| 2 | ISSUED FOR 100% DD | 08-26-202 |
| D | Issued for PCC Review | 10-25-202 |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |


VANTAGE CA31


2590 WALSH AVENUE SANTA CLARA, CA 95051 APN: 216-28-112

ISSUED FOR PCC REVIEW

Existing Tree Inventory List

| 87 | Liquidambar styraciflua | Sweetgum | 8 | Fair | Fair | Fair | Remove Based On Conflicts With Layout | Low |
|-----|-------------------------|------------------|----|-----------|-----------|-----------|---------------------------------------|----------|
| 88 | Liriodendron tulipifera | Tulip Tree | 12 | Good | Good | Good | Remove Based On Conflicts With Layout | Moderate |
| 89 | Liriodendron tulipifera | Tulip Tree | 12 | Good | Good | Good | Remove Based On Conflicts With Layout | Moderate |
| 90 | Sequoia sempervirens | Coastal Redwood | 32 | Excellent | Excellent | Excellent | Remove Based On Conflicts With Layout | High |
| 91 | Sequoia sempervirens | Coastal Redwood | 14 | Excellent | Excellent | Excellent | Remove Based On Conflicts With Layout | High |
| 91 | Sequoia sempervirens | Coastal Redwood | 28 | Excellent | Excellent | Excellent | Remove Based On Conflicts With Layout | High |
| 92 | Sequoia sempervirens | Coastal Redwood | 30 | Excellent | Excellent | Excellent | Remove Based On Conflicts With Layout | High |
| 95 | Prunus cerasifera | Purpleleaf Plum | 8 | Fair | Fair | Fair | Remove Based On Conflicts With Layout | Low |
| 96 | Sequoia sempervirens | Coastal Redwood | 12 | Excellent | Excellent | Excellent | Preserve | High |
| 97 | Sequoia sempervirens | Coastal Redwood | 8 | Excellent | Excellent | Excellent | Preserve | High |
| 98 | Sequoia sempervirens | Coastal Redwood | 14 | Excellent | Excellent | Excellent | Remove Based On Conflicts With Layout | High |
| 99 | Sequoia sempervirens | Coastal Redwood | 14 | Excellent | Excellent | Excellent | Remove Based On Conflicts With Layout | High |
| 100 | Sequoia sempervirens | Coastal Redwood | 16 | Excellent | Excellent | Excellent | Remove Based On Conflicts With Layout | High |
| 101 | Sequoia sempervirens | Coastal Redwood | 14 | Good | Excellent | Good | Remove Based On Conflicts With Layout | High |
| 102 | Sequoia sempervirens | Coastal Redwood | 28 | Excellent | Good | Excellent | Remove Based On Conflicts With Layout | High |
| 103 | Sequoia sempervirens | Coastal Redwood | 32 | Excellent | Excellent | Excellent | Remove Based On Conflicts With Layout | High |
| 104 | Sequoia sempervirens | Blackwood Acacia | 20 | Excellent | Excellent | Excellent | Remove Based On Conflicts With Layout | High |
| 105 | Sequoia sempervirens | Coastal Redwood | 32 | Excellent | Excellent | Excellent | Remove Based On Conflicts With Layout | High |
| 106 | Sequoia sempervirens | Coastal Redwood | 32 | Excellent | Excellent | Excellent | Remove Based On Conflicts With Layout | High |
| 107 | Sequoia sempervirens | Coastal Redwood | 36 | Excellent | Excellent | Excellent | Remove Based On Conflicts With Layout | High |
| 108 | Sequoia sempervirens | Coastal Redwood | 38 | Excellent | Excellent | Excellent | Remove Based On Conflicts With Layout | High |





OWNER



SHEEHAN
NAGLE
HARTRAY
ARCHITECTS

SHEEHAN NAGLE HARTRAY ARCHITECTS 130EastRandolph Street, Suite 3100 CHICAGO, IL 60601 MEP ENGINEER






STRUCTURAL ENGINEER



CIVIL ENGINEER





PRORES SELICITION PROCESSIVATION PROPERTY OF THE PROPERTY OF T

| No. | Description | D |
|-----|--------------------|----------|
| 1 | ISSUED FOR 100% SD | 07-16-20 |
| 2 | ISSUED FOR 100% DD | 08-26- |
| | SITE UPDATES | 10-04- |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |

VANTAGE CA31


2590 WALSH AVENUE SANTA CLARA, CA 95051 APN : 216-28-112

ISSUED FOR 100% DD

Landscape Construction Details

L3.0

SCALE: AS NOTED



SHEEHAN NAGLE HARTRAY **ARCHITECTS** SHEEHAN NAGLE HARTRAY ARCHITECTS 130 East Randolph Street, Suite 3100 CHICAGO, IL 60601 MEP ENGINEER Industries Union City, CA 94587 510.477.3300 STRUCTURAL ENGINEER San Jose, California CIVIL ENGINEER 1570 Oakland Road San Jose, CA 95131 HMHca.com REED ASSOCIATES
LANDSCAPE ARCHITECTURE
477 SOUTH TAAFFE STREET
SUNNYVALE, CALIFORNIA 94086
P II ON E: 408.481.9020

SITE UPDATES 10-04-2021
2 ISSUED FOR 100% DD 08-26-2021
1 ISSUED FOR 100% SD 07-16-2021
No. Description Date

VANTAGE CA31


2590 WALSH AVENUE SANTA CLARA, CA 95051 APN : 216-28-112

ISSUED FOR 100% DD

Landscape Construction Details

L3.1

SCALE: AS NOTED



SHEEHAN **NAGLE HARTRAY**








STRUCTURAL ENGINEER



CIVIL ENGINEER







| No. | Description | Da |
|-----|--------------------|-----------|
| 1 | ISSUED FOR 100% SD | 07-16-202 |
| 2 | ISSUED FOR 100% DD | 08-26-2 |
| | SITE UPDATES | 10-04-2 |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |

VANTAGE CA31

2590 WALSH AVENUE SANTA CLARA, CA 95051 APN: 216-28-112

ISSUED FOR 100% DD

Landscape Construction Details

© 2018 SHEEHAN NAGLE HARTRAY ARCHITECTS, LTD.

C. CONTROL WIRE LANDSCAPE SPECIFICATIONS 1.4 WARRANTY 1. DIRECT BURIAL REMOTE CONTROL WIRES, U.L. APPROVED TYPE U.F. MINIMUM OF 4/64 INCH VINYL INSULATION. CONSULT VALVE MANUFACTURER'S CURRENT WIRE SIZING F. IRON SULFATE: STANDARD COMMERCIAL BRAND. FURNISH OWNER WITH GUARANTEE THAT IRRIGATION SPRINKLER SYSTEM IS FREE FROM DEFECTS IN MATERIALS AND WORKMANSHIP, AND THE WORK HAS BEEN COMPLETED IN ACCORDANCE WITH THE ACCORDANCE AND SPECIFICATIONS, ORDINARY WEAR AND TEAR, UNUSUAL IRRIGATION SPRINKLER SYSTEM AND LANDSCAPE PLANTING C. WOOD CHIP MULCH 2. COMMON RETURN WIRE = WHITE, PILOT WIRE = RED, ORANGE, OR BLACK. 1.0 GENERAL ALL PLANTED AREAS, EXCEPT TURF, SHALL RECEIVE A TOP DRESSING OF MULCH CONSISTING OF RECYCLED, NON-DYED WOOD CHIPS OR FIR CHIPS, MEDIAN GRIND 3/8 TO TO 3/4" DIAMETER AT 3 INCH DEPTH. SHREDDED BARK IS UNACCEPTABLE. 3. MAKE SPLICES WITH "SCOTCH LOK" NO. 3577 CONNECTOR SEALING PACKS, OR A. THE WORK INCLUDES LABOR, MATERIALS, AND EQUIPMENT REQUIRED TO COMPLETE WORK INDICATED IN DRAWINGS AND DESCRIBED IN SPECIFICATIONS. PROVIDE GUARANTEE FOR REPAIR OR REPLACEMENT OF DEFECTS IN MATERIAL OR WORKMANSHIP, SETTLING OF BACKFILLED TRENCHES, AND TO REPAIR OR REPLACE DAMAGE RESULTING FROM THE REPAIRS OR REPLACEMENTS OF DEFECTS WITHOUT ADDITIONAL COST TO D. SPRINKLER HEADS, REMOTE CONTROL VALVES, AUTOMATIC CONTROLLER, QUICK COUPLER | D. PLANT MATERIAL 1. PERFORM WORK IN ACCORDANCE WITH BEST STANDARDS OF PRACTICE RELATING TO VARIOUS TRADES, AND UNDER CONTINUOUS SUPERVISION OF A COMPONENT FOREMAN 1. TYPE, SIZE, AND LOCATION INDICATED IN DRAWINGS. CONFORM PLANT MATERIAL, INDICATED IN DRAWINGS BY THE LISTED NAMES, TO "STANDARD PLANT NAMES", SECOND EDITION. EXCEPT FOR NAMES NOT INCLUDED, FOLLOW THE ESTABLISHED CUSTOMS OF THE NURSERY TRADE. MAKE REPAIRS OR REPLACEMENTS, INCLUDING COMPLETE RESTORATION OF DAMAGED PLANTING, PAVING, OR OTHER IMPROVEMENTS OF ANY KIND, WITHIN A REASONABLE TIME CAPABLE OF INTERPRETING DRAWINGS AND SPECIFICATIONS. 2. LOCATE REMOTE CONTROL VALVES AND QUICK COUPLERS A MAXIMUM OF 12 INCHES FROM CURB, WALK, OR HEADERBOARD. B. PRIOR TO CONSTRUCTION, VERIFY THAT CONTRACT DOCUMENTS REFLECT LATEST REVISIONS, 2. ALL PLANTS SHALL BE TRUE TO NAME. TAG ONE OF EACH BUNDLE OR LOT WITH THE NAME AND SIZE OF THE PLANT, IN ACCORDANCE WITH STANDARDS OF PRACTICE IN THE EVENT OF FAILURE BY CONTRACTOR TO MAKE REPAIRS OR REPLACEMENTS WITHIN A TEN DAYS AFTER RECEIPT OF WRITTEN NOTICE, REPAIRS OR REPLACEMENTS WILL BE MADE BY OTHERS AT THE EXPENSE OF SUB-CONTRACTOR. E. BACKFLOW PREVENTION CONSTRUCT IRRIGATION SYSTEM USING MATERIAL AND METHODS CONFORMING TO APPLICABLE PROVISIONS OF UNIFORM PLUMBING CODE, PUBLISHED BY WESTERN PLUMBING OFFICIALS ASSOCIATION, NATIONAL ELECTRICAL CODE, AND OTHER CODES PROPERLY GOVERNING THESE ACTIVITIES AT THE LOCATION OF THE WORK. RECOMMENDED BY AMERICAN ASSOCIATION OF NURSERYMEN. 1. BACKFLOW PREVENTERS AS INDICATED IN DRAWINGS OR AS APPROVED BY LOCAL 3. ALL PLANT MATERIALS SHALL MEET THE SPECIFICATIONS OF FEDERAL, STATE, AND GOVERNING BODY. WARRANTY PERIOD FOR IRRIGATION SPRINKLER SYSTEM, 1 YEAR FROM DATE OF ACCEPTANCE COUNTY LAWS, REQUIRING INSPECTION FOR PLANT DISEASES AND INSECT INFESTATIONS. BY OWNER. 2. DO NOT LOCATE IN LAWN AREAS. 1. VERIFY LOCATIONS OF EXISTING UTILITIES WHETHER OR NOT SHOWN IN DRAWINGS. ASSUME RESPONSIBILITY FOR THEIR PROTECTION. 4. PLANTS SHALL BE SYMMETRICAL, TYPICAL FOR VARIETY AND SPECIES, SOUND, HEALTHY, VIGOROUS, FREE FROM PLANT DISEASES, INSECT PESTS, OR OTHER EGGS, WITH HEALTHY, NORMAL ROOT SYSTEMS, WELL FILLING THEIR CONTAINERS, BUT NOT TO THE 1.5 LANDSCAPE MAINTENANCE AND GUARANTEE 3. SCREEN UNIT WITH PLANT MATERIAL SHOWN ON PLANTING PLAN IN LOCATION OF BACKFLOW PREVENTER OR ELSEWHERE ON SITE WHEN DIRECTED BY LANDSCAPE D. THE CONTRACT DOCUMENTS ARE NOT INTENDED TO CONFLICT WITH REQUIREMENTS OF GOVERNING ORDINANCES. WHEN DRAWINGS AND SPECIFICATIONS DESCRIBE MATERIALS, WORKMANSHIP, OR CONSTRUCTION OF BETTER QUALITY, HIGHER STANDARD, PROVISIONS OF DRAWINGS AND SPECIFICATIONS TAKE PRECEDENCE. A. PROVIDE MAINTENANCE FOR PLANTING AND IRRIGATION FOR 60 CALENDAR DAYS AFTER STAGE 4. AVOID USING PVC PIPING IN BACKFLOW PREVENTER ASSEMBLIES. 5. USE ONLY PLANT MATERIALS THAT ARE FIRST CLASS REPRESENTATIVE OF THE SPECIES AND CULTIVARS SPECIFIED AND THAT CONFORM TO ALL STATE AND LOCAL LAWS GOVERNING THE SALE, TRANSPORTATION, AND INSPECTION OF PLANT MATERIALS. . WORK INCLUDES, BUT IS NOT LIMITED TO, WATERING, WEEDING, MOWING, FERTILIZING, CULTIVATING, SPRAYING, CUTTING, AND PRUNING NECESSARY TO KEEP PLANTS IN A HEALTHY GROWING CONDITION, AND TO KEEP PLANTED AREAS NEAT AND ATTRACTIVE F. VALVE BOXES E. OBTAIN AND PAY FOR PERMITS AND INSPECTIONS REQUIRED FOR THE WORK. 1. CONTROL VALVE BOXES, AMETEK NO. 10-70-00 WITH GREEN COVER LID NO. 10-173-004, OR EQUAL. PROVIDE EXTENSIONS IF REQUIRED. BEFORE PROCEEDING WITH THE WORK, VERIFY DIMENSIONS AND QUANTITIES.
IMMEDIATELY INFORM LANDSCAPE ARCHITECT OF DISCREPANCY BETWEEN DRAWINGS,
SPECIFICATIONS, AND ACTUAL CONDITIONS. COMMENCE WORK IN AREAS OF DISCREPANCY 6. PROVIDE ONLY PLANTS WITH STRAIGHT, SINGLE TRUNKS, UNLESS OTHERWISE INDICATED IMMEDIATELY REPLACE DAMAGED, UNHEALTHY, OR DEAD TREES, SHRUBS, AND GROUND COVERS WITH SIZE AND KIND INDICATED IN DRAWINGS. 2.2 LANDSCAPE PLANTING MATERIALS 7. THOSE SPECIFIED TO BE MULTI-TRUNK SHALL HAVE AT LEAST THREE MAIN LEADERS ONLY AFTER RECEIVING INSTRUCTIONS FROM LANDSCAPE ARCHITECT. 3. PRIOR TO END OF MAINTENANCE PERIOD, APPLY FERTILIZED 'D' (15-2-6) AT THE RATE OF 4 POUNDS PER 1,000 SQUARE FEET UNIFORMLY OVER ALL PLANTING AREAS. A. SOIL DIMENSIONS INDICATED IN DRAWINGS ARE APPROXIMATE. PROVIDE OFFSETS, FITTINGS, SLEEVES, ETC., REQUIRED TO COMPLETE THE PROJECT. PERFORM SIMILAR OPERATIONS FOR EXISTING SURFACE SOIL, UNLESS OTHERWISE INDICATED IN DRAWINGS, FREE FROM SUBSOIL, REFUSE, ROOTS, HEAVY OR STIFF CLAY, ROCKS, STICKS, BRUSH OR OTHER 4. UPON COMPLETION OF INITIAL 60 DAY MAINTENANCE PERIOD, NOTIFY LANDSCAPE ARCHITECT 48 HOURS PRIOR TO DATE OF INITIAL INSPECTION. LIKE CONDITIONS WITHOUT ADDITIONAL COST TO OWNER. 9. THE HEIGHT AND SPREAD OF PLANT MATERIALS SHALL BE MEASURED WITH BRANCHES 1.1 SUBSTITUTIONS IN THEIR NORMAL POSITION. MEASURE SIZES OF PLANTS ON THE PLANT LIST. 2. NATIVE SOIL, MATERIAL EXCAVATED FROM PLANTING HOLES, FREE FROM ROCK OVER 1/2 INCH IN DIAMETER. GUARANTEE THAT PLANTS AND PLANTING AREAS ARE IN HEALTHY, THRIVING CONDITION FOR AN ADDITIONAL 60 DAYS AFTER INITIAL ACCEPTANCE OF PROJECT BY LANDSCAPE ARCHITECT A. FURNISH MATERIALS IN QUANTITIES, SIZE, AND MANUFACTURE INDICATED IN DRAWINGS AND A. 5 AND 15 GALLON CAN CONTAINER STOCK SHALL HAVE BEEN GROWN IN THAT CONTAINER NOT LESS THAN SIX (6) MONTHS, BUT SHALL NOT HAVE BEEN OVERGROWN IN THE CONTAINERS SO AS TO HAVE BECOME ROOT BOUND. 3. IMPORTED SOIL, IF REQUIRED, SANDY LOAM TEXTURE. 1. FINAL ACCEPTANCE MAY BE GRANTED AT THIS TIME AS DETERMINED BY LANDSCAPE FOR A PERIOD OF 30 DAYS AFTER EXECUTION OF CONTRACT, LANDSCAPE ARCHITECT WILL CONSIDER FORMAL REQUESTS FROM CONTRACTOR FOR SUBSTITUTION OF PRODUCTS IN PLACE OF THOSE SPECIFIED ONLY UNDER THESE CONDITIONS. SUBMIT SOIL SAMPLES AND ANALYSIS OF IMPORTED SOIL TO LANDSCAPE ARCHITECT FOR APPROVAL PRIOR TO DELIVERY TO PROJECT SITE. B. 15 GALLON CAN CONTAINER STOCK SHALL HAVE A PLANTED HEIGHT OF 6 FEET WITH 1 INCH CALIPER TRUNK. 2.0 PRODUCTS B. SHOULD LANDSCAPE ARCHITECT REJECT ANY PORTION OF DELIVERED SOIL, FOR ANY REASON, SELECT SOIL MATERIAL FROM A DIFFERENT SOURCE AND RESUBMIT TO LANDSCAPE ARCHITECT FOR APPROVAL WITHOUT ADDITIONAL COST TO OWNER. 1. WHEN SPECIFIED PRODUCTS ARE NOT AVAILABLE THROUGH NO FAULT OF SUB-CONTRACTOR. 2.1 IRRIGATION SPRINKLER MATERIALS 2.3 SOURCE QUALITY CONTROL WHEN IT IS CLEARLY SEEN, IN THE JUDGMENT OF OWNER, THAT A SUBSTITUTION WILL BE TO OWNER'S BEST INTERESTS IN TERMS OF TIME, COST, OR OTHER CONSIDERATIONS. A. PVC PLASTIC PIPE AND FITTINGS A. PERFORM INSPECTIONS OF CONSTRUCTION FOR THE FOLLOWING PARTS OF THE WORK: B. ORGANIC FERTILIZERS AND SOIL AMENDMENTS INSPECTION UPON COMPLETION OF PRELIMINARY FINISH GRADING AND IRRIGATION SPRINKLER SYSTEM. MAIN LINE (PRESSURE) PIPING, TYPE 1120-1220 SCHEDULE 40, NSF APPROVED, LASCO, JOHNS MANVILLE, OR APPROVED EQUAL. C. SUBMIT A SEPARATE REQUEST FOR EACH SUBSTITUTION. PROVIDE COMPLETE DATA SUBSTANTIATING COMPLIANCE OF PROPOSED SUBSTITUTION, INCLUDING PRODUCT COMMERCIAL GRADE ORGANIC FERTILIZERS AND SOIL AMENDMENTS, UNIFORM IN COMPOSITION, DRY AND FREE—FLOWING, DELIVERED TO SITE IN ORIGINAL, UNOPENED CONTAINERS, EACH BEARING THE MANUFACTURER'S GUARANTEED ANALYSIS. DENTIFICATION, MANUFACTURER'S NAME AND ADDRESS, MANUFACTURER'S LITERATURE, AND A. MAIN LINE PVC PIPE FITTINGS, TYPE 1-11 SCHEDULE 40, NSF APPROVED. 2. INSPECTION OF PLANTS PRIOR TO LAYOUT. LATERAL (NON-PRESSURE) LINE PIPING, TYPE 1120-1220 SCHEDULE 40, CLASS 200, NSF APPROVED, LASCO, JOHNS MANVILLE, OR APPROVED EQUAL. LAYOUT INSPECTION OF SPOTTED PLANTS. D. MANUFACTURER'S WARRANTIES WILL NOT RELIEVE SUB—CONTRACTOR OF HIS LIABILITY UNDER THE GUARANTEE, ONLY SUPPLEMENT THE GUARANTEE. 2. MATERIAL WHICH BECOMES CAKED OR OTHERWISE DAMAGED, MAKING IT UNSUITABLE FOR USE, WILL BE REJECTED. 4. INITIAL INSPECTION UPON COMPLETION OF PLANTING AND TREE STAKING, PRIOR TO COMMENCEMENT OF MAINTENANCE PERIOD. A. LATERAL PVC PIPE FITTINGS, TYPE 1-11 SCHEDULE 40, NSF APPROVED, LASCO, SLOANS, OR APPROVED EQUAL. A. FERTILIZER 'A': ORGANIC FERTILIZER FOR GENERAL SOIL FERTILITY IMPROVEMENT IN ALL
TURF AND PLANTING AREAS SHALL BE GRANULATED/PELLETIZED TYPE 1.2 RECORD DRAWINGS 5. FINAL INSPECTION AT CONCLUSION OF ADDITIONAL 60 DAY LANDSCAPE MAINTENANCE HAVING A N6-P20-K20 FORMULA. FURNISH OWNER WITH A SET OF RECORD DRAWINGS (REPRODUCIBLE VELLUMS) OF IRRIGATION SPRINKLER SYSTEM AT CONCLUSION OF THE INSTALLATION. SOLVENT, TYPE APPROVED BY MANUFACTURER OF PIPE AND FITTINGS. USE SCHEDULE 80 PVC THREADED NIPPLES IN RISER ASSEMBLIES. ORGANIC FERTILIZER TO BE APPLIED TO LAWN AREAS PRIOR TO SEEDING OR SODDING SHALL BE GRANULATED/PELLETIZED TYPE HAVING N6-P2-K0 (WITH 1% IRON). B. FERTILIZER 'B': LISTED INSPECTIONS WILL BE MADE BY LANDSCAPE ARCHITECT OR AN AUTHORIZED REPRESENTATIVE. 1. OBTAIN VELLUMS FROM LANDSCAPE ARCHITECT AT COST OF REPRODUCTION PLUS 25 PERCENT. . USE ONLY PVC PLASTIC PIPE FREE FROM BLISTERS, INTERNAL STRIATIONS, DENTS, WRINKLES, CRACKS, HOLES, FOREIGN MATERIALS, SMOOTH INTERIOR WALL WITH A GLASS— ORGANIC FERTILIZER TO BE INCORPORATED IN EACH PLANT PIT SHALL
BE A PLANT TAB WITH FORMULA N20-P10-K5, SUCH AS C. FERTILIZER 'C': 1. REQUEST INSPECTION BY LANDSCAPE ARCHITECT AT LEAST 48 HOURS IN ADVANCE OF TIME INSPECTION IS REQUIRED. B. INDICATE IN RECORD DRAWINGS ALL CHANGES MADE TO IRRIGATION SYSTEM DESIGN. GRO-POWER. A. CONTINUOUSLY AND PERMANENTLY MARK EACH PIPE WITH MANUFACTURER'S NAME, KIND OF PIPE, MATERIAL, SIZE SCHEDULE OR TYPE, AND MANUFACTURER'S QUALITY CONTROL IDENTIFICATION. ORGANIC FERTILIZER TO BE APPLIED TO LAWN AREAS AFTER TURF IS ESTABLISHED AND AROUND INSTALLED CONTAINER PLANTS DURING THE MAINTENANCE PERIOD SHALL BE PELLETED TYPE FURNISH OWNER WITH 2 EACH OF THE FOLLOWING MATERIALS FOR EACH TYPE OF VALVE AND SPRINKLER HEAD INSTALLED IN THE SYSTEM: IRRIGATION SPRINKLER SYSTEM B. GALVANIZED PIPE AND FITTINGS A. PREPARATION E. SOIL AMENDMENT: IMPORT TOPSOIL TO MEET ORGANIC MATTER CONTENT OF A MIN. OF 3.5% BY DRY WEIGHT OR 1 INCH OF COMPOST. WHERE INDICATED IN DRAWINGS, USE ASA SCHEDULE 40 MILD STEEL SCREWED PIPE, GALVANIZED, WITH MEDIUM GALVANIZED SCREWED BEADED MALLEABLE IRON FITTINGS. VALVE KEYS. SERVICE WRENCHES. COORDINATE INSTALLATION OF SPRINKLER MATERIALS, INCLUDING PIPE, TO ELIMINATE INTERFERENCE WITH, OR DIFFICULTY IN PLANTING SHRUBS, TREES, GROUND COVER, EXISTING OR PROPOSED UTILITIES, AND OTHER CONSTRUCTION. RESTORE TO ORIGINAL CONTOURS AND ESTABLISHED GRADES CHANGED DURING COURSE OF THE WORK. QUICK COUPLER VALVE KEYS. "OPTION 1" -REQUIRE IMPORT TOPSOIL TO MEET ORGANIC MATTER CONTENT HOSE SWIVELS COMPATIBLE WITH QUICK COUPLER VALVES.
KEYS TO OPEN AUTOMATIC CONTROL CABINET. A. GALVANIZED COUPLINGS MAY BE MERCHANT COUPLING. "OPTION 2" —SUBMIT SOILS REPORT THAT IDENTIFIES EXISTING TOPSOIL MEETS ORGANIC MATTER OF CONTENT OF 3.5% BY DRY WEIGHT OR GREATER. C. CUT PIPE CUT STRAIGHT AND TRUE. B. INSTALLATION A. IN THE EVENT OF SUCH COMPACTION, CONTRACTOR WILL BE REQUIRED TO RECULTIVATE COMPACTED AREAS. D. AFTER CUTTING, REAM OUT ENDS TO THE FULL INSIDE DIAMETER OF THE PIPE PRIOR TO INSTALLATION, LAYOUT AND STAKE PRESSURE SUPPLY LINES, LATERAL LINES, AND LOCATION OF SPRINKLER HEADS. OBTAIN APPROVAL LAYOUT FROM LANDSCAPE FOLLOWING MATERIAL, PER 1,000 SQUARE FEET, INTO THE TOP 6 INCHES OF SOIL, USING A ROTOTILLER OR SIMILAR MACHINE, THEN THOROUGHLY WATER. E. IN CHANGING PIPE DEPTHS, USE 45Ø ELBOWS. SODDING: RAKE AREAS TO FINISH GRADE ELEVATION TO 1 INCH LOWER THAN ADJACENT PAVING TO ACCOMMODATE SOD THICKNESS. 6 CU. YDS. - RECYCLED COMPOST MATERIAL (SOIL AMENDMENT) F. SPRINKLER HEADS A. IF EQUIPMENT IS INCORRECTLY LOCATED WITHOUT APPROVAL, RELOCATE PER DIRECTIONS OF LANDSCAPE ARCHITECT WITHOUT ADDITIONAL COST TO OWNER. A. SPREAD 20 POUNDS PER 1,000 SQUARE FEET OF FERTILIZER 'B' ON SOIL SURFACES PRIOR TO SODDING. THEN NEATLY INSTALL SOD SLABS. INSTALL TURF HEADS, WHERE ADJACENT TO FIXED OBJECTS SUCH AS HEADERBOARDS, CURBS, OR MOWING STRIPS, SO POWERED EDGING TOOLS CAN PASS BETWEEN TURF HEAD AND FIXED OBJECT WITHOUT DIFFICULTY. 2. CONNECT SPRINKLER IRRIGATION SYSTEM TO POINT OF CONNECTION (P.O.C.) INDICATED IN DRAWINGS. 2. CULTIVATE EXISTING PLANTING AREAS WITH HAND TOOLS. B. STAGGER END JOINTS, TIGHTLY JOINTED WITH NO VISIBLE SPACES. 3. PREPARED SOIL MIX FOR BACKFILL IN PITS FOR TREES, VINES, AND SHRUBS, CONSISTING LOCATE SHRUB HEADS MINIMUM 12 INCHES FROM BACK OF CURBS AND EDGE OF WALKWAYS WHEN SHRUB HEAD IS MOUNTED ABOVE GRADE ON A RISER. LIGHTLY WATER AND ROLL ENTIRE AREAS. THEN HEAVILY WATER TO ASSURE WATER PENETRATION OF AT LEAST A DEPTH OF 8 INCHES. A. MAKE CONNECTIONS AT APPROXIMATE LOCATIONS SHOWN IN DRAWINGS. RECYCLED COMPOST MATERIAL (SOIL AMENDMENT)
NATIVE SOIL B. ASSUME RESPONSIBILITY FOR CHANGES CAUSED BY ACTUAL SITE CONDITIONS. . SEEDING: APPLY FERTILIZER 'B' TO FINISH GRADED SURFACES AT THE RATE OF 4 POUNDS PER 1,000 SQUARE FEET. INSTALL ELECTRIC, NORMALLY CLOSED ANGLE CONTROL VALVES AS INDICATED IN DRAWINGS AND AS SPECIFIED BY MANUFACTURER. C. TRENCHING & BACKFILLING A. USE ONLY SEED THAT IS WEED FREE, FRESH, RECLEANED, GRADE A, NEW CROP CONSISTING OF THE PERCENTAGE OF MIX AS DESCRIBED IN DRAWINGS. AND ORGANIC FERTILIZER 'C' AS FOLLOWS (GRO-POWER TABS OR EQUAL) EXCAVATION INCLUDES REMOVAL OF WATER AND MATERIALS, OR OBSTRUCTIONS OF ANY NATURE THAT WOULD INTERFERE WITH THE WORK. SET VALVES IN VERTICAL POSITION, HOUSED IN AMETEK OR EQUAL VALVE BOX WITH REMOVABLE COVER, FLUSH WITH FINISHED GRADE. WHEREVER POSSIBLE, INSTALL IN A 1 GAL: 5 GAL: 15 GAL: B. LABEL SEED IN ACCORDANCE WITH THE U.S. DEPARTMENT OF AGRICULTURE RULES AND REGULATIONS UNDER THE FEDERAL SEED ACT PRESENTLY IN EFFECT AND SHALL BE DELIVERED TO PROJECT SITE IN BAGS BEARING DEALER'S LABEL AND CHARACTER 2. REMOVE FROM THE SITE EXCESS AND WASTE MATERIAL RESULTING FROM TRENCHING 6-8 TABS FOR BOXED MATERIAL H. ELECTRICAL WORK 3. DIG TRENCHES STRAIGHT AND SUPPORT PIPE CONTINUOUSLY ON BOTTOM OF DITCH. 4. CONDUCT SOIL PREPARATION AND PLANTING OPERATIONS ONLY UNDER FAVORABLE WEATHER CONDITIONS. SOIL SHALL NOT BE WORKED WHEN EXCESSIVELY DRY OR WET. PERFORM ELECTRICAL WORK IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE, THE STATE OF CALIFORNIA ELECTRICAL SAFETY ORDERS, OTHER APPLICABLE STATE AND LOCAL CODES AND REGULATIONS. C. SOW SEED IN 2 DIRECTIONS AT A TOTAL COMBINED RATE OF 10 POUNDS PER 1,000 SQUARE FEET. A. LAY PIPE TO AN EVEN GRADE. FOLLOW LAYOUT FOR TRENCHING EXCAVATION INDICATED IN DRAWINGS AND AS NOTED. A. LANDSCAPE ARCHITECT RESERVES THE RIGHT TO STOP WORK TAKING PLACE DURING A PERIOD WHEN CONDITIONS ARE CONSIDERED DETRIMENTAL TO SOIL STRUCTURE SOW SEED BY EXPERIENCED PERSONNEL AT A TIME WHEN LITTLE OR NO WIND IS 2. ASSUME RESPONSIBILITY FOR THE COORDINATION OF ALL ELECTRICAL SERVICE CONNECTIONS TO THE CONTROLLER. A. PROVIDE MINIMUM COVER OF 18 INCHES FOR PRESSURE SUPPLY LINES. E. LIGHTLY RAKE INTO TOP 1/8 INCH OF SOIL. C. PLANTING TREES, SHRUBS, & VINES FIELD QUALITY CONTROL B. PROVIDE MINIMUM COVER OF 18 INCHES FOR ALL NON-PRESSURE LINES INDICATED IN DRAWINGS. F. DO NOT MOW UNTIL TURF IS 2-1/2 INCHES HIGH, AND FOR INITIAL MOWING DO NOT MOW LOWER THAN 1-1/2 INCHES. REMOVE ALL CLIPPINGS. 1. DIG PITS FOR PLANTS SQUARE PER DETAIL IN DRAWINGS. FLUSH PIPES BY REMOVING HEADS AND OPERATING THE SYSTEM AT FULL PRESSURE UNTIL ALL RUST, SCALE, SAND, ETC., IS REMOVED. A. LEVEL SIZE OF PITS SHALL BE 2 TIMES DIAMETER OF ROOT BALL, AND ONE—HALF AGAIN AS DEEP AS THE DEPTH OF ROOT BALL. C. PROVIDE MINIMUM COVER OF 24 INCHES OVER PIPE UNDER VEHICULAR WAYS. FERTILIZING DURING MAINTENANCE: APPLY FERTILIZER 'D', 30 CALENDAR DAYS AFTER PLANTING, AT THE RATE OF 5 POUNDS PER 1,000 SQUARE FEET. A. DIVERT FLUSHING WATER TO PREVENT PONDING OR SOIL EROSION. D. PROVIDE MINIMUM COVER OF 18 INCHES FOR CONTROL WIRING. B. SOIL AT SIDES AND BOTTOMS SHALL BE LOOSENED BY SCARIFYING TO ENSURE ROOT PENETRATION. AVOID SMOOTH CIRCULAR SIDES. 2. TEST PIPING UNDER FULL PRESSURE, WITH RISERS CAPPED FOR A PERIOD OF TWO HOURS. A. REPEAT EVERY 30 DAYS THROUGH MAINTENANCE. E. PROVIDE 3 INCH SAND BACKFILL, ALL SIDES OF PVC PIPE, WHERE SOILS CONTAIN GREATER THAN 50% ROCKS OR OTHER MATERIAL 1/2 INCH OR LARGER IN DIAMETER F. WEED CONTROL, PEST CONTROL, & MULCHING 2. BACKFILL PITS WITH "PREPARED SOIL" TO THE BOTTOM OF THE ROOT BALL. THEN SET THE PLANT IN AN UPRIGHT POSITION IN CENTER OF HOLE. BACKFILL SPACE AROUND IT WITHIN NATIVE BACKFILL MATERIAL. 3. INSPECT PIPE FOR LEAKS. WEED CONTROL MATERIAL SHALL BE A PRE—EMERGENT HERBICIDE, TRIFLUROLIN (TREFLAN) OR DIPHENAMID (DYMID OR ENIDE) OR APPROVED EQUAL, APPLIED ON PLANTED AREAS. DON'T APPLY TO TURF DEVELOPED AREAS. D. COMPACTION A. CORRECT ANY LEAKAGE DISCOVERED DURING TESTS. A. WHEN THE BACKFILL AROUND THE PLANT IS APPROXIMATELY TWO—THIRDS COMPLETED, THOROUGHLY WATER. BACKFILL COMPLETE TO THE GRADE OF THE . COMPACT BACKFILL FOR TRENCHING TO A DRY DENSITY EQUAL TO ADJACENT UNDISTURBED SOIL IN PLANTING AREAS AND TO 90% IN PAVED AREAS. 4. REPEAT TESTS UNTIL SATISFACTORY. NOTE: IN CITIES AND FOR PROJECTS THAT DO NOT ALLOW FOR SYNTHETIC PRE-EMERGENTS USE A CORN GLUTEN MEAL PRODUCT. 5. TEST SPRINKLER HEADS: 2. CONFORM TO ADJACENT GRADES WITHOUT DIPS, SUNKEN AREAS, HUMPS, OR OTHER 2. CONSIDER IT PART OF CONTRACTOR'S WORK TO CONTROL ON—SITE OR NEARBY PESTS THAT ARE DISTURBING THE CONDITION OF LANDSCAPE IMPROVEMENTS. B. THE CROWN OF THE PLANT SHALL BE 1-1/2 INCHES ABOVE (MINIMUM) FINISHED A. TO DETERMINE THAT THEY FUNCTION ACCORDING TO MANUFACTURER'S DATA, AND 3. CONTROL OF PESTS INCLUDES, BUT IS NOT LIMITED TO RODENTS, RABBITS, INSECTS, DEER, ETC. 3. PLACE INITIAL BACKFILL ON ALL LINES OF A FINE GRANULAR MATERIAL. B. TO DETERMINE THAT THE INSTALLATION WILL PROVIDE DESIGN COVERAGE. 3. PREPARE A SOIL RING AT LEAST 3 INCHES HIGH AND AS WIDE AS ROOT BALL AROUND EACH PLANT (NOT IN A TURF AREA) TO RETAIN WATER. 4. FOREIGN MATTER LARGER THAN 1/2 INCH IN SIZE WILL NOT BE PERMITTED. 6. ALLOW OR CAUSE WORK TO BE COVERED UP OR ENCLOSED ONLY AFTER IT HAS BEEN INSPECTED, TESTED, AND APPROVED BY LANDSCAPE ARCHITECT. REPAIR DAMAGE THAT OCCURS TO THE ORIGINAL CONDITION OF IMPROVEMENTS, INCLUDING REPLACEMENT OF PLANT MATERIAL WHEN REQUIRED, WITHOUT ADDITIONAL COST TO OWNER. 5. IF SETTLEMENT OCCURS AND ADJUSTMENTS IN PIPE, VALVES, SPRINKLER HEADS, LAWN OR PLANTING, OR OTHER CONSTRUCTION ARE NECESSARY, MAKE REQUIRED ADJUSTMENTS A. WATER THOROUGHLY TO ELIMINATE AIR POCKETS. A. SHOULD ANY WORK BE CLOSED OR COVERED UP BEFORE INSPECTION AND TESTS ARE SATISFACTORILY COMPLETED, UNCOVER THE WORK, AND AFTER IT HAS BEEN INSPECTED, TESTED, AND APPROVED, MAKE ALL REPAIRS WITH MATERIALS AS MAY WITHOUT ADDITIONAL COST TO OWNER. B. REMOVE TURF IN A 24 INCH DIAMETER RING AROUND EACH TREE BASE IN TURF 5. SPREAD BARK CHIP MULCH EVENLY OVER ENTIRE PLANTED AREA, EXCEPT TURF DEVELOPED AREAS, TO A MINIMUM DEPTH OF 3". E. HANDLING OF PIPE E NECESSARY TO RESTORE DISTURBED WORK TO ITS ORIGINAL AND PROPER D. PLANTING GROUND COVERS CONDITION WITHOUT ADDITIONAL COST TO OWNER. INSTALL PVC PIPE ALLOWING A SMALL AMOUNT OF EXCESS LENGTH IN THE LINE TO COMPENSATE FOR CONTRACTION OR EXPANSION OF THE PIPE. G. PRELIMINARY INSPECTION AND STAGE ACCEPTANCE PLANTING SHALL TAKE PLACE IN THE EXISTING PREPARED MOIST AND FRIABLE SOIL, NEVER DRY OR WET AND SOGGY. LANDSCAPE PLANTING PROCEDURES 1. UPON COMPLETION OF PLANTING WORK, NOTIFY LANDSCAPE ARCHITECT THAT PROJECT IS READY FOR INSPECTION. A. ACCOMPLISH EXCESS LENGTH BY "SNAKING" THE LINE IN THE TRENCH DURING A. CLEARING & GRUBBING A. THE MOIST CONDITION SHALL EXTEND TO THE FULL DEPTH OF CULTIVATION. 2. UPON INSPECTION, IF LANDSCAPE ARCHITECT FINDS ENTIRE PROJECT COMPLETE AND IN COMPLIANCE WITH DRAWINGS AND SPECIFICATIONS, STAGE ACCEPTANCE WILL BE 1. PRESERVE EXISTING TREES IN AN UNDISTURBED CONDITION. 2. HANDLE AND ASSEMBLE PIPE, FITTINGS, AND ACCESSORIES BY SKILLED TRADESMEN USING APPROVED METHODS AND TOOLS. EXERCISE CARE TO PREVENT DAMAGE TO MATERIALS OR EQUIPMENT. 2. SPACE GROUND COVER PLANTS AS INDICATED IN DRAWINGS AND IN THE PLANT LIST. 2. ROUGH GRADE EARTHEN MOUNDS TO CONTOURS INDICATED IN DRAWINGS. 3. PLANT IN EVENLY SPACED ROWS WITH STAGGERED TRIANGULAR SPACING AND AROUND SHRUBS AND TREES TO WITHIN ONE FOOT. 3. CONSTRUCT MOUNDS WITH ENOUGH EXCESS MATERIAL TO ALLOW FOR FUTURE SETTLEMENT. 3. IF ASPECTS OF PROJECT ARE INCOMPLETE OR IMPROPERLY INSTALLED, CONTRACTOR WILL BE NOTIFIED AND HAVE 5 WORKING DAYS IN WHICH TO CORRECT OR COMPLETE THE A. KEEP INTERIOR OF PIPES, FITTINGS, AND ACCESSORIES CLEAN AT ALL TIMES. CLOSE OPENINGS IN PIPING RUNS AT THE END OF WORK EACH DAY TO PREVENT ENTRY OF FOREIGN MATERIALS. 4. NO GROUND COVER SHALL BE PLANTED LESS THAN ONE-HALF OF THE SPECIFIED SPACING FROM ANY CURB OR WALKWAY. A. FINAL LOCATION OF MOUNDS SHALL NOT CONFLICT WITH EXISTING UTILITIES, UTILITY BOXES, VALVE BOXES, ETC. 4. STAGE ACCEPTANCE WILL BE GIVEN ONLY WHEN ALL WORK IS CORRECT AND COMPLETE. E. PLANTING TURF GRASS B. BENDING OF GALVANIZED STEEL PIPE WILL NOT BE PERMITTED. 5. THE STAGE ACCEPTANCE BY LANDSCAPE ARCHITECT OF LANDSCAPE PROJECT WILL ESTABLISH THE BEGINNING OF PLANT MAINTENANCE PERIOD. 4. NO COMPACTION WILL BE ALLOWED, EXCEPT FOR NORMAL GRADING AND SHAPING . PERFORM JOINTING BY COMPETENT TRADESMEN SPECIALLY TRAINED IN THE TYPE OF WORK REQUIRED, USING TOOLS AND EQUIPMENT RECOMMENDED BY THE MANUFACTURERS OF THE PIPE, FITTINGS, OR EQUIPMENT. AFTER ALL SOIL AMENDMENT AND ORGANIC FERTILIZERS HAVE BEEN APPLIED AND CULTIVATED INTO SOIL, FINE GRADE ALL AREAS. 5. UPON COMPLETION OF GRADING OPERATIONS, SPREAD EXCESS MATERIAL IN AREAS 2. REMOVE RIDGES AND DEPRESSIONS. AREAS SHALL BE SMOOTH, CONTINUOUS, FIRM PLANES THAT ENSURE PROPER SURFACE DRAINAGE. A. TAKE EVERY PRECAUTION TO SECURE A PERMANENT, WATER-TIGHT JOINT BETWEEN EACH LENGTH OF PIPE. DIRECTED BY LANDSCAPE ARCHITECT. UPON COMPLETION OF WORK, REMOVE EXCESS MATERIALS, RUBBISH, DEBRIS, AND SUB-CONTRACTOR'S CONSTRUCTION AND INSTALLATION EQUIPMENT FROM THE PREMISES. B. SOIL CONDITIONS 3. REMOVE ROCKS, SOIL LUMPS, AND DELETERIOUS MATERIALS LARGER THAN 1 INCH, RAKE AND COMPACT AREAS WITH A 200 POUND ROLLER. B. JOINTING PROCEDURES AND METHODS ADOPTED BY CONTRACTOR SHALL BE IN STRICT ACCORDANCE WITH RECOMMENDATIONS OF MANUFACTURER OF JOINTING FINAL INSPECTION OF THE WORK WILL BE MADE BY LANDSCAPE ARCHITECT IN THE PRESENCE OF THE SUB-CONTRACTOR WHEN WORK IS COMPLETED. NOTIFICATION SHALL BE MADE BY THE CONTRACTOR 48 HOURS IN ADVANCE OF SUCH INSPECTION. 1. CULTIVATE PLANTED AREAS TO A LIGHT AND FRIABLE CONSISTENCY. UNIFORMLY TILL THE 4. AVOID ADDITIONAL COMPACTION OF THE SOILS AFTER TREATMENT. DO NOT PERMIT VEHICULAR OR EQUIPMENT TRAFFIC OVER AREAS.

DWNER



ARCHITECT
SHEEHAN
NAGLE
HARTRAY

SHEEHAN NAGLE HARTRAY ARCHITECTS 130EastRandolph Street, Suite 3100 CHICAGO, IL 60601





STRUCTURAL ENGINEER

PEOPLES ASSOCIATES STRUCTURAL ENGINEERS

Pleasanton, California

San Jose, California

CIVIL ENGINEER





PROPERTY OF THE PROPERTY OF TH

| No. | Description | Dat |
|-----|--------------------|-----------|
| 1 | ISSUED FOR 100% SD | 07-16-202 |
| 2 | ISSUED FOR 100% DD | 08-26-20 |
| | SITE UPDATES | 10-04-20 |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |

VANTAGE CA31


2590 WALSH AVENUE SANTA CLARA, CA 95051 APN: 216-28-112


ISSUED FOR 100% DD

Landscape Specifications

L4.0

SCALE: AS NOTED
















2590 WALSH AVENUE SANTA CLARA, CA 95051

