DOCKETED	
Docket Number:	19-IEPR-04
Project Title:	Transportation
TN #:	228787-8
Document Title:	Current and Future Freight Container Mobility Systems for CA - October 15, 2015
Description:	DRISI - Automated Freight Systems
Filer:	Wendell Krell
Organization:	California Energy Commission
Submitter Role:	Commission Staff
Submission Date:	6/19/2019 9:22:42 AM
Docketed Date:	6/19/2019



Automated Freight Systems: Current and Future Freight Container Mobility Systems for CA

Requested by Cameron Oakes, Division of Transportation Planning, Caltrans October 15, 2015

> Produced by Ms. Lee Provost, P.E., M.S., DRISI

The Caltrans Division of Research, Innovation and System Information (DRISI) receives and evaluates numerous research problem statements for funding every year. DRISI conducts Preliminary Investigations on these problem statements to better scope and prioritize the proposed research in light of existing credible work on the topics nationally and internationally. Online and print sources for Preliminary Investigations include the National Cooperative Highway Research Program (NCHRP) and other Transportation Research Board (TRB) programs, the American Association of State Highway and Transportation Officials (AASHTO), the research and practices of other transportation agencies, and related academic and industry research. Other website searches, such as Google Scholar, yielded limited sources to download since they required registration and payment for copyright usage. The views and conclusions in cited works, while generally peer reviewed or published by authoritative sources, may not be accepted without qualification by all experts in the field. The contents of this document reflect the views of the authors, who are responsible for the facts and accuracy of the data presented herein. The contents do not necessarily reflect the official views or policies of the California Department of Transportation, the State of California, or the Federal Highway Administration. This document does not constitute a standard, specification, or regulation. No part of this publication should be construed as an endorsement for a commercial product, manufacturer, contractor, or consultant. Any trade names or photos of commercial products appearing in this publication are for clarity only.

TABLE OF CONTENTS

Executive Summary	2
Background	2
Summary of Findings	2
Related Research and Resources	2
ATS- Automated Freight System	2
TEUs – Twenty Feet Equivalent Container Units and Freight Container Mobility	3
Freight Efficiency Emissions	3
Gaps in Findings	4
Next Steps	4
Detailed Findings – Related Research and Resources	5
Google Search: Automated Freight System (AFS), Twenty Feet Equivalent Units (TEU)	
AFS	
AFS TEU	
TRID Searches – TEU, Automated Freight Systems	
TEU	
AFS	
Freight Container Mobility	
Google Search	
TRID Search	
Best Topic Found	
Regulations	
Operations	
Smart Freight Transportation	
Ports	
Trucks	
International	
Warehousing, Supply Chain	
CO ₂ , GHG, Fuel Efficiency	

Background

This research preliminary investigation (PI) will support the state of California (CA) Governor Brown's Executive Order (EO) B-32-15 (July 17, 2015) for Caltrans and other state agencies to establish clear targets to improve freight efficiency, transition to zero-emission technologies and increase the competitiveness, sustainability and effectiveness of CA's freight system. The PI will explore automated freight systems which utilize electric-rail infrastructure, above and underground, adaptable to transporting twenty-foot equivalent units (TEUs) or other types of freight transport containers (e.g. capsules or pods) and investigate if similar systems are in place today in the United States or elsewhere. Identification of modal shifting strategies specific to the movement of freight containers from shipping port to urban areas (drayage), to distribution centers and ultimately the final scheduled destination will also be investigated.

Summary of Findings

Related Research and Resources

Internet website searches were conducted on the Transportation Research Board (TRB) TRID database <u>http://trid.trb.org</u> and Google. Key words used were: TEU's, Automated Freight System and Freight Efficiency Emissions. Due to the compressed timeframe to complete this PI other search words suggested by the requestor were not used. However, sufficient information was obtained relating to the PI request. As for the question: "What type of systems are in place today that can be adaptable to the freight container mobility system?" more time is needed.

The general concept understood to investigate is the movement of freight from ships in urban areas, such as Los Angeles to the distribution center- how these containers are disbursed and where they need to go, how the system infrastructure today results in traffic congestion and air pollution and what systems can be applied to help reduce this problem in the future.

The idea of creating policy incentives toward improving urban goods movement, using dedicated infrastructure such as rail or freight corridors, reducing GHG emissions, incorporating energy efficiency, improving delivery time of goods, and thusly helping the economy in CA are the general ideas used in this literature search.

ATS- Automated Freight System

The research that resulted from the Google searches identified U-Tube videos showing futuristic underground cargo freight transportation pods. High speed rail using magnetic levitation technology was also found. The idea is to create a new infrastructure underground to eliminate container trucks on roads by using a tunnel system. Problems could arise with trying to avoid existing underground utilities (sewer, power lines) and obstacles (water, difficult soils, etc.). No existing systems were found in use.

The TRID searches yielded traffic simulation models for predicting travel times on the rail and road network at the ports of Los Angeles and Long Beach to help manage freight flows and traffic in general. Cooperative Adaptive Cruise Control(CACC) utilizing vehicle-to-vehicle communication, automated truck platooning, connected vehicle/automated (CV/AV) technologies as well as Intelligent and Autonomous Vehicles (IAV's) that dynamically join,

transport containers (up to 40 feet equivalent) and disjoin again helps cope with the increasing container traffic at ports were found during the literature search.

TEUs - Twenty Feet Equivalent Container Units and Freight Container Mobility

It was found that improvements in shipping port productivity/efficiency are needed with the steady increase of international sea freight container trade and the introduction of the world's largest Maersk Triple-E class ships that can carry twice what is currently used, that is up to 22,000 TEU's.

An interesting find was the yearly Swiss Transportation Research Conferences (STRC), which post numerous papers presented on their website. One most notable article is "Optimization of operations in container terminals: hierarchical vs. integrated approaches", dated September 2010. It discusses a promising research trend using the integrated optimization of decision problems that are highly interdependent, yet usually solved hierarchically by port terminal planners. For instance, the simultaneous optimization of berth allocation and quay crane scheduling, or on the landside, transfer and storage planning, which are two important problems affecting the efficiency of the port operations. Congestion issues at the container terminals have been solved with innovative technology, such as yard truck scheduling and innovative crane trucks.

The literature search also found military operations of TEUs. Deployable container solutions used for military operations may be an interesting option to explore.

Freight Efficiency Emissions

A list of 25 pages with 25 records were made available through the TRID database. Another search word that may be used in the future could be "Freight Transport Logistics" or "Supply Chain Management". The top 25 reports that were discovered have been categorized into 5 topic areas: 1.) Regulations, 2.) Operations-Trucks, Ports, Highways, 3.) International, 4.) Warehousing, Supply Chains and 5.) GHG, CO2 Emissions, Fuel Efficiency.

The best report that popped up in this quick TRB literature search was the article by the Transportation Research Board Annual Meeting held in 2015, Paper # 15-3578, which was sponsored by the AT025 Urban Freight Committee. It seems to encompass all concepts described in the PI. The authors developed a mathematical model to simulate the impact that different policies could have on logistics costs, traffic level, congestion and emissions. There were many papers presented at this conference, all related to the topic. The website location is: http://amonline.trb.org/2015-subject-index?qr=1. Click on Freight transportation and scroll down to see the several items discussed, some have power point or papers attached.

Another paper of interest was found on Smart Freight: "Applications of Information and Communications Technologies to Freight System Efficiently" with the corporate authors by the American Council for Energy-Efficient Economy.

Gaps in Findings

No actual operations using the modal shifting strategies such as underground automated freight systems, underground transit tubes for container freight, or electric-rail (mag-lev) rail transport infrastructure for cargo was found in this PI.

New infrastructure will take considerable efforts in planning, funding, right of way acquisitions and environmental concerns that will take years to take through to construction and operation. The futuristic ideas are in place which may eventually replace existing methods of moving goods by conventional rail or truck road transportation.

Next Steps

More time is needed and the scope of this literature search would need to be narrowed. A full scale research project may be warranted or a team of experts to decide on a strategic plan with specific goals may need to be developed, which is outside the scope of this PI.

Detailed Findings – Related Research and Resources

Google Search: Automated Freight System (AFS), Twenty Feet Equivalent Units (TEU)

AFS

https://www.google.com/?gws_rd=ssl#q=Automated+Freight+System_About 574,000 results 10-9-15



Automated Transport Systems Bury Freight Traffic

<u>http://www.industrytap.com/automated-transport-systems-bury-freight-traffic-underground/15489</u> Feb 9, 2014 - If the technology is cheap enough underground transport *system* have many advantages over traditional technologies.

Megacities & Metropolitan Areas Need Underground Cargo Transport

Those who have lived in crowded urban areas have experienced streets choked with delivery trucks idling loudly while emitting poisonous, acrid fumes into the air. Many have heard of the <u>"hyperloop"</u> <u>project</u> recently popularized by Elon Musk, but a huge number of scientists, engineers and companies around the globe have been working on tube-like underground freight transport systems that would provide a solution to the worst aspects of urban traffic congestion.

Capacity Limits of Roads & the Need for Transport Tubes

"Large diameter" tubes, those one foot in diameter or larger, have been conceived for moving freight and packaged goods. <u>CargoCap</u> of Germany, for example, has developed aerodynamic "Caps" carrying two euro-pallets each and traveling on electric-powered wheels. Lateral guide rollers keep the Caps on the track.

Caps consume low amounts of energy, can be constructed at low cost, have long lifetimes and need minimal maintenance.

http://www.industrytap.com/automated-transport-systems-bury-freight-traffic-underground/15489



Click below to watch a U Tube video on this concept https://www.youtube.com/watch?v=U9G5HzYD Hc

Evacuated Tube Transport- U Tube

US Dept. of Energy with Oak Ridge National Laboratory

https://www.youtube.com/watch?v=9y_XMwAOfJ0

Future Trains- super magnetic levitation- U Tube

https://www.youtube.com/watch?v=tZJuqYk3YYE (1 hour video)

Proposal to have mag lev train to travel from Disneyland in Anaheim, CA to travel to Las Vegas, Nevada at speeds of 180-310 mph, instead of travelling by car on Interstate I-15.

Alstrom Engineering in France uses the LGV high speed train for 20 years operating at 200 mph and is studying to implement a faster AGV high speed train. Trains are most efficient in and more cost effective than other modes of travel, such as aircraft to move people.

[PDF](2005) Financing and Deploying Automated Freight Systems

nexus.umn.edu/papers/AutomatedFreight.pdf by D Levinson and Zi Zou 2005 - <u>Related articles</u> https://ideas.repec.org/p/nex/wpaper/automatedfreight.html - *Cannot read entire document*

New technologies are bringing Automated Freight Systems (AFS), which aim to reduce congestion, mitigate environmental impacts and enhance public safety, to fruition. The financing and deployment issues of AFS differ from other Intelligent Transport System applications. This chapter briefly introduces major concepts of AFS. The financing strategies for these concepts are discussed, in which the government subsidies play an important role through the use of public-private partnership. Economies of scale and externalities of the current and new systems are discussed. In the discussion of the deployment of AFS, it is suggested that deployment schemes are highly correlated with financing strategies.

Conclusions: Increasing traffic congestion argues for innovations that either enhance the capacity of current infrastructure or divert traffic to newly constructed infrastructure. The concern of the public in environmental conservation, community integrity and 23sustainable development makes the simple expansion of conventional highways more difficult than ever. The innovations in automated freight systems provide opportunities to mitigate congestion, enhance transport productivity, and reduce vehicle pollution without a large amount of land consumption. The number of alternatives for the technology of AFS is large and each results in different scenarios for their deployment and financing.

Financing strategies for the three concepts of AFS discussed in this chapter possess different characteristics in terms of monetary resources, private participation, cost sharing and management. Specific financing schemes should be designed according to these factors.

Government subsidies in the form of loans, grants, or tax breaks may be vital during the early years of AFS to construct infrastructure. The reduced negative externalities of AFS make them good candidates for public investments. However, the instruments of the government subsidies vary according to the deployment scheme of AFS. A comprehensive AFS deployment strategy will prompt the market penetration process, but until a clearer picture of technology and financing emerges, the path of deployment remains murky.

Automated freight - YouTube

2:55 www.youtube.com/watch?v=e_Q_OICXeFs Jul 22, 2013 - Uploaded by Oak Ridge National Laboratory In this conceptual animation, a container is moved from a ship into the *automated freight system*.

Automated Freight, Goods Movement and Tube Technologies

University of Washington Oct 1, 2015 - <u>https://faculty.washington.edu/jbs/itrans/afreight.htm</u>

Links are provided to several descriptions of automated freight movement technologies. Some are operational, some under development and some are still conceptual. Some are above ground, others are underground. Large scale systems thinking on this topic is particularly noteworthy in the Netherlands and Japan.

See <u>http://www.capsu.org/library/large-diameter.html</u> for an overview of recent, global, activity in this field.

Link to the dramatic <u>Hyperloop</u> proposal for passenger and freight transportation in partially evacuated tubes

Link to a City Lab article on the future of US freight movement, 10/2014

Link to <u>CargoFish website</u> - for automated, area-wide distribution of small goods in cities, in a pipe. <u>Volpe report on intermodalism: a 20-year perspective</u>

Link to German Baumer Group - Airport Baggage Handling technology




Fig. 13 A conceptual image of the underground freight transport system

Source: Koshi, Masaki, An <u>Automated Underground Tube Network for Urban Goods Transport</u>, IATSS Research, 16:2, 1992

<u>Autran Corporation</u> - a system with carrier vehicles that will carry autos on platforms, passenger cabins and freight containers

<u>Capsule pipelines</u> - link to a website that provides considerable information on this goods movement approach.

<u>CargoCap</u> - innovative transportation system for conveyance of piece goods through pipelines, being developed in Germany. Virtual test system has been constructed and has been in use since 2007. Website include two excellent videos.

<u>CargoRail</u> - one of the new systems being developed by MegaRail Transportation Systems, Inc., described in a product overview. Also available is <u>MegaRail's presentation to the Gateway Council of</u>

<u>Governments</u> regarding an application of a CargoRail and CargoTram system to serve the freight movement and air pollution reduction needs of the Port of Long Beach, California, pdf format, 21 pages Also, see the more recent (September '07) <u>Port Operating Plan</u>, 10 pp. <u>Click here for the most recent</u> <u>Cargo Rail presentation (October, 2009)</u> Currently (2013) inactive

<u>CargoTunnel</u> - an underground network concept for goods movement with cities <u>Evacuated Tube Transportation</u> - link to a website that provides considerable information on this concept - deals with both people and freight.

<u>Frog Navigation Systems</u> - link to a website that describes automated cargo applications of guided vehicles in the Netherlands.

<u>MagneTrak</u> - link to a press release that describes this revolutionary material handling system being developed by MagneMotion and a Swiss company.

<u>Magplane</u> - link to a website that describes a maglev-based pipeline system currently being demonstrated in Florida. An initial project has been

built in Mongolia.

<u>Magtube, Inc.</u> - link to a website that describes an evacuated tube concept using maglev for moving freight. <u>See patent for more details</u>.

<u>MegaRail</u> - link to a website that describes a system that includes an automated freight component, called <u>Cargo Rail</u>, being developed in Ft. Worth, Texas.


<u>MonoFreight</u> - link to a YouTube animation of a suspended monorail-type automated container transport system

Pipenet - an innovative system being developed in Italy, website now has a section in English

<u>Pipeline Transportation</u> - an automated freight transportation system that utilizes linear electric motors (author not doing further work but a good reference paper for previous work on this topic).

HOME

<u>Public Roads - Tube Freight Transportation, Autumn 1994 -</u> Federal Highway Administration- last modified 6-15-15 <u>https://www.fhwa.dot.gov/publications/publicroads/94fall/p94au21.cfm</u>



Tube transportation systems are inherently high capital cost, low operating cost systems, but the economic feasibility of tube transportation systems carrying general merchandise is unknown as no such system has been built and operated in commercial service. This article is quite comprehensive in the description of the types of tube freight transportation systems.

The Future of Automated Freight Transport: Concepts, Design

www.amazon.com > ... > Industries > Transportation Amazon.com, Inc. Costs \$150 for this publication Feb 2006 This book explores the many challenges faced by the development and implementation of *automated freight* transport *systems*.

<u>A world without trucks: underground freight networks - Low ...</u> www.lowtechmagazine.com/2008/02/a-world-without.html



Feb 22, 2008 - Note that pneumatic *systems* could deliver physical objects, which is hard to do with email or any other *automatic* technology in use today.

Automated Transportation Logistics and Analysis System ...

<u>http://energy.gov/em/downloads/automated-transportation-logistics-and-analysis-system-atlas</u> United States Department of Energy- Office of Packaging and Transportation

The Department of Energy's (DOE's) Automated Transportation Logistics and Analysis System ATLAS is an integrated web-based logistics management system allowing users to manage inbound and outbound freight shipments by highway, rail, and air. ATLAS is based on the core competencies of Automated Transportation Management System (ATMS) and provides an integrated framework for data sharing between Carriers and Shippers.

ATMS became operational in the early 1990s, and underwent a series of major improvements over its lifecycle. An assessment was deemed necessary by DOE to establish current cost reasonableness by reviewing benefits, user satisfaction and assess the long-term management approach (including expansion of site applications) for ATMS, and the viability of alternative logistics management systems. This resulted in the integration of ATMS functionality into ATLAS.

A World without trucks: underground freight networks

Low Tech Magazine <u>http://www.lowtechmagazine.com/2008/02/a-world-without.html</u>

Some Western European countries are getting serious about transporting consumer goods through automated subterranean networks – introducing a fifth transport mode next to road, rail, air and water. This rare combination of low-tech sense and high-tech knowledge could lead to a further economic growth without destroying the environment and the quality of life. Super fast underground cargo transport is a favourite subject of futurologists. Yet, the key to the feasibility of the proposed systems is their very low but constant speed.

Searches related to Automated Freight System
Automated transportation system
automated transportation management system

TEU

Mostly yielded company products 10-9-15



World Shipping Council Partners in Trade

http://www.worldshipping.org/about-the-industry/how-liner-shipping-works

The website has information on the shipping industry, how TEU's are transferred from port to the consumer as well as industry issues. It has animated examples on how products are brought to market and how liner container shipping works in 10 steps. <u>http://www.worldshipping.org/about-the-industry/how-liner-shipping-works/the-step-by-step-process</u>. This may aid in identifying what steps could be eliminated or improved upon.

Forecast of Container Vessel Specifications and Port Calls within San Pedro Bay Mercator Transport Group 2005

https://www.portoflosangeles.org/DOC/REPORT_SPB_Vessel_Forecast.pdf

This report summarizes a series of detailed analyses undertaken by Mercator Transport Group, in collaboration with Herbert Engineering Corporation and MDS Transmodal Ltd., for the Ports of Long Beach and Los Angeles, in order to forecast future container vessel activity levels in San Pedro Bay. In producing these forecasts, the Mercator Project Team (Mercator) utilized a three-phased work plan, in accordance with the component analyses contained in the Ports' Request for Proposal. In the third phase, Mercator consolidated its assessments of the various fundamental drivers listed above and built upon its near-term forecasts to project how carriers' global and trans-Pacific service networks would be likely to evolve between 2008 and 2020, in terms of vessel deployment patterns and geographical configurations, as well as in terms of ship sizes and other key vessel characteristics. These projections were then used to estimate vessel service patterns, vessel call activity levels, and load factors – by ship size – for the two San Pedro Bay ports.

Port Call Forecast Results and Conclusions -Container Vessel Forecast For San Pedro Bay Ports: Because the World Fleet, the Trans Pacific Fleet and the San Pedro Bay Fleet are so very closely interrelated, and because the San Pedro Bay port call forecast is so strongly dependent on the composition and deployment of the vessel fleet, a common forecast tool has been developed that addresses these elements together. The forecast as developed by Mercator involves a systematic expansion of the number of services and the introduction of progressively larger vessels in each trade. The hypothetical carrier service plans as developed in the prior section provide a guide as to how the service networks will evolve and how they will likely be structured as of 2020. In addition, checks are made at each forecast time point to confirm that -

- the capacity for the overall trade and sub-segments of the trade are in line with expectations for growth
- the number of overall services is consistent with expectations for industry structure and satisfies service frequency requirements
- the vessel size mix is consistent with pre-existing fleets and expectations derived from our deployment feasibility and unit cost assessments
- the rate of vessel retirements or "cascading" of smaller vessels into secondary services does not appear to exceed the level that those services can accommodate.

Based on the analysis of carrier deployment planning issues, and after developing a range of fleet expansion and deployment scenarios, it is Mercator's view that carriers, following the delivery and integration into service of the considerable quantity of vessels now on order, will eventually introduce single screw ships in the 10000-11000 TEU size category to the

Transpacific. 12000 TEU class ships, which we believe would need to be of a higher cost twin-screw design, will prove to be unattractive because their increased operational and commercial challenges are not offset by meaningful cost reductions.

The next size increment beyond the 10000 TEU class will thus be the 14000 TEU class vessel, which we believe will not be deployed into the Transpacific under either the low or medium growth scenarios. Only under the high growth scenario would we expect any of these vessels to be deployed, and then only in limited numbers.

Forecast results for each of the six scenarios (low, medium and high growth, each without and with a change to the Panama Canal dimensions) are contained in Appendix. A brief recap of each is provided in data columns following the conclusion in the report.

Definition of TEU- Wikipedia

https://www.google.com/url?url=https://en.wikipedia.org/wiki/Twentyfoot_equivalent_unit&rct=j&frm=1&q=&esrc=s&sa=U&ved=0CBQQFjAAahUKEwiEq6eZobbIAhVOWYgK HfFSBYM&usg=AFQjCNGIGhBmTP2QhTJqk2h63DCp0nZcgQ

The twenty-foot equivalent unit (often TEU or teu) is an inexact unit of cargo capacity often used to describe the capacity of <u>container ships</u> and <u>container terminals.[1]</u> It is based on the volume of a 20-foot-long (6.1 m) <u>intermodal container</u>, a standard-sized metal box which can be easily transferred between different modes of transportation, such as ships, trains and trucks.

Stock Trade for TEU's- Box Ships Inc., a shipping company http://finance.yahoo.com/q?s=TEU

TRID Searches – TEU, Automated Freight Systems

<u>TEU</u>

10-9-15

Title:	Estimation of the perceived value of transit time for containerized cargoes
Accession Number:	01573933
Record Type:	Component
Language:	English
Record URL:	http://dx.doi.org/10.1016/j.tra.2015.04.014
Record URL:	http://www.sciencedirect.com/science/article/pii/S0965856415001007
Abstract:	This paper proposes a novel method for estimating the perceived value of transit time of containers by shipping lines. The key idea is that a shipping line's published schedule is the optimal decision that minimizes the sum of fuel cost and time-associated costs of the containers adopted by the shipping line. Using the proposed method, the authors find that the adopted values of transit time for nine trans- Pacific services operated by Orient Overseas Container Line and five trans-Pacific services operated by Maersk Line are between US\$5/TEU/day and US\$30/TEU/day. The authors further demonstrate how the adopted value can be used for designing the optimal transit times between ports, analyzing the viability of slow-steaming, checking whether ships should speed up to catch up to connecting ships on other services, and helping to predict the market share of less polluting fuels in view of rules on air emission.
Supplemental Notes:	Abstract reprinted with permission of Elsevier.
TRIS Files:	TRIS
Media Type:	Web
Pagination:	pp 298-308
Authors:	Wang, Shuaian Qu, Xiaobo Yang, Ying
Availability:	Find a library where document is available Order URL: <u>http://worldcat.org/issn/09658564</u>
Publication Date:	20150800

Serial:	Transportation Research Part A: Policy and Practice Volume: 78 Publisher: Elsevier ISSN: 0965-8564 Serial URL: <u>http://www.sciencedirect.com/science/journal/09658564</u>
Index Terms:	Cargo handling; Containers; Costs; Estimation theory; Optimization; Ship lines; Transit times; Travel time; Value of time
Subject Areas:	Finance; Freight Transportation; Marine Transportation; Planning and Forecasting; I10: Economics and Administration; I72: Traffic and Transport Planning

Title:	Use of the Delphi method to determine the constraints that affect the future size of large container ships
Accession Number:	01560358
Record Type:	Component
Language:	English
Record URL:	http://dx.doi.org/10.1080/03088839.2013.870358
Abstract:	Who would have foreseen 40 years ago the launching of an 18 000 TEU container ship? The unprecedented growth of such ships presents an increasing challenge for port infrastructure planners. The paper concludes that during the next 20 years, the growth of container ships will depend on factors related to supply and demand, and to external factors. These factors will be defined as the constraints. These constraints have been determined using a semi-quantitative methodology, which starts with a pre-foresight analysis, then continues with a foresight analysis based on the judgment of experts, using the Delphi technique. The experts' judgment, with a vision shared by 82% of those participating, establishes that the trend for growth in the size of container ships will depend principally on the following factors: economic growth, port access channels, berth depth alongside, air draft, and limitations in natural channels and straits. This result, representing the experts' group vision, is offered as a basis for the establishment of long term policies.
Supplemental Notes:	Abstract reprinted with permission of Taylor & Francis.
TRIS Files:	TRIS
Media Type:	Web
Pagination:	pp 263-277

Authors:	Gomez Paz, Maria Alejandra Camarero Orive, Alberto González Cancelas, Nicoletta
Availability:	Find a library where document is available Order URL: <u>http://worldcat.org/oclc/2899960</u>
Publication Date:	20150400
Serial:	Maritime Policy & Management Volume: 42 Issue Number: 3 Publisher: Taylor & Francis ISSN: 0308-8839 EISSN: 1464-5254 OCLC: 2899960 Serial URL: <u>http://www.tandfonline.com/loi/tmpm20</u>
Index Terms:	Constraints; Containerships; Delphi method; Forecasting; Long range planning; Policy analysis; Vehicle capacity; Vehicle size
Subject Areas:	Marine Transportation; Planning and Forecasting; Vehicles and Equipment; I91: Vehicle Design and Safety
Title: Accession Number: Record Type:	Out with the old, in with the TEU? 01564340 Component

Record Type:	Component
Language:	English
Source Agency:	Northwestern University Transportation Library
Abstract:	Linton Nightingale travels to Berlin for the Fruit Logistica trade fair and learns of the growing influence of the big box lines in the movement of perishable goods.
TRIS Files:	TLIB
Pagination:	pages 32-36
OCLC:	907083509
Authors:	Nightingale, Linton
Availability:	Available from Northwestern University Transportation Library through interlibrary loan or document delivery Order URL:

	http://www.library.northwestern.edu/transportation/services.html Find a library where document is available Order URL: http://worldcat.org/oclc/907083509
Publication Date:	20150300
Period Covered:	March 2015
Serial:	Containerisation International Publisher: T&F Informa UK, Limited ISSN: 0010-7379 OCLC: 03601838 Serial URL: <u>http://www.ci-online.co.uk</u>
Index Terms:	Refrigerated cargo; Refrigerated ships
Subject Areas:	Marine Transportation; Vehicles and Equipment
Title:	Border-crossing constraints, railways and transit transports in Estonia
Accession Number:	01554935
Record Type:	Component
Language:	English
Record URL:	http://dx.doi.org/10.1016/j.rtbm.2014.10.010
Record URL:	http://www.sciencedirect.com/science/article/pii/S2210539514000728
Abstract:	North-East Europe has served as a general cargo transit area for Russia and other emerging economies of the East for decades. Typically, this activity was initiated with road transport, but after some years of operation, border-crossings became problematic and in some cases even impossible to conduct. Volume of transit transport was therefore severely constrained. As one remedy to sustain transit traffic, the Baltic States have implemented container trains to eastern destinations. Even though, overall transit traffic through Estonia has decreased mainly due to the increased volumes of Russian seaports, the container transit traffic has increased steadily: Volumes were really minor a decade ago, but have increased from several thousand containers up to above 50,000 TEU (twenty-foot equivalent unit) in 2013. This has enabled hinterland transport and incoming container volumes in the port of Tallinn to develop. This research work analyzes not only second hand data regarding Estonian general cargo transit, but also includes case study visits. The case company has established many international container train connections. Container transit traffic has an optimistic

	future outlook in Estonia. However, the main operational constraints are related to gauge widths, border-crossing operations, delivery time issues, low price level of road transport, unpredictable Russian market and legislation and infrastructure investments.
Supplemental Notes:	Abstract reprinted with permission of Elsevier.
TRIS Files:	TRIS
Media Type:	Digital/other
Pagination:	pp 72-79
Authors:	Hilmola, Olli-Pekka Henttu, Ville
Availability:	Find a library where document is available Order URL: <u>http://worldcat.org/issn/22105395</u>
Publication Date:	20150300
Serial:	Research in Transportation Business & Management Volume: 14 Issue Number: Publisher: Elsevier ISSN: 2210-5395 Serial URL: <u>http://www.sciencedirect.com/science/journal/22105395</u>
Index Terms:	Case studies; Containers; Estonia; Freight traffic; Freight trains; International borders; Ports; Russia (Federation)
Subject Areas:	Freight Transportation; Operations and Traffic Management; Railroads; I73: Traffic Control

Title:	Increasing rail mode share in Fremantle inner harbour
Accession Number:	01545163
Record Type:	Component
Record URL:	http://railknowledgebank.com/Presto/coLTIIYWUtZWFjM2U2OTE0ZDY3&bckToL=VHJ1ZQ
Source Agency:	ARRB Group Limited 500 Burwood Highway Vermont South, Victoria 3133
Abstract:	Intermodal terminals form a critical part of the overall freight system in Western Australia. Rail

freight can be an efficient means of transporting goods where market conditions are suitable and adequate infrastructure is available. The Western Australian government has set a series of strateg priorities to ensure the freight system is developed towards maximising the amount of freight that transported on rail. In 2002, a target was set of 30% rail mode share (versus road) for the Fremantl Inner Harbour. To date, this target is yet to be achieved, although solid progress has been made. The overall planning strategy for the Inner Harbour has included close consideration of the integration land use and transport logistics. Land use planning for the expansion of the Inner Harbour has link future development of logistics operations to the planned transport infrastructure, maximising the efficiency and attractiveness of future transport operations in the Inner Harbour. The North Quay Rail Terminal, located within the Fremantle Inner Harbour, is the primary rail link between inland freight precincts and the container port at Fremantle. Rail transport into the port has evolved since the port was first constructed, and the current North Quay Rail Terminal was completed in 2005. A part of a suite of infrastructure upgrades aimed at increasing the rail mode share, the Federal and State governments jointly committed to extending the existing North Quay Rail Terminal sidings from 400m to 690m in length. The planning for the terminal included two primary stages; and configuration. This planning allowed for the current operator operating preferences to be respected whilst allowing for infrastructure upgrades which would be required in future to reach the propose ultimate throughput of up to 360,000 TEU/annum. Following planning, detailed design was subsequently completed. This design included close consideration of a number of design aspects, including constructability of the works and staging. The construction contract for the upgrade was awarded on 23 October 2013 at a cost of \$AUD31 million. This project will increase the terminal capacity dramatically and will improve rail efficiency and competitiveness as a transport mode. Following upgrades to other system bottlenecks and improvement in market conditions over time, is planned that the terminal will achieve its goal of handling a 30% mode share of all containers transported through the Fremantle Inner Harbour. Achievement of this goal will provide overall system efficiency benefits and also benefits to the community surrounding the Inner Harbour.

TRIS Files:	ATRI
Pagination:	8p. ; PDF
Authors:	Turner S
Monograph Title:	Rail transport for a vital economy: CORE 2014: conference on railway engineering, 5-7 May 2014 Adelaide, South Australia
Monograph Accession Number:	01545126
Publication Date:	20140500
Conference:	CORE 2014, Rail transport for a vital economy, conference on railway engineering, Adelaide, Sou Australia, 5-7 May 2014 Location: Date: 00000 - 00000
Index	Freight transport; Freight transportation; Intermodal terminals; Terminus; Transport depot

Terms:

Subject Areas:	Freight Transportation; Terminals and Facilities
-------------------	--

Title:	Preparing port container terminals for the future: making the most of Intelligent Transport Systems (ITS)
Accession Number:	01534693
Record Type:	Component
Language:	English
Record URL:	http://dx.doi.org/10.2495/UT140351
Record URL:	http://library.witpress.com/pages/PaperInfo.asp?PaperID=26155
Abstract:	Governments and legislators all over the world view ports and terminals as vital infrastructure assets as they play a critical role in economic growth by attracting and generating trade. A port that does not have the ability to cope with rapidly advancing technologies will not be in a position to foster the development of the trade sector. Their ability to 'go green' by reducing their carbon footprint and by being more sensitive to environmental considerations is vital to their success. The future is bringing increased demands for greater efficiency and for more sustainable designs in cargo handling technologies. Moreover, the scarcity of land is forcing port companies to realise higher area utilizations. With the arrival of the next generation ultra-large Triple-E vessels carrying 18,000 TEU (twenty foot equivalent unit), it is important to investigate the opportunities to introduce innovation in the development of terminal operations and the logistics chain. The crucial terminal management problem is how to balance the integration of the current technology with the new state of the art technology such as the Intelligent Autonomous Vehicle (IAV). Although the IAV is not exactly new, what makes it different is that it does not require a guidance system such as rails or transponders set into the ground, to reach its destination. Traffic management and space optimization is a problem with the future development of container terminals. The problem can be solved by having a remote 'traffic control centre' directing vehicles to marshalling areas where the containers are handled by IAV's. The challenge is to find innovative solutions to balance service requirements while integrating automated and non- automated cargo handling equipment in container terminals to ensure sustainability, safety and security.
Supplemental Notes:	Abstract reprinted with permission from WIT Press.

TRIS Files:	TRIS
Media Type:	Web
Pagination:	pp 419-427
Authors:	McGinley, K
Monograph Title:	Urban Transport XX
Monograph Accession Number:	01528763
Corporate Authors:	WIT Press Ashurst Lodge Ashurst, Southampton SO40 7AA United Kingdom
Editors:	C A Brebbia
Availability:	WIT Press Ashurst Lodge Ashurst, Southampton SO40 7AA United Kingdom Order URL: <u>http://www.witpress.com/978-1-84564-778-0.html</u> Find a library where document is available Order URL: <u>http://worldcat.org/isbn/9781845647780</u>
ISBN:	9781845647780
Publication Date:	20140000
Conference:	20th International Conference on Urban Transport and the Environment Location: Faro Algarve, Portugal Date: 20140528 - 20140530
Serial:	WIT Transactions on the Built Environment Issue Number: 138 Publisher: Wessex Institute of Technology ISSN: 1743-3509 Serial URL: <u>http://library.witpress.com/pages/listBooks.asp?tID=2</u>
Index Terms:	Automation; Cargo handling equipment; Container terminals; Intelligent transportation systems; Ports
Subject Areas:	Freight Transportation; Marine Transportation; Planning and Forecasting; Terminals and Facilities; I21: Planning of Transport Infrastructure
Title: Co	lumbia River Vessel Arrival/Departure Analysis

Accession Number:	01522209	
Record Type:	Component	
Language:	English	
Record URL:	http://dx.doi.org/10.1061/9780784413067.046	
Abstract:	The recently completed Columbia River deepening (43 feet/13.1 meters) project provides Columbia River ports with opportunities for handling larger vessels. The deepened channel, in conjunction with the LOADMAX numerical hydraulic analysis stage prediction tool, optimizes available navigational depths and consequently maximizes the benefits from recent new dredging work and annual maintenance dredging. As a result, the Port of Portland (Port) requested that an arrival/departure analysis of water depths and transit times for a potential larger class of vessel (i.e., 6,500 TEU container ships) be performed in order to determine if regularly scheduled service is feasible. This paper summarizes the methodology and results of the vessel routing arrival/departure analysis.	
Supplemental Notes:	© 2013 American Society of Civil Engineers.	
TRIS Files:	TRIS, ASCE	
Media Type:	Web	
Pagination:	pp 437-446	
Authors:	Krcma, Karl Burnette, Eric Degens, Sebastian	
Monograph Title:	Ports 2013: Success through Diversification	
Monograph Accession Number:	01523287	
Corporate Authors:	American Society of Civil Engineers 1801 Alexander Bell Drive Reston, VA 20191-4400 United States	
Editors:	Bruce I Ostbo Don Oates	
Availability:	American Society of Civil Engineers 1801 Alexander Bell Drive Reston, VA 20191-4400 United States Order URL:	

	http://www.asce.org/Product.aspx?ID=2147487569&ProductID=192556110 Find a library where document is available Order URL: http://worldcat.org/isbn/9780784413067	
ISBN:	9780784413067	
Publication Date:	20130800	
Conference:	Ports '13: 13th Triennial International Conference Location: Seattle Washington, United States Date: 20130825 - 20130828 Sponsors: American Society of Civil Engineers	
Index Terms:	Columbia River; Containerships; Depth; Feasibility analysis; Methodology; Ports; Ship operations; Travel time	
Subject Areas:	Marine Transportation; Planning and Forecasting; Terminals and Facilities; I72: Traffic and Transport Planning	
Title:	Bridging the Gap - Cai Lan International Container Terminal, Vietnam	
Accession Number:	01521958	
Record Type:	Component	
Language:	English	
Record URL:	http://dx.doi.org/10.1061/9780784413067.188	
Abstract:	Located 160 km (100 miles) east of Hanoi on the southwest shores of Bai Chay Bay, Cai Lan International Container Terminal is the largest deep water port in Northern Vietnam. Capable of handling a half-million 20-foot equivalent units (TEU) of containers annually, the terminal is strategically located to take advantage of regional growth in agriculture and manufacturing. The addition of this 594-meter-long (1,950 foot), three-berth structure situated between two existing berths completes the development of the 1995 master plan for the port and, more importantly, supplies the region with the additional capacity needed to meet the expected growth in containerized cargo volumes. This paper describes the background, planning, design, and construction challenges involved in creating and implementing a master plan for a modern container terminal located between two existing operating terminals in Northern Vietnam.	
Supplemental Notes:	© 2013 American Society of Civil Engineers.	
TRIS Files:	TRIS, ASCE	

Media Type:	Web	
Pagination:	pp 1842-1851	
Authors:	Malla, Ajaya P Cornell, Christopher B	
Monograph Title:	Ports 2013: Success through Diversification	
Monograph Accession Number:	01523287	
Corporate Authors:	American Society of Civil Engineers 1801 Alexander Bell Drive Reston, VA 20191-4400 United States	
Editors:	Bruce I Ostbo Don Oates	
Availability:	American Society of Civil Engineers 1801 Alexander Bell Drive Reston, VA 20191-4400 United States Order URL: <u>http://www.asce.org/Product.aspx?ID=2147487569&ProductID=192556110</u> Find a library where document is available Order URL: <u>http://worldcat.org/isbn/9780784413067</u>	
ISBN:	9780784413067	
Publication Date:	20130800	
Conference:	Ports '13: 13th Triennial International Conference Location: Seattle Washington, United States Date: 20130825 - 20130828 Sponsors: American Society of Civil Engineers	
Index Terms:	Construction; Container terminals; Deepwater harbors; Planning and design; Vietnam	
Subject Areas:	Construction; Design; Marine Transportation; Planning and Forecasting; Terminals and Facilities; I20: Design and Planning of Transport Infrastructure; I50: Construction and Supervision of Construction	
Title:	Deltaport Intermodal Railyard Capacity Study	
Accession Number:	01521947	

Record Type:	Component	
Language:	English	
Record URL:	http://dx.doi.org/10.1061/9780784413067.177	
Abstract:	Deltaport is the largest container terminal in Canada. It is located in the Port of Vancouver and operated by Terminal Systems Inc (TSI). Approximately 60% of the vessel throughput at Deltaport moves via the on-terminal intermodal railyard (IY). The Port, TSI, and BC Rail (the rail operator for switching) felt that the IY, in its current configuration, was the limiting factor in overall terminal capacity and undertook a detailed simulation study to determine how to accommodate a growth of approximately 50% through the IY. The IY is served by rail-mounted gantry cranes (RMGs). The study first analyzed historical IY RMG productivity. Historical data were used to calibrate simulation models of terminal activity which include rail, vessel, and gate moves. Once a successful calibration was achieved, future cases corresponding to annual throughput of 2.4M annual vessel TEU were simulated with various combinations of numbers of tractors, yard cranes and rail switching. Output from these models of future peak shift operations was used to define a range of likely RMG productivity levels for future operations. These data, along with peaking factors and estimates of downtime for train switching, along with the minimum practical operating distance between RMGs were used to develop annual lift capacity for the IY. These capacity figures were compared to previously calculated values for berth and container yard operations to ensure that the facility was capable of handling 2.4M TEU overall. At the start of the study, it was assumed that the IY would need to be extended in length in order to accommodate the target throughput. The study indicated that - by adding working tracks in parallel, adding RMGs and identifying rail switching methods - TSI should be able to meet the target volume within the existing	
Supplemental Notes:	© 2013 American Society of Civil Engineers.	
TRIS Files:	TRIS, ASCE	
Media Type:	Web	
Pagination:	pp 1736-1742	
Authors:	Sisson, Mark	
Monograph Title:	Ports 2013: Success through Diversification	
Monograph Accession Number:	01523287	

Corporate Authors:	American Society of Civil Engineers 1801 Alexander Bell Drive Reston, VA 20191-4400 United States	
Editors:	Bruce I Ostbo Don Oates	
Availability:	American Society of Civil Engineers 1801 Alexander Bell Drive Reston, VA 20191-4400 United States Order URL: <u>http://www.asce.org/Product.aspx?ID=2147487569&ProductID=192556110</u> Find a library where document is available Order URL: <u>http://worldcat.org/isbn/9780784413067</u>	
ISBN:	9780784413067	
Publication Date:	20130800	
Conference:	Ports '13: 13th Triennial International Conference Location: Seattle Washington, United States Date: 20130825 - 20130828 Sponsors: American Society of Civil Engineers	
Index Terms:	Canada; Container terminals; Forecasting; Freight capacity; Freight transportation; Gantry cranes; Intermodal yards; Port of Vancouver; Productivity; Rail marine interface	
Subject Areas:	Freight Transportation; Marine Transportation; Planning and Forecasting; Railroads; Terminals and Facilities; I72: Traffic and Transport Planning	
Title:	Mega Vessels and Quay Walls	
Accession Number:	01521711	
Record Type:	Component	
Language:	English	
Record URL:	http://dx.doi.org/10.1061/9780784413067.139	
Abstract:	In 2011, the shipping company Maersk announced Triple-E class ships, expected to be the world's largest ships in service. Following this, 22,000 TEU container ships may become a future reality. This proposed evolution in vessel size will necessitate engineering evaluation of most modern ports to determine the capacity to receive these mega vessels. Basic infrastructure, such as the entrance channels, basins, turning circles, and the berthing and	

	waiting areas in a port, must have adequate capacity. Quay walls, jetties, etc. must have sufficient strength to berth and moor these mega vessels safely while supporting heavier quay cranes with longer outreaches. Recently constructed infrastructure in the Port of Rotterdam, designed for Suezmax vessels, was examined to determine if there is sufficient reserve capacity to cope with the much larger 22,000 TEU vessels. The conclusion was that growth in vessel size had been anticipated during the design phase. Therefore, relatively small adaptations were required in the infrastructure. In some scenarios, operational limitations could be imposed to compensate for increased ship dimensions and associated capacity requirements.
Supplemental Notes:	© 2013 American Society of Civil Engineers.
TRIS Files:	TRIS, ASCE
Media Type:	Web
Pagination:	pp 1355-1364
Authors:	Taneja, P Zwakhals, J W Vellinga, T
Monograph Title:	Ports 2013: Success through Diversification
Monograph Accession Number:	01523287
Corporate Authors:	American Society of Civil Engineers 1801 Alexander Bell Drive Reston, VA 20191-4400 United States
Editors:	Bruce I Ostbo Don Oates
Availability:	American Society of Civil Engineers 1801 Alexander Bell Drive Reston, VA 20191-4400 United States Order URL: http://www.asce.org/Product.aspx?ID=2147487569&ProductID=192556110 Find a library where document is available Order URL: http://worldcat.org/isbn/9780784413067
ISBN:	9780784413067
Publication Date:	20130800
Conference:	Ports '13: 13th Triennial International Conference

Index Terms: Subject Areas:	Location: Seattle Washington, United States Date: 20130825 - 20130828 Sponsors: American Society of Civil Engineers Planning and design; Port capacity; Port of Rotterdam; Quays; Ships; Size; Walls Design; Marine Transportation; Terminals and Facilities; Vehicles and Equipment; I20: Design and Planning of Transport Infrastructure	
Title:	Scheduling of Intelligent and Autonomous Vehicles under pairing/unpairing collaboration strategy in container terminals	
Accession Number	01489562	
Record Type:	Component	
Language:	English	
Record URL:	http://dx.doi.org/10.1016/j.trc.2013.04.006	
Record URL:	http://www.sciencedirect.com/science/article/pii/S0968090X1300079X	
Abstract:	A new class of Intelligent and Autonomous Vehicles (IAVs) has been designed in the framework of Intelligent Transportation for Dynamic Environment (InTraDE) project funded by the European Union. This type of vehicle is technologically superior to the existing Automated Guided Vehicles (AGVs) in many respects. They offer more flexibility and intelligence in maneuvering within confined spaces where the logistic operations take place. This includes the ability of pairing/unpairing, enabling a pair of 1-TEU (20-foot Equivalent Unit) IAVs dynamically to join, transport containers of any size between 1- TEU and 1-FFE (40-foot Equivalent) and disjoin again. Deploying IAVs helps port operators to remain efficient in coping with the ever increasing volume of container traffic at ports and eliminate the need for deploying more 40-ft transporters in the very confined area of ports. In order to accommodate this new feature of IAVs, the authors review and extend one of the existing mixed integer programming models of AGV scheduling in order to minimize the makespan of operations for transporting a set of containers of different sizes between quay cranes and yard cranes. In particular, they study the case of Dublin Ferryport Terminal. In order to deal with the complexity of the scheduling model, the authors develop a Lagrangian relaxation-based decomposition approach equipped with a variable fixing procedure and a primal heuristics to obtain high-quality solution of instances of the problem.	
Supplemental Not	es: Abstract reprinted with permission from Elsevier.	

TRIS Files:	TRIS	
Media Type:	Print	
Pagination:	pp 1-21	
Authors:	Gelareh, Shahin Merzouki, Rochdi McGinley, Kay Murray, Roisin	
Availability:	Find a library where document is available Order URL: <u>http://worldcat.org/issn/0968090X</u>	
Publication Date:	20130800	
Serial:	Transportation Research Part C: Emerging Technologies Volume: 33 Issue Number: Publisher: Elsevier ISSN: 0968-090X Serial URL: <u>http://www.sciencedirect.com/science/journal/0968090X</u>	
Serial: Index Terms:	Volume: 33 Issue Number: Publisher: Elsevier ISSN: 0968-090X	

Title:	Vessel Calls Snapshot, 2011
--------	-----------------------------

Accession	01502019
Number:	01302019

- **Record Type:** Monograph
- Language: English
- **Record URL:** <u>http://www.marad.dot.gov/documents/Vessel_Calls_at_US_Ports_Snapshot.pdf</u>
- Abstract: This snapshot contains data on calls by oceangoing vessels of 10,000 deadweight (DWT) or greater at United States ports. Vessel capacities are expressed in terms of deadweight tons for all vessel types, twenty-foot equivalent units (TEU's) for containerships and cubic meters (CM) for gas carriers. In 2011, 7,836 oceangoing vessels made 68,036 calls at U.S. ports. Vessel calls were up 7.9 percent from five years earlier, but 13.6 percent from the year before. The recovery was spread over all of the major vessel types. Of

	the 2011 calls, 35 percent were by tankers, 32.5 percent were by containerships, 16.1 percent were by dry bulk vessels, 9.1 percent were by Roll-On/Roll-Off (Ro-Ro) vessels, and 5.9 percent were by general cargo ships. In 2011, 98 percent of the tanker calls were by double-hull tankers, up from 83.7 percent five years earlier.
Supplemental Notes:	Released: March 2013; Revised: November 2013.
TRIS Files:	TRIS, ATRI, USDOT
Media Type:	Digital/other
Pagination:	24p
Authors:	Olsen, Ryan Perkins, Gail Byington, Russel Hsieh, Jon
Corporate Authors:	Maritime Administration Office of Policy and Plans 1200 New Jersey Avenue, SE Washington, DC 20590
Availability:	National Technical Information Service 5301 Shawnee Road Alexandria, VA 22312 United States Order Number: PB2014-101268
Publication Date:	20130300
Edition:	Revised
Index Terms:	Cargo ships; Containerships; Ports; Ships; Tankers; United States; Vehicle capacity
Subject Areas:	Freight Transportation; Marine Transportation; Terminals and Facilities; I70: Traffic and Transport

<u>AFS</u>

Title:

Optimum Routing of Freight in Urban Environments under Normal Operations and Disruptions using a Co-simulation Optimization Control Approach

Accession Number:	01572360
Record Type:	Project
Language:	English
Record URL:	http://www.metrans.org/research-projects/metrans-utc
Source Agency:	National Center for Metropolitan Transportation Research School of Policy, Planning and Development 650 Childs Way, RGL 238 Los Angeles, CA 90089-0626 United States
Source Data:	RiP Project 39747
Abstract:	The complexity and dynamics of the road and rail networks that are also shared by passengers together with the unpredictability of the effect of incidents, disruptions and demand, in temporal and spacial coordinates makes the scheduling and optimum routing of freight a very challenging task despite recent advances in information technologies. Estimating travel times in an urban road network environment is a real challenge especially during incidents and other disruptive events. Current practices rely on historical data and limited available real time information in order to make routing decisions that minimize a certain cost objective which in the case of road network is usually travel time. Incidents, disruptions, changes in demand, planned and unpredictable events may change the historical patterns of traffic, rendering decisions ineffective leading to imbalances in capacity across time and space coordinates. The purpose of this project is to exploit the availability of powerful computational and software tools together with advances in optimization and feedback control for dynamical systems in order to come up with a methodology that can lead to more efficient decisions in freight scheduling and routing. The method relies on the use of real time simulation models, for predicting travel times, traffic flows, fuel consumption and pollution by going beyond to what can be achieved today based on historical and limited real time data. The simulation models are used in a feedback loop with an optimization model and a load-balancing controller. The simulation models receive historical and streaming data and are able to automatically reconfigure themselves to simulate the subsequent effects of incidents and disruptions. They can be used to estimate costs (travel time, fuel consumption, pollution etc.) along different links in the network by fast-forwarding. In addition they can be used to test different decision scenarios before reaching a final decision. The predicted states of the network can be used to generate c

	the network and change the initially estimated costs leading to an unbalanced network load in space and/or time. A load balancing controller exercises the simulation model and tests different load distributions along the possible routes. The approach leads to an iterative feedback process with the objective of reducing the value of the cost index further till a stopping criterion is met in which case the final decision is applied to the real system. The objective of this project is focused on the effectiveness of the methodology as a tool for freight scheduling and routing in a complex urban environment. The project will investigate whether the use of simulation models operating in real time with optimization and automated control techniques can provide much better decisions than existing approaches that rely on past data and limited real time information. Issues such as speed of computations, scalability, convergence, ability for fast reconfiguration during incidents and disruptions are important research problems. While most of the work will concentrate on developing and analyzing the main components of the proposed co-simulation potimization control approach all simulations, testing and evaluations will be carried out by using a validated microscopic simulation model of part of the rail and road network in the Los Angeles and Long Beach area that includes the two major ports. The deliverables of the project will include the demonstration of the co-simulation optimization control approach and its benefits in upgrading current practices to a new level that takes full advantage of available technologies that include computations and automation of decisions in addition to information technologies. Our experience with traffic models indicates that even though duplicating the real world is an impossible task, simulation models provide much better information than static or equilibrium models and therefore their use in managing freight flows and traffic in general offer a strong potential for dramatic improvements
TRIS Files:	UTC, RiP
Contract Numbers:	DTRT13-G-UTC57
Funding:	100000.00
Start Date:	20150701
Performing Agencies:	National Center for Metropolitan Transportation Research School of Policy, Planning and Development 650 Childs Way, RGL 238 Los Angeles, CA 90089-0626 United States

Funding Agencies: Research and Innovative Technology Administration University Transportation Centers Program

	Washington, DC 20590 United States
Responsible Individuals:	Giuliano, Genevieve
Index Terms:	Freight traffic; Incident management; Optimization; Real time information; Routing; Service disruption; Simulation; Urban areas
Subject Areas:	Freight Transportation; Highways; Operations and Traffic Management; Planning and Forecasting
Title:	Repeatability & reproducibility: Implications of using GPS data for freight activity chains
Accession Number:	01563271
Record Type:	Component
Language:	English
Record URL:	http://dx.doi.org/10.1016/j.trb.2015.03.007
Record URL:	http://www.sciencedirect.com/science/article/pii/S0191261515000508
Abstract:	As transport modellers the authors are interested in capturing the behaviour of freight vehicles that includes the locations at which vehicles perform their activities, the duration of activities, how often these locations are visited, and the sequence in which they are visited. With disaggregated freight behaviour data being scarce, transport modellers have identified vehicle tracking and fleet management companies as ideal third party sources for global positioning system (GPS) travel data. GPS data does not provide us with behavioural information, but allows us to infer and extract behavioural knowledge using a variety of processing techniques. Many researchers remain skeptical as specific human intervention, referred to as 'expert knowledge', is often required during the processing phase: each GPS data set has unique characteristics and requires unique processing techniques and validation to extract the necessary behavioural information. Although much of the GPS data processing is automated through algorithms, human scrutiny is required to decide what algorithmic parameters as considered 'best', or at least 'good'. In this paper the authors investigate the repeatability and reproducibility (R&R) of a method that entails variable human intervention in processing GPS data. More specifically, the judgement made by an observer with domain expertise on what clustering parameters applied to GPS data best identify the facilities where commercial vehicles perform their activities. By studying repeatability the authors want to answer the question 'if the same expert analyses the GPS data more

	than once, how similar are the outcomes?', and with reproducibility the authors want to answer the question 'if different experts analyse the same GPS data, how similar are their outcomes?' The authors follow two approaches to quantify the R&R and conclude in both cases that the measurement system is accurate. The use of GPS data and the associated expert judgments can hence be applied with confidence in freight transport models.
Supplemental Notes:	Abstract reprinted with permission of Elsevier.
TRIS Files:	TRIS
Media Type:	Print
Pagination:	pp 81-92
Authors:	Joubert, Johan W Meintjes, Sumarie
Availability:	Find a library where document is available Order URL: <u>http://worldcat.org/issn/01912615</u>
Publication Date:	20150600
Serial:	Transportation Research Part B: Methodological Volume: 76 Issue Number: Publisher: Elsevier ISSN: 0191-2615 Serial URL: <u>http://www.sciencedirect.com/science/journal/01912615</u>
Index Terms:	Activity chains; Algorithms; Freight transportation; Global Positioning System; Human factors; Information processing; Mathematical models; Travel behavior; Trucks; Validation
Subject Areas:	Data and Information Technology; Freight Transportation; Highways; Planning and Forecasting; I72: Traffic and Transport Planning
Title:	Exploring the heavy goods vehicle fleet behaviour through simulations: notes from the German toll system
Accession Number:	01558366
Record Type:	Component
Language:	English
Record URL:	http://dx.doi.org/10.1049/iet-its.2013.0175
Abstract:	The automatic German toll system is both a software-intensive system

Title:	Commercial Truck Platooning
Subject Areas:	Data and Information Technology; Finance; Motor Carriers; Operations and Traffic Management; I10: Economics and Administration
Index Terms:	Automated toll collection; Germany; Human factors; Product development; Quality of service; Simulation; Software; Systems analysis; Truck driving; Trucks; Vehicle fleets
Serial:	IET Intelligent Transport Systems Volume: 9 Issue Number: 3 Publisher: Institution of Engineering and Technology ISSN: 1751-956X EISSN: 1751-9578 Serial URL: <u>http://digital-library.theiet.org/content/journals/iet-its</u>
Publication Date:	20150400
Availability:	Find a library where document is available Order URL: <u>http://worldcat.org/issn/1751956X</u>
Authors:	Pfitzinger, Bernd Macos, Dragan Jestädt, Thomas
Pagination:	pp 285-292
Media Type:	Digital/other
TRIS Files:	TRIS
Supplemental Notes:	Abstract reprinted with permission of the Institution of Engineering and Technology.
	 relying on the on-board units to collect the toll charges due – and a socio-technical system – the user can influence the system behaviour. The overall dynamic system behaviour emerges both from the technical implementation of the system and the users' interaction with the system limiting the effectiveness of common software engineering practices. Simulations are an additional tool to reduce the operational risks and to improve the performance of system development projects. The authors have developed a realistic microscopic discrete event simulation model of the automatic tolling processes to simulate the overall system behaviour at a scale of 1:1. Taking this model their research investigates the effect of the HGV fleet behaviour on the dynamic system behaviour. To that end the system simulation model is accompanied by a separate model of the HGV driving patterns.

Accession Number:	01567081
Record Type:	Project
Language:	English
Source Agency:	Texas Department of Transportation 125 E. 11th Street Austin, TX 78701-2483 United States
Source Data:	RiP Project 39904
Abstract:	Commercial Truck Platooning will perform the most practical commercial vehicle platooning effort in the U.S. Existing studies indicate platooning offers major safety and fuel saving benefits that are two critical issues for fleet operators. Truck Platooning, defined as electronically coupling two or more trucks (or vehicles) where the following truck longitudinal and lateral functions are automated to mimic the leading truck while maintain a tight distance. Texas is one of the key trucking hubs in the national supply chain, making it a perfect test bed for developing and implementing this technology. The Performing Agency or "Research Team" offers significant expertise and experience in truck automation.
TRIS Files:	RiP, STATEDOT
Contract Numbers:	0-6836
Funding:	1181094.00
-	
Start Date:	20150331
Start Date: Actual Completion Date:	
Actual Completion Date:	20150331
Actual Completion Date:	20150331 20160331 Texas A&M Transportation Institute, College Station Texas A&M University System 3135 TAMU
Actual Completion Date: Performing Agencies:	20150331 20160331 Texas A&M Transportation Institute, College Station Texas A&M University System 3135 TAMU College Station, TX 77843-3135 United States Texas Department of Transportation 125 E. 11th Street
Actual Completion Date: Performing Agencies: Funding Agencies: Responsible	20150331 20160331 Texas A&M Transportation Institute, College Station Texas A&M University System 3135 TAMU College Station, TX 77843-3135 United States Texas Department of Transportation 125 E. 11th Street Austin, TX 78701-2483 United States

Title:	Cooperative Adaptive Cruise Control (CACC) for Truck Platooning: Operational Concept Alternatives
Accession Number:	01577574
Record Type:	Monograph
Language:	English
Record URL:	http://escholarship.org/uc/item/7jf9n5wm
Source Agency:	UC Berkeley Transportation Library
Source Data:	Caltrans 2959
Abstract:	Cooperative Adaptive Cruise Control (CACC) provides an intermediate step toward a longer-term vision of trucks operating in closely coupled automated platoons. There are important distinctions between CACC and automated truck platooning. First, with CACC, only truck speed control will be automated, using vehicle to vehicle (V2V) communication to supplement forward sensors. The drivers will still be responsible for actively steering the vehicle, lane keeping, and monitoring roadway and traffic conditions. Second, while truck platooning systems have relied on a Constant Distance Gap (CDG) control strategy, CACC has relied on a Constant-Time Gap (CTG) control strategy, where the distance between vehicles is proportional to the speed. For these reasons, a series of trucks using CACC is referred to as a string, rather than a platoon. This report mainly focuses on describing the various CACC operational concept alternatives at the level of individual vehicles, local groups of vehicles and their drivers, and which alternatives should be employed in this research project. These operational concepts can be broken into four categories: string formation, steady-state cruising, string split maneuvers, and faults or abnormal operating conditions.
TRIS Files:	CALTRANS, TRIS, ATRI, USDOT, STATEDOT
Report/Paper Numbers:	UCB-ITS-PRR-2015-05
Contract Numbers:	DTFH61-13-H-00012
Media Type:	Digital/other
Pagination:	37p
OCLC:	920485096
Authors:	Nowakowski, Christopher

	Shladover, Steven E Lu, Xiao-Yun Thompson, Deborah Kailas, Aravind	
Corporate Authors:	 University of California, Berkeley California PATH Program, Institute of Transportation Studies Richmond Field Station, 1357 South 46th Street Richmond, CA 94804-4648 United States Volvo Trucks North Amercia 7900 National Service Road Greensboro, NC United States California Department of Transportation Division of Research, Innovation and System Information P.O. Box 942873 Sacramento, CA 94273-0001 United States Federal Highway Administration Exploratory Advanced Research Program 6300 Georgetown Pike McLean, VA 22101-2296 United States 	
Availability:	Find a library where document is available Order URL: <u>http://worldcat.org/oclc/920485096</u>	
Publication Date:	20150300	
Serial:	PATH Research Report Publisher: University of California, Berkeley ISSN: 1055-1425	
Index Terms:	Autonomous intelligent cruise control; Dedicated short range communications; Speed control; Traffic platooning; Trucks; Vehicle to vehicle communications	
Subject Areas:	Data and Information Technology; Freight Transportation; Operations and Traffic Management; I72: Traffic and Transport Planning	
Title:	Critical Next Steps for AV/CV Applications in Freight Operations	
Accession Number:	01552201	
Record Type:	Project	
Language:	English	
Record URL:	http://apps.trb.org/cmsfeed/TRBNetProjectDisplay.asp?ProjectID=3936	

Source Agency:	Transportation Research Board 500 Fifth Street, NW Washington, DC 20001 United States	
Source Data:	RiP Project 39006	
Abstract:	P Project 39006 nnected vehicle/automated CV/AV technologies offer potential nefits to improve safety and increase efficiency of freight and goods ovement in North America. The freight industry is extremely portant to the economic vitality of the nation. Trucking is a strong mponent of this, as over 70% of all freight is carried by truck at some ge in the supply chain. The trucking industry faces critical challenges maintaining adequate workforce. AV/CV technologies could be eful to fill in the unmet needs with automated resources, raise the tus of a career in trucking, and reduce the workload of the driver in ag-haul (and other) operations. Truck parking and rest areas are often ategically located to align with hours-of-service limitations. If hours- service were modified due to AV systems, national planning for rest as and en-route facilities could be modified. Truck platooning is mmonly identified as a near term application, but to make that a dity a variety of platooning protocols and procedures need to be fined and verified. Automated drayage and automated docking are quently noted as highly desirable by the trucking industry. The gulatory, policy, and technical aspects of AV technologies on the cking and freight operations industry need to be evaluated and commendations developed for state departments of transportation OT) and local agencies that are involved with freight operations. The earch team will review existing literature and develop a list of key ues and challenges in the regulatory, policy, and operations descape of freight system operations and identify the pain points or cas where policy and operations strategy changes are necessary to commodate (or facilitate) CV/AV deployment. In particular, truck tooning concepts should be explored and a list of near-term actions ould be developed to answer the key research and policy questions.	
Supplemental Notes:	Contract to a Performing Organization has not yet been awarded.	
TRIS Files:	TRB, RiP	
Contract Numbers:	Project 20-102(03)	
Funding:	150000.00	
Start Date:	20150201	
Funding Agencies:	Federal Highway Administration 1200 New Jersey Avenue, SE Washington, DC 20590 United States American Association of State Highway & Transportation Officials	

	 444 North Capitol Street, NW, Suite 225 Washington, DC 20001 United States National Cooperative Highway Research Program Transportation Research Board 500 Fifth Street, NW Washington, DC 20001 United States 	
Responsible Individuals:	Rogers, William C	
Index Terms:	Drayage; Freight traffic; Intelligent vehicles; Mobile communication systems; North America; Parking facilities; Policy analysis; Roadside rest areas; Traffic platooning; Trucking	
Subject Areas:	Freight Transportation; Highways; Motor Carriers; Operations and Traffic Management; Terminals and Facilities	
Title:	Truck platooning: driving the future of transportation	
Accession Number:	01560460	
Record Type:	Monograph	
Language:	English	
Record URL:	https://www.tno.nl/en/about-tno/news/2future-of-transportation-tno- whitepaper/	
Source Agency:	ARRB Group Limited 500 Burwood Highway Vermont South, Victoria 3133	
Abstract:	Truck Platooning is the future of transportation in which trucks drive cooperatively at less than 1 second apart made possible by automated driving technology. Transportation companies benefit from lower fuel consumption and improvements in (driver) productivity, while society benefits from fewer accidents, safer traffic and less congested roads, and lower carbon emissions. In this TNO whitepaper, we explain what platooning is, what kind of benefits it brings for which parties in the supply chain, and the roadmap towards deployment of platooning on Dutch and European roads. Developments in the underlying Cooperative Adaptive Cruise Control (CACC) technology have been ongoing for years, yet widescale deployment of truck platooning is a system-wide innovation challenge that requires a concerted approach of all stakeholders in society. For instance, policy-makers have to contribute supporting legislation, regulators such as the RDW need to develop safety-focussed type approval methodologies, truck	

	manufacturers and OEM should strive for plug-and-plug compatibility of platooning systems, insurance firms are required to develop new liability coverage schemes, and shippers can urge their carriers and logistics service providers to form as many platoons as possible and change their supply chains, while other road users need to learn to accommodate the two-truck road trains. Right now the political and economic climate is positive for a broad deployment of platooning as initial legislation amendments are proposed to allow testing and experimentation on Dutch roads. For this system-wide innovation, we suggest to establish a Shared Innovation Programme, based on open innovation principles. In the programme, we can jointly work towards commercial deployment of platooning to implement a safe, reliable and efficient two-truck platooning concept by 2020.
TRIS Files:	ATRI
Pagination:	35p
Authors:	Janssen, R Zwijnenberg, H Blankers, I de Kruijff, J
Corporate Authors:	TNO Delft
Publication Date:	20150200
Index Terms:	Advanced vehicle control systems; Advanced vehicle control systems; Advanced vehicle control systems (AVCS); Bunching; Bunching; Innovation; Innovation; Intelligent transport system; Policy; Policy; Research; Research and development; Truck; Trucks
Subject Areas:	Motor Carriers; Policy; Research
Title:	Innovative and Automated Freight Systems Assess
Accession Number:	01569095
Record Type:	Project
Language:	English
Source Agency:	Texas Department of Transportation 125 E. 11th Street Austin TX 78701-2483 United States

Austin, TX 78701-2483 United States

Source Data: RiP Project 39967

Abstract:	Many innovative and automated freight delivery strategies and technologies have been proposed to address the future freight needs of Texas' growing population. The Receiving Agency (hereafter referred to as "Texas Department of Transportation" or "TXDOT") and local transportation planners need to evaluate operational changes or technology applications to ensure continued, timely flow of commercial freight through the Texas transportation system. Emerging freight delivery technologies, such as automated freight vehicles or airborne small package delivery, and innovative operational freight strategies, such as nighttime off-peak hour deliveries or conversion of managed lanes to truck-only use during high port traffic periods. Are potential ways to better use existing infrastructure. Changes in buying habits of consumer goods toward direct home package delivery also could dramatically shift distribution patterns and increase the number of intercity and local delivery trucks on TxDOT roadways. The primary objective of this project is to establish a process to evaluate freight Operational changes or technology applications in order to ensure continued timely flow of commercial freight through the Texas transportation system. This project will develop and adapt the necessary evaluation metrics for future use. This project will also access several currently proposed freight strategies and technologies to determine which of these should be further evaluated for implementation on the Texas transportation system in future project phases.	
TRIS Files:	RIP, STATEDOT	
Contract Numbers:	0-6837	
Funding:	517892.00	
Start Date:	20150130	
Actual Completion Date:	20151231	
Performing Agencies:	Texas A&M Transportation Institute, College Station Texas A&M University System 3135 TAMU College Station, TX 77843-3135 United States	
Funding Agencies:	Texas Department of Transportation 125 E. 11th Street Austin, TX 78701-2483 United States	
Responsible Individuals:	Odell, Wade	

operations; Texas; Truck lanes

Subject Areas:Aviation; Freight Transportation; Operations and Traffic Management;
Planning and Forecasting; Terminals and Facilities

Title:	Facility Layout for an Automated Guided Vehicle System	
Accession Number:	01574281	
Record Type:	Component	
Language:	English	
Record URL:	http://dx.doi.org/10.1016/j.procs.2015.07.007	
Record URL:	http://www.sciencedirect.com/science/article/pii/S1877050915014829	
Abstract:	The facility layout problem (FLP) aims to minimize the material handling costs by determining the most efficient arrangement of facilities within a space. Among several types of layout structure, bay layout is used in a wide variety of manufacturing contexts of which the workstations are assigned to several parallel bays. Concerning the world trend in automation and advantages of flexibility and space utilization, the Automated Guided Vehicle (AGV) systems are considered in this paper to address the bay layout problems. A two-stage model called Spine Bay Layout is developed to allocate the workstations into several inter-bay systems such that not only the material handling cost can be minimized, but also the flexibility in applications can be enhanced. In order to compare with the conventional system and facilitate the flexible applications, an extended model is presented for the Single Spine Bay Layout. The results show that in comparison with the previous research, the proposed model reduces not only the total cost; but also the solution time. Moreover, due to the high complexity of the model, a sub-model called Allocation Model is proposed to provide the feasibility condition of the two-stage model.	
Supplemental Notes:	© 2015 Hsiao-Fan Wang and Ching-Min Chang. Published by Elsevier B.V.	
TRIS Files:	TRIS	
Media Type:	Digital/other	
Pagination:	pp 52-61	
Authors:	Wang, Hsiao-Fan Chang, Ching-Min	

Availability:	Find a library where document is available Order URL: <u>http://worldcat.org/issn/18770509</u> 20150000	
Publication Date:	20150000	
Conference:	3rd International Conference on Information Technology and Quantitative Management, ITQM 2015 Location: Rio De Janeiro , Brazil Date: 20150721 - 20150724	
Serial:	Procedia Computer Science Volume: 55 Publisher: Elsevier ISSN: 1877-0509 Serial URL: <u>http://www.sciencedirect.com/science/journal/18770509</u>	
Index Terms:	Automated guided vehicle systems; Costs; Facilities; Handling and storage; Workplace layout	
Subject Areas:	Freight Transportation; Planning and Forecasting; Terminals and Facilities; I72: Traffic and Transport Planning	

Title:	Automated Vehicles and the Rethinking of Mobility and Cities	
Accession Number:	01554691	
Record Type:	Component	
Language:	English	
Record URL:	http://dx.doi.org/10.1016/j.trpro.2015.01.002	
Record URL:	http://www.sciencedirect.com/science/article/pii/S2352146515000034	
Abstract:	http://www.sciencedirect.com/science/article/pii/S2352146515000034 The project CityMobil2 has carried out a forward-looking exercise to investigate alternative cybermobility scenarios, including both niche and large-market innovations, and their impacts on European cities and their transport systems. The paper describes the current status of and main trends in automated vehicles, a preliminary vision of the future city with mobility supported mainly by automated vehicles, and freight distribution. The expected positive impacts derive from the development of car sharing, the reduction of space required for parking vehicles, the possibilities for older people or those with disabilities to use cars, the enhancement of safety, and the improvement of efficiency of the transport system.	
Supplemental Notes:	© 2015 Adriano Alessandrini et al. Published by Elsevier B.V.	
TRIS Files:	TRIS	

Media Type:	Digital/other	
Pagination:	pp 145-160	
Authors:	Alessandrini, Adriano Campagna, Andrea Site, Paolo Delle Filippi, Francesco Persia, Luca	
Availability:	Find a library where document is available Order URL: <u>http://worldcat.org/issn/23521465</u>	
Publication Date:	20150000	
Serial:	Transportation Research Procedia Volume: 5 Issue Number: Publisher: Elsevier ISSN: 2352-1465 Serial URL: <u>http://www.sciencedirect.com/science/journal/23521465/</u>	
Index Terms:	Aged; Europe; Intelligent vehicles; Mobility; Parking; Persons with disabilities; Urban areas; Vehicle sharing	
Subject Areas:	Highways; Planning and Forecasting; Public Transportation; Vehicles and Equipment; I20: Design and Planning of Transport Infrastructure	
	and Equipment; I20: Design and Planning of Transport Infrastructure	
Title:	and Equipment; I20: Design and Planning of Transport Infrastructure Lehrte MegaHub to open in 2017	
Title: Accession Number:		
	Lehrte MegaHub to open in 2017	
Accession Number:	Lehrte MegaHub to open in 2017 01541638	

	automated container sorting system is the most innovative element of the project.
TRIS Files:	TRIS
Media Type:	Print
Pagination:	pp 67-68, 70
Authors:	Muller, Christopher
Availability:	Find a library where document is available Order URL: <u>http://worldcat.org/issn/03735346</u>
Publication Date:	20140900
Serial:	Railway Gazette International Volume: 170 Issue Number: 9 Publisher: DVV Media Group ISSN: 0373-5346 Serial URL: <u>http://www.railwaygazette.com/about-us.html</u>
Index Terms:	Case studies; Container handling; Freight transportation; Germany; Innovation; Intermodal terminals; Railroads; Sorting; Water transportation
Subject Areas:	Construction; Freight Transportation; Marine Transportation; Railroads; Terminals and Facilities; I50: Construction and Supervision of Construction

Title:Online Container Transport Planning with Decision Trees based on Offline
Obtained Optimal Solutions

- Accession 01542295
- **Record Type:** Component
- Language: English
- Record URL: http://www.icms.polyu.edu.hk/Proceedings/Proceedings%20of%20IFSPA%202014.pdf
- Abstract: Hinterland networks for container transportation require planning methods in order to increase efficiency and reliability of the inland road, rail and waterway connections. Earlier proposed centralised methods can in theory find the optimal solution for the multimodal inland transportation problem in retrospect, but are not suitable when information becomes gradually available. Besides real-time up-to-date information on inland services necessary for applying these methods in practice is typically not available. In this paper the authors aim to derive online decision rules for suitable

allocations of containers to inland services by analysing the solution structure of a centralised optimisation method used offline. The online decision support system (DSS) must be able to instantaneously allocate incoming orders to suitable services, without the need for continuous planning updates. Such a DSS is beneficial, as it is easier to implement in the current practice of container transportation than a fully automated planning system, while providing a better performance. A case study is used to show the method's purpose and to compare the quality of the resulting plan with alternatives.

Supplemental Notes:	Abstract reprinted with permission of Hong Kong Polytechnic University	
TRIS Files:	TRIS	
Media Type:	Digital/other	
Pagination:	pp 50-60	
Authors:	van Riessen, Bart Negenborn, Rudy R Dekker, Rommert	
Monograph Title:	Proceedings of the International Forum on Shipping, Ports and Airports (IFSPA) 2014: Sustainable Development in Shipping and Transport Logistics	
Monograph Accession Number:	01540053	
Corporate Authors:	Hong Kong Polytechnic University Department of Logistics and Maritime Studies Tung International Centre for Maritime Studies Hong Kong China	
Editors:	Chin-Shan Lu Petrus Choy Kee-Hung Lai YH Venus Lun Tsz Leung Yip	
Publication Date:	20140800	
Conference:	International Forum on Shipping, Ports and Airports (IFSPA) 2014: Sustainable Development in Shipping and Transport Logistics Location: Hong Kong , China Date: 20140519 - 20140521 Sponsors: Hong Kong Polytechnic University	
Index Terms:	Case studies; Containerization; Decision support systems; Decision trees; Hinterlands;	

Intermodal services; Logistics; Optimization; Real time information

SubjectFreight Transportation; Highways; Marine Transportation; Planning and Forecasting;Areas:Railroads; I72: Traffic and Transport Planning

Title:	Connected and Autonomous	Vehicles 2040 Vision
The:	Connecteu anu Autonomous	venicles 2040 vision

Accession Number: 01539697 Record Type: Monograph

Language: English

Record URL: https://www.google.com/url?sa=t&rct=j&...kipjOPZJdIGA&sig2=akTbtWT7uy0Qc3i2aPVzPA

- Abstract: The Pennsylvania Department of Transportation (PennDOT) commissioned a one-year project, Connected and Autonomous Vehicles 2040 Vision, with researchers at Carnegie Mellon University (CMU) to assess the implications of connected and autonomous vehicles on the management and operation of the state's surface transportation system. This report explores the impacts of connected and autonomous vehicles on design and investment decisions, communication devices investment, real-time data usage, existing infrastructure, workforce training needs, driver licensing and freight flow as they relate to PennDOT. For each of these areas, a set of recommendations has been provided. As connected and autonomous technologies are advancing, it is recommended that PennDOT take these actions in a timely manner. A timeline for the recommended actions has been provided to help PennDOT plan accordingly. The timelines are based on current available information and the time frames are likely to change over time.
- TRIS Files: TRIS, ATRI, USDOT, STATEDOT

Report/Paper Numbers:	FHWA-PA-2014-004-CMU WO 1
Contract Numbers:	CMUIGA2012 - CMU WO 1
Media Type:	Digital/other
Pagination:	163p
Authors:	Hendrickson, Chris Biehler, Allen Mashayekh, Yeganeh
Corporate Authors:	Carnegie Mellon University Pittsburgh, PA United States Pennsylvania Department of Transportation

	Bureau of Planning and Research, 400 North Street, 6th Floor Harrisburg, PA 17120-0064 United States Federal Highway Administration 1200 New Jersey Avenue, SE Washington, DC 20590 United States
Availability:	National Technical Information Service 5301 Shawnee Road Alexandria, VA 22312 United States
Publication Date:	20140710
Edition:	Final Report
Period Covered:	7/11/2013 - 7/10/2014
Index Terms:	Driver licensing; Freight traffic; Infrastructure; Intelligent vehicles; Investments; Mobile communication systems; Pennsylvania Department of Transportation; Real time information; Recommendations; Training
Subject Areas:	Highways; Planning and Forecasting; Vehicles and Equipment; I20: Design and Planning of Transport Infrastructure; I90: Vehicles

Title:	Huge UPS hub is big on freight
Accession Number:	01535546
Record Type:	Component
Language:	English
Record URL:	http://www.progressiverailroading.com/and-more-cargo-is-on-the- horizon40371
Abstract:	The United Parcel Service (UPS) operates the Worldport complex, a major hub next to the Louisville International Airport. Worldport generates a huge amount of freight each day, which is sorted using a highly-efficient automated system and sent on to final destinations. Most packages are collected during the day and sorted at smaller hubs around the world before being air-freighted to Worldport, where they arrive around midnight. In addition to air freight, the complex distributes rail freight through a nearby intermodal terminal. Recent expansions to the complex have improved its capacity, and officials are looking toward further development.
TRIS Files:	TRIS

Media Type:	Print
Pagination:	pp 26, 28, 30-31
Authors:	Stagl, Jeff
Availability:	Find a library where document is available Order URL: <u>http://worldcat.org/oclc/4175009</u>
Publication Date:	20140500
Serial:	Progressive Railroading Volume: 57 Issue Number: 5 Publisher: Trade Press Publishing Corporation ISSN: 0033-0817 OCLC: 4175009 Serial URL: <u>http://www.progressiverailroading.com</u>
Index Terms:	Air cargo; Delivery service; Freight terminals; Freight trains; Hubs; Intermodal terminals; Logistics; Louisville (Kentucky); United Parcel Service
Subject Areas:	Aviation; Freight Transportation; Planning and Forecasting; Railroads; Terminals and Facilities; I72: Traffic and Transport Planning
Title:	On-board intelligence for the Furbot: a new concept for urban freight transport
Accession Number:	01540789
Record Type:	Component
Language:	English

Record URL:	http://tra2014.traconference.eu/papers/pdfs/TRA201	4_Fpaper_18047.pdf

Source Agency: Swedish National Road and Transport Research Institute (VTI) Linköping SE-581 95 Sweden

Abstract: The Furbot project proposes to develop a new concept for urban freight transport. The novelty of the concept is twofold. A new architecture of light-duty, full-electrical vehicle is proposed. A great effort is devoted to energy management: new power train layout integrated in the chassis; new battery and energy management system; regenerative braking... But if attention is given to energy management for one vehicle, the Furbot concept consists in having a fleet of several vehicles offering a new sustainable and very adaptable (evolvable) urban freight transport system. In this article, we focus on the intelligent on-board unit. It has

Title:	SARTRE automated platooning vehicles
Subject Areas:	Energy; Freight Transportation; I90: Vehicles
Index Terms:	Commodities; Delivery vehicle; Delivery vehicles; Electric vehicle; Electric vehicles; Freight; Handling (mech); Handling and storage; Robot; Robots
Conference:	Transport Research Arena (TRA) 5th Conference: Transport Solutions from Research to Deployment Location: Paris , France Date: 20140414 - 20140417 Sponsors: European Commission; Conference of European Directors of Roads (CEDR); European Road Transport Research Advisory Council (ERTRAC); WATERBORNE ^{TP} ; European Rail Research Advisory Council (ERRAC); Institut Francais des Sciences et Technologies des Transports, de l'Aménagement et des Réseaux (IFSTTAR); Ministère de l'Écologie, du Développement Durable et de l'Énergie
Publication Date:	20140400
Corporate Authors:	Institut Francais des Sciences et Technologies des Transports, de l'Aménagement et des Réseaux (IFSTTAR) 14-20 bd Newton, Cité Descartes, Champs su Marne 77447 Marne la Vallée Cedex 2 France
Monograph Accession Number:	01528196
Monograph Title:	Transport Research Arena (TRA) 2014 Proceedings
Authors:	Pollard, Evangeline Pérez, Joshué Nashashibi, Fawzi
Pagination:	10p
TRIS Files:	VTI, TRIS, ATRI
	mainly two functions. First, it offers assistance to the driver: emergency braking, obstacle avoidance, parking assistance, itinerary assistance or adaptive speed control. Second, it proposes automation abilities for the loading/unloading of the payload. Regarding the multi-sensorial perception system, an intelligent human-machine interface is also conceived in order to let the driver choose between the driving modes (fully manual, assisted, automated loading), in order to provide him general information (map, mission, fleet state) and warn him about safety issues, power caution and vehicle diagnosis.

Accession Number:	01530678
Record Type:	Component
Language:	English
Record URL:	http://tra2014.traconference.eu/papers/pdfs/TRA2014_Fpaper_20075.pdf
Source Agency:	ARRB Group Limited 500 Burwood Highway Vermont South, Victoria 3133
Abstract:	The SARTRE project develops and integrates solutions to allow trucks and cars to drive in platoons to reduce fuel consumption, increase safety, improve road congestion and increase driver convenience. The lead vehicle in the platoon is driven normally and the following vehicles are automated, allowing the drivers to perform other tasks. The platoon vehicles operate on conventional motorways in a mixed environment with other non-platoon traffic, without requiring changes to the road infrastructure. A demonstration system with two trucks and three cars was operated on test tracks and on the public motorway at speeds of up to 90 km/h and gap sizes from 4-25m. They were used to measure the fuel consumption gains at a range of inter-vehicle gaps, demonstrating the potential for significant fuel savings for both trucks and cars. The business case for the introduction of automated platooning systems in trucks and cars was investigated, and estimates for the costs as well as the benefits were evaluated.
TRIS Files:	VTI, TRIS, ATRI
Pagination:	9p
Authors:	Chan, E
Monograph Title:	Transport Research Arena (TRA) 2014 Proceedings
Monograph Accession Number:	01528196
Corporate Authors:	Institut Francais des Sciences et Technologies des Transports, de l'Aménagement et des Réseaux (IFSTTAR) 14-20 bd Newton, Cité Descartes, Champs su Marne 77447 Marne la Vallée Cedex 2 France
Publication Date:	20140400
Conference:	Transport Research Arena (TRA) 5th Conference: Transport Solutions from Research to Deployment Location: Paris , France Date: 20140414 - 20140417 Sponsors: European Commission; Conference of European Directors of

Index Terms:	Roads (CEDR); European Road Transport Research Advisory Council (ERTRAC); WATERBORNE ^{TP} ; European Rail Research Advisory Council (ERRAC); Institut Francais des Sciences et Technologies des Transports, de l'Aménagement et des Réseaux (IFSTTAR); Ministère de l'Écologie, du Développement Durable et de l'Énergie Advanced vehicle control systems; Advanced vehicle control systems; Advanced vehicle control systems (AVCS); Automated highway systems; Automated highway systems (AHS); Automobiles; Benefit cost analysis; Bunching; Bunching; Car; Cost benefit analysis; Fuel consumption; Fuel consumption; Intelligent transport system; Test track; Test tracks; Trucks
Subject Areas:	Energy; Motor Carriers; Operations and Traffic Management
Title:	Rail trends recap : shared strategies, mixed signals
Accession Number:	01521313
Record Type:	Component
Language:	English
Source Agency:	Northwestern University Transportation Library
Abstract:	From growing pains to safety to regulation, the rail industry will cross many challenges in the year ahead, and they all affect shippers. Inbound logistics bring you abroad with Rail Trends conference coverage.
TRIS Files:	TLIB
Pagination:	p. 193-202
OCLC:	871269879
Authors:	O'Reilly, Joseph
Availability:	Available from Northwestern University Transportation Library through interlibrary loan or document delivery Order URL: <u>http://www.library.northwestern.edu/transportation/services.html</u> Find a library where document is available Order URL: <u>http://worldcat.org/oclc/871269791</u>
Publication Date:	20140100
Period Covered:	Jan. 2014
Serial:	Inbound Logistics

	Volume: 34 Issue Number: 1 Publisher: Thomas Publishing Company ISSN: 0888-8493 OCLC: 21894848 Serial URL: http://www.inboundlogistics.com
Index Terms:	Commodities; Freight service; Railroads; United States
Subject Areas:	Freight Transportation; Railroads

Freight Container Mobility

Google Search

This search basically yielded industry products to use, such as shipping containers or truck mounted cranes. 10-9-15

Container Mobility Leading Edge Technology for TEU's in Trucking Industry

http://containermobility.com/#

Container Mobility Co. uses an innovative crane truck. They have the capability to deliver containers up to 80,000 lbs or 36 tonnes into specific positions, including tight spots that traditional truck deliveries cannot handle.

Shipping Containers for Sale

https://www.bslcontainers.com/shipping-container-manufacturers/

Deployable Container Solutions- for Military Use

http://www.dytecna.co.uk/business-areas-new/systems-integration/deployable-container-solutions/

Dytecna design and supply containers and shelters for a wide range of demanding applications. Bespoke solutions are tailored exactly to client requirements and delivered by a team with a wealth of experience, capability and engineering excellence. Exsel Dytecna has extensive experience in the design, production and installation of a variety of mobile, static and special to type systems.

Container Terminal- Handling, Transport- Wikipedia https://en.wikipedia.org/wiki/Container_terminal

Operations Research at Container Terminals: a Literature Update OR Spectrum Jan 2008 Springer International Publishing http://link.springer.com/chapter/10.1007%2F3-540-26686-0_1#page-1_ Abstract: The current decade sees a considerable growth in worldwide container transportation and with it an indispensable need for optimization. Also the interest in and availability of academic literatures as well as case reports are almost exploding. With this paper an earlier survey which proved to be of utmost importance for the community is updated and extended to provide the current state of the art in container terminal operations and operations research. Keywords: Container terminal Logistics Planning Optimization Simulation

Problem: Must pay to read this article

STRC Swiss Transportation Research Conferences Lausanne, Switzerland http://www.strc.ch/

Optimization of operations in container terminals: hierarchical vs integrated approaches STRC Swiss Transportation Research Conference Sept 2010 Lausanne, Switzerland http://www.strc.ch/conferences/2010/Vacca.pdf

Abstract

Over the last years, international sea freight container transportation has grown dramatically and container terminals play nowadays a key role within the global shipping network. Terminal's operations have received increasing interest in the scientific literature and operations research techniques are more and more used to improve efficiency and productivity.

In this work we provide an overview of container terminal's operations and associated decision problems. We review state-of-the-art optimization approaches in terminal's management and we discuss what are in our opinion the current research trends. In particular, we focus on the following streams: the integrated optimization of interdependent decision problems, the analysis of issues related to traffic congestion in the yard and the tactical planning of operations.

The discussion is based on the Tactical Berth Allocation Problem (TBAP), an integrated decision problem that deals with the simultaneous optimization of berth allocation and quay crane assignment. Yard housekeeping costs are also taken into account in the objective function. We use the TBAP as a case study to illustrate the benefits of an integrated optimization approach. A comparative analysis with the traditional hierarchical solution approach is provided. Computational results based on real-world data provided by the MCT (port of Gioia Tauro, Italy) show that the additional computational effort required by the integrated optimization approach allows for more efficient solutions.

Keywords: container terminals, berth allocation, quay crane assignment, integrated optimization

STRC- A Multi-Modal Network for MATsim- traffic simulation, map routes, performance and routing http://www.strc.ch/conferences/2015/Boesch_Ciari.pdf

The approach presented in this paper enables the generation of fully-multimodal MATSim networks and schedules from open data. Only fully-multimodal networks allow the simulation of competition for road capacity between PT and private transport. They are therefore a necessary part of transport simulations in a time when limited road capacity is an issue not only but especially in urban areas. The immense effort that must be invested in any road capacity expansion today, and which is more and more difficult to justify given environmental and social trends, exacerbates the problem and makes it even more relevant. Projects such as NetCap search for alternative approaches to solve this problem. An optimization of the PT supply can lead to capacity increase, but it must be implemented with political sensitivity. The support and review of this optimization with new approaches, such as MFDs in NetCap, enable new solutions.

Rail Infrastructure Maintenance: A new Approach Freight System Swiss Technology Research Conference Emile Quinet Paris School of Economics Keynote Speech 2014 http://www.strc.ch/conferences/2014/Quinet.pdf

Several European rail lines were compared with mathematical economics equations. Principle drawn from technical analysis: At the start from a renewal, quality of service is high Progressively, as long as the time elapses, quality of service decreases due to traffic damages, and can be increased through current maintenance. As time elapses, the maintenance level necessary to maintain quality of service is higher, as damages are linked to cumulated traffic. At some point of time, it is better to renew the track than to continue current maintenance.

There are so many articles that may be of interest at this STRC website it would take a few days to read and go through all of these.

TRID Search

Best Topic Found

Title:	Modeling Public Policies on Urban Freight Distribution: Tackling Emissions, Congestion, and Logistics Costs
Accession Number:	01555493
Record Type:	Component
Language:	English
Order URL:	http://amonline.trb.org/
Source Data:	Transportation Research Board Annual Meeting 2015 Paper #15-3578
Abstract:	The urban environment, logistics performance, and cities' economic competitiveness can benefit greatly from programs that improve logistics efficiency and distribution networks, and as such, these improvements should be on policymakers' radar. Since decisions originating in the private sector affect cities' mobility and green-house- gas (GHG) emission levels, appropriate government responses to these issues are fundamental to achieve sustainable development in urban environments. The objective of this work is to increase the understanding on how policies focused on improving urban goods movement, such as dedicated infrastructure (freight corridors and platforms), traffic regulations (time window deliveries and vehicle constraints), city logistics network optimization, and voluntary cooperation (to achieve better consolidation levels between shippers and carriers), can contribute to economic and social development in

	metropolitan areas, whilst reducing or minimizing the emissions of GHGs. The authors developed a mathematical model to simulate the impacts that different policies could have on logistics costs, traffic level, congestion, and emissions.
Supplemental Notes:	This paper was sponsored by TRB committee AT025 Urban Freight Transportation.
TRIS Files:	TRIS, TRB, ATRI
Report/Paper Numbers:	15-3578
Media Type:	Digital/other
Pagination:	12p
Authors:	Fioravanti, Reinaldo
	Guerrero, Pablo Chung Cho, Eun
Monograph Title:	TRB 94th Annual Meeting Compendium of Papers
	TRD 94ar Minuar Meeting Compendium of Lapers
Monograph Accession Number:	01550057
Corporate Authors:	Transportation Research Board 500 Fifth Street, NW Washington, DC 20001 United States
Availability:	Transportation Research Board Business Office 500 Fifth Street, NW Washington, DC 20001 United States
Publication Date:	20150000
Conference:	Transportation Research Board 94th Annual Meeting Location: Washington DC, United States Date: 20150111 - 20150115
Index Terrer	Sponsors: Transportation Research Board
Index Terms:	Costs; Economic development; Logistics; Mathematical models; Pollutants; Public policy; Sustainable development; Traffic congestion; Urban goods movement

Regulations

Title:	NAFTA at 20: Time to open the internal borders of North American to cabotage
Accession Number:	01577498
Record Type:	Component
Language:	English
Record URL:	http://dx.doi.org/10.1016/j.rtbm.2015.07.002
Record URL:	http://www.sciencedirect.com/science/article/pii/S2210539515000309
Abstract:	The deeply integrated North American economy depends on efficient freight transport systems. This essay examines cabotage in Canada, the U.S. and Mexico from an economic and policy perspective. Cabotage is restricted by a web of regulations in North America that remain pervasive and continue to impose significant restraints on freight transportation. Liberalizing cabotage could improve efficiency/productivity, increase trade opportunities and regional economic integration. Open cabotage could also reduce greenhouse gas emissions. However, reform is difficult because these regulations are linked to tax, immigration and other customs issues and because they protect the interests of domestic transport industries. The creation of a North American trading bloc is a work in progress. While various initiatives since the North American Free Trade Agreement (NAFTA) have failed to advance cabotage, the authors of this report remain optimistic that freer trade in transportation is inevitable.
Supplemental Notes:	Abstract reprinted with permission of Elsevier.
TRIS Files:	TRIS
Media Type:	Digital/other
Pagination:	pp 4-14
Authors:	Blank, Stephen Prentice, Barry E
Availability:	Find a library where document is available Order URL: <u>http://worldcat.org/issn/22105395</u>
Publication Date:	20150900
Serial:	Research in Transportation Business & Management Volume: 16 Publisher: Elsevier ISSN: 2210-5395

Serial URL: http://www.sciencedirect.com/science/journal/22105395

Index Terms:Cabotage; Economic factors; Environmental impacts; North America; North America
Free Trade Agreement; Policy; Productivity; Regulatory reformSubject
Areas:Freight Transportation; Planning and Forecasting; I72: Traffic and Transport Planning

Operations

Smart Freight Transportation

Title:	Smart Freight: Applications of Information and Communications Technologies to Freight System Efficiency
Accession Number:	01544636
Record Type:	Monograph
Language:	English
Record URL:	http://www.aceee.org/files/pdf/white-paper/smart-freight-ict.pdf
Abstract:	This paper focuses on the energy savings potential of information and communications technology (ICT) as applied to freight transportation. It identifies savings that can be realized by reducing miles traveled, improving the efficiency of freight networks, and maximizing freight vehicle operations. Case studies are included of companies using ICT to reduce emissions and conserve fuel. Barriers to implementation are reviewed, recommendations made, and the role of public policy is examined.
TRIS Files:	TRIS
Media Type:	Digital/other
Pagination:	29p
Authors:	Langer, Therese Vaidyanathan, Shruti
Corporate Authors:	American Council for an Energy-Efficient Economy 529 14th Street NW, Suite 600 Washington, DC 20045-1000 United States
Publication Date:	20140700
Index Terms:	Case studies; Communication; Freight transportation; Fuel consumption; Information technology; Intelligent transportation systems; Pollutants; Public policy; Recommendations; Technological innovations

Ports	
Title:	Multimodal Freight Distribution to Support Increased Port Operations
Accession Number:	01566137
Record Type:	Project
Language:	English
Record URL:	http://www.matsutc.org/multimodal-freion-to-support-increased- port-operations/
Source Agency:	Mid-Atlantic Transportation Sustainability Center Charlottesville, Virginia United States
Source Data:	RiP Project 37246
Abstract:	It is projected that more containers will pass through the major ports of the mid-Atlantic region with the completion of the Panama Canal expansion, and as shippers and carriers find it more efficient to move cargo on larger container vessels. As a result, not only is it expected that a larger number of containers will be unloaded/loaded every time a New-Panamax vessel docks at a port, it is also widely anticipated that these larger ships will concentrate among a small of number ports, particularly those that have deeper channel depths, such as the Port of Virginia. It is going to be vital to the regional economies and to the surrounding areas to be prepared to handle the anticipated increase in container traffic with energy-efficient and environmentally-friendly technologies and transport options. In particular, efficiency in handling high-volume of containers at the ports and in transporting containers beyond the ports is critical. This study will bring together researchers from multiple universities to investigate strategies to optimize container handling inside the terminals, to more heavily utilize inland waterways and rail systems, and to optimize logistics to reduce Greenhouse Gas emissions while maintaining mobility needs. In particular, the team from Old Dominion University (ODU) will investigate port operations strategies where both rail and truck traffic in and out of the port is considered. Interactions between these transport modes, and staging and handling of containers within the port will be investigated. Motivated by the rail connectivity available at the Port of Virginia.

ODU will lead the research effort that will explore the use of rail to more efficiently move cargo out of the port. The team will explore optimization and simulation methods to study various complex interactions and factors influencing the flow of containers over multiple modes. These methods will help identify more cost and energy efficient strategies to handle large volume of container traffic inside the terminals. New models will be developed to understand the feasibility and potential benefits of such strategies. The team from VT will support research in the area of optimization of freight movement within the context of fuel consumption and emission modeling which requires the development of fuel consumption and emission models for the various types of freight modes. Virginia Tech's team will focus on developing the fuel consumption and emission models for various ground transportation modes including trucks and trains. The focus will be on developing models that can be easily calibrated using publically available data. In addition, the VT team will consider developing smart systems to reduce the energy consumption of freight transport (e.g. eco-cruise control systems, eco-adaptive cruise control systems, etc.). While optimizations for network-wide freight logistics have been focused on either flow maximization or total system travel time minimization, little research has focused on the greenhouse gas emissions and fuel consumptions in the context of multimodal freight logistics. The team from UVA will work on formulating and developing an optimization approach for multimodal freight networks to minimize greenhouse gas emissions or fuel consumption. Implementation Potential implementation of project outcomes During this research, the team members will work closely with the Port of Virginia, rail lines (e.g. Norfolk Southern), and the private industry. The developed tools, techniques, and solutions will be shared with them for potential implementation. Various components and algorithms for eco-cruise control systems, eco-adaptive cruise control systems, and eco-routing systems will be developed for more energy-efficient transportation of freight. Impacts Expected benefits and impacts A new suite of modeling and simulation tools and methodologies is envisioned to result from this research that can be used throughout the nation to combat congestion at the ports in a post panama canal expansion era. Development of fuel consumption and emission models for various ground transportation modes including trucks and trains. Impacts of various modes of transporting containers on greenhouse gas emission UTC, RiP

Contract Numbers: DTRT13-G-UTC33

Funding: 258000.00

TRIS Files:

Start Date:	20150101
Actual Completion Date:	20151231
Performing Agencies:	Virginia Polytechnic Institute and State University, Blacksburg Blacksburg, VA 24061 United States University of Virginia, Charlottesville Charlottesville, VA 22902 United States Old Dominion University Norfolk, VA 23529 United States
Funding Agencies:	Research and Innovative Technology Administration University Transportation Centers Program Washington, DC 20590 United States Virginia Polytechnic Institute and State University, Blacksburg Blacksburg, VA 24061 United States Old Dominion University Norfolk, VA 23529 United States
Responsible Individuals:	Parkany, Emily
Index Terms:	Cargo handling; Container handling; Container terminals; Freight traffic; Inland waterways traffic; Middle Atlantic States; Multimodal transportation; Panama Canal; Port operations; Truck tractors; Trucks
Subject Areas:	Freight Transportation; Highways; Marine Transportation; Terminals and Facilities
Title:	Energy efficiency and time charter rates: Energy efficiency savings recovered by ship owners in the Panamax market
Accession Number:	01535320
Record Type:	Component
Language:	English
Record URL:	http://dx.doi.org/10.1016/j.tra.2014.05.004
Record URL:	http://www.sciencedirect.com/science/article/pii/S0965856414001189
Abstract:	This paper presents the first analysis on how financial savings arising from energy efficient ships are allocated between owners and those hiring the ships. This is an important undertaking as allocation of financial savings is expected to have an impact on the incentives faced

	by ship owners to invest in more energy efficient vessels. The authors focus on the dry bulk Panamax segment as it contributes to around 50 Mt (5%) of total CO ₂ emissions from shipping in 2007 and therefore its importance in terms of environmental impact should not be neglected. The time charter market represents a classical example of the principal–agent problem similar to the tenant–landlord problem in the buildings sector. The authors discovered that on average only 40% of the financial savings delivered by energy efficiency accrue to ship owner for the period 2008–2012. The finding that only part of the savings are recouped by shipowners affecting their incentives towards energy efficiency could consequently have implications on the type of emission reduction policies opted at both, global and regional levels.
Supplemental Notes:	Abstract reprinted with permission of Elsevier.
TRIS Files:	TRIS
Media Type:	Web
Pagination:	pp 173-184
Authors:	Agnolucci, Paolo Smith, Tristan Rehmatulla, Nishat
Availability:	Find a library where document is available Order URL: <u>http://worldcat.org/issn/09658564</u>
Publication Date:	20140800
Serial:	Transportation Research Part A: Policy and Practice Volume: 66 Issue Number: Publisher: Elsevier ISSN: 0965-8564 Serial URL: <u>http://www.sciencedirect.com/science/journal/09658564</u>
Index Terms:	Carbon dioxide; Dry bulk carriers; Energy consumption; Panamax (Ship dimensions); Pollutants; Savings; Shipowners
Subject Areas:	Energy; Environment; Finance; Freight Transportation; Marine Transportation; I10: Economics and Administration; I15: Environment

Trucks

Title:	Heavy Truck Cooperative Adaptive Cruise Control: Evaluation, Testing, and Stakeholder Engagement for Near Term Deployment: Phase One Final Report
Accession Number:	01567393
Record Type:	Monograph
Language:	English
Record URL:	http://atri-online.org/2015/05/27/4410/
Abstract:	Under the Federal Highway Administration (FHWA) Exploratory Advanced Research project "Heavy Truck Cooperative Adaptive Cruise Control: Evaluation, Testing, and Stakeholder Engagement for Near Term Deployment" this document provides a summary of Phase I results for evaluating the commercial feasibility of Driver Assistive Truck Platooning (DATP). DATP is a form of Cooperative Adaptive Cruise Control for heavy trucks (two truck platoons). DATP takes advantage of increasing maturity of vehicle-vehicle (V2V) communications, plus widespread deployment of DSRC-based V2V connectivity expected over the next decade, to improve freight efficiency, fleet efficiency, safety, and highway mobility, plus reduce emissions. Notably, truck fleets can proceed with implementing DATP regardless of the regulatory timeline for DSRC. Results of Phase I research are provided here. Phase I examined industry perceptions of DATP to provide input to a preliminary business case analysis. Technical investigations addressed system modeling and on track evaluations, aerodynamics modeling, operations research to develop algorithms for platoon formation, initial human-machine interface evaluations, wireless communications examining DSRC aspects specific to tractor-trailer combinations, and traffic modeling to assess traffic flow impacts with various levels of DATP market penetration. Appendices include a DATP Concept of Operations and Requirements document. Phase II plans are also described.
TRIS Files:	TRIS, ATRI, USDOT
Media Type:	Digital/other
Pagination:	135p
Authors:	Bevly, David Murray, Chase Lim, Alvin Turochy, Rod Sesek, Richard Smith, Scott Apperson, Grant

	Woodruff, Jonathan Gao, Song Gordon, Mikhail Smith, Nicholas Watts, Andrew Batterson, Joshua Bishop, Richard Murray, Daniel Torrey, Ford Korn, Alan Switkes, Josh
Corporate Authors:	Boyd, StephenAuburn UniversityDepartment of Mechanical Engineering270 Ross HallAuburn, AL 36849-5341 United StatesFederal Highway Administration1200 New Jersey Avenue, SEWashington, DC 20590 United StatesAmerican Transportation Research InstituteMeritor WABCOPeloton TechnologyPeterbilt Trucks
Publication Date:	20150430
Edition:	Final Report
Period Covered:	10/2013-12/2014
Index Terms:	Algorithms; Autonomous intelligent cruise control; Driver vehicle interfaces; Evaluation; Stakeholders; Tractor trailer combinations; Traffic flow; Traffic models; Traffic platooning; Trucks; Vehicle to vehicle communications
Subject Areas:	Highways; Motor Carriers; Planning and Forecasting; Vehicles and Equipment; I72: Traffic and Transport Planning; I91: Vehicle Design and Safety

Title:	Reducing Truck Fuel Use and Emissions: Tires, Aerodynamics, Engine Efficiency, and Size and Weight Regulations
Accession Number:	01562733

Record Type:	Monograph
Language:	English
Record URL:	http://hdl.handle.net/2027.42/109749
Abstract:	This report explores ways in which the properties of trucks and regulations governing them might be modified to improve freight efficiency and reduce fuel use and emissions in the challenging world of transportation economics and environmental stewardship. Trucks are the dominant mode of non-bulk commodity freight transport in the U.S. Compared to all other modes combined (rail + water + air + pipelines), trucks transport approximately twice the amount of freight by weight and approximately 1.8 times the amount of freight by value. Trucking has the most extensive distribution network of any transport mode, having access to over 3.9 million miles of roadways. Improvements in truck freight efficiency can be expected to show direct improvement of the nation's overall transportation system. This study has identified four key focus areas that influence truck and truck freight efficiency: 1. Tire rolling resistance, 2. Aerodynamics, 3. Engine efficiency, and 4. Truck size and weight regulation. Each of the four focus areas are discussed in terms of past and present performance, along with projections to the future. The final section of the report presents estimated potential realistic improvements for each of the four key focus areas, as well as the respective levels of technical challenge.
TRIS Files:	TRIS
Report/Paper Numbers:	UMTRI-2014-27
Media Type:	Digital/other
Pagination:	41p
Authors:	Woodrooffe, John
Corporate Authors:	University of Michigan Transportation Research Institute 2901 Baxter Road Ann Arbor, MI 48109-2150 United States University of Michigan, Ann Arbor Sustainable Worldwide Transportation 2901 Baxter Road Ann Arbor, MI 48109 United States
Publication Date:	20141100
Index Terms:	Aerodynamics; Commercial vehicles; Diesel engine exhaust gases; Engine efficiency; Freight transportation; Fuel consumption; Motor carriers; Rolling resistance; Size and weight regulations; Tires; Trucks
Subject Areas:	Economics; Energy; Environment; Motor Carriers; Vehicles and Equipment;

I10: Economics and Administration; I15: Environment; I70: Traffic and Transport; I90: Vehicles

International

Title:	Estimated impacts of the sulphur directive on the Nordic industry
Accession Number:	01561047
Record Type:	Component
Language:	English
Record URL:	http://dx.doi.org/10.1007/s12544-015-0158-4
Abstract:	The International Maritime Organization and the European Parliament (EP) have stated that ships must lower sulfur emissions significantly in a specific region in Northern Europe, that is, in the Sulphur Emission Control Area (SECA), where sulfur content in bunkers is not allowed to exceed 0.1 percent. The Nordic companies have been examined somewhat marginally from the point of view of the SECA-directive, and how it will affect the cost-efficiency of the industry. The research data contains information about export to four large European countries that form the biggest markets in Europe for the case mill. The transport costs (freight costs per ton) were taken from the mill database on the customer level. The actual and forecasted mill data was copied into Excel spreadsheets for analysis. Results of this case study strongly indicate that the sulfur directive has direct impacts to the economy of the Nordic bulk industry. When the bunker fuel prices increase from the year 2015 onward, it reflects directly to sea freight prices in the SECA-region. This will noticeably increase the total transportation costs per ton. The sulfur directive will be an additional cost burden for the Nordic industry, which in turn is something that from 2015 onward local European paper mills and other manufacturing industries will benefit from outside the traditional business environment. The impacts of the sulfur directive will vary heavily from market to market and transportation costs from Finland to Europe can increase by average more than 20 percent in ℓ/t ; this can also be an underestimation. Profitability can drop by tens of percentage due to more expensive logistics. Logistics costs' percentage in turnover will increase in the Nordic countries, but existing low oil price (2015) will mitigate the expected price increase of the MDO (Marine Diesel Oil) in the near future.
Supplemental Notes:	© 2015 Esa Hämäläinen
TRIS Files:	TRIS

Media Type:	Digital/other
Pagination:	13p
Authors:	Hämäläinen, Esa
Availability:	Find a library where document is available Order URL: <u>http://worldcat.org/issn/18668887</u>
Publication Date:	20150600
Serial:	European Transport Research Review Volume: 7 Issue Number: 2 Publisher: Springer Publishing ISSN: 1866-8887 EISSN: 1867-0717 Serial URL: <u>http://link.springer.com/journal/12544</u>
Index Terms:	Costs; Environmental protection; Freight traffic; International Maritime Organization; Markets; Pollutants; Scandinavia; Sulfur
Subject Areas:	Administration and Management; Environment; Freight Transportation; Marine Transportation; I10: Economics and Administration; I15: Environment

Title:	The CITI project: an update on Australia's first deployment of cooperative intelligent transport systems targeting heavy vehicle safety
Accession Number:	01563021
Record Type:	Component
Language:	English
Record URL:	http://acrs.org.au/publications/conference-papers/database/
Source Agency:	ARRB Group Limited 500 Burwood Highway Vermont South, Victoria 3133
Abstract:	Cooperative Intelligent Transport Systems (CITS) is the term generally used to describe a form of Intelligent Transport Systems in which information is shared amongst vehicles or between vehicles and roadside infrastructure such as traffic signals. This has the potential to greatly improve road safety, improve network efficiency and reduce greenhouse gases. The Cooperative Intelligent Transport

Title:	Greening and safety assurance of future modular road vehicles
Subject Areas:	Highways; Safety and Human Factors; I91: Vehicle Design and Safety
Index Terms:	Australia; Driver information; Driver information; Driver information systems; Driver vehicle interfaces; Exhaust gases; Field test; Field tests; Heavy vehicles; Human factors; Human machine interface; Human machine systems; Intelligent transport system; Lorry; New South Wales; Test tracks; Vehicle emissions; Vehicle to infrastructure communications; Vehicle to roadside communications; Vehicle to vehicle communications; Vehicle to vehicle communications; Warning; Warning signals
Conference:	Australasian Road Safety Research Policing Education Conference, 2014, Melbourne, Victoria, Australia Location: Date: 00000 - 00000
Publication Date:	20141100
Monograph Accession Number:	01563042
Monograph Title:	Australasian Road Safety Research, Policing and Education Conference, 12-14 November 2014, Melbourne, Australia
Authors:	Tyler, P Wall, J
Pagination:	7p
TRIS Files:	ITRD, ATRI
	Initiative (CITI) pilot will be the first semipermanent CITS field test bed site in Australia. The Objective of the CITI project is to construct a 42 km connected freight corridor test facility in the Illawarra Region of NSW south of Sydney. This will be one of the first large scale test facilities dedicated to Heavy Vehicles in the world. The first stage of the project will fit in-vehicle dedicated short range communication (DSRC) transceivers in up to 60 trucks that regularly travel the planned route. In addition, three signalised intersections are being equipped with DSRC roadside units which will communicate with the trial vehicles. A 40 km/h truck and bus speed zone warning system is also planned for installation at the top of Mt Ousley to alert drivers about to descend the very steep (up to 12 percent downhill gradient) south bound section of the road. This paper will provide an update on the progress of the CITI project and examine issues including project planning, equipment licensing, human machine interface development, data management and participant recruitment.

Accession Number:	01553558
Record Type:	Component
Language:	English
Record URL:	http://road-transport-technology.org/conferenceproceedings/2014-hvtt13/
Source Agency:	ARRB Group Limited 500 Burwood Highway Vermont South, Victoria 3133
Abstract:	Recent megatrends can be distinguished which have a strong impact on logistic and transport concepts. Such megatrends are typically related to climate change, growing transport demand, urbanisation and scarcity of resources. The resulting logistic and transport concepts are intermodal transport, European Modular System (EMS) and hub & spoke systems (H&S). For the transport modes there is a need for multiples of loading units. This has motivated a consortium, consisting of automotive industry partners, knowledge institutes and universities to investigate these trends with the objective of developing new vehicle concepts that meet the following requirements: 1. Significant reduction of CO2 emission per unit payload; 2. Meeting the (future) needs of logistic companies in terms of flexibility, efficiency and TCO (total cost of ownership); 3. Based on existing modules to facilitate intermodality (rail-road-water-air); 4. Possible usage across Europe for cross-border long-distance road transport; 5. Compatibility with the existing infrastructure; 6. Designed/evaluated by using performance-based standards.
TRIS Files:	ATRI
Pagination:	26p
Authors:	Nijmeijer, H BESSELINK, I Prati, A Meijs, M Kraaijenhagen, B Barth, T Kural, K Pauwelussen, J
Monograph Title:	Expanding horizons: 13th International Symposium on Heavy Vehicle Transport Technology, San Luis, Argentina, 27-31 October 2014
Monograph Accession Number:	01553537
Publication Date:	20141000

Conference:	HVTT13: International Symposium on Heavy Vehicle Transport Technology, 13th, 2014, San Luis, Argentina Location: Date: 00000 - 00000
Index Terms:	Air quality management; Emissions control; Europe; Freight transport; Freight transport logistics; Freight transportation; Heavy vehicle; Heavy vehicles; Intermodal transport; Intermodal transportation; Logistics; Logistics; Performance based standard (PBS)
Subject Areas:	Environment; Freight Transportation
Title:	Swiss contribution to Eureka Project Ecovehicle E!7219: Defining road and rail vehicles with a low environmental footprint
Accession Number:	01534403
Record Type:	Project
Language:	English
Source Agency:	Ecole Polytechnique Fédérale de Lausanne (EPFL) Lausanne CH-1015 Switzerland
Source Data:	ITRD E649608
Abstract:	The increase in the number of Heavy Duty Vehicles (HDV) is inherently accompanied by increase in congestion, pollutant emissions, noise and energy use as well as infrastructure overuse, all of which have broad societal implications. In addition to affecting the environment, contributing markedly to global warming, significant implications for the health of many residents living along traffic corridors as well as increases in the cost of infrastructure maintenance are logical consequences. Using individual vehicle data, the footprint project (ASTRA 2004/020, ASTRA 2004/008, ASTRA 2010/019) has shown that within every vehicle category there are those with a very high combined footprint considering noise, dynamic load and pollutant emissions. Up to now the Swiss heavy vehicle fee (LSVA) based on the environmental differential charging, has been very successful in reducing the impact of pollutant emissions at source and to the more economical transport of goods. The aim of this follow up project is to develop new instruments to encourage vehicles with a low total footprint. Specifically, to develop methods to include noise as a parameter in the differential charging of LSVA. This is in line with the European noise directive (2002/49/EC) and Swiss policy to develope a long-term strategy, which includes objectives to reduce the number of people affected by noise in the longer term, and provides a framework for developing existing community policy on noise reduction from source. This will be achieved in parallel within a new European project Ecovehicle (E!7219). This project fits well within the key targets of

ASTRA/BAFU/ARE R&D concept

(http://www.ressortforschung.admin.ch/html/dokumentation/Forschungskonzept_13-16/Forschungskonzept_Raum_2013-16%20d.pdf) defined for the period 2013-2016. Specifically in terms of noise abatement, protection of the natural environment, promotion of further reduction of emissions of heavy vehicles and innovations in promoting a sustainable environment.

TRIS Files:	ITRD	
Contract Numbers:	ITRD ASTRA 2014 001	
Funding:	0.00	
Start Date:	20140900	
Expected Completion Date:	20170900	
Performing Agencies:	EMPA Abteilung fuer Strassenbau / Abdichtungen Ueberlandstrasse 129 Duebendorf CH-8600 SUISSE	
Funding Agencies:	BUNDESAMT FUER STRASSENBAU (ASTRA) / OFFICE FEDERAL DES ROUTES (OFROU) Muehlestrasse 2, Ittige Duebendorf CH-3003 SUISSE	
Responsible Individuals:	POULIKAKOS, L	
Index Terms:	Ecology; Economic efficiency; Economic efficiency; Emission; Environment; Freight traffic; Goods traffic; Load; Loads; Noise; Noise; Pollutant; Pollutants; Rail bound transport; Railroad transportation; Research project; Research projects; Transport; Transportation; Vehicle; Vehicles; Weight; Weight	
Subject Areas:	Freight Transportation; Railroads; Vehicles and Equipment; I15: Environment; I90: Vehicles	
Title:	Road freight energy efficiency and CO ₂ emissions in the Nordic countries	
Accession Num	ber: 01549166	
Record Type:	Component	
Language:	English	

Record URL:	http://dx.doi.org/10.1016/j.rtbm.2014.08.001
Record URL:	http://www.sciencedirect.com/science/article/pii/S221053951400056X
Abstract:	Nordic countries have committed to improve the energy efficiency and decrease the CO_2 emissions of freight transport. The aim of this paper is to compare the energy efficiency and CO_2 emissions in the road industry for the Nordic countries in 2010, in order to identify the key factors and their impact on energy efficiency and CO_2 emissions. A joint analysis method was developed to compare data. Quantitative data was used to conduct a decomposition analysis for several sectors, taking several indicators into account. Statistics from Denmark, Finland, Norway and Sweden include continuous road haulier surveys, national account data and fuel consumption data. The CO_2 emissions of road freight transport in the Nordic countries vary from 1.14 Mt in Denmark to 2.27 Mt in Sweden. While the size of the economy, measured in gross value added (GVA), is a major determinant for the emissions, the differences in transport intensity and energy efficiency also have a significant effect on the total emissions. This study is the first of its kind for the Nordic countries. This research can be used as a first step in a continuous evaluation of the determinants of road freight CO_2 emissions in the European countries.
Supplemental Notes:	Abstract reprinted with permission of Elsevier.
TRIS Files:	TRIS
Media Type:	Digital/other
	Digital/otilei
Pagination:	pp 11-19
Pagination: Authors:	
C	pp 11-19 Liimatainen, Heikki Arvidsson, Niklas Hovi, Inger Beate Jensen, Thomas Christian
Authors:	pp 11-19 Liimatainen, Heikki Arvidsson, Niklas Hovi, Inger Beate Jensen, Thomas Christian Nykänen, Lasse Find a library where document is available
Authors: Availability:	pp 11-19 Liimatainen, Heikki Arvidsson, Niklas Hovi, Inger Beate Jensen, Thomas Christian Nykänen, Lasse Find a library where document is available Order URL: <u>http://worldcat.org/issn/22105395</u>

Subject Areas: Environment; Freight Transportation; Highways; 115: Environment

Title: Bi-level Optimization Model for Last Mile Retail Cargo

Accession 01542182 Number:

- **Record Type:** Component
- Language: English

Record URL: http://www.icms.polyu.edu.hk/Proceedings/Proceedings%20of%20IFSPA%202014.pdf

Abstract: This paper focuses on the consolidation of last mile retail cargo using an urban consolidation centre, placed strategically in close proximity to high demand traffic locations for a very dense supply chain configuration, which involves four receiving gateways, several hundred retail outlets of varying demand rates daily, and lumpy delivery schedules. The authors model this problem from the perspective of a Stackelberg game model involving the operator (leader) of the urban consolidation centre and the logistics service provider (follower) who manages the last mile delivery. The leader makes his operational decision by considering the derived demand from the follower and from the economic efficiency, environmental emissions, and constraints of highly dependent time windows with penalties for late deliveries. Simultaneously, the follower arranges his transportation plan by considering the cost of the delivery orders from the stores and the time window set by the operator at the upper level.

Supplemental Notes:	Abstract reprinted with permission of Hong Kong Polytechnic University.
TRIS Files:	TRIS
Media Type:	Digital/other
Pagination:	pp 306-310
Authors:	Qu, Shao-Jian Goh, Mark de Souza, Robert
Monograph Title:	Proceedings of the International Forum on Shipping, Ports and Airports (IFSPA) 2014: Sustainable Development in Shipping and Transport Logistics
Monograph Accession	01540053

Number:

Corporate Authors:	Hong Kong Polytechnic University Department of Logistics and Maritime Studies Tung International Centre for Maritime Studies Hong Kong China
Editors:	Chin-Shan Lu Petrus Choy Kee-Hung Lai YH Venus Lun Tsz Leung Yip
Publication Date:	20140800
Conference:	International Forum on Shipping, Ports and Airports (IFSPA) 2014: Sustainable Development in Shipping and Transport Logistics Location: Hong Kong , China Date: 20140519 - 20140521 Sponsors: Hong Kong Polytechnic University
Index Terms:	Environmental impacts; Logistics; Logistics service providers; Operating costs; Optimization; Retail trade; Singapore; Stackelberg game; Supply chain management; Time windows; Urban transportation
Subject Areas:	Environment; Freight Transportation; I15: Environment

Warehousing, Supply Chain

Title:	Reprint of "Green supply chain decisions – Case-based performance analysis from the food industry"
Accession Number:	01557527
Record Type:	Component
Language:	English
Record URL:	http://dx.doi.org/10.1016/j.tre.2014.12.005
Record URL:	http://www.sciencedirect.com/science/article/pii/S1366554514002117
Abstract:	Environmental impacts, such as GHC emissions, have been introduced to supply chain management as an additional parameter to traditional cost, lead- time and on-time delivery. Supply chain management represents a significant

	source of decisions affecting the eco-efficiency of many products. This paper analyses cases from the food industry, mainly order-picking, transportation, warehousing, and distribution aspects from the greening point of view. Three case examples of decisions in supply chain design in the food industry are considered. The results show dependencies between performance measures. Finally, a framework of decisions and their impact on performance is presented.
Supplemental Notes:	Abstract reprinted with permission of Elsevier.
TRIS Files:	TRIS
Media Type:	Web
Pagination:	pp 11-21
Authors:	Ala-Harja, Hanne Helo, Petri
Availability:	Find a library where document is available Order URL: <u>http://worldcat.org/issn/13665545</u>
Publication Date:	20150200
Serial:	Transportation Research Part E: Logistics and Transportation Review Volume: 74 Issue Number: Publisher: Elsevier ISSN: 1366-5545 Serial URL: <u>http://www.sciencedirect.com/science/journal/13665545</u>
Index Terms:	Environmental impacts; Food industry; Logistics; Performance measurement; Supply chain management
Subject Areas:	Environment; Freight Transportation; Planning and Forecasting; I15: Environment; I72: Traffic and Transport Planning
Title:	Optimization of Empty Pallet Low-Carbon Dispatching Based on Intermodal Freight Transport

Accession Number:	01541388
Record Type:	Component
Language:	English
Record URL:	http://dx.doi.org/10.1061/9780784413753.217

Abstract:	With the wide spread of pallets in containerized transport, and due to low efficiency, high cost, high resource consumption and other shortcomings, the disposable pallets cannot adapt to the future development of containerized transport. A pallet pool can realize the recycling of pallets and improve handing and transport efficiency while reducing the cost and consumption of resources. However, the cargo volume varies in different areas, and certain goods are seasonal transport, making the pallets in the pallet pool mode unbalanced. This paper mainly focuses on railway and highway transport to analyze the dispatching of empty pallets. Based on the carbon emissions, transport time and priority of dispatching, this paper establishes the objective model of minimum cost in order to make the decision on empty pallet dispatching routes and modes of transport. In this paper, the ILOG Cplex software is used to solve the model and verify the feasibility and superiority of the model through a case.
Supplemental Notes:	© 2014 American Society of Civil Engineers.
TRIS Files:	TRIS, ASCE
Media Type:	Web
Pagination:	pp 1430-1436
Authors:	Zhou, Kang He, Shiwei Song, Rui Xu, Yue
Monograph Title:	ICLEM 2014: System Planning, Supply Chain Management, and Safety
Monograph Accession Number:	01540895
Corporate Authors:	American Society of Civil Engineers 1801 Alexander Bell Drive Reston, VA 20191-4400 United States
Editors:	Jin Zhang Xiaoqiang Zhang Ping Yi Kun Wang
Availability:	Find a library where document is available Order URL: <u>http://worldcat.org/isbn/9780784413753</u>
ISBN:	9780784413753
Publication Date:	20140900

Conference:	2014 International Conference of Logistics Engineering and Management (ICLEM) Location: Shanghai , China Date: 20141009 - 20141011 Sponsors: Southwest Jiaotong University; Shanghai Maritime University; American Society of Civil Engineers
Index Terms:	Container traffic; Costs; Dispatching; Empty pallets; Freight trains; Intermodal transportation; Mathematical models; Minimization; Optimization; Pallets; Recycling; Trucking
Subject Areas:	Freight Transportation; Highways; Planning and Forecasting; Railroads; I72: Traffic and Transport Planning
Title:	Green supply chain decisions – Case-based performance analysis from the food industry

Accession Number: 01538457

Record Type: Component

Language: English

Record URL: <u>http://dx.doi.org/10.1016/j.tre.2014.05.015</u>

Record URL: http://www.sciencedirect.com/science/article/pii/S1366554514000921

Abstract: Environmental impacts, such as GHC emissions, have been introduced to supply chain management as an additional parameter to traditional cost, leadtime and on-time delivery. Supply chain management represents a significant source of decisions affecting the eco-efficiency of many products. This paper analyses cases from the food industry, mainly order-picking, transportation, warehousing, and distribution aspects from the greening point of view. Three case examples of decisions in supply chain design in the food industry are considered. The results show dependencies between performance measures. Finally, a framework of decisions and their impact on performance is presented.

Supplemental Notes: Abstract reprinted with permission of Elsevier.

TRIS Files: TRIS

Media Type:Digital/otherPagination:pp 97-107

Authors: Ala-Harja, Hanne Helo, Petri

Availability:	Find a library where document is available Order URL: <u>http://worldcat.org/issn/13665545</u>
Publication Date:	20140900
Serial:	Transportation Research Part E: Logistics and Transportation Review Volume: 69 Issue Number: Publisher: Elsevier ISSN: 1366-5545 Serial URL: <u>http://www.sciencedirect.com/science/journal/13665545</u>
Index Terms:	Environmental impacts; Food industry; Logistics; Performance measurement; Supply chain management
Subject Areas:	Environment; Freight Transportation; Planning and Forecasting; I15: Environment; I72: Traffic and Transport Planning

 CO_2 , GHG , Fuel Efficiency

Title:	The tractor and semitrailer routing problem with many-to-many demand considering carbon dioxide emissions
Accession Number:	01552038
Record Type:	Component
Language:	English
Record URL:	http://dx.doi.org/10.1016/j.trd.2014.10.004
Record URL:	http://www.sciencedirect.com/science/article/pii/S136192091400145X
Abstract:	The tractor and semitrailer routing problem with many-to-many demand (TSRP-MMD) is investigated in this study. The TSRP-MMD extends the existing studies on the rollon–rolloff vehicle routing problem (RRVRP) to a many-to-many problem with an intercity line- haul network background. To demonstrate and utilize the energy efficiency of the tractor and semitrailer combination, the TSRP-MMD takes carbon dioxide (CO_2) emissions per ton-kilometer as the objective. Because the problem is NP-hard, a modified Clarke and Wright Savings heuristic algorithm (CW) followed by an improvement phase and a local search phase is developed to solve the TSRP-MMD. The integer program is used to find optimum solutions for small-scale problems. The computational results show that the developed heuristics can be efficiently used to solve the problem.

Supplemental Notes:	Abstract reprinted with permission of Elsevier.
TRIS Files:	TRIS
Media Type:	Digital/other
Pagination:	pp 68-82
Authors:	Li, Hongqi Lv, Tan Li, Yanran
Availability:	Find a library where document is available Order URL: <u>http://worldcat.org/issn/13619209</u>
Publication Date:	20150100
Serial:	Transportation Research Part D: Transport and Environment Volume: 34 Issue Number: Publisher: Elsevier ISSN: 1361-9209 Serial URL: <u>http://www.sciencedirect.com/science/journal/13619209</u>
Index Terms:	Carbon dioxide; Demand; Heuristic methods; Intercity transportation; Pollutants; Routing; Trailers; Truck tractors
Subject Areas:	Environment; Freight Transportation; Operations and Traffic Management; I15: Environment; I73: Traffic Control
Title:	A Roadmap for Reducing the GHG Emissions of Trucking: Looking Beyond Technology Mandates
Accession Number:	01554415
Record Type:	Component
Language:	English
Order URL:	http://amonline.trb.org/
Source Data:	Transportation Research Board Annual Meeting 2015 Paper #15-5762
Abstract:	The trucking sector in the US has been receiving considerable attention from regulatory agencies that are seeking to reduce Greenhouse Gas (GHG) emissions. In California, Heavy-Duty trucks are now required to be retrofitted with certain Fuel Saving Technologies (low rolling resistance tires and aerodynamic deflectors), and at the national level emission standards have been introduced that force manufactures to improve the technology of new trucks. This paper finds that these

	programs are likely to reduce costs as well as emissions, because extensive evidence shows that most trucking firms are not making these seemingly cost-effective investments in efficiency on their own. This corroborates many previous studies and supports the rational for these government programs. However, while effective and desirable at first, this regulatory approach based on mandates has shortcomings in the long-run. This paper develops a roadmap for how emission reductions can be achieved in more sophisticated and efficient ways moving forward, based on the results of a policy simulation using a model of the trucking sector and an understanding of the factors causing this 'efficiency gap' (e.g. split incentives, uncertainty, search costs, financial constraints). Results indicate that California's 2020 emission target can be achieved by implementing other interventions that sidestep the root causes of the efficiency gap just as the technology mandates, such as increasing weight limits and managing trucking demand. However, moving past 2020 it is necessary to tackle the efficiency gap directly, to reduce emissions and allow for the introduction of incentives-based interventions that harness market forces (e.g fuel taxes and technology subsidies). To produce even stronger incentives towards efficiency, strategy complementarity could be exploited and efforts should likely be coordinated at the national level.
Supplemental Notes:	This paper was sponsored by TRB committee AT010 Freight Transportation Economics and Regulation.
TRIS Files:	TRIS, TRB, ATRI
Report/Paper Numbers:	15-5762
Media Type:	Digital/other
Pagination:	18p
Authors:	Guerrero, Sebastian E Madanat, Samer Leachman, Robert
Monograph Title:	TRB 94th Annual Meeting Compendium of Papers
Monograph Accession Number:	01550057
Corporate Authors:	Transportation Research Board 500 Fifth Street, NW Washington, DC 20001 United States
Availability:	Transportation Research Board Business Office 500 Fifth Street, NW

	Washington, DC 20001 United States
Publication Date:	20150000
Conference:	Transportation Research Board 94th Annual Meeting Location: Washington DC, United States Date: 20150111 - 20150115 Sponsors: Transportation Research Board
Index Terms:	California; Greenhouse gases; Heavy duty trucks; Policy; Pollutants; Simulation; Size and weight regulations; Taxes; Trucking
Subject Areas:	Environment; Freight Transportation; Motor Carriers; I15: Environment
Title:	Assessment of the Energy Consumption of LNG Carriers and the Impact of Improving the Energy Efficiency on the Natural Gas Supply Chain
Accession Number:	01554391
Record Type:	Component
Language:	English
Order URL:	http://amonline.trb.org/
Source Data:	Transportation Research Board Annual Meeting 2015 Paper #15-4835
Abstract:	With the booming natural gas trade, the Liquefied Natural Gas (LNG) carriers, the primary transportation method for intercontinental trade on natural gas, has been experiencing explosive growth. This study offers a novel analysis that connects 2011 in-use LNG fleet characteristics, global satellite data on ship movement, and literature on LNG trade to assess the long-term prospects for increasing energy efficiency of LNG carriers. This analysis also investigates how efficiency characteristics (such as age, size, technology, operational practices) influence the efficiency of the LNG fleet, and develops a ship stock model to independently track technical and operational efficiency practices in LNG carriers. The findings indicate that industry-leading LNG carriers are about 40% more efficient than industry laggards. This analysis indicates that, by fully embracing the available technical and in-use practices of the low-carbon industry leaders of today, the fleet could reduce CO_2 emissions by 30 million metric tons (MMT) by 2040, or about 8 MMT of natural gas, equivalent to \$4 billion savings in the LNG supply chain. This study has important implications for the shipping industry and policy makers. The industry has to address split incentives to take the advantage of energy-saving opportunities. And

Title:	Analyzing the Impacts of Global Transport CO2 Emissions Using Multi-Sectoral Tool
Subject Areas:	Energy; Environment; Freight Transportation; Marine Transportation; I15: Environment
Index Terms:	Bulk carriers; Carbon dioxide; Energy consumption; Liquefied natural gas; Pollutants; Shipping
Conference:	Transportation Research Board 94th Annual Meeting Location: Washington DC, United States Date: 20150111 - 20150115 Sponsors: Transportation Research Board
Publication Date:	20150000
Availability:	Transportation Research Board Business Office 500 Fifth Street, NW Washington, DC 20001 United States
Corporate Authors:	Transportation Research Board 500 Fifth Street, NW Washington, DC 20001 United States
Monograph Accession Number:	01550057
Monograph Title:	TRB 94th Annual Meeting Compendium of Papers
Authors:	Wang, Haifeng Rutherford, Dan
Pagination:	14p
Media Type:	Digital/other
Report/Paper Numbers:	15-4835
TRIS Files:	TRIS, TRB, ATRI
Supplemental Notes:	Alternate title: Assessment of Energy Consumption of Liquefied Natural Gas Carriers and Impact of Improving Energy Efficiency on Natural Gas Supply Chain. This paper was sponsored by TRB committee ADC70 Transportation Energy.
	regulations that set targets for the energy efficiency of the in-use fleet may ultimately help the industry harvest the efficiency gains while mitigating the climate impact from the industry.

Accession Number:	01554260
Record Type:	Component
Language:	English
Order URL:	http://amonline.trb.org/
Source Data:	Transportation Research Board Annual Meeting 2015 Paper #15-5209
Abstract:	The Global Calculator was built to model carbon dioxide (CO_2) emissions in 2050 based on a variety of user selections for different sectors. This paper focuses on the modeling and results relating to the transport sector, which was developed to estimate an accurate base year as well as aid in determining four different Levels of Effort to reduce CO_2 emissions for six levers: passenger demand, freight demand, mode, occupancy and load, electric or hydrogen vehicles, and vehicle efficiency. Level 1 represents minimal effort made in the sector to reduce emissions, while Level 4 represents the maximum effort the sector can achieve. This model shows us that action or inaction in the transport sector can result in an increase or decrease of 20% in CO_2 emissions from what is considered business as usual, the International Energy Agency (IEA) 6 degree scenario. Vehicle efficiency and mode share are very important for reducing emissions from the transport sector, while effectiveness of electrifying the fleet relies heavily on having a green grid. This also provides a global bottom-up model that can be used to compare both lifestyle and technological changes which will impact future emissions.
Supplemental Notes:	This paper was sponsored by TRB committee ADC70 Transportation Energy.
TRIS Files:	TRIS, TRB, ATRI
Report/Paper Numbers:	15-5209
Media Type:	Digital/other
Pagination:	14p
Authors:	Cooper, Erin Lefevre, Benoit Pestiaux, Julien
Monograph Title:	TRB 94th Annual Meeting Compendium of Papers
Monograph Accession Number:	01550057
Corporate Authors:	Transportation Research Board

	500 Fifth Street, NW Washington, DC 20001 United States
Availability:	Transportation Research Board Business Office 500 Fifth Street, NW Washington, DC 20001 United States
Publication Date:	20150000
Conference:	Transportation Research Board 94th Annual Meeting Location: Washington DC, United States Date: 20150111 - 20150115 Sponsors: Transportation Research Board
Index Terms:	Carbon dioxide; Environmental impacts; Forecasting; Pollutants; Transportation
Subject Areas:	Environment; Planning and Forecasting; Transportation (General); I15: Environment; I72: Traffic and Transport Planning

Title:	Environmentally Friendly Driving Feedback Systems Research and Development for Heavy Duty Trucks
Accession Number:	01554058
Record Type:	Project
Language:	English
Record URL:	http://ncst.ucdavis.edu/project/ucr-ct-to-007/
Source Agency:	National Center for Sustainable Transportation Davis, CA United States
Source Data:	RiP Project 37004
Abstract:	Among several strategies to reduce fuel consumption and greenhouse gas emissions from heavy duty trucks, "eco-driving" is one that has the potential to be very cost effective. Eco-driving can be defined as fuel- efficient operation of a vehicle to achieve better fuel economy and lower tailpipe emissions while not compromising the safety of oneself and other road users. The core of eco-driving programs is to provide drivers with a variety of advice and feedback to reduce fuel consumption. The advice and feedback can be provided through various means including websites, classes or training, and in-vehicle driving feedback systems. The University of California, Riverside's Center for Environmental Research and Technology (UCR CE-CERT) researchers

	have developed a variety of next-generation eco-driving technologies as part of a three-year Department of Energy research program and now are planning on applying these technologies to heavy-duty trucks to determine their potential at improving fuel efficiency. The developed eco-driving technology includes: 1) Eco-Friendly Fleet Planning; 2) Eco-Routing Navigation, 3) Connected Eco-Driving Feedback, and 4) an Eco-Score and Eco-Ranking System. Three of these technologies (numbers 2, 3, and 4 above) will be adapted and integrated with a state- of-the-art truck driving simulator located at UCR, where experienced truck drivers will comprehensively test the technology across a range of truck driving scenarios. By establishing a baseline of driving, and then introducing the eco-driving technology, it will be possible to quantitatively measure the potential fuel and greenhouse gas (GHG) emission benefits. It is expected that these eco-driving technologies will collectively result in fuel and GHG emission savings in the range of 5% - 20% depending on the driving scenarios
TRIS Files:	UTC, RiP
Contract Numbers:	DTRT13-G-UTC29
Funding:	136000.00
Start Date:	20141001
Performing Agencies:	University of California, Riverside Center for Environmental Research and Technology 900 University Avenue Riverside, CA 92521-0425 United States National Center for Sustainable Transportation Davis, CA United States
Funding Agencies:	California Department of Transportation 1120 N Street Sacramento, CA 95814 United States
Index Terms:	California; Driver feedback; Economic benefits; Environmental impacts; Fuel consumption; Greenhouse gases; Heavy duty trucks; Pollutants; Sustainable transportation
Subject Areas:	Data and Information Technology; Freight Transportation; Research; I15: Environment
Title:	Towards a global CO ₂ calculation standard for supply chains: Suggestions for methodological improvements
Accession Number:	01545360

Record Type:	Component
Language:	English
Record URL:	http://dx.doi.org/10.1016/j.trd.2014.08.023
Record URL:	http://www.sciencedirect.com/science/article/pii/S1361920914001242
Abstract:	Improving the efficiency and sustainability of supply chains is a shared aim of the transport industry, its customers, governments as well as industry organizations. To optimize supply chains and for the identification of best practice, standards for their analysis are needed in order to achieve comparable evaluations. This need for an evaluation standard also applies to CO_2 emission calculations. This research focuses on the transportation within supply chains and possible approaches towards a global standard for calculating its CO_2 emissions. In the recent past, several organisations, national and international, have come forward with possible methods, tools and databases for the calculation of CO_2 emissions along supply chains, but almost all of them do not cover the entire transportation chain. Also standards for CO_2 emissions of products and production in general do exist but they do not take the particular requirements of transportation into consideration. Therefore a global standard specifically for transportation could not yet be introduced. The EN 16258 standard is the only international standard for emission calculation of transportation in supply chains. It was therefore analyzed as a possible starting point for a global standardization approach. Analysis shows it too contains gaps and ambiguities which render comparisons of supply chains difficult. These gaps of the EN 16258 are analyzed, followed by suggestions for methodological improvements for their closure. The research concludes with an outlook on next steps needed towards a global CO ₂ calculation standard for transportation within supply chains.
Supplemental Notes:	Abstract reprinted with permission of Elsevier.
TRIS Files:	TRIS
Media Type:	Digital/other
Pagination:	pp 362-372
Authors:	Davydenko, Igor Ehrler, Verena de Ree, Diederik Lewis, Alan Tavasszy, Lorant
Availability:	Find a library where document is available

	Order URL: http://worldcat.org/issn/13619209
Publication Date:	20141000
Serial:	Transportation Research Part D: Transport and Environment Volume: 32 Issue Number: Publisher: Elsevier ISSN: 1361-9209 Serial URL: <u>http://www.sciencedirect.com/science/journal/13619209</u>
Index Terms:	Carbon dioxide; Methodology; Optimization; Organizations; Pollutants; Standards; Supply chain management
Subject Areas:	Environment; Freight Transportation; Planning and Forecasting; I15: Environment; I72: Traffic and Transport Planning
Title:	The impact of port operations on efficient ship operation from both economic and environmental perspectives
Accession Number:	01540016
Record Type:	Component
Language:	English
Record URL:	http://dx.doi.org/10.1080/03088839.2014.931607
Abstract:	Recently, shipping lines have focused on efficient ship operation, which relates to energy efficiency issues in shipping and, particularly, to operational issues such that the minimisation of fuel consumption and resulting greenhouse gas emissions. Efficient ship operation in container lines is closely related to the ship's time at sea and ship's time in port. Reduction in port time, thanks to high-quality port operations, allows improvement in the operational efficiency of a liner service by reducing the fuel consumption of a ship at sea and its resulting CO ₂ emissions. The main goal of this article is to investigate how time in port affects efficient ship operation in terms of operating costs, CO ₂ emissions and externalities. For this, as a methodology, a simulation based upon system dynamics is introduced. Major finding is that less time in port resulting from the improvement of port operations contributes to efficient ship operation in terms of operating costs, amount of CO ₂ emissions and external effects in the liner shipping industry. In particular, a sensitivity analysis on efficient ship operation vis-à-vis the quality of port operation shows that bigger ships need to select highly productive calling ports that provide less time in port.
Supplemental Notes:	Abstract reprinted with permission of Taylor & Francis.

TRIS Files:	TRIS
Media Type:	Web
Pagination:	pp 444-461
Authors:	Moon, Daniel Seong-Hyeok Woo, Jong Kyun
Availability:	Find a library where document is available Order URL: <u>http://worldcat.org/oclc/2899960</u>
Publication Date:	20140700
Serial:	Maritime Policy & Management Volume: 41 Issue Number: 5 Publisher: Taylor & Francis ISSN: 0308-8839 EISSN: 1464-5254 OCLC: 2899960 Serial URL: <u>http://www.tandfonline.com/loi/tmpm20</u>
Index Terms:	Externalities; Fuel consumption; Greenhouse gases; Operating costs; Port operations; Ship lines; Ship operations
Subject Areas:	Economics; Environment; Freight Transportation; Marine Transportation; Terminals and Facilities; I10: Economics and Administration; I15: Environment