

DOCKETED	
Docket Number:	21-BSTD-04
Project Title:	2022 Energy Code Compliance Manuals and Forms
TN #:	243465-5
Document Title:	CF2R-ALT-05-E PRESCRIPTIVE RESIDENTIAL ALTERATIONS NON-HERS FIELD VERIFICATION
Description:	CF2R-ALT-05-E PRESCRIPTIVE RESIDENTIAL ALTERATIONS NON-HERS FIELD VERIFICATION
Filer:	Che Geiser
Organization:	California Energy Commission
Submitter Role:	Commission Staff
Submission Date:	6/7/2022 11:18:58 AM
Docketed Date:	6/7/2022



SAMPLE FORM – NOT VALID FOR SUBMISSION TO BUILDING DEPARTMENTS

CERTIFICATE OF INSTALLATION

Project Name:	Enforcement Agency:
Dwelling Address:	Permit Number:
City and Zip Code:	Permit Application Date:

This compliance document is only applicable to simple alterations that do not require HERS verification for compliance. When HERS verification is required, a CF1R-ALT-01 shall first be registered with a HERS Provider Data Registry.

Alterations to Space Conditioning Systems that are exempt from HERS verification requirements may use the CF1R-ALT-05 and CF2R-ALT-05 Compliance Documents. Possible exemptions from duct leakage testing include: less than 25 feet (ft) of ducts were added or replaced; or the existing duct system was insulated with asbestos; or the existing duct system was previously tested and passed by a HERS Rater. If space conditioning systems are altered and are not exempt from HERS verification, then a CF1R-ALT-02 must be completed and registered with a HERS Provider Data Registry.

Alterations that utilize closed cell Spray Polyurethane Foam (ccSPF) with a density of 1.5 to less than 2.5 pounds per cubic foot having an R-value greater than 5.8 per inch, or open cell Spray Polyurethane Foam (ocSPF) with a density of 0.4 to less than 1.5 pounds per cubic foot having an R-value of 3.6 per inch, shall complete and register a CF1R-ALT-01 with a HERS Provider Data Registry.

If more than one person has responsibility for installation of the items on this certificate, each person shall prepare and sign a certificate applicable to the portion of construction for which they are responsible. Alternatively, the person with chief responsibility for construction shall prepare and sign this certificate for the entire construction. All applicable Mandatory Measures shall be met. Temporary labels shall not be removed before verification by the building inspector.



SAMPLE FORM – NOT VALID FOR SUBMISSION TO BUILDING DEPARTMENTS

A. General Information

01	Project Name:		02	Date Prepared:	
03	Project Location:		04	Building Front Orientation (deg):	
05	CA City:		06	Number of Altered Dwelling Units	
07	Zip Code:		08	Fuel Type:	
09	Climate Zone:		10	Total Conditioned Floor Area (ft ²) (Addition):	
11	Building Type:		12	Slab Area (ft ²):	
13	Project Scope:				



SAMPLE FORM – NOT VALID FOR SUBMISSION TO BUILDING DEPARTMENTS

Insulation

The altered components shall comply with all applicable requirements in The Energy Standards, Sections 110.7, 110.8, 150.0; All joints, penetrations and other openings in the building envelope that are potential sources of air leakage shall be caulked, gasketed, weather stripped, or otherwise sealed to limit infiltration and exhalation.

B. Roof/Ceiling Insulation

01	02	03	04	05	06	07	08
I.D.	Manufacturer & Brand	Framing Material	Framing Size & Spacing	Insulation Type	Cavity Insulation R-value	Insulation Depth (inches)	Below Deck Insulation R-value

C. Wall Insulation

01	02	03	04	05	06	07	08	09
I.D.	Manufacturer & Brand	Framing Material	Framing Size & Spacing	Insulation Type	Cavity Insulation R-value	Insulation Depth (inches)	Exterior Wall Insulation R-value	Interior Wall Insulation R-value



SAMPLE FORM – NOT VALID FOR SUBMISSION TO BUILDING DEPARTMENTS

D. Mass Insulation

01	02	03	04	05	06	07	08
I.D.	Manufacturer & Brand	Location	Mass Thickness (inches)	Furring Strip Type/ Depth (inches)	Insulation Type	Exterior Insulation R-value	Interior Insulation R-value

E. Raised Floor Insulation

01	02	03	04	05	06	07	08	09
I.D.	Manufacturer & Brand	Framing Material	Framing Size & Spacing	Insulation Type	Cavity Insulation R-value	Insulation Depth (inches)	Exterior Floor Insulation R-value	Interior Floor Insulation R-value

F. Slab Floor/Perimeter Insulation

01	02	03	04	05	06	07	08
I.D.	Manufacturer & Brand	Floor Type	Insulation Type	Insulation Depth (inches)	Insulation R-Value	Vertical Insulation Length (inches)	Horizontal Insulation Length (feet)



SAMPLE FORM – NOT VALID FOR SUBMISSION TO BUILDING DEPARTMENTS

Roofing and Radiant Barrier

G. Radiant Barrier

01	Brand Name and Product Number	
02	Installation Type	
03	Total Attic Area (ft ²)	

H. Required Vent Area

01	Combined net free area (NFA) of installed upper and lower vents (in ²)	
02	Minimum required combined net free area (NFA) of upper and lower vents (in ²)	
03	Net free area (NFA) of installed upper vents (in ²)	
04	Minimum required net free area (NFA) of upper vents (in ²)	

I. Roofing Products (Cool Roof) Installation Information

01	02	03	04	05	06	07	08
Roof Pitch	CRRC Product ID Number	Product Type	CRRC Listed Aged Solar Reflectance	Initial Solar Reflectance	Aged Solar Reflectance	Thermal Emittance	SRI



SAMPLE FORM – NOT VALID FOR SUBMISSION TO BUILDING DEPARTMENTS

J. Radiant Barrier and Attic Ventilation – Additional Requirements

Radiant Barrier

01	Radiant barrier must be installed on all vertical surfaces in the attic including gable ends.
02	The emittance of the radiant barrier shall be less than or equal to 0.05 as tested with American Society for Testing and Materials (ASTM) C1371, or E408.
03	The product shall meet all requirements for California certified insulation materials [radiant barriers] of the Department of Consumer Affairs, Bureau of Household Goods and Services, as specified by California Reference Code (CCR), Title 24, Part 12, Chapter 12-13, Standards for Insulating Material
04	When determining the Total Attic Area, the area over unconditioned spaces such as the garage is included when the attic spaces are connected.

Lower Vents

05	Lower vents are within one foot of the eave.
----	--

Upper Vents

06	Upper vents are within three feet of the ridge
----	--



SAMPLE FORM – NOT VALID FOR SUBMISSION TO BUILDING DEPARTMENTS

Vent Area

The responsible person’s signature on this compliance document affirms that all applicable requirements in this table have been met.

07	The net free area (NFA) of upper vents must be within required NFA range of upper vents Note: per Exception to R806.2 of the California Building Code (CBC) Title 24, Part2, Vol.2.5, if the net free ventilating area is less than 1:150, then the upper ventilation must be at least 40 percent and no more than 50 percent. Part 2 contains additional requirements that must be met if the area is less than 1:150.
----	--

K. Roofing Products (Cool Roof) Additional Requirements

The responsible person’s signature on this compliance document affirms that all applicable requirements in this table have been met.

01	Any roof area covered by building integrated photovoltaic (PV) panels and solar thermal panels are exempt from the above Cool Roof requirements.
02	Liquid field applied coatings must comply with installation criteria from section 110.8(i)4.
03	Mass roof 25 pounds per square foot (lb/ft ²) or greater: Mass roofs are not required to have a cool roof even if the climate zone specifies minimum performance requirements.



SAMPLE FORM – NOT VALID FOR SUBMISSION TO BUILDING DEPARTMENTS

M. Fenestration/Glazing – Additional Requirements

The responsible person's signature on this compliance document affirms that all applicable requirements in this table have been met.

01	For existing buildings the U-factor and solar heat gain coefficient (SHGC) values should be the same or better than the required Energy Commission prescriptive requirements.
02	Temporary labels should not be removed until verified by the building inspector.
03	The fenestration product manufacturer's installation specifications shall be followed when installing these products. The space between the fenestration product and rough opening shall be completely filled with insulation. If batt insulation is used, it is cut to size and placed properly around the fenestration product.



SAMPLE FORM – NOT VALID FOR SUBMISSION TO BUILDING DEPARTMENTS

Mechanical and Plumbing

N. Space Conditioning (SC) Systems – Heating/Cooling (Section 150.2(b))

Alterations to Space Conditioning Systems shall be exempt from HERS verification requirements as prerequisite for use of the CF1R-ALT-05 and CF2R- ALT-05 Compliance Documents. If new space conditioning systems are installed or existing systems are altered and are not exempt from HERS verification, then a CF1R-ALT-02 shall be completed and registered with a HERS Provider Data Registry. In each row below for each dwelling unit in the building, check the box that indicates the exemption from HERS verification compliance:

- ☐ a: space conditioning system was not altered;
☐ b: less than 25 feet (ft) of ducts were added or replaced;
☐ c: (exempt from duct leakage testing) if: the existing duct system was insulated with asbestos;
☐ d: (exempt from duct leakage testing) if: the existing duct system was previously tested and passed by a HERS Rater.

Table with 3 columns: 01 SC System Identification or Name, 02 SC System Location or Area Served, 03 Exemption from HERS Verification (checkboxes a, b, c, d). Multiple rows for data entry.

O. Water Heating Systems (Section 150.2(b)1H)



SAMPLE FORM – NOT VALID FOR SUBMISSION TO BUILDING DEPARTMENTS

List water heaters and boilers for both domestic hot water (DHW) heaters and hydronic space heating.

01	Is natural gas connected to the existing water heater?	
----	--	--

02	03	04	05	06	07	08
Water Heating System ID or Name	Water Heating System Type	System Option (from §150.2(b)1Hiii)	Water Heater Type	Volume	Fuel Type	# of Water Heaters in System

Options:

1. Gas or propane water heating system; or
2. A single heat pump water heater. The storage tank shall not be located outdoors and shall be placed on an incompressible, rigid insulated surface with a minimum thermal resistance of R-10. The water heater shall be installed with a communication interface that meets either the requirements of Section 110.12(a) or has a ANSI/CTA-2045-B communication port; or
3. A single heat pump water heater that meets the requirements of NEEA Advanced Water Heater Specification Tier 3 or higher; or
4. If no natural gas is connected to the existing water heater location, a consumer electric water heater

P. Installed Water Heater Manufacturer Information

01	02	03
Water Heating System ID or Name	Manufacturer	Model Number



SAMPLE FORM – NOT VALID FOR SUBMISSION TO BUILDING DEPARTMENTS

DOCUMENTATION AUTHOR'S DECLARATION STATEMENT

1. I certify that this Certificate of Installation documentation is accurate and complete.

Table with 2 columns: Documentation Author Name, Documentation Author Signature, Documentation Author Company Name, Date Signed, Address, CEA/HERS Certification Identification (If applicable), City/State/Zip, Phone.

RESPONSIBLE PERSON'S DECLARATION STATEMENT

2. I certify the following under penalty of perjury, under the laws of the State of California:

- 1. The information provided on this Certificate of Installation is true and correct.
2. I am either: a) a responsible person eligible under Division 3 of the Business and Professions Code...
3. The constructed or installed features, materials, components or manufactured devices (the installation) identified on this Certificate of Installation conforms to all applicable codes and regulations...
4. I understand that a registered copy of this Certificate of Installation shall be posted or made available with the building permit(s) issued for the building...
5. I understand that a registered copy of this Certificate of Installation is required to be included with the documentation the builder provides to the building owner at occupancy...

Table with 3 columns: Responsible Builder/Installer Name, Responsible Builder/Installer Signature, Company Name: (Installing Subcontractor or General Contractor or Builder/Owner), Position With Company (Title), Address, CSLB License, City/State/Zip, Phone, Date Signed.

For assistance or questions regarding the Energy Standards, contact the Energy Hotline at: 1-800-772-3300

CERTIFICATE OF INSTALLATION – USER INSTRUCTIONS	CF2R-ALT-05-E
Prescriptive Residential Alterations That Do Not Require HERS Field Verification	(Page 1 of 8)

CF2R-ALT-05-E User Instructions

NOTE: If more space is needed, print a duplicate page and fill in.

Minimum requirements for prescriptive alteration compliance can be found in Building Energy Efficiency Standards Section 150.2(b)1.

Completing these documents will require that you have the Reference Appendices for the 2022 Building Energy Efficiency Standards. This document contains the Joint Appendices which are used to determine climate zone. When the term CF2R is used it means the CF2R-ALT-05. Worksheets are identified by their entire name and subsequently by only the worksheet number, such as ENV-02.

Instructions for sections with column numbers and row letters are given separately.

If any part of the alteration does not comply, prescriptive compliance fails, in which case the performance compliance approach must be used in an attempt to achieve compliance.

A. General Information

1. Project Name: Identifying information, such as owner's name.
2. Date Prepared: Date of document preparation.
3. Project Location: Legal street address of property or other applicable identifying information.
4. Building Front Orientation: Building front orientation expressed in degrees, where North = 0, East = 90, South = 180, and West = 270. Indicate cardinal if it is a subdivision project built in multiple orientations. The Standards (Section 100.1) include the following additional details for determining orientation:
 - Cardinal covers all orientations (for buildings that will be built in multiple orientations);
 - North is oriented to within 45 degrees of true north, including 45 degrees east of north;
 - East is oriented to within 45 degrees of true east, including 45 degrees south of east;
 - South is oriented to within 45 degrees of true south, including 45 degrees west of south;
 - West is oriented to within 45 degrees of true west, including 45 degrees south of west.
5. CA City: Legal city/town of property.
6. Number of Dwelling Units: 1 for single-family.
7. Zip Code: 5-digit zip code for the project location (used to determine climate zone).
8. Fuel Type: Natural Gas, Liquefied Propane Gas, or Electricity.
9. Climate zone: From Reference Appendices, Joint Appendix, JA2.1.1.

CERTIFICATE OF INSTALLATION – USER INSTRUCTIONS	CF2R-ALT-05-E
Prescriptive Residential Alterations That Do Not Require HERS Field Verification	(Page 2 of 8)

10. Total Conditioned Floor Area: Enter the new conditioned floor area in square feet (ft²), as measured from the outside of exterior walls of the dwelling unit or building being altered.
11. Building Type: Single Family (includes duplex).
12. Slab Area: Area of the first floor slab (if any) in square feet (ft²).
13. Project Scope: Insulation, Roof Replacement, Fenestration/Glazing, Heating System, Cooling System, Duct System, and/or Water Heating System alteration.

B. Roof/Ceiling Insulation

1. I.D.: A label from the plans (e.g., A1.4 or Roof) documenting the location of the installed insulation.
2. Manufacturer & Brand: Indicate the manufacturer and brand of the product being installed.
3. Framing Material: Wood or Metal.
4. Framing Size & Spacing: Indicate the framing size and spacing (e.g., 2x4 @ 16 in O.C.); enter N/A if not applicable.
5. Insulation Type: List the type of insulation used, such as: Batt, Loose Fill, or Spray Polyurethane Foam (SPF).
- 6.
7. Cavity Insulation R-value: Indicate the cavity insulation R-value.
8. Insulation Depth: Indicate, in inches, the amount of insulation installed.
9. Below Deck Insulation R-Value: Indicate the R-value of the continuous insulation, having no framing penetration, installed below the roof deck.

C. Wall Insulation

1. I.D.: A label from the plans, (e.g., A1.4 or Wall1) documenting the location of the installed insulation.
2. Manufacturer & Brand: Indicate the manufacturer and brand of the product being installed.
3. Framing Material: Wood or Metal.
4. Framing Size & Spacing: Indicate the framing size and spacing (e.g., 2x4 @ 16 in O.C.); enter N/A if not applicable.
5. Insulation Type: List the type of insulation used, such as batt, loose fill, or SPF.
6. Cavity Insulation R-value: Indicate the cavity insulation R-value.
7. Insulation Depth: Indicate, in inches, the amount of insulation installed.
8. Exterior Wall Insulation R-Value: Indicate the R-value of the continuous insulation, having no framing penetration, installed on the outside of the wall.
9. Interior Wall Insulation R-Value: Indicate the R-value of the continuous insulation, having no framing penetration, installed on the inside of the wall.

D. Mass Insulation

CERTIFICATE OF INSTALLATION – USER INSTRUCTIONS	CF2R-ALT-05-E
Prescriptive Residential Alterations That Do Not Require HERS Field Verification	(Page 3 of 8)

1. I.D.: A label from the plans (e.g., A1.4 or Wall1) documenting the location of the installed insulation.
2. Manufacturer & Brand: Indicate the manufacturer and brand of the product being installed.
3. Location: Indicate the location of the insulation, such as: Above Grade, Below Grade, Wall, or Roof.
4. Mass Thickness: Indicate the thickness of the mass, in inches, the insulation is applied to.
5. Furring Strip Type/Depth: Indicate the type, and thickness, of furring material installed (e.g., wood/1.0 inch thick).
6. Insulation Type: List the type of insulation used, such as: Spray Polyurethane Foam (SPF), Expanded Polystyrene (EPS), or Ethylene Propylene Diene Monomer (EPDM).
7. Exterior Insulation R-Value: Indicate the R-value of the continuous insulation, having no framing penetration, installed on the outside of the assembly.
8. Interior Insulation R-Value: Indicate the R-value of the continuous insulation, having no framing penetration, installed on the inside of the assembly.

E. Raised Floor Insulation

1. I.D.: A label from the plans (e.g., A1.4 or Floor1) documenting the location of the installed insulation.
2. Manufacturer & Brand: Indicate the manufacturer and brand of the product being installed.
3. Framing Material: Wood or Metal.
4. Framing Size & Spacing: Indicate the framing size and spacing (e.g., 2x4 @ 16 in O.C.); enter N/A if not applicable.
5. Insulation Type: List the type of insulation used, such as: Batt, Loose Fill, or Spray Polyurethane Foam (SPF).
6. Cavity Insulation R-value: Indicate the cavity insulation R-value.
7. Insulation Depth: Indicate, in inches, the amount of insulation installed.
8. Exterior Floor Insulation R-Value: Indicate the R-value of the continuous insulation, having no framing penetration, installed on the outside of the floor.
9. Interior Floor Insulation R-Value: Indicate the R-value of the continuous insulation, having no framing penetration, installed on the inside of the floor.

F. Slab Floor/Perimeter Insulation

1. I.D.: A label from the plans (e.g., A1.4 or Slab Floor1) documenting the location of the installed insulation.
2. Manufacturer & Brand: Indicate the manufacturer and brand of the product being installed.
3. Floor Type: Indicate the type of floor the insulation is being applied to, such as: Heated Slab or Slab on Grade.
4. Insulation Type: List the type of insulation used, such as: Ethylene Propylene Diene Monomer (EPDM), Polyisocyanurate (ISO), or Polystyrene.
5. Insulation Depth: Indicate, in inches, the depth of insulation installed.
6. Insulation R-Value: Indicate the insulation R-value being installed vertically and horizontally (if applicable).
7. Vertical Insulation Length: Indicate, in inches, the length of the insulation being installed.

CERTIFICATE OF INSTALLATION – USER INSTRUCTIONS	CF2R-ALT-05-E
Prescriptive Residential Alterations That Do Not Require HERS Field Verification	(Page 4 of 8)

8. Horizontal Insulation Length: Indicate, in feet, the length of the insulation being installed from the outside edge of the vertical insulation to the center of the slab.

G. Radiant Barrier

1. Brand Name and Product Number: Indicate the brand name and product number of the product used.
2. Installation Type: Indicate the installation type from the following list:
 - i. Attached to underside of roof deck;
 - ii. Attached to bottom of truss/rafters;
 - iii. Attached between truss/rafters;
 - iv. Draped over top of truss/rafters;
 - v. Attached to underside of roof deck with air space; or
 - vi. Attached to underside of roof deck with baffle.

NOTE: One of these six installation methods must be used; no other methods are allowed.

3. Total Attic Area (ft²): Provide the total attic area over conditioned space. When determining the total attic area, the area over unconditioned spaces such as garage is included when the attic spaces are connected. At least one square foot of net free venting area is required for each 300 square feet of attic (1:300).

H. Required Vent Area

1. Combined net free area (NFA) of installed upper and lower vents (in²): Indicate the total combined NFA of installed upper and lower vents in square inches.
2. Minimum required combined net free area (NFA) of upper and lower vents (in²): Total attic area divided by 300 and multiplied by 144.
3. Net free area (NFA) of installed upper vents (in²): Indicate the total NFA of installed upper vents in square inches.
4. Minimum required net free area (NFA) of upper vents (in²): Table H item 1 (combined NFA of installed upper and lower vents) multiplied by 0.3.

CERTIFICATE OF INSTALLATION – USER INSTRUCTIONS	CF2R-ALT-05-E
Prescriptive Residential Alterations That Do Not Require HERS Field Verification	(Page 5 of 8)

I. Roofing Products (Cool Roof) Installation Information

1. Roof Pitch: Indicate whether the roof pitch is less than 2:12 or greater than or equal to 2:12
2. CRRC Product ID Number: If a cool roof is installed, obtain the Product ID Number from the Cool Roof Rating Council’s (CRRC) product packaging label or [rated products directory](#).
3. Product Type: Indicate the product type being used.
4. CRRC Listed Aged Solar Reflectance: State whether the 3-year aged solar reflectance value of the product used is listed on the Cool Roof Rating Council’s (CRRC) product packaging label or [rated products directory](#)—Yes or No.
5. Installed Initial Solar Reflectance: Indicate the initial solar reflectance value of the product used; obtained from the Cool Roof Rating Council’s (CRRC) product packaging label or [rated products directory](#).
6. Aged Solar Reflectance: Indicate the aged solar reflectance value of the product used; obtained from the CRRC product packaging label or rated product directory.

NOTE: If the 3-year aged value is not available then use the equation in Section 110.8(i)2 of the Energy Standards to calculate an aged solar reflectance. One can also use the “Calculated Aged Solar Reflectance” from the Solar Reflectance Index (SRI) Calculator” available at the [California Energy Commission’s website](#).

7. Thermal Emittance: Indicate the thermal emittance value of the product used; obtained from the Cool Roof Rating Council’s (CRRC) product packaging label or [rated products directory](#). This can be either the initial or aged value.
8. Solar Reflectance Index (SRI): If applicable, obtain the value of the product used from the [Cool Roof Rating Council’s \(CRRC\) rated products directory](#), or the “Solar Reflectance Index (SRI) Calculator” available at the [California Energy Commission’s website](#).

J. Radiant Barrier and Attic Ventilation – Additional Requirements

This section contains additional requirements for Radiant Barriers, Lower Vents, Upper Vents, and Vent Area.

K. Roofing Products (Cool Roof) – Additional Requirements

This section contains additional requirements for Roofing Products. Other exceptions apply for additions and/or alterations.

L. Fenestration/Glazing

1. Tag/ID: The labeling format used in the plans - ensure each unique type is used consistently throughout the plan set (elevations, finish schedules, etc.) to identify each matching fenestration product, such as: Window-1, Skylight-1 etc. It should also be consistently used on the other compliance documents.
2. Manufacturer/Brand: Provide the manufacturer and brand name which identifies the fenestration product being installed.
3. Fenestration Area (ft²): Indicate the total installed surface area in square feet (ft²) of the fenestration.

CERTIFICATE OF INSTALLATION – USER INSTRUCTIONS	CF2R-ALT-05-E
Prescriptive Residential Alterations That Do Not Require HERS Field Verification	(Page 6 of 8)

4. Orientation: Indicate the orientation of the same like fenestration. Use different lines if the orientation of the same fenestration varies. Enter N, S, E, or W.
5. Chromogenic: Is the glazing product chromogenic? Yes or No
6. U-factor: Indicate the specified U-factor of the fenestration product(s) being installed. Do not mix different types on the same line.
7. U-factor Source: National Fenestration Rating Council (NFRC), California Energy Commission (CEC) Default, NA6 Alternative, or Area-weighted Average Worksheet (ENV-02). Enter the appropriate temporary label certificate identified as NFRC, CEC Default, NA6, or Area-weighted Average Worksheet (ENV-02). All windows installed must have a label certificate which identifies the window’s efficiencies. NFRC rated products have a temporary label that can be looked up in the [NFRC product directory](#) at..
8. SHGC: Indicate the specified solar heat gain coefficient (SHGC) of the fenestration product(s) being installed. Do not mix different types on the same line.
9. SHGC Source: National Fenestration Rating Council (NFRC), California Energy Commissioner (CEC) Default, NA6 Alternative, or Area-weighted Average Worksheet (ENV-02). Enter the appropriate temporary label certificate identified as NFRC, CEC Default, NA6, or Area-weighted Average Worksheet (ENV-02). All windows installed must have a label certificate which identifies the window’s efficiencies. NFRC rated products have a temporary label that can be looked up in the [NFRC product directory](#) at.
10. Fenestration Type: Provide a description of the window type, for instance, the frame material, coatings, whether it is operable or fixed.
11. Exterior Shading Devices: If exterior shading devices are installed in conjunction with fenestration then indicate the type used (e.g., sunscreens, vertical roller or shades, retractable or drop arm or operable awnings, or roll down blinds or slats); or if an overhang is, or will be, installed.
12. Comments/Special Features: Additional information for the field inspector.

M. Fenestration/Glazing – Additional Requirements

This section contains additional requirements for Fenestration/Glazing.

CERTIFICATE OF INSTALLATION – USER INSTRUCTIONS	CF2R-ALT-05-E
Prescriptive Residential Alterations That Do Not Require HERS Field Verification	(Page 7 of 8)

N. Space Conditioning (SC) Systems – Heating/Cooling

Requirements of the Standards apply to a heating and cooling system alteration based on the type of alteration and the system type (Section 150.2(b)1). A completely new system will meet all mandatory and prescriptive requirements, which vary by climate zone (based on Section 150.2(b)1C).

When parts of a system are replaced, it may trigger some of the same requirements that apply to new systems and duct alterations. A Certificate of Compliance for Alterations to Space Conditioning Systems (CF1R-ALT-02) is required for each dwelling unit with a space conditioning system alteration.

1. SC System Identification or Name: Name of the space conditioning (SC) system or any other identifying name.
2. SC System Location or Area Served: Zone, or area, served by the space conditioning (SC) system.
3. Exemption from HERS Verification: Section 150.2(b)1E
 - a. Space Conditioning (SC) System was not altered.
 - b. Duct systems with less than 25 linear feet in unconditioned spaces as determined by visual inspection.
 - c. Existing duct systems constructed, insulated, or sealed with asbestos.
 - d. Duct systems that have been documented to have been previously sealed as confirmed through field verification and diagnostic testing in accordance with procedures in the Reference Appendices, Residential Appendix, RA3.1.

O. Installed Water Heating System

Water heating compliance for an alteration is described in Section 150.2(b)1H.

Options:

1. Gas or propane water heating system; or
2. A single heat pump water heater. The storage tank shall not be located outdoors and shall be placed on an incompressible, rigid insulated surface with a minimum thermal resistance of R-10. The water heater shall be installed with a communication interface that meets either the requirements of Section 110.12(a) or has a ANSI/CTA-2045-B communication port; or
3. A single heat pump water heater that meets the requirements of NEEA Advanced Water Heater Specification Tier 3 or higher; or
4. If no natural gas is connected to the existing water heater location, a consumer electric water heater

NOTE: If the proposed installation does not meet the requirements allowed specifically for alterations, then use the computer performance approach to show compliance.

1. Is natural gas connected to the existing water heater? Yes or No.
2. Water Heating System Identification or Name: Name of the Water Heating System or any other identifying name.

CERTIFICATE OF INSTALLATION – USER INSTRUCTIONS	CF2R-ALT-05-E
Prescriptive Residential Alterations That Do Not Require HERS Field Verification	(Page 8 of 8)

3. System Option (from §150.2(b)1Hiii): Indicate the prescriptive option: 1, 2, 3, or 4.
4. Water Heating System Type: Domestic Hot Water (DHW), Hydronic, or Combined Hydronic. DHW is for domestic hot water, hydronic is a water heating system used for space heating only; combined hydronic is when the water heater will provide both space conditioning and domestic hot water.
5. Water Heater Type: Consumer Instantaneous, Consumer Storage, Heat pump water heater, NEEA Tier 3 heat pump water heater
6. Volume: Indicate the volume of the storage tank. For consumer instantaneous, enter 'n/a'.
7. Fuel Type: Natural Gas, Propane, Heat Pump, Electricity.
8. Number of Water Heaters in System: Enter the total number of water heaters for each system.

P. Installed Water Heater Manufacturer Information

This table reports the manufacturer information of the installed water heater(s). Require one line for each installed water heater.

1. Water Heating System ID or Name: Name of the water heating system or any other identifying name.
2. Manufacturer: Provide the manufacturer’s name which identifies the water heater being installed.
3. Model Number: Provide the model number which identifies the water heater being installed.

Documentation Declaration Statements

1. The person who prepared the CF2R will sign and complete the fields for their name, company (if applicable), address, phone number, certification information (if applicable), date and signature.
2. The person who is assuming responsibility for the project being built to comply with Title 24, Part 6, will complete the fields for their name, company (if applicable), address, phone number, license number (if applicable), date and signature.