DOCKETED			
Docket Number:	19-BSTD-06		
Project Title:	Local Ordinances Exceeding the 2019 Energy Code		
TN #:	243730-10		
Document Title:	City of Santa Clara - 2019 Residential Retrofit 2021-08-27 Cost- effectiveness Report		
Description:	Plain text of the City of Santa Clara 2019 August 27, 2021 Residential Retrofit Cost-effectiveness Study		
Filer:	Danuta Drozdowicz		
Organization:	City of Santa Clara		
Submitter Role:	Public Agency		
Submission Date:	6/27/2022 3:54:52 PM		
Docketed Date:	6/27/2022		



2019 Cost-Effectiveness Study: Existing Single Family Residential Building Upgrades

Last Modified: 2021-08-27 Prepared by: Frontier Energy, Inc. Misti Bruceri & Associates, LLC **Prepared for:** Kelly Cunningham Codes and Standards Program Pacific Gas and Electric Company SoCalGas Pacific Gas and Electric Company® EDISON Energy for What's Ahead A Sempra Energy utility AC Sempra Energy utility*

LEGAL NOTICE

This report was prepared by Pacific Gas and Electric Company and funded by the California utility customers under the auspices of the California Public Utilities Commission.

Copyright 2020, Pacific Gas and Electric Company. All rights reserved, except that this document may be used, copied, and distributed without modification.

Neither PG&E nor any of its employees makes any warranty, express or implied; or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any data, information, method, product, policy or process disclosed in this document; or represents that its use will not infringe any privately-owned rights including, but not limited to, patents, trademarks or copyrights.

Acronym List

ACH50	Air Changes per Hour at 50 pascals pressure differential
AC	Air Conditioner
ACM	Alternative Calculation Method
AFUE	Annual Fuel Utilization Efficiency
А	Ampere
B/C	Benefits-to Cost; as in Lifecycle Benefit-to-Cost Ratio
BSC	Building Standards Commission
Btu	British thermal units
CALGreen	Title 24, Part 11
CASE	Codes and Standards Enhancement
CBECC-Res	California Building Energy Code Compliance – Residential: Computer program developed by the California Energy Commission for use in demonstrating compliance with the California Residential Building Energy Efficiency Standards
CFI	California Flexible Installation
CFL	Compact Fluorescent Lamp
CO ₂ e	Carbon Dioxide (CO ₂)-equivalent
CPAU	City of Palo Alto Utilities
CRRC	Cool Roof Rating Council
CZ	California Climate Zone
DHW	Domestic Hot Water
E3	Energy and Environmental Economics
EDR	Energy Design Rating
EER	Energy Efficiency Ratio
ft ²	Square foot
GHG	Greenhouse Gas
GRC	General Rate Case
gpm	Gallons per minute
HERS Rater	Home Energy Rating System Rater
HPWH	Heat Pump Water Heater
HSPF	Heating Seasonal Performance Factor
HVAC	Heating, Ventilation, and Air Conditioning
IC	Insulation Contact
IOU	Investor-Owned Utility
ITC	Income Tax Credit (federal)

kWh	Kilowatt-hour
kW _{DC}	Kilowatt Direct Current; nominal rated power of a photovoltaic system
lb(s)	Pound(s)
LCC	Lifecycle Cost
LED	Light-Emitting Diode
MF	Multifamily
NEEA	Northwest Energy Efficiency Alliance
NEM	Net Energy Metering
NPV	Net Present Value
PG&E	Pacific Gas and Electric Company
PV	Photovoltaic
SCE	Southern California Edison
SDG&E	San Diego Gas and Electric
SEER	Seasonal Energy Efficiency Ratio
SHGC	Solar Heat Gain Coefficient
SMUD	Sacramento Municipal Utility District
TDV	Time Dependent Valuation
therm	Unit for quantity of heat that equals 100,000 Btu
Title 24	Title 24, Part 6
TOU	Time-of-Use
UEF	Uniform Energy Factor
V	Volt
W	Watt
W _{DC}	Watt Direct Current

1 TABLE OF CONTENTS

 Introduction Methodology and Assumptions 3.1 Building Prototypes 3.2 Efficiency Measures 3.2.1 Building Envelope/Non-Preempted Measures 3.2.2 Photovoltaics (PV) and Battery Measures 3.2.3 Equipment Fuel Substitution Measures – Heat Pump Replacements 3.3 Efficiency Packages 3.3.1 Envelope and Duct Packages 3.3.2 Additional Packages 3.4 Measure Cost 3.4.1 Building Envelope/Non-Preempted Measures 	
 3.1 Building Prototypes. 3.2 Efficiency Measures. 3.2.1 Building Envelope/Non-Preempted Measures. 3.2.2 Photovoltaics (PV) and Battery Measures. 3.2.3 Equipment Fuel Substitution Measures – Heat Pump Replacements	
 3.1 Building Prototypes. 3.2 Efficiency Measures. 3.2.1 Building Envelope/Non-Preempted Measures. 3.2.2 Photovoltaics (PV) and Battery Measures. 3.2.3 Equipment Fuel Substitution Measures – Heat Pump Replacements	
 3.2 Efficiency Measures	
 3.2.1 Building Envelope/Non-Preempted Measures	
 3.2.2 Photovoltaics (PV) and Battery Measures	
 3.2.3 Equipment Fuel Substitution Measures – Heat Pump Replacements	
 3.3.1 Envelope and Duct Packages 3.3.2 Additional Packages 3.4 Measure Cost 	
3.3.2 Additional Packages 3.4 Measure Cost	
3.4 Measure Cost	
3.4.1 Building Envelope/Non-Preempted Measures	11 15 16 17
	15 16 17
3.4.2 PV and Battery Measures	16 17
3.4.3 Equipment Fuel Substitution Measures – Heat Pump Equipment	17
3.5 Cost Effectiveness	
3.5.1 On-Bill LCC	40
3.5.2 TDV LCC	
3.6 Greenhouse Gas (GHG) Emissions Reductions	
3.7 Energy Performance Equivalency of Retrofit Measures and Packages	19
4 Results	21
4.1 Building Envelope/Non-Preempted Measures	
4.2 Envelope and Duct Packages	
4.3 Water Heating and Lighting Measures/Packages	
4.4 PV and Batteries	
4.5 Equipment Fuel Substitution Measures	
5 Energy Performance Equivalency	41
6 Recommendations and Discussion	
6.1 Recommended Efficiency Measures	
6.3 Other Considerations	
7 References	51
8 Appendices	53
8.1 Appendix A: Map of California Climate Zones	
8.2 Appendix B: Utility Rate Schedules	54
8.3 Appendix C – Standards Sections	
8.4 Appendix D – Measure Cost-Effectiveness Tables	
8.5 Appendix E – Details on Energy Performance Equivalency	

LIST OF TABLES

TABLE 1: PROTOTYPE CHARACTERISTICS	4
TABLE 2: EFFICIENCY CHARACTERISTICS FOR THREE VINTAGE CASES	5
TABLE 3: SINGLE FAMILY PV SIZING FOR 1,665 FT ² HOME BY CLIMATE ZONE (KWDC)	8
TABLE 4: MEASURE DESCRIPTIONS & COST ASSUMPTIONS - NON-PREEMPTED MEASURES ^A	
TABLE 5: MEASURE DESCRIPTIONS & COST ASSUMPTIONS – PV AND BATTERIES ^A	14
TABLE 6: HVAC MEASURE COST ASSUMPTIONS – ELECTRIC REPLACEMENTS	15

TABLE 7: WATER HEATING MEASURE COST ASSUMPTIONS – ELECTRIC REPLACEMENTS	
TABLE 8: ELECTRIC READY MEASURE COST ASSUMPTIONS	
TABLE 9: IOU UTILITY TARIFFS APPLIED BASED ON CLIMATE ZONE	
TABLE 10: RESULTS TABLE LEGEND	
TABLE 11: SUMMARY OF SINGLE FAMILY EFFICIENCY MEASURES – ON-BILL & 2019 TDV	
TABLE 12: SUMMARY OF SINGLE FAMILY EFFICIENCY PACKAGES – ON-BILL & 2019 TDV	
TABLE 13: SUMMARY OF SINGLE FAMILY PV & BATTERIES – ON-BILL & 2019 TDV	. 30
TABLE 14: SUMMARY OF SINGLE FAMILY EQUIPMENT FUEL SUBSTITUTION-ON-BILL & TDV – FEDERAL MINIMUM EFFICIENCY	. 37
TABLE 15: SUMMARY OF SINGLE FAMILY EQUIPMENT FUEL SUBSTITUTION + PV - ON-BILL & TDV - FEDERAL MINIMUM	
EFFICIENCY	
TABLE 16: SUMMARY OF SINGLE FAMILY ELECTRIC READY MEASURES AT PV INSTALL – ON-BILL & 2019 TDV	
TABLE 17: ENERGY PERFORMANCE EQUIVALENCY FOR EACH VINTAGE BY CLIMATE ZONE	
TABLE 18: ENERGY PERFORMANCE EQUIVALENCY BY MEASURE FOR CLIMATE ZONE 12	
TABLE 19: PERFORMANCE EQUIVALENCY OPTIONS – PRE-1978 HOME	
TABLE 20: PERFORMANCE EQUIVALENCY OPTIONS – 1992-2010 HOME	
TABLE 21: PG&E BASELINE TERRITORY BY CLIMATE ZONE	. 54
TABLE 22: PG&E MONTHLY GAS RATE (\$/THERM)	
TABLE 23: SCE BASELINE TERRITORY BY CLIMATE ZONE	
TABLE 24: SOCALGAS BASELINE TERRITORY BY CLIMATE ZONE	. 60
TABLE 25: SOCALGAS MONTHLY GAS RATE (\$/THERM)	. 60
TABLE 26: SDG&E BASELINE TERRITORY BY CLIMATE ZONE	
TABLE 27: SDG&E MONTHLY GAS RATE (\$/THERM)	
TABLE 28: CPAU MONTHLY GAS RATE (\$/THERM)	
TABLE 29: REAL UTILITY RATE ESCALATION RATE ASSUMPTIONS	
TABLE 30: CZ 1 - SINGLE FAMILY EFFICIENCY UPGRADE COST-EFFECTIVENESS RESULTS	. 73
TABLE 31: CZ 1 - SINGLE FAMILY EFFICIENCY PACKAGES COST-EFFECTIVENESS RESULTS	. 74
TABLE 32: CZ 1 - SINGLE FAMILY PV & BATTERY COST-EFFECTIVENESS RESULTS	. 75
TABLE 33: CZ 1 - SINGLE FAMILY EQUIPMENT FUEL SUBSTITUTION COST-EFFECTIVENESS RESULTS	. 76
TABLE 34: CZ 2 - SINGLE FAMILY EFFICIENCY UPGRADE COST-EFFECTIVENESS RESULTS	. 78
TABLE 35: CZ 2 - SINGLE FAMILY EFFICIENCY PACKAGES COST-EFFECTIVENESS RESULTS	
TABLE 36: CZ 2 - SINGLE FAMILY PV & BATTERY COST-EFFECTIVENESS RESULTS	
TABLE 37: CZ 2 - SINGLE FAMILY EQUIPMENT FUEL SUBSTITUTION COST-EFFECTIVENESS RESULTS	
TABLE 38: CZ 3 - SINGLE FAMILY EFFICIENCY UPGRADE COST-EFFECTIVENESS RESULTS	. 83
TABLE 39: CZ 3 - SINGLE FAMILY EFFICIENCY PACKAGES COST-EFFECTIVENESS RESULTS	. 84
TABLE 40: CZ 3 - SINGLE FAMILY PV & BATTERY COST-EFFECTIVENESS RESULTS	
TABLE 41: CZ 3 - SINGLE FAMILY EQUIPMENT FUEL SUBSTITUTION COST-EFFECTIVENESS RESULTS	
TABLE 42: CZ 4 (PG&E) - SINGLE FAMILY EFFICIENCY UPGRADE COST-EFFECTIVENESS RESULTS	
TABLE 43: CZ 4 (PG&E) - SINGLE FAMILY EFFICIENCY PACKAGES COST-EFFECTIVENESS RESULTS	
TABLE 44: CZ 4 (PG&E) - SINGLE FAMILY PV & BATTERY COST-EFFECTIVENESS RESULTS	
TABLE 45: CZ 4 (PG&E) - SINGLE FAMILY EQUIPMENT FUEL SUBSTITUTION COST-EFFECTIVENESS RESULTS	
TABLE 46: CZ 4 (CPAU) - SINGLE FAMILY EFFICIENCY UPGRADE COST-EFFECTIVENESS RESULTS	
TABLE 47: CZ 4 (CPAU) - SINGLE FAMILY EFFICIENCY PACKAGES COST-EFFECTIVENESS RESULTS	
TABLE 48: CZ 4 (CPAU) - SINGLE FAMILY PV & BATTERY COST-EFFECTIVENESS RESULTS	
TABLE 49: CZ 4 (CPAU) - SINGLE FAMILY EQUIPMENT FUEL SUBSTITUTION COST-EFFECTIVENESS RESULTS	
TABLE 50: CZ 5 (PG&E) - SINGLE FAMILY EFFICIENCY UPGRADE COST-EFFECTIVENESS RESULTS	
TABLE 51: CZ 5 (PG&E) - SINGLE FAMILY EFFICIENCY PACKAGES COST-EFFECTIVENESS RESULTS	
TABLE 52: CZ 5 (PG&E) - SINGLE FAMILY PV & BATTERY COST-EFFECTIVENESS RESULTS	
TABLE 53: CZ 5 (PG&E) - SINGLE FAMILY EQUIPMENT FUEL SUBSTITUTION COST-EFFECTIVENESS RESULTS	
TABLE 54: CZ 5 (PG&E/SoCaLGAS) - SINGLE FAMILY EFFICIENCY UPGRADE COST-EFFECTIVENESS RESULTS	
TABLE 55: CZ 5 (PG&E/SOCALGAS) - SINGLE FAMILY EFFICIENCY PACKAGES COST-EFFECTIVENESS RESULTS	
TABLE 56: CZ 5 (PG&E/SoCaLGAS) - SINGLE FAMILY PV & BATTERY COST-EFFECTIVENESS RESULTS	
TABLE 57: CZ 5 (PG&E/SoCaLGAS) - SINGLE FAMILY EQUIPMENT FUEL SUBSTITUTION COST-EFFECTIVENESS RESUL	
TABLE 58: CZ 6 - SINGLE FAMILY EFFICIENCY UPGRADE COST-EFFECTIVENESS RESULTS	108

TABLE 59: CZ 6 - SINGLE FAMILY EFFICIENCY PACKAGES COST-EFFECTIVENESS RESULTS	109
TABLE 60: CZ 6 - SINGLE FAMILY PV & BATTERY COST-EFFECTIVENESS RESULTS	110
TABLE 61: CZ 6 - SINGLE FAMILY EQUIPMENT FUEL SUBSTITUTION COST-EFFECTIVENESS RESULTS	111
TABLE 62: CZ 7 - SINGLE FAMILY EFFICIENCY UPGRADE COST-EFFECTIVENESS RESULTS	
TABLE 63: CZ 7 - SINGLE FAMILY EFFICIENCY PACKAGES COST-EFFECTIVENESS RESULTS	
TABLE 64: CZ 7 - SINGLE FAMILY PV & BATTERY COST-EFFECTIVENESS RESULTS	
TABLE 65: CZ 7 - SINGLE FAMILY EQUIPMENT FUEL SUBSTITUTION COST-EFFECTIVENESS RESULTS	
TABLE 66: CZ 8 - SINGLE FAMILY EFFICIENCY UPGRADE COST-EFFECTIVENESS RESULTS	
TABLE 67: CZ 8 - SINGLE FAMILY EFFICIENCY PACKAGES COST-EFFECTIVENESS RESULTS	
TABLE 68: CZ 8 - SINGLE FAMILY PV & BATTERY COST-EFFECTIVENESS RESULTS	
TABLE 69: CZ 8 - SINGLE FAMILY EQUIPMENT FUEL SUBSTITUTION COST-EFFECTIVENESS RESULTS	
TABLE 70: CZ 9 - SINGLE FAMILY EFFICIENCY UPGRADE COST-EFFECTIVENESS RESULTS	
TABLE 71: CZ 9 - SINGLE FAMILY EFFICIENCY PACKAGES COST-EFFECTIVENESS RESULTS	
TABLE 72: CZ 9 - SINGLE FAMILY PV & BATTERY COST-EFFECTIVENESS RESULTS	
TABLE 72: 02 0 - SINGLE FAMILY FOR DATTER OF CONTRACTOR RECORDED FOR THE CONTRACTOR	
TABLE 74: CZ 10 (SCE/SoCalGas) - SINGLE FAMILY EFFICIENCY UPGRADE COST-EFFECTIVENESS RESULTS	
TABLE 75: CZ 10 (SCE/SOCALGAS) - SINGLE FAMILY EFFICIENCY PACKAGES COST-EFFECTIVENESS RESULTS	
TABLE 76: CZ 10 (SCE/SOCALGAS) - SINGLE FAMILY PV & BATTERY COST-EFFECTIVENESS RESULTS	
TABLE 70: CZ 10 (SCE/SOCALGAS) - SINGLE FAMILY FV & DATTERY COST-EFFECTIVENESS RESULTS	
TABLE 11. CZ 10 (SCE/SOCALGAS) - SINGLE FAMILY EQUIPMENT FUEL SUBSTITUTION COST-EFFECTIVENESS RESUL	
TABLE 78: CZ 10 (SDG&E) - SINGLE FAMILY EFFICIENCY UPGRADE COST-EFFECTIVENESS RESULTS	
TABLE 70: CZ 10 (SDG&E) - SINGLE FAMILY EFFICIENCY PACKAGES COST-EFFECTIVENESS RESULTS TABLE 79: CZ 10 (SDG&E) - SINGLE FAMILY EFFICIENCY PACKAGES COST-EFFECTIVENESS RESULTS	
TABLE 79: CZ 10 (SDG&E) - SINGLE FAMILY PV & BATTERY COST-EFFECTIVENESS RESULTS	
TABLE 80: CZ 10 (SDG&E) - SINGLE FAMILY FV & DATTERY COST-EFFECTIVENESS RESULTS	
TABLE 82: CZ 10 (3DG&E) - SINGLE FAMILY EQUIPMENT FOEL SUBSTITUTION COST-EFFECTIVENESS RESULTS	
TABLE 82: CZ 11 - SINGLE FAMILY EFFICIENCY OF GRADE COST-EFFECTIVENESS RESULTS	
TABLE 83: CZ 11 - SINGLE FAMILY EFFICIENCY FACKAGES COST-EFFECTIVENESS RESULTS TABLE 84: CZ 11 - SINGLE FAMILY PV & BATTERY COST-EFFECTIVENESS RESULTS	
TABLE 64. CZ 11 - SINGLE FAMILY FV & BATTERY COST-EFFECTIVENESS RESULTS TABLE 85: CZ 11 - SINGLE FAMILY EQUIPMENT FUEL SUBSTITUTION COST-EFFECTIVENESS RESULTS	
TABLE 86: CZ 12 (PG&E) - SINGLE FAMILY EFFICIENCY UPGRADE COST-EFFECTIVENESS RESULTS	
TABLE 87: CZ 12 (PG&E) - SINGLE FAMILY EFFICIENCY PACKAGES COST-EFFECTIVENESS RESULTS	
TABLE 88: CZ 12 (PG&E) - SINGLE FAMILY PV & BATTERY COST-EFFECTIVENESS RESULTS	
TABLE 89: CZ 12 (PG&E) - SINGLE FAMILY EQUIPMENT FUEL SUBSTITUTION COST-EFFECTIVENESS RESULTS	
TABLE 90: CZ 12 (SMUD/PG&E) - SINGLE FAMILY EFFICIENCY UPGRADE COST-EFFECTIVENESS RESULTS TABLE 91: CZ 12 (SMUD/PG&E) - SINGLE FAMILY EFFICIENCY UPGRADE COST-EFFECTIVENESS RESULTS TABLE 92: CZ 12 (SMUD/PG&E) - SINGLE FAMILY EFFICIENCY UPGRADE COST-EFFECTIVENESS RESULTS	
TABLE 91: CZ 12 (SMUD/PG&E) - SINGLE FAMILY EFFICIENCY PACKAGES COST-EFFECTIVENESS RESULTS	
TABLE 92: CZ 12 (SMUD/PG&E) - SINGLE FAMILY PV & BATTERY COST-EFFECTIVENESS RESULTS	
TABLE 93: CZ 12 (SMUD/PG&E) - SINGLE FAMILY EQUIPMENT FUEL SUBSTITUTION COST-EFFECTIVENESS RESULTS	
TABLE 94: CZ 13 - SINGLE FAMILY EFFICIENCY UPGRADE COST-EFFECTIVENESS RESULTS.	
TABLE 95: CZ 13 - SINGLE FAMILY EFFICIENCY PACKAGES COST-EFFECTIVENESS RESULTS	
TABLE 96: CZ 13 - SINGLE FAMILY PV & BATTERY COST-EFFECTIVENESS RESULTS	
TABLE 97: CZ 13 - SINGLE FAMILY EQUIPMENT FUEL SUBSTITUTION COST-EFFECTIVENESS RESULTS	
TABLE 98: CZ 14 (SCE/SoCALGAS) - SINGLE FAMILY EFFICIENCY UPGRADE COST-EFFECTIVENESS RESULTS	
TABLE 99: CZ 14 (SCE/SoCALGAS) - SINGLE FAMILY EFFICIENCY PACKAGES COST-EFFECTIVENESS RESULTS	
TABLE 100: CZ 14 (SCE/SoCALGAS) - SINGLE FAMILY PV & BATTERY COST-EFFECTIVENESS RESULTS	
TABLE 101: CZ 14 (SCE/SoCALGAS) - SINGLE FAMILY EQUIPMENT FUEL SUBSTITUTION COST-EFFECTIVENESS RESU	
TABLE 102: CZ 14 (SDG&E) - SINGLE FAMILY EFFICIENCY UPGRADE COST-EFFECTIVENESS RESULTS	
TABLE 103: CZ 14 (SDG&E) - SINGLE FAMILY EFFICIENCY PACKAGES COST-EFFECTIVENESS RESULTS	
TABLE 104: CZ 14 (SDG&E) - SINGLE FAMILY PV & BATTERY COST-EFFECTIVENESS RESULTS	
TABLE 105: CZ 14 (SDG&E) - SINGLE FAMILY EQUIPMENT FUEL SUBSTITUTION COST-EFFECTIVENESS RESULTS	
TABLE 106: CZ 15 - SINGLE FAMILY EFFICIENCY UPGRADE COST-EFFECTIVENESS RESULTS.	
TABLE 107: CZ 15 - SINGLE FAMILY EFFICIENCY PACKAGES COST-EFFECTIVENESS RESULTS	
TABLE 108: CZ 15 - SINGLE FAMILY PV & BATTERY COST-EFFECTIVENESS RESULTS	
TABLE 109: CZ 15 - SINGLE FAMILY EQUIPMENT FUEL SUBSTITUTION COST-EFFECTIVENESS RESULTS	
TABLE 110: CZ 16 - SINGLE FAMILY EFFICIENCY UPGRADE COST-EFFECTIVENESS RESULTS	173

TABLE 111: CZ 16 - SINGLE FAMILY EFFICIENCY PACKAGES COST-EFFECTIVENESS RESULTS	174
TABLE 112: CZ 16 - SINGLE FAMILY PV & BATTERY COST-EFFECTIVENESS RESULTS	175
TABLE 113: CZ 16 - SINGLE FAMILY EQUIPMENT FUEL SUBSTITUTION COST-EFFECTIVENESS RESULTS	176
TABLE 114: ENERGY PERFORMANCE EQUIVALENCY BY MEASURE FOR THE PRE-1978 VINTAGE HOME	179
TABLE 115: ENERGY PERFORMANCE EQUIVALENCY BY MEASURE FOR THE 1978-1991 VINTAGE HOME	181
TABLE 116: ENERGY PERFORMANCE EQUIVALENCY BY MEASURE FOR THE 1992-2010 VINTAGE HOME	183
TABLE 117: ENERGY PERFORMANCE EQUIVALENCY FOR PACKAGES FOR ALL VINTAGES	

List of Figures

FIGURE 1: NET BENEFIT-ROOFTOP PV SYSTEM SIZED TO NEW CONSTRUCTION STANDARDS (2-4 KW): 1992-2010	28
FIGURE 2: NET BENEFIT - ROOFTOP PV + 10 KWH BATTERY, TOU CONTROL: PRE-1978.	29
FIGURE 3: NET BENEFIT - ROOFTOP PV + 10 KWH BATTERY, TOU CONTROL: 1992-2010	29
FIGURE 4: NET BENEFIT – MINIMUM EFFICIENCY HEAT PUMP AT HVAC REPLACEMENT: 1992-2010	31
FIGURE 5: NET BENEFIT - HIGH-EFFICIENCY HEAT PUMP AT HVAC REPLACEMENT: 1992-2010	32
FIGURE 6: NET BENEFIT - MIN EFFICIENCY HEAT PUMP AT HVAC REPLACEMENT + PV: 1992-2010	33
FIGURE 7: NET BENEFIT - MIN EFFICIENCY HEAT PUMP AT HVAC REPLACEMENT + PV + PANEL UPGRADE: 1992-20103	33
FIGURE 8: NET BENEFIT - MINIMUM EFFICIENCY HPWH AT DHW REPLACEMENT: 1992-2010	34
FIGURE 9: NET BENEFIT – HIGH-EFFICIENCY HPWH AT DHW REPLACEMENT: 1992-2010	35
FIGURE 10: NET BENEFIT - MIN EFFICIENCY HPWH AT DHW REPLACEMENT + PV: 1992-2010	36
FIGURE 11: NET BENEFIT - MIN EFFICIENCY HPWH AT DHW REPLACEMENT + PV + PANEL UPGRADE: 1992-2010	36
FIGURE 12: NET BENEFIT – PV AND ELECTRIC READINESS: 1992-2010.	39
FIGURE 13: MAP OF CALIFORNIA CLIMATE ZONES.	53

1 Overview

The California Statewide Codes and Standards Reach Codes Team (Statewide Reach Code Team) has updated the prior cost-effectiveness study for existing building upgrades completed in February 2020 (Statewide Reach Codes Team, 2020). This analysis evaluates the feasibility and cost effectiveness of retrofit measures in California existing single family homes built before 2010. A lifecycle cost (LCC) approach to evaluating cost effectiveness was applied quantifying the savings associated with energy efficiency measures compared to measure costs. The focus of this study was to revisit the recommended retrofit efficiency measure and package cost effectiveness based on latest utility rates, updated measure costs and evaluate cost effectiveness of additional efficiency and grid integration measures, including:

- Revisit base case assumptions for different vintages.
- Additional efficiency upgrade options including:
 - High-efficiency equipment replacement as alternative to non-preempted upgrade measures.
 - Higher ceiling insulation requirements.
 - o Improved duct insulation and reduced duct leakage.
- PV system installation.
- Evaluation of electrification measures at equipment change-out and electrification-ready measures.
- Electrification measures tied to installation of PV system.
- Battery storage measures.

2 Introduction

The California Codes and Standards Reach Codes program provides technical support to local governments considering adopting a local ordinance (reach code) intended to support meeting local and/or statewide energy and greenhouse gas reduction goals. The program facilitates adoption and implementation of the code when requested by local jurisdictions by providing resources such as cost effectiveness studies, model language, sample findings, and other supporting documentation. Local jurisdictions that are considering adopting ordinances may contact the program for support through its website, <u>LocalEnergyCodes.com</u>.

The California Building Energy Efficiency Standards, or Title 24, Part 6 (Title 24) (California Energy Commission, 2018) is maintained and updated every three years by two state agencies: the California Energy Commission (Energy Commission) and the Building Standards Commission (BSC). In addition to enforcing the code, local jurisdictions have the authority to adopt local energy efficiency ordinances—or reach codes—that exceed the minimum standards defined by Title 24 (as established by Public Resources Code Section 25402.1(h)2 and Section 10-106 of the Building Energy Efficiency Standards). Local jurisdictions must demonstrate that the requirements of the proposed ordinance are cost-effective and result in buildings consuming less energy than is permitted by Title 24. In addition, the jurisdiction must obtain approval from the Energy Commission and file the ordinance with the BSC for the ordinance to be legally enforceable.

This report documents cost-effective combinations of measures that exceed the minimum state requirements, the 2019 Building Energy Efficiency Standards, effective January 1, 2020. Local jurisdictions in California may consider adopting local energy ordinances to achieve energy savings beyond what will be accomplished by enforcing building efficiency requirements that apply statewide. This report was developed in coordination with the California Statewide Investor-Owned Utilities (IOUs) Codes and Standards Program, key consultants, and engaged cities—collectively known as the Statewide Reach Code Team.

The focus of this study is on existing single family buildings. This analysis does not apply to low- or high-rise multifamily buildings. Each jurisdiction must establish the appropriate structure and threshold for triggering the requirements. Some common structures include triggering the requirements at major remodels, additions, or date-certain (upgrades must be completed by a specific date). Some of these measures could be triggered with a permit for another specific measure, such as a reroof. The analysis includes scenarios of individual measures, as well as package upgrades, and identifies cost-effective options based on the existing conditions of the building in all 16 California Climate Zones (CZ) (see Appendix A: Map of California Climate Zones for a graphical depiction of climate zone locations).

This analysis does not evaluate the impact of retrofit measures on Title 24 compliance margins, as the proposed measures are required in addition to achieving compliance with all codes.

3 Methodology and Assumptions

This analysis uses two different metrics to assess cost effectiveness of the proposed upgrades. Both methodologies require estimating and quantifying the incremental costs and energy savings associated with each energy efficiency measure. The main difference between the methodologies is the manner in which they value energy and thus the cost savings of reduced or avoided energy use:

- <u>Utility Bill Impacts (On-Bill)</u>: Customer-based Lifecycle Cost (LCC) approach that values energy based upon estimated site energy usage and customer On-Bill savings using electricity and natural gas utility rate schedules over a 30-year duration accounting for discount rate and energy cost inflation.
- <u>Time Dependent Valuation (TDV)</u>: Energy Commission LCC methodology, which is intended to capture the societal value or cost of energy use including long-term projected costs, such as the cost of providing energy during peak periods of demand and other societal costs, such as projected costs for carbon emissions, as well as grid transmission and distribution impacts. This metric values energy use differently depending on the fuel source (natural gas, electricity, and propane), time of day, and season. Electricity used (or saved) during peak periods has a much higher value than electricity used (or saved) during off-peak periods (Horii et al., 2014). This is the methodology used by the Energy Commission in evaluating cost effectiveness for efficiency measures in Title 24. Both 2019 and 2022 TDV multipliers are evaluated and documented in this analysis.

The general approach applied in this analysis is to evaluate performance and determine cost effectiveness of various energy retrofit measures, individually and as packages, in single family homes. Three unique building vintages are considered: pre-1978, 1978-1991, and 1992-2010. The vintages were defined based on review of historic Title 24 code requirements and selecting year ranges with distinguishing features. The applied approach establishes recommendations based on existing conditions and cost effectiveness of each measure or package.

The California Building Energy Code Compliance – Residential (CBECC-Res) 2019.1.2 and 2022.0.1 compliance simulation tools were used to evaluate energy savings for most measures, with the exception of those outside the code compliance scope. In these cases, a combination of the Department of Energy's BEopt software and EnergyPlus v9.3. simulation engine was used.

This analysis builds on the work completed earlier in 2020 for the 2019 Title 24 (Statewide Reach Codes Team, 2020) and has been updated to reflect changes in measure costs over time as well as current utility tariffs. Energy simulations were re-evaluated in CBECC-Res 2019 to evaluate cost effectiveness from a TDV perspective under the 2019 Title 24. TDV cost effectiveness was also completed using the 2022 TDV and weather files to evaluate cost effectiveness with the latest version of the software for future code cycles.

3.1 Building Prototypes

The Energy Commission defines building prototypes which it uses to evaluate the cost effectiveness of proposed changes to Title 24 requirements. Average home size has steadily increased over time,¹ and the Energy Commission single family new construction prototypes are larger than many existing single family homes across California. For this analysis, an existing home prototype developed by the Energy Commission for residential ACM testing² was used with the following revisions. The original prototype includes an existing 1,440 square foot (ft²) space and a 225 ft² addition. For this analysis, the entire 1,665 ft² was evaluated as existing space and features (i.e., insulation levels, glazing) were applied consistently across the entire building consistent with the existing home specifications in Table 2. Additions are not evaluated in this analysis as they are already addressed in Section 150.2 of Title 24, Part 6. Table 1 describes the basic characteristics of the single family prototype.

¹ <u>https://www.census.gov/const/C25Ann/sftotalmedavgsqft.pdf</u>

² Residential ACM test U12 can be accessed at the following website: <u>http://www.bwilcox.com/BEES/cbecc2016.html</u>

	Single Family
Existing Conditioned Floor Area	1,665 ft ²
Num. of Stories	1
Num. of Bedrooms	3
Window-to-Floor Area Ratio	13%
Attached Garage	2-car garage

Table 1: Prototype Characteristics

Three building vintages were evaluated to determine sensitivity of existing building performance on cost effectiveness of upgrades. For example, it is widely recognized that adding attic insulation in an older home with no insulation is cost-effective, however, newer homes will likely have at least some existing insulation in the attic reducing the potential savings from the measure. The building characteristics for each vintage were determined based on either prescriptive requirements from Title 24 that were in effect or standard construction practice during that time period. Homes built under 2001 Title 24 are subject to prescriptive envelope code requirements very similar to homes built under the 2005 code cycle, which was in effect until January 1, 2010.

Table 2 summarizes the assumptions for each of the three vintages. Additionally, the analysis assumed the following features when modeling the prototype buildings:

- Individual space conditioning and water heating systems, one per single family building.
- Split-system air conditioner with natural gas furnace. Efficiency defined by year of the most recent equipment replacement (based on standard equipment lifetime).
- Small storage natural gas water heater. Efficiency defined by year of most recent equipment replacement (based on standard equipment lifetime).
- Gas cooktop, oven, and clothes dryer.

Building Component Efficiency	Vintage Case			
Feature	Pre-1978	<u>1978-1991</u>	<u>1992-2010</u>	
Envelope				
Exterior Walls	2x4, 16 inch on center wood frame, R-0 ^a	2x4 16inch on center wood frame, R-11	2x4 16inch on center wood frame, R-13	
Foundation Type & Insulation	Uninsulated slab (CZ 2-15) Raised floor, R-0 (CZ 1 & 16)	Uninsulated slab (CZ 2-15) Raised floor, R-0 (CZ 1 & 16)	Uninsulated slab (CZ 2-15) Raised floor, R-19 (CZ 1 & 16)	
Ceiling Insulation & Attic Type	Vented attic, R-11 @ ceiling level Vented attic, R-5 @ ceiling level (CZ 6 & 7)	Vented attic, R-19 @ ceiling level	Vented attic, R-30 @ ceiling level	
Roofing Material & Color	Asphalt shingles, dark (0.10 reflectance, 0.85 emittance)	Asphalt shingles, dark (0.10 reflectance, 0.85 emittance)	Asphalt shingles, dark (0.10 reflectance, 0.85 emittance)	
Radiant Barrier	No	No	No	
Window Type: U-factor/SHGC ^b	Metal, single pane: 1.16/0.76	Metal, dual pane: 0.79/0.70	Vinyl, dual pane Low-E: 0.55/0.40	
House Infiltration	15 ACH50	10 ACH50	7 ACH50	
HVAC Equipment				
Heating Efficiency	78 AFUE (assumes 2 replacements)	78 AFUE (assumes 1 replacement)	78 AFUE	
Cooling Efficiency	10 SEER (assumes 2 replacements)	10 SEER (assumes 1 replacement)	13 SEER, 11 EER	
Duct Location & Details	Attic, R-2.1, 30% leakage	Attic, R-2.1, 25% leakage	Attic, R-4.2, 15% leakage	
Whole Building Mechanical Ventilation	None	None	None	
Water Heating Equipment				
Water Heater Efficiency	0.575 Energy Factor (assumes 2 replacements)	0.575 Energy Factor (assumes 1 replacement)	0.575 Energy Factor	
Water Heater Tank	40-gallon uninsulated tank	40-gallon uninsulated tank	40-gallon uninsulated tank	
Pipe Insulation	None	None	None	
Hot Water Fixtures	Standard, non-low flow	Standard, non-low flow	Standard, non-low flow	

Table 2: Efficiency Characteristics for Three Vintage Cases

^a Pre-1978 wall modeled with R-5 cavity insulation to better simulate uninsulated wall performance with field data and not overestimate energy use.

^b Window type selections were made based on conversations with window industry expert, Ken Nittler. If a technology was entering the market during the time period (e.g., Low-E during 1992-2010 or dual pane during 1978-1991) that technology was included in the analysis. This provides a conservative assumption for overall building performance and additional measures may be cost-effective for buildings with lower performing windows, for example buildings with metal single pane windows in the 1978-1991 vintage.

3.2 Efficiency Measures

The methodology used in the analyses for each of the prototypical building types begins with a design that matches the specifications as described in Table 2 for each of the three vintages. Prospective energy efficiency measures were modeled in each of the prototypes to determine the projected electricity and natural gas energy savings relative to the baseline vintage. In some cases, where logical, measures were packaged together. Unless specified otherwise, all measures were evaluated using CBECC-Res.

All measures are evaluated assuming they are not otherwise required by Title 24. For example, duct sealing is required by code whenever HVAC equipment is altered. For this analysis duct sealing was evaluated for those projects where it is not already triggered by code (i.e., no changes to the heating or cooling equipment). Where appropriate, measure requirements align with those defined in Title 24. In some cases, cost-effective measures were identified that exceed Title 24 requirements, such as attic insulation, cool roofs, and duct sealing.

Following are descriptions of each of the efficiency upgrade measures applied in this analysis.

3.2.1 Building Envelope/Non-Preempted Measures

<u>Attic Insulation</u>: Add attic insulation in buildings with vented attic spaces to meet R-49. For pre-1992 vintage homes this measure was also evaluated to include retrofitting of existing recessed can luminaires that are not rated for insulation contact (IC) to be airtight and allow for insulation contact. This can be accomplished by installing a recessed light cover over existing non-compliant luminaires and sealing the covers to the ceiling plane with foam or replacing non-IC-rated luminaires with IC-rated luminaires. The energy analysis includes savings from adding insulation and upgrading compact fluorescent lamp (CFL) recessed cans to LED lighting but does not include any reduced infiltration benefits. Newer vintage homes are assumed to have IC-rated recessed light luminaires that can be covered in insulation.

<u>Air Sealing and Weather-stripping:</u> Apply air sealing practices throughout all accessible areas of the building. For this study, it was assumed that older vintage homes would be leakier than newer buildings and that approximately 30 percent improvement in air leakage was achievable through air sealing of all accessible areas. For modeling purposes, it was assumed that air sealing can reduce infiltration levels from 15 to ten air changes per hour at 50 Pascals pressure difference (ACH50) in the oldest vintages (pre-1978), from ten to seven ACH50 for the 1978 to 1991 vintage, and from seven to five ACH50 in the 1992 to 2010 vintage.

Cool Roof: For steep slope roofs, install a roofing product rated by the Cool Roof Rating Council (CRRC) with an aged solar reflectance of 0.25 or higher and thermal emittance of 0.75 or higher. This measure only applies to buildings that are installing a new roof as part of the scope of the remodel; the cost and energy savings associated with this upgrade reflects the incremental step between a standard roofing product with one that is CRRC rated with an aged solar reflectance of 0.25. This is similar to cool roof requirements in 2019 Title 24 Section 150.2(b)1li but assumes a higher solar reflectance.

Raised Floor Insulation: In existing homes with raised floors and no insulation, add R-19 insulation.

<u>Wall Insulation</u>: Blow-in R-13 wall insulation in existing homes that currently have no insulation in the walls (pre-1978 vintages).

Window Replacement: Replace existing metal-frame windows with a non-metal dual-pane product, which has a U-factor equal to 0.30 Btu/hour-ft²-°F or lower and a Solar Heat Gain Coefficient (SHGC) equal to 0.23 or lower, except in heating dominated climates (Climate Zones 1, 3, 5, and 16) where an SHGC of 0.35 was evaluated. This measure was only evaluated for the two older vintages, pre-1992, which are assumed to have either single-or dual-pane, metal-frame windows. This aligns with new window requirements in 2019 Title 24.

Duct Sealing, New Ducts, and Duct Insulation: Air seal all ductwork to meet the requirements of the 2019 Title 24, Part 6 Section 150.2(b)1E. For this analysis, final duct leakage values of both 15 percent (which corresponds to Option i in the Title 24 section referenced), and ten percent (proposed revised leakage rate for 2022 Title 24) were evaluated. Replacing existing ductwork with entirely new ductwork to meet Sections 150.2(b)1Di and 150.2(b)1Diia of the 2019 Title 24 was also evaluated. This assumed new ducts meet five percent duct leakage and R-8 duct insulation in all climates.

Water Heater Blanket: Add R-6 insulation to the exterior of existing residential tank storage water heaters. For the analysis, the water heater was modeled within conditioned space, which is a typical configuration for older homes. This assumption is conservative since a water heater located in unconditioned space will tend to have higher tank losses and installing a water heater blanket in those situations will result in additional savings. The energy savings for this measure reflect water heating energy savings only, and do not include any impacts to the space conditioning load, which reduces space cooling loads and increases space heating loads. The impact on space conditioning energy used is minimal and in most climate zones, except for heating dominated ones, the combination of these two impacts results in net energy savings. This measure was evaluated using EnergyPlus for individual water heaters only and does not apply to central water heating systems.

Hot Water Pipe Insulation: Insulate all accessible hot water pipes with R-3 pipe insulation. In certain buildings such as those with slab on grade construction where the majority of pipes are located either underground or within the walls, most of the pipes are inaccessible. For the purposes of this analysis a conservative assumption that only ten percent of the pipes could be insulated was applied. In buildings where pipes are located in the attic, crawlspace, or are otherwise more accessible, energy savings will be higher than those presented in this analysis. This measure was evaluated using BEopt and EnergyPlus.

Low-Flow Fixtures: Upgrade sink and shower fittings to meet current Title 24, Part 11 (CALGreen) requirements, which require maximum flow rates of 1.8 gallons per minute (gpm) for showerheads and kitchen faucets, and 1.2 gpm for bathroom faucets. Baseline whole house hot water use was based on BEopt assumptions and this measure assumed the upgraded fixtures reduce flow rates by ten percent for showerheads and 20 percent for all faucets based on a 2010 water use study (ConSol, 2010). This measure was evaluated using BEopt and EnergyPlus.

LED Lighting: Replace screw-in (A-based for lamps) incandescent lamps and CFLs with light-emitting diode (LED) A-lamps. This analysis was conducted external to the energy model and evaluated replacement of a 13 W CFL lamp with an 11 W LED lamp operating 620 hours annually. Annual hour estimates were based on whole building average hours of operation from a 2010 lighting study by KEMA (KEMA, 2010). Lifetime assumptions were 10,000 hours for CFLs and 25,000 hours for LED lamps. For incremental cost calculations it was assumed CFLs have a lifetime of 15 years, are installed five years prior to the retrofit, and would need to be replaced at year ten and 25.

Exterior Lighting Controls: Evaluation of exterior lighting controls was completed on a per-luminaire basis external to the energy model and assumes a screw-in photosensor control is installed in outdoor lighting luminaires. Energy savings of 12.1 kWh per year was applied based on analysis done by the Consortium for Energy Efficiency, assuming LED lamps, 2.6 hours per day of operation, and that photosensor controls reduce operating hours on average 20 percent each day (CEE, 2014). Energy savings will be higher for incandescent or CFL luminaires.

3.2.2 Photovoltaics (PV) and Battery Measures

PV: Installation of on-site PV is required in the 2019 residential code for new construction but not for additions or alterations to existing buildings. This report does not focus on optimizing PV system sizing for each prototype and climate zone. For this study, the PV system was sized to the 2019 new construction standards for a 1,665 ft² home or sized to offset 100 percent of annual building electricity use, whichever was smaller. Based on prior studies, PV system cost effectiveness was not sensitive to system sizing up to 90 percent of annual electricity use (Statewide Reach Codes Team, 2019). The system is sized to offset a portion of annual building electricity use for a new construction home and avoid oversizing which would violate net energy metering (NEM) rules. In only one case was the PV system downsized to ensure that over-generation did not occur. In all cases, PV is evaluated in CBECC-Res according to the California Flexible Installation (CFI) assumptions. Table 3 summarizes the PV sizing used in the analysis.

CA Climate Zone	PV Capacity (kW _{DC})ª	CA Climate Zone	PV Capacity (kW _{DC})ª
1	2.59	9	2.38
2	2.25	10	2.45
3	2.17	11	2.83
4	2.19	12	2.42
5	2.03	13	3.00
6	2.22 (2.19 1992-2010 vintage) ^b	14	2.49
7	2.10	15	4.07
8	2.35	16	2.20

Table 3: Single Family PV Sizing for 1,665 ft² home by Climate Zone (kWDc)

^a PV system sized using residential new construction sizing methodology based on climate zone and house size.

^b PV system was downsized for this vintage to prevent overgeneration of PV.

Energy Storage (Batteries): This measure includes installation of batteries to allow energy generated through PV to be stored and used later, providing energy cost and resiliency benefits. This report does not focus on optimizing battery sizes or controls for each prototype and climate zone. A ten kWh battery system was evaluated in CBECC-Res in conjunction with a PV system sized to the 2019 new construction standards, with control type set to "Time of Use" (TOU) and with default efficiencies of 95 percent for both charging and discharging (round trip efficiency of 90 percent). The TOU option assumes batteries are charged anytime PV generation is greater than the house load but controls when the battery storage system discharges. During the summer months (July – September) the battery begins to discharge at the beginning of the peak period at a maximum rate until fully discharged. During discharge the battery first serves the house load but will discharge to the electric grid if there is excess energy available. During other months, the battery discharges whenever the PV system does not cover the entire house load and does not discharge to the electric grid. This control option is considered to be most reflective of the current products on the market. This control option requires an input for the "First Hour of the Summer Peak" and the Statewide Reach Codes Team applied the default hour in CBECC-Res which differs by climate zone (either a 6pm or 7pm start).

3.2.3 Equipment Fuel Substitution Measures – Heat Pump Replacements

The baseline for the retrofit analysis assumed a mixed-fuel baseline for all cases, with natural gas-fired furnaces for space heating and natural gas storage tank water heaters for domestic hot water (DHW). For fuel substitution cases, the natural gas appliances were assumed to be replaced with heat pump technology at the end of equipment life, when the equipment is being replaced.

Ducted Heat Pump: Replace existing ducted natural gas furnace and air conditioner (AC) with an electric heat pump. Minimum federal efficiency (14 SEER, 11.7 EER, 8.2 HSPF) and higher efficiency (21 SEER, 13.5 EER, 11 HSPF) heat pumps were evaluated as replacements to existing equipment. Savings are relative to a new ducted natural gas furnace/AC (14 SEER, 11.7 EER, 80 AFUE).

<u>Heat Pump Water Heater (HPWH)</u>: Replace existing natural gas storage tank water heater with either a minimum efficiency (UEF 2.0) 50-gallon HPWH, or a HPWH that meets the Northwest Energy Efficiency Alliance

(NEEA)³ Tier 3 rating. The evaluated NEEA HPWH is an 80-gallon unit with a UEF of 3.45. Savings are relative to a new 50-gallon natural gas storage water heater (UEF 0.63).

3.3 Efficiency Packages

Some of the measures described above were also evaluated as packages.

3.3.1 Envelope and Duct Packages

Five envelope and duct packages were developed as described below. Air sealing and attic insulation are very often applied as a package in building retrofits. From a performance perspective, air sealing of the boundary between the attic and living space should be addressed any time there is significant work in the attic, such as adding attic insulation and sealing or replacing ductwork. When the building shell is being improved, air sealing is an important component to be addressed. The boundary between the living space and vented attics is where a significant amount of building air leakage can occur and sealing these areas prior to covering the attic floor with insulation is both practical and effective. These measures also directly address occupant comfort, as they reduce heat transfer, and result in more even temperatures within the building. When ductwork is located in the attic there are synergies with addressing all three of these building aspects at the same time.

- 1. <u>R-49 Attic Insulation and Air Sealing:</u> This package includes attic insulation and air sealing measures, as described below:
 - R-49 attic insulation installed in attic.
 - Air sealing and weatherstripping to reduce total building air leakage by 30 percent. Target air leakage assumptions are ten ACH50 for pre-1978 vintage, seven ACH50 for 1978 to 1991 vintage, and five ACH50 for the 1992 to 2010 vintage.
 - Retrofitting all non-IC-rated recessed light luminaires to be airtight and allow for coverage by insulation. This submeasure only applies to homes without IC-rated recessed can luminaires.
- 2. <u>R-49 Attic Insulation and Duct Sealing:</u> This package includes attic insulation and duct sealing measures, as described below:
 - R-49 attic insulation installed in attic.
 - Ductwork sealed to ten percent of nominal airflow.
 - Retrofitting all non-IC-rated recessed light luminaires to be airtight and allow for coverage by insulation. This submeasure only applies to homes without IC-rated recessed can luminaires.
- 3. <u>R-49 Attic Insulation, Air Sealing, and Duct Sealing:</u> This package includes attic insulation, air sealing, and duct sealing measures, as described below:
 - R-49 attic insulation installed in attic.
 - Ductwork sealed to ten percent of nominal airflow.
 - Air sealing and weatherstripping to reduce total building air leakage by 30 percent. Target air leakage assumptions are ten ACH50 for pre-1978 vintage, seven ACH50 for 1978 to 1991 vintage, and five ACH50 for the 1992 to 2010 vintage.
 - Retrofitting all non-IC-rated recessed light luminaires to be airtight and allow for coverage by insulation. This submeasure only applies to homes without IC-rated recessed can luminaires.

³ Based on operational challenges experienced in the past, NEEA established rating test criteria to ensure newly installed HPWHs perform adequately, especially in colder climates. The NEEA rating requires an Energy Factor equal to the ENERGY STAR[®] performance level and includes requirements regarding noise and prioritizing heat pump use over supplemental electric resistance heating.

- This combination of measures is common when a whole building performance upgrade is done in combination with HVAC equipment replacement. Incorporating these measures can allow for contractor to downsize HVAC equipment by lowering heating and cooling loads in the house.
- 4. <u>R-49 Attic Insulation, Air Sealing, and Entirely New Ducts:</u> This package is similar to Package 3 above but assumes that all existing ductwork is replaced with new R-8 ducts and sealed to new construction standards (five percent total leakage). This package assumes that if an existing HVAC system is being replaced with new ductwork, the area between the vented attic and conditioned space be air sealed and insulation added to the attic.
 - R-49 attic insulation installed in attic.
 - New R-8 ductwork sealed to five percent of nominal airflow.
 - Air sealing and weatherstripping to reduce total building air leakage by 30 percent. Target air leakage assumptions are ten ACH50 for pre-1978 vintage, seven ACH50 for 1978 to 1991 vintage, and five ACH50 for the 1992 to 2010 vintage.
 - Retrofitting all non-IC-rated recessed light luminaires to be airtight and allow for coverage by insulation. This submeasure only applies to homes without IC-rated recessed can luminaires.
 - This combination of measures is common when a whole building performance upgrade is done in combination with HVAC equipment replacement. Incorporating these measures can allow for contractor to downsize HVAC equipment by lowering heating and cooling loads in the house.
- 5. Advanced Envelope Package: Attic Insulation, Recessed Cans, Air and Duct Sealing, plus Wall Insulation and New Windows: This package includes all the measures in Package 3, in addition to insulating exterior walls, and replacing existing single-pane windows with improved high-performance windows. This package only applies to older vintage homes with no wall cavity insulation and single-pane windows.
 - R-49 attic insulation installed in attic.
 - Ductwork sealed to ten percent of nominal airflow.
 - Air sealing and weatherstripping to reduce total building air leakage by 30 percent. Target air leakage assumptions are ten ACH50 for pre-1978 vintage, seven ACH50 for 1978 to 1991 vintage, and five ACH50 for the 1992 to 2010 vintage.
 - Retrofitting all non-IC-rated recessed light luminaires to be airtight and allow for coverage by insulation. This submeasure only applies to homes without IC-rated recessed can luminaires.
 - Insulate exterior walls to R-13.
 - New windows with 0.30 U-factor and 0.23 SHGC (0.35 SHGC in Climate Zones 1, 3, 5, and 16).
 - This combination of measures is common when a whole building performance upgrade is done in combination with HVAC equipment replacement. Incorporating these measures can allow for contractor to downsize HVAC equipment by lowering heating and cooling loads in the house.

3.3.2 Additional Packages

<u>Water Heating Package:</u> Includes water heater blanket, hot water pipe insulation, and low-flow fixtures: These three water heating measures are all relatively low cost and work together to reduce building hot water energy use. Additional water savings measures and model language are documented on the LocalEnergyCodes.com website.⁴

PV plus Batteries: PV sized to Residential New Construction Standards and a ten kWh battery system with TOU control.

⁴ <u>https://localenergycodes.com/</u>

<u>PV plus Heat Pump</u>: PV sized to Residential New Construction Standards and one fuel substitution measure, either a ducted heat pump for space heating or heat pump water heater.

<u>PV plus Heat Pump plus Panel Upgrade</u>: The PV plus Heat Pump package with the additional cost included for upgrading the electric panel.

PV plus Electric Ready Measures: Includes adding electric ready measures for future replacement of natural gas furnace and water heater with heat pumps, along with installation of an on-site PV system. The electric ready measures include prewiring 240 V power to the furnace location in the attic and the water heater location in the garage, and panel upgrade to allow for installation of future electric appliances at a future date.

3.4 Measure Cost

Measure costs were obtained from various sources, including prior reach code studies, past Title 24 Codes and Standards Enhancement (CASE) work, local contractors, internet searches, past projects, and technical reports.

3.4.1 Building Envelope/Non-Preempted Measures

Table 4 summarizes the cost assumptions for the building envelope and non-preempted HVAC measures evaluated.

3.4.2 PV and Battery Measures

The costs for installing PV and batteries are summarized in Table 5. For PV, they include first cost to purchase and install the system, inverter replacement costs, and annual maintenance costs. Upfront solar PV system costs are reduced by the federal income tax credit (ITC) by 26 percent based on renewal of the credit through the year 2023.

Costs for batteries include first cost and replacement at year 10 and 20, assuming a 10 year battery life. Batteries are also eligible for the ITC if they are installed at the same time as the renewable generation source and at least 75 percent of the energy used to charge the battery comes from a renewable source.

Measure	Performance		emental C Family B		Source	Notes						
	Level	Pre 1978	1978 – 1991	1992 - 2010								
Building Enve	lope				•							
Wall Insulation	R-13	\$3,360	N/A	N/A	Retrofit contractor ^b	\$2.14/ ft ² exterior wall area. Drill 2-inch holes from outside.						
Raised Floor Insulation	R-19	\$3,147	N/A	N/A	Retrofit contractor ^b	1.89/ ft ² of raised floor area. Assumes installation of R-19 batt insulation when existing condition is no insulation.						
Attic Insulation	R-49	\$2,851	\$2,393	\$1,852	2022 Alterations CASE Report	 \$1.71/ ft² ceiling area to add insulation to existing R-11 insulation. \$1.44/ ft² to add insulation to existing R-19 insulation. 						
	R-49 + Recessed Can Retrofit	\$3,332	\$2,874	\$2,333	(Statewide CASE Team, 2020)	Added cost of 0.29 / ft^2 ceiling area to retrofit non-IC-rated to be airtight and allow coverage with insulation and seal the covers to the ceiling plane with foam. Added cost used for pre-1992 homes.						
10 ACH50		\$1,474	N/A	N/A		Based on contractor quote to seal building shell and reduce building air						
Air Sealing	7 ACH50	N/A	\$1,474	N/A	Retrofit contractor ^b	leakage by 30%. Assumes all accessible leaks are sealed and assumes						
	5 ACH50	N/A	N/A	\$1,474		existing attic insulation is not removed.						
Cool Roof	Aged Solar Reflectance <u>></u> 0.25	\$778	\$778	\$778	2022 Alterations CASE Report (Statewide CASE Team, 2020)	Based on \$0.32/ ft ² roof area first incremental cost for cool asphalt shingle product. Total costs assume present value of replacement at year 20 and residual cost for remaining product life at end of 30-year analysis period. Higher reflectance values for lower cost are achievable for tile roof products						
Window U-factor/SHGC	0.30 U-factor. 0.23 SHGC in CZs 2,4,6-15. 0.35 SHGC in CZs 1,3,5,16	\$9,810	N/A	N/A	Retrofit contractor ^c	Based on \$45/ ft ² window area installed cost.						
HVAC/DHW	•											
Duct Sealing	15% nominal airflow	\$423	\$423	N/A	HVAC	Assume ducts in attic with 5 wye branches, 8 supplies & 1 return. \$223 in labor (~2 hours at \$120/hour) and \$20 material for 15% leakage from a starting point of 25-30% and for 10% from a starting point of 15%. \$463 in						
Duct Sealing -	10% nominal airflow	\$683	\$683	\$423	contractor	labor (~4 hours at \$120/hour) and \$40 material for 10% leakage from a starting point of 25-30%. \$180 for HERS Rater.						

Table 4: Measure Descriptions & Cost Assumptions - Non-Preempted Measures^a

Measure	Performance		emental C Family B		Source	Notes		
	Level	Pre 1978	1978 – 1991	1992 - 2010				
Entirely New Ducts	R-8 ducts; 5% duct leakage	\$3,986	\$3,986	\$3,986	Retrofit contractor ^b	Based on duct layout provided for prototype single story model, and all ducts located in attic.		
Water Heater Blanket	R-6		\$40		Internet search	\$20 blanket + $\frac{1}{2}$ -hour labor (\$40.30/hour laborer rate). ^d Six-year life assuming that the water heater will need to be replaced after 6 years on average.		
Hot Water Pipe Insulation	3/4 inch (R-3)		\$42		Internet search	\$0.20/ft of ¾ inch pipe insulation. 10ft total + 1-hour labor (\$40.30/hour common labor rate). ^d 15-year life assumed.		
Low-flow Fixtures	CALGreen		\$126		Retrofit contractor ^c	Showerheads at \$34.74 each + sink aerators at \$5.37 each + 1-hour labor (\$40.30/hour common labor rate). ^d 2 showerheads & 3 aerators assumed for single family. 15-year life assumed.		
Lighting								
LED Lamp	11 W screw-in lamp	\$3	\$3.99/luminaire		\$3.99/luminaire		Internet search	\$3.99 for LED dimmable A19 lamp 60 W equivalent. \$1.83 for an equivalent CFL product which was used to estimate total replacement costs at years 10 and 25. Cost based on a single LED lamp replacement.
Exterior Lighting Controls	Photocell control with motion sensor	\$	10.50/devic	ce .	Internet search	Incremental cost of \$10.50, based on a screw-in photosensor control, was obtained from an on-line product search of available products. A five-year lifetime for this type of control was assumed.		

^a Costs include contractor overhead and profit.

^b Source: Retrofit contractor pricing. 2020. Phone outreach.

^c Source: Retrofit contractor pricing obtained by Davis Energy Group through the Stockton Energy Challenge neighborhood retrofit program (DEG, 2017).

Measure	Performance		emental C Family B		Source	Notes					
	Level	Pre 1978	1978 – 1991	1992 - 2010							
PV/Batteries											
PV	Sized to 2019 New Construction Standards: System size varies by climate (2.03- 4.07 kW)	\$6	\$3.18/W _{DC} 5,467 - \$12,9		(LBNL, 2019)	First costs are from LBNL's Tracking the Sun 2019 costs (Barbose et al., 2019) and represent costs for the first half of 2019 of \$3.70/W _{DC} for residential systems. These costs were reduced by 26% for the solar ITC, which is the average credit over years 2021-2022. Inverter replacement cost of \$0.14/W _{DC} present value includes replacements at year 11 at \$0.15/W _{DC} (nominal) and at year 21 at \$0.12/W _{DC} (nominal) per the 2019 PV CASE Report (California Energy Commission, 2017). System maintenance costs of \$0.31/W _{DC} present value assume \$0.02/W _{DC} (nominal) annually per the 2019 PV CASE Report (California Energy Commission, 2017).					
Batteries	10 kWh, TOU controls		\$11,372 \$1,137/kWh	1	(SGIP, 2020), (E Source Companies, 2020).	 \$1,000/kWh first cost in 2020 based on Self-Generation Incentive Program residential participant cost data. To estimate the first cost in future years this was reduced by 7% annually based on SDG&E's Behind- the-Meter Battery Market Study (E Source Companies, 2020). The first cost is reduced by the Residential Storage Step 7 SGIP incentive of \$0.15/Wh and the solar ITC of 26%. Costs are presented as the average of 2021 and 2022. Replacement cost at year 10 and 20 calculated based on the 2020 cost of \$1,000/kWh reduced by 7% annually over the next 11 years for a future value cost of \$450 (present value of \$335 in year 10 and \$249 in year 20). 					

Table 5: Measure Descriptions & Cost Assumptions – PV and Batteries^a

^a Costs include contractor overhead and profit.

3.4.3 Equipment Fuel Substitution Measures – Heat Pump Equipment

The cost assumptions used for fuel substitution measures are summarized in Table 6 and Table 7. Incremental costs for the heat pump replacement measures were obtained from several sources, including a 2019 report on residential building electrification in California (Energy & Environmental Economics, 2019), pricing information provided from Sacramento Municipal Utility District's (SMUD's) electric appliance incentive program (SMUD, 2020), online equipment pricing, and contractor outreach. Both material and labor costs are included, assuming that existing natural gas equipment is being replaced with heat pumps at the end of equipment life, at time of equipment replacement.

For both the space heating and water heating cases, costs for service panel upgrades are not included as it is assumed many existing homes have the service capacity to support converting one appliance from gas to electric. In some homes and in cases where multiple end uses are electrified, a larger electrical panel may be necessary. Cost assumptions for electric ready measures including panel upgrade for future equipment fuel substitution measures are included in Table 8.

Ducted Heat Pump: The base case assumes that an existing AC is replaced. In mild climates, where AC may not be installed, there will be additional costs for installing an outdoor unit, refrigerant lines, and condensate drain pan.

Table 6 presents estimated costs to replace existing equipment with a heat pump instead of a minimum efficiency natural gas furnace and AC. It is assumed there is no incremental labor except in providing new 240 V electrical service to the air handler location.

The lifetime for the heat pump, furnace, and air conditioner are based on the Database for Energy Efficient Resources (DEER) (California Public Utilities Commission, 2021). In DEER, heat pump and air conditioner measures are assigned an effective useful lifetime (EUL) of 15 years and a furnace an EUL of 20 years. The heating and cooling system components are typically replaced at the same time when one reaches the end of its life and the other is near it. Therefore, it is assumed that both the furnace and air conditioner are replaced at the same time at year 17.5, halfway between 15 and 20 years. Present value replacement costs are included in the LCC.

The base case assumes that an existing AC is replaced. In mild climates, where AC may not be installed, there will be additional costs for installing an outdoor unit, refrigerant lines, and condensate drain pan.

	Gas Furnace/ AC	14 SEER Heat Pump	21 SEER Heat Pump	Notes
First Cost	\$8,738	\$9,101	\$11,247	Equipment costs from on-line sources and HVAC contractors. Other supply and labor costs from 2019 report on residential building electrification in California (Energy & Environmental Economics, 2019). First cost includes disposal, electrical upgrade, and labor costs.
Replacement Cost (Future Value)	\$8,738	\$6,729	\$8,445	Future total replacement costs for the heat pumps are reduced by 20% to account for cost reductions because of a maturing market and electrical upgrade costs are removed.
Replacement Cost (Present Value)	\$5,209	\$4,319	\$5,421	Based on 17.5-year lifetime for gas furnace/AC, 15-year lifetime for heat pumps, and 3% discount rate.
Remaining Value at Year 30	(\$1,029)	\$0	\$0	Residual value of the gas furnace/AC to account for the remaining life at end of 30-year analysis period.
Total Lifecycle Cost	\$12,918	\$13,419	\$16,667	
Incremental Cost	-	\$501	\$3,749	

Table 6: HVAC Measure Cost Assumptions – Electric Replacements

<u>Heat Pump Water Heater (HPWH):</u> Table 7 presents estimated costs for the replacement of a natural gas storage water heater located in a garage with a HPWH. Costs include all material and installation labor

including providing new 240 V electrical service to the water heater location. Total installed costs are based on data from SMUD's HPWH incentive program between 2018 and 2020 (SMUD, 2020). Equipment replacement costs are included based on an equipment life of 15 years for both the base case gas water heater and the HPWH. Present value replacement costs are included in the LCC.

ltem	Gas Storage Water Heater	2.0 UEF HPWH	NEEA Tier 3 HPWH	Notes
First Cost	\$1,600	\$4,018	\$4,155	First cost based on 2018-2020 costs from SMUD incentive program for NEEA Tier 3 HPWH (SMUD, 2020). 2.0 UEF first cost assumes 90% of equipment cost compared to NEEA Tier 3 unit based on on-line product research. Includes equipment cost, electrical upgrade, permitting, and labor.
Replacement Cost (Future Value)	\$1,600	\$1,874	\$1,943	Future replacement cost assumes the same labor for the gas and HPWH case. HPWH replacement equipment costs are reduced by 50% to account for cost reductions because of a maturing market.
Replacement Cost (Present Value)	\$1,027	\$1,203	\$1,247	Based on 15-year lifetime and 3% discount rate.
Total Lifecycle Cost	\$2,627	\$5,221	\$5,402	
Incremental Cost	-	\$2,594	\$2,775	

Table 7: Water Heating Measure Cost Assumptions – Electric Replacements

Electric Ready: Table 8 presents electric ready measure costs. Appliance pre-wiring costs assume materials and labor for prewiring 240 V, 30 A dedicated circuits to the existing furnace location in the attic and the water heater location in the garage. Panel upgrade costs are based on upgrading from 100 A to 200 A service to allow for electric appliance installation at a future date.

Table 8: Electric Ready Measure Cost Assumptions

Measure	Incremental Cost	Notes
Appliance pre-wire	\$455 per appliance. \$910 total for space and water heating	\$125 parts, \$330 labor. (E3, 2019)
Panel upgrade	\$3,181	(TRC, 2016)

3.5 Cost Effectiveness

Cost effectiveness was evaluated for all climate zones and is presented based on both TDV energy, using the Energy Commission's LCC methodology, and an On-Bill, customer-based approach using residential customer utility rates. Both methodologies require estimating and quantifying the value of the energy impact associated with energy efficiency measures over the life of the measures (30 years) as compared to the prescriptive Title 24 requirements.

Additional analysis included evaluating the measures using both the 2019 and proposed 2022 TDV multipliers. The proposed 2022 weather files were also used to evaluate On-Bill energy performance. The 2022 weather files were updated in 2019 and are considered to better represent conditions now and in the future. They tend to increase cooling and reduce space heating energy use, based on recent warming trends throughout the state.

Cost effectiveness is presented using both lifecycle NPV savings and benefit-to-cost (B/C) ratio metrics, which represent the cost effectiveness of a measure over a 30-year lifetime taking into account discounting of future savings and costs and financing of incremental first costs.

- **NPV Savings:** NPV benefits minus NPV costs is reported as a cost-effectiveness metric. If the net savings of a measure or package is positive, it is considered cost-effective. Negative savings represent net costs. A measure that has negative energy cost benefits (energy cost increase) can still be cost-effective if the costs to implement the measure are more negative (i.e., material and maintenance cost savings).
- **B/C Ratio:** Ratio of the present value of all benefits to the present value of all costs over 30 years (NPV benefits divided by NPV costs). The criteria for cost effectiveness is a B/C ratio greater than one. A value of one indicates the NPV of the savings over the life of the measure is equivalent to the NPV of the lifetime incremental cost of that measure. A value greater than one represents a positive return on investment. The B/C ratio is calculated according to Equation 1.

Equation 1 Benefit - to - Cost Ratio = $\frac{NPV \text{ of lifetime benefit}}{NPV \text{ of lifetime cost}}$

Improving the efficiency of a project often requires an initial incremental investment. In most cases the benefit is represented by annual On-Bill utility or TDV savings, and the cost by incremental first cost and replacement costs. However, some packages result in initial construction cost savings (negative incremental cost), and either energy cost savings (positive benefits), or increased energy costs (negative benefits). In cases where both construction costs and energy-related savings are negative, the construction cost savings are treated as the 'benefit' while the increased energy costs are the 'cost.' In cases where a measure or package is cost-effective immediately (i.e., upfront construction cost savings and lifetime energy cost savings), B/C ratio cost effectiveness is represented by ">1". Because of these situations, NPV savings are also reported, which, in these cases, are positive values.

The lifetime costs or benefits are calculated according to Equation 2.

Equation 2
NPV of lifetime cost or benefit =
$$\sum_{t=0}^{n} \frac{(Annual \ cost \ or \ benefit)_{t}}{(1+r)^{t}}$$

Where:

- *n* = analysis term
- r = discount rate

The following summarizes the assumptions applied in this analysis to both methodologies.

- Analysis term of 30 years
 - o 15-year analysis term for the water heating package
 - Five-year analysis term for the exterior light controls
- Real discount rate of three percent

3.5.1 On-Bill LCC

Residential utility rates at the time of the analysis were applied to calculate utility costs for all cases and determine On-Bill cost effectiveness for the proposed measures and packages. The Statewide Reach Code Team obtained the recommended utility rates from each IOU based on the assumption that the reach codes go into effect in 2020. First-year utility costs were calculated using hourly electricity and natural gas output from CBECC-Res and applying the utility tariffs summarized in Table 9. Appendix B: Utility Rate Schedules includes details on the utility rate schedules used for this study. The applicable residential TOU

rate was applied to all cases. For cases with PV generation, the approved NEM2 tariffs were applied along with minimum daily use billing and mandatory non-bypassable charges. For the PV cases annual electric production was always less than annual electricity consumption; and therefore, no credits for surplus generation were necessary. Future changes to the NEM tariffs are likely; however, there is uncertainty about what those changes will be and if they will become effective during the 2019 Title 24 code cycle (2020-2022).

Utility rates were applied to each climate zone based on the predominant IOU serving the population of each zone according to Table 9. Climate Zones 10 and 14 are evaluated with both SCE/SoCalGas and SDG&E tariffs since each utility has customers within these climate zones. Climate Zone 5 is evaluated under both PG&E and SoCalGas natural gas rates. Two municipal utility rates were also evaluated: SMUD in Climate Zone 12 and City of Palo Alto Utilities (CPAU) in Climate Zone 4.

Climate Zones	Electric/Gas Utility	Electricity	Natural Gas
1-5, 11-13, 16	PG&E	E-TOU-C	G1
5	PG&E/SoCalGas	E-TOU-C	GR
6, 8-10, 14, 15	SCE/SoCalGas	TOU-D-4-9	GR
7, 10, 14	SDG&E	D TOU-DR1	GR
12	SMUD/PG&E	R-TOD (RT02)	G1
4	CPAU	E-1	G-2

Table 9: IOU Utility Tariffs Applied Based on Climate Zone

Source: Utility websites, see Appendix B: Utility Rate Schedules for details on the tariffs applied.

Utility rates are assumed to escalate over time, using assumptions from research conducted by Energy and Environmental Economics (E3) in the 2019 study Residential Building Electrification in California study (Energy & Environmental Economics, 2019). Escalation of natural gas rates between 2019 and 2022 is based on the currently filed General Rate Cases (GRCs) for PG&E, SoCalGas, and SDG&E. From 2023 through 2025, natural gas rates are assumed to escalate at four percent per year above inflation, which reflects historical rate increases between 2013 and 2018. Escalation of electricity rates from 2019 through 2025 is assumed to be two percent per year above inflation, based on electric utility estimates. After 2025, escalation rates for both natural gas and electric rates are assumed to drop to a more conservative one percent escalation per year above inflation for long-term rate trajectories beginning in 2026 through 2050. See Appendix B: Utility Rate Schedules – Escalation Assumptions for additional details.

In calculating On-Bill cost effectiveness, incremental first costs are assumed to be financed into a mortgage or loan with a 30-year loan term and four percent interest rate. The only exceptions are the lighting measures. These are low-cost measures that are more likely than the other measures evaluated to be installed by the homeowner and are not assumed to be financed. Present value of replacement cost is included for measures with equipment lifetimes less than the evaluation period.

3.5.2 TDV LCC

Cost effectiveness was also assessed using the Energy Commission's TDV LCC methodology. TDV is a normalized monetary format developed and used by the Energy Commission for comparing electricity and natural gas savings, and it considers the cost of electricity and natural gas consumed during different times of the day and year. Both 2019 and proposed 2022 TDV values were used and are based on long term discounted costs of 30 years for all residential measures. The CBECC-Res simulation software results are expressed in terms of TDV kBtu. The present value of the energy cost savings in dollars is calculated by multiplying the TDV kBtu savings by a NPV factor, also developed by the Energy Commission. The 30-year

NPV factor \$0.173/TDV kBtu, used for both 2019 and 2022 Title 24 code cycles for residential buildings, was used.

Like the customer B/C ratio, a TDV B/C ratio value of one indicates the savings over the life of the measure are equivalent to the incremental cost of that measure. A value greater than one represents a positive return on investment. The ratio is calculated according to Equation 3. In calculating TDV cost effectiveness, incremental first costs were not assumed to be financed into a mortgage or loan.

Equation 3 $TDV Benefit - to - Cost Ratio = \frac{TDV \ energy \ savings \ * \ NPV \ factor}{NPV \ of \ lifetime \ incremental \ cost}$

3.5.2.1 2019 and 2022 TDV Differences

There were key changes to the 2022 TDV methodology as compared to the 2019 TDV, including the major updates below:

- Updated weather files to reflect historical data from recent years.
- New load profiles representing building and transportation electrification and renewable generation.
- Addition of internalized cost streams to account for carbon emissions.
- Shaped retail rate adjustment partially scaled to hourly marginal cost of service.
- Addition of non-combustion emissions from methane and refrigerant leakage.

The impact of these key changes for electricity TDV are lower values during the mid-day that correspond with an abundance of solar production and a shift of the peak TDV to later in the day as a result of increasing levels of rooftop PV systems. However, the overall magnitude of the 2022 TDV does not increase significantly relative to 2019 TDV. For natural gas TDV there is a large increase in magnitude with the 2022 TDV being roughly 70 percent higher than in 2019. This is driven by the new retail rate forecast, increased fixed costs for maintaining the distribution system, and the new carbon cost component. Additional details about 2022 TDV are described in the final 2022 TDV methodology report (Energy & Environmental Economics, 2020).

The updated weather files represent an updated dataset based on historical weather sampled from recent years (1998-2017) to reflect the impacts of climate change. Cooling loads increase significantly, particularly for the mild climates zones where cooling energy use was previously low. Heating loads decrease on average 30 percent across all climate zones. The weather files used for the 2019 code cycle had not been updated since the 2013 code cycle and represented data only up until 2009. The Energy Commission and the Statewide Reach Codes Team contend that the updated 2022 weather files better reflect changing climate conditions in California. Therefore, the 2022 files are used for all the analysis reported in this study.

3.6 Greenhouse Gas (GHG) Emissions Reductions

Equivalent CO_2 emission reductions were calculated based on outputs from the CBECC-Res 2022.0.1 simulation software. Electricity emissions vary by region and by hour of the year. CBECC-Res applies two distinct hourly profiles, one for Climate Zones 1 through 5 and 11 through 13 and another for Climate Zones 6 through 10 and 14 through 16. For natural gas, a fixed factor of 9.9 pounds (lbs) per therm is used. To compare the mixed-fuel and all-electric cases side-by-side, GHG emissions are presented as lbs CO_2 -equivalent (CO_2e) emissions for the 1,665 ft² prototype.

3.7 Energy Performance Equivalency of Retrofit Measures and Packages

Efficiency measures were evaluated based on three distinct vintage homes with typical characteristics applied to each. However, the existing building stock is quite varied, and year of construction is not always

an accurate indicator of efficiency and performance as homes may have been upgraded over time. To provide flexibility in the ordinance structure, the Statewide Reach Codes Team developed an energy performance equivalency methodology where the efficiency characteristics of a home and upgrades are valued relative to one another. This provides a flexible approach in two forms:

- 1) Where retrofit requirements are based on home vintage, applicants can value upgrades that may have been completed on their home (HERS Rater verified) to determine the closest vintage bin their house falls into, providing credit for improvements made to the house after it was constructed.
- 2) Applicants can pick from a menu of efficiency upgrades that in combination result in equivalent performance as a prescriptive package of measures or single measure that may be required as part of a retrofit reach code.

Energy performance equivalency is based on the source energy use metric (Energy Design Rating (EDR) 1) developed for the 2022 code cycle and is calculated by climate zone relative to the pre-1978 prototype home used in this analysis. The scoring is unique to each climate zone where different heating and cooling loads contribute to distinct values for various upgrades. For example, high efficiency heating equipment has a greater impact on score in heating dominated climates such as Climate Zone 1 and 16 as compared to Climate Zone 15, a cooling dominated climate.

As an example, the pre-1978 prototype home in Climate Zone 12 has an EDR1 score of 39 kBtu/ft²-year and the pre-1978 prototype home with upgraded R-49 attic insulation has an EDR1 score of 36 kBtu/ft²-year, the equivalent energy performance for R-49 insulation in Climate Zone 12 is valued at 3. The same approach is applied to packages of measures. Equivalent energy performance was calculated for most of the retrofit measures and packages described in Section 3.2 and Section 3.3, as well as a variety of additional building efficiency characteristics (see Appendix E – Details on Energy Performance Equivalency for a complete list).

4 Results

The primary objective of the evaluation is to identify cost-effective energy upgrade measures and packages for existing single family buildings, to support the design of local ordinances requiring upgrades, which may be triggered by different events, such as at the time of a significant remodel or addition. Cost-effectiveness analysis was completed for all climate zones based on single family prototype designs representing buildings features commonly used during each of three vintages.

Table 11 through Table 14 summarize cost effectiveness of efficiency measures and packages. Costeffectiveness analysis was evaluated using both On-Bill and TDV cost-effectiveness criteria described in Section 3.5. Detailed cost-effectiveness analysis results, along with energy savings are presented in Appendix D – Measure Cost-Effectiveness Tables, in Table 30 through Table 113, by climate zone and building vintage. Site energy savings, cost savings, measure cost, and cost effectiveness including lifecycle B/C ratio and NPV of savings are provided. For climate zones that are served by multiple utilities, where cost effectiveness may differ based on applicable utility rates, cost-effectiveness results are reported for both applicable utility territories.

Where measures are dependent on climate zone and building vintage (envelope efficiency measures), cost effectiveness is reported for each vintage and climate zone. Some measure results do not differ between the vintages such as LED lamp replacement and water heating upgrades. The water heating and LED lighting measures are cost-effective in all cases. A summary of these results is provided below.

Cost effectiveness by metric for each climates zone and building vintage is represented in the tables as summarized in Table 10:

Cost Effectiveness	Label
Cost-effective both On-Bill and TDV	Both
Cost-effective TDV only, not On-Bill	TDV
Cost-effective On-Bill only, not TDV	On-Bill
Not cost-effective On-Bill or TDV	N/A

Table 10: Results Table Legend

Unless called out specifically, TDV cost effectiveness is based on the 2019 TDV, using the 2019 version of CBECC-Res software. On-Bill cost effectiveness assumes savings based on 2022 weather files.

4.1 Building Envelope/Non-Preempted Measures

A summary of the cost effectiveness of individual efficiency measures is summarized in Table 11 based on both the On-Bill and 2019 TDV metrics.

<u>R-49 Attic Insulation</u>: R-49 attic insulation is cost-effective both On-Bill and TDV in older vintage homes except some coastal climates (Climate Zones 1, 3, and 5), and less cost-effective in newer vintage homes because of reduced energy savings.

<u>Air Sealing:</u> Reducing building leakage by 30 percent alone is only cost-effective in a handful of climates.

Duct Sealing: Duct sealing to ten percent of nominal airflow has the best economics of the envelope/duct measures in most climates and vintages and is cost-effective. It is not cost-effective in Climate Zones 3 and 5 through 7 in the 1992-2010 vintage homes.

<u>New Ducts:</u> Replacing old ductwork with new R-8 ducts sealed to five percent of nominal airflow has similar economics as the duct sealing measure and is cost-effective in many cases. It is not cost-effective in Climate Zones 3, 5, and 7 in any vintage and is only cost-effective in a handful of climate zones in 1992-2010 vintage homes.

<u>Cool Roof:</u> Cool roof is cost-effective for all vintages of single family homes in Climate Zones 8 through 15. It is also cost-effective for homes built before 1992 for homes in Climate Zone 2, 4, 6, and 7.

<u>Wall Insulation</u>: Blowing in wall insulation into exterior walls is only practical in pre-1978 homes with no insulation installed in the wall cavities. It is cost-effective On-Bill in Climate Zones 1 and 11 through 16, and it is cost-effective based on TDV in Climate Zones 1, 2, and 9 through 16.

<u>Window Replacement:</u> Window replacements are only cost-effective in homes built before 1978 in Climate Zones 10 through 15, and in Climate Zones 11 through 15; in addition, window replacements are also cost-effective in Climate Zone 10 for 1978 through 1991 vintage homes in SDG&E territory.

Climate	e Zone	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Util	ity	PG&E	PG&E	PG&E	PG&E CPAU	PG&E SCG	SCE	SDG&E	SCE	SCE	SCE SDGE	PG&E	PG&E SMUD	PG&E	SCE SDGE	SCE	PG&E
	Pre- 1978	N/A	Both	N/A	Both	N/A	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both
R-49 Attic Insulation	1978- 1991	N/A	TDV	N/A	Both TDV	N/A	N/A	N/A	Both	Both	Both	Both	Both TDV	Both	Both	Both	Both
	1992- 2010	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	TDV	N/A	On-Bill	N/A On-Bill	Both	N/A
	Pre- 1978	On-Bill	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	Both	N/A	N/A	TDV Both	Both	Both
Air Sealing	1978- 1991	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	TDV	N/A	N/A	N/A	N/A	N/A
	1992- 2010	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
	Pre- 1978	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both
Duct Sealing	1978- 1991	Both	Both	Both	Both	Both TDV	Both	On-Bill	Both	Both	Both	Both	Both	Both	Both	Both	Both
	1992- 2010	Both	TDV	N/A	TDV	N/A	N/A	N/A	Both	Both	Both	Both	Both	Both	Both	Both	Both
	Pre- 1978	Both	Both	N/A	Both	N/A	TDV	On-Bill	Both	Both	Both	Both	Both	Both	Both	Both	Both
New Ducts	1978- 1991	Both	TDV	N/A	Both TDV	N/A	N/A	N/A	Both	Both	Both	Both	Both	Both	Both	Both	Both
	1992- 2010	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	Both	TDV	Both	TDV Both	Both	N/A

 Table 11: Summary of Single Family Efficiency Measures – On-Bill & 2019 TDV

Existing Building Efficiency Upgrade Cost-Effectiveness Study

Climate	e Zone	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Util	lity	PG&E	PG&E	PG&E	PG&E CPAU	PG&E SCG	SCE	SDG&E	SCE	SCE	SCE SDGE	PG&E	PG&E SMUD	PG&E	SCE SDGE	SCE	PG&E
	Pre- 1978	N/A	Both	N/A	Both	N/A	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	On-Bill
Cool Roof	1978- 1991	N/A	TDV	N/A	Both TDV	N/A	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	N/A
	1992- 2010	N/A	N/A	N/A	N/A	N/A	N/A	N/A	Both	Both	TDV Both	Both	Both TDV	Both	Both	Both	N/A
Insulate Walls	Pre- 1978	Both	Both	N/A	N/A	N/A	N/A	N/A	N/A	TDV	TDV	Both	Both TDV	Both	Both	Both	Both
W/indowe	Pre- 1978	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	Both	Both	Both TDV	Both	Both	Both	N/A
Windows –	1978- 1991	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A On-Bill	Both	TDV	Both	TDV Both	Both	N/A

^a Duct Sealing requires sealing all ductwork to 10% of nominal airflow (as proposed in 2022 Title 24).
 ^b Air Sealing requires sealing all accessible cracks, holes, and gaps in the building envelope at walls, floors, and ceilings.

4.2 Envelope and Duct Packages

Cost effectiveness of the various envelope and duct packages are summarized in Table 12 based on both the On-Bill and 2019 TDV metrics. Cost effectiveness tends to be better in older vintage homes where potential for heating and cooling savings are higher.

- <u>R-49 Attic Insulation and Air Sealing:</u> Increasing attic insulation to R-49 and air sealing the building is costeffective based on either On-Bill or TDV in all climates except Climate Zones 3 and 5 in pre-1978 homes, and 1 and 3 through 8 in 1978 to 1991 vintage homes. Air sealing and attic insulation are less cost-effective in newer vintages and in mild climates where heating and cooling energy use is lower.
- <u>2.</u> <u>R-49 Attic Insulation and Duct Sealing:</u> Increasing attic insulation to R-49 and duct sealing is cost-effective both On-Bill and TDV in all climates except Climate Zones 3 and 5 in pre-1978 homes, and 3 and 5 through 7 in 1978 to 1991 vintage homes. In newer vintage homes (1992-2010) this package is cost-effective On-Bill in Climate Zones 11, 13, 15, and in SDG&E territory in Climate Zones 10 and 14. The newer vintage is cost-effective based on TDV in Climate Zones 9 through 15.
- <u>3.</u> <u>R-49 Attic Insulation, Air Sealing, and Duct Sealing:</u> Duct sealing is more cost-effective than air sealing and attic insulation measures. Packaging these measures provides improved cost effectiveness relative to these additional measures on their own. All three of these measures are cost-effective for the following vintages and climates:
 - Pre-1978: Climate Zones 1, 2, 4, and 7 through 16 (On-Bill), and 6 (TDV only).
 - 1978-1991: Climate Zones 1, 8 through 16 (On-Bill), and 2 and 4 (TDV only).
 - 1992-2010: Climate Zones 13 and 15 (On-Bill), and 11, and 13 through 15 (TDV only).
- <u>4.</u> <u>R-49 Attic Insulation, Air Sealing, and New Ducts:</u> Results for this package are not presented in Table 12 but cost effectiveness is similar to Package 3.
- 5. Advanced Envelope Package R-49 Attic Insulation, Air Sealing, and Duct Sealing, plus Wall Insulation and New Windows: This package only applies to pre-1978 homes without wall insulation. It is cost-effective in the following climates:
 - On-Bill: Climate Zones 10 through 16, except SMUD.
 - TDV: Climate Zones 2, 4, and 9 through 16.

4.3 Water Heating and Lighting Measures/Packages

Cost effectiveness of water heating and lighting measures are also summarized in Table 12. Cost effectiveness was evaluated based on customer On-Bill basis only. TDV cost effectiveness was not evaluated because the evaluation periods for these measures was less than the 30-year evaluation period used for TDV in some cases.

<u>Water Heating Package – Water Heater Blanket, Hot Water Pipe Insulation, and Low-Flow Fixtures:</u> The package including these three water heating measures is cost-effective On-Bill in all climate zones and vintages.

Lighting Measures – LED Lamps and Exterior Photocell Control: Replacing either an existing CFL or incandescent lamp with an LED lamp is cost-effective in all climate zones and vintages. The lighting results in Appendix D report cost effectiveness for replacement of CFLs with LED lamps. Replacement of incandescent with LED lamps results in better cost effectiveness. Savings for exterior photocell controls assume LED luminaires. Exterior photocell controls are cost-effective in all cases except in Climate Zone 4 with CPAU rates and Climate Zone 12 with SMUD rates.

Climate	Zone	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Utilit		PG&E	PG&E	PG&E	PG&E CPAU	PG&E SCG	SCE	SDG&E	SCE	SCE	SCE SDGE	PG&E	PG&E SMUD		SCE SDGE	SCE	PG&E
	Pre- 1978	On-Bill	Both	N/A	Both TDV	N/A	TDV	On-Bill	Both	Both	Both	Both	Both	Both	Both	Both	Both
R-49 Attic & Air Sealing	1978- 1991	N/A	TDV	N/A	N/A	N/A	N/A	N/A	N/A	TDV	Both	Both	Both TDV	Both	Both	Both	On-Bill
	1992- 2010	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
	Pre- 1978	Both	Both	N/A	Both	N/A	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both
R-49 Attic & Duct Sealing	1978- 1991	Both	Both	N/A	Both TDV	N/A	N/A	N/A	Both	Both	Both	Both	Both	Both	Both	Both	Both
Package	1992- 2010	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	TDV	TDV Both	Both	TDV	Both	Both	Both	N/A
R-49, Air	Pre- 1978	Both	Both	N/A	Both	N/A	Both	On-Bill	Both	Both	Both	Both	Both	Both	Both	Both	Both
Sealing & Duct Sealing	1978- 1991	On-Bill	TDV	N/A	Both TDV	N/A	N/A	N/A	Both	Both	Both	Both	Both	Both	Both	Both	Both
Package	1992- 2010	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	TDV	N/A	Both	TDV Both	Both	N/A
Advanced Envelope Package	Pre- 1978	N/A	TDV	N/A	TDV	N/A	N/A	N/A	N/A	TDV	Both	Both	Both TDV	Both	Both	Both	Both

Table 12: Summary of Single Family Efficiency Packages – On-Bill & 2019 TDV

Existing Building Efficiency Upgrade Cost-Effectiveness Study

Climate	Zone	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Utility		PG&E	PG&E	PG&E	PG&E CPAU	PG&E SCG	SCE	SDG&E	SCE	SCE	SCE SDGE	PG&E	PG&E SMUD	PG&E	SCE SDGE	SCE	PG&E
Water Heating Package	All Vintages	On-Bill	On-Bill	On-Bill	On-Bill	On-Bill	On-Bill	On-Bill	On-Bill	On-Bill	On-Bill	On-Bill	On-Bill	On-Bill	On-Bill	On-Bill	On-Bill
LED Lamps	All Vintages	On-Bill	On-Bill	On-Bill	On-Bill	On-Bill	On-Bill	On-Bill	On-Bill	On-Bill	On-Bill	On-Bill	On-Bill	On-Bill	On-Bill	On-Bill	On-Bill
Exterior Photosensor	All Vintages	On-Bill	On-Bill		On-Bill N/A	On-Bill	On-Bill	On-Bill	On-Bill	On-Bill	On-Bill	On-Bill	On-Bill	On-Bill	On-Bill	On-Bill	On-Bill

^a Duct Sealing requires sealing all ductwork to 10% of nominal airflow (as proposed in 2022 Title 24).

^b Air Sealing requires sealing all accessible cracks, holes, and gaps in the building envelope at walls, floors, and ceilings. ^c Water heating package includes water heater blanket, hot water pipe insulation, and low-flow fixtures.

^d Lighting package includes replacement of screw-in CFL and incandescent lamps with LED luminaires and installation of photocell control on exterior lighting luminaires.

4.4 PV and Batteries

On-Bill and 2019 TDV cost effectiveness for PV and PV with batteries are summarized in Table 13. Cost effectiveness for PV is not sensitive to building vintage but when paired with batteries results differ by vintage and the package is not as cost-effective with newer vintage homes.

PV: For this analysis, a PV system sized to offset the electricity use per the 2019 new construction standards by climate zone was assumed. PV systems are cost-effective in all climate zones and vintages based on both an On-Bill and TDV basis. 30-year On-Bill net benefits exceed \$5,000 across all the IOU scenarios, but cost effectiveness is marginal under both CPAU and SMUD municipal utility rates. Figure 1 summarizes both customer On-Bill and TDV lifecycle net benefits. PV cost effectiveness is not very sensitive to system size until the PV system size approaches net zero on an annual basis, or with very small systems which are more costly per kilowatt.




Figure 1: Net Benefit–Rooftop PV system sized to new construction standards (2-4 kW): 1992-2010.

PV and Batteries: Pairing a ten kWh battery storage system with a PV system sized to the 2019 new construction sizing criteria is cost-effective for the following vintages and climates:

- Pre-1978: Climate Zones 3 through 16 based on TDV; On-Bill everywhere except Climate Zones 4 under CPAU and 12 under SMUD municipal utility rates.
- 1978-1991: Climate Zones 3 through 16 based on TDV; On-Bill everywhere except Climate Zones 1; 4 under CPAU and 12 under SMUD municipal utility rates.
- 1992-2010: Climate Zones 3 through 16 based on TDV; On-Bill everywhere except Climate Zones 1, 2, 6; 4 under CPAU and 12 under SMUD municipal utility rates..

Figure 2 and Figure 3 summarize customer On-Bill and TDV lifecycle net benefits for PV and Battery for the pre-1978 vintage and the 1992-2010 vintage, respectively.




Figure 2: Net benefit - rooftop PV + 10 kWh battery, TOU control: pre-1978.




Figure 3: Net benefit - rooftop PV + 10 kWh battery, TOU control: 1992-2010.

Climat	e Zone	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Uti	lity	PG&E	PG&E	PG&E	PG&E CPAU	PG&E SCG	SCE	SDG&E	SCE	SCE	SCE SDGE	PG&E	PG&E SMUD	PG&E	SCE SDGE	SCE	PG&E
PV	All Vintages	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both
	Pre- 1978	On-Bill	On-Bill	Both	Both TDV	Both	Both	Both	Both	Both	Both	Both	Both TDV	Both	Both	Both	Both
PV + Battery	1978- 1991	N/A	On-Bill	Both	Both TDV	Both	Both	Both	Both	Both	Both	Both	Both TDV	Both	Both	Both	Both
	1992- 2010	N/A	N/A	Both	Both TDV	Both	TDV	Both	Both	Both	Both	Both	Both TDV	Both	Both	Both	Both

 Table 13: Summary of Single Family PV & Batteries – On-Bill & 2019 TDV

4.5 Equipment Fuel Substitution Measures

On-Bill and TDV (both 2019 and 2022) cost effectiveness for electric fuel substitution measures are summarized in Table 14 and Table 15. Cost-effectiveness for these measures is not as sensitive to building vintage as the building envelope and duct measures but HVAC heat pump installations in newer vintage homes tend to be more cost-effective than in older vintage homes.

<u>Heat Pump at HVAC Replacement:</u> Cost-effectiveness of replacing a ducted furnace and air conditioner with a minimum efficiency ducted air-source heat pump is limited. It is cost-effective On-Bill in SMUD territory with SMUDS's favorable electricity utility rates relative to natural gas rates. In all other climates, shifting from natural gas to electricity for space heating with a minimum efficiency heat pump results in both an increase in incremental lifecycle installed cost and utility costs. Incremental first costs are similar between a heat pump and gas furnace/AC, but because the assumed average equipment lifetime is 15 years for a heat pump compared to 17.5 years for the gas furnace/AC, lifetime incremental costs are slightly higher than first costs for heat pumps. TDV cost effectiveness is very different under the 2019 and 2022 metrics, and results are more favorable under the 2022 TDV where it is cost-effective in the newer vintage homes in Climate Zones 2 through 4 and 11 through 13, and cost-effective in older vintage homes in Climate Zones 1 through 4, 9, and 11 through 13. Figure 4 compares lifecycle net benefit of the heat pump installation based on customer On-Bill, 2019 TDV, and 2022 TDV for newer vintage homes.

Cost effectiveness for the no AC scenario is not shown. In mild climates without AC, the higher incremental costs do not justify heat pump replacement unless the project is planning on installing AC at replacement.




Figure 4: Net benefit – minimum efficiency heat pump at HVAC replacement: 1992-2010.

<u>High-Efficiency Heat Pump at HVAC Replacement:</u> Cost-effectiveness of replacing a ducted furnace and air conditioner with a high-efficiency, 21 SEER, 11 HSPF ducted air-source heat pump is also limited. Higher efficiency provides operating cost savings in most cases, but incremental costs are also higher. In 1992-2010 vintage homes it is cost-effective On-Bill in Climate Zones 13, and 15, and in 12 with SMUD rates.




Figure 5: Net benefit – high-efficiency heat pump at HVAC replacement: 1992-2010.

HVAC Heat Pump + PV: Combining heat pump installation with a new PV system when replacing a natural gas furnace/AC increases first costs but improves cost effectiveness (see Figure 6 and Table 15). PV offsets additional electricity used by the heat pump, resulting in net energy cost savings and On-Bill cost effectiveness in all cases except homes in Climate Zone 1 (older vintage homes only), 16 and 4 in CPAU territory. Adding the \$3,181 cost to upgrade the main service panel, the combination of these measures is still cost-effective in most cases (see Figure 7).




Figure 6: Net benefit – min efficiency heat pump at HVAC replacement + PV: 1992-2010.




Figure 7: Net benefit – min efficiency heat pump at HVAC replacement + PV + panel upgrade: 1992-2010.

<u>Heat Pump at DHW Replacement:</u> Cost effectiveness of replacing a natural gas storage water heater with a minimum efficiency HPWH is limited under customer On-Bill and 2019 TDV metrics. Due to higher incremental costs and operating costs relative to natural gas storage water heaters, it is only cost-effective On-Bill in SMUD territory due to the favorable electricity utility rates relative to natural gas rates. A HPWH is cost-effective in all climate zones except 1 and 16 based on 2022 TDV economics. Figure 8 compares lifecycle net benefit of the HPWH installation for customer On-Bill, 2019 TDV, and 2022 TDV, showing how cost effectiveness is positive for most climates based on 2022 TDV.




Figure 8: Net benefit – minimum efficiency HPWH at DHW replacement: 1992-2010.

High-Efficiency Heat Pump at DHW Replacement: Cost effectiveness improves when replacing a natural gas storage water heater with a NEEA Tier 3 HPWH but still is limited under customer On-Bill and 2019 TDV metrics. Higher efficiency equipment results in operating cost savings in many climate zones, but due to higher incremental costs it is still only cost-effective On-Bill in SMUD territory. Similar to the minimum efficiency HPWH case, the high-efficiency HPWH is cost-effective based on 2022 TDV in all climate zones except 16. Figure 9 compares lifecycle net benefit of the HPWH installation for customer On-Bill, 2019 TDV, and 2022 TDV, showing how cost effectiveness is positive for most climates based on 2022 TDV.





Figure 9: Net benefit – high-efficiency HPWH at DHW replacement: 1992-2010.

HPWH + PV: Combining installation of PV with a HPWH at the time of water heater replacement increases first costs but improves On-Bill cost effectiveness (see Figure 10 and Table 15). PV offsets additional electricity used by the HPWH, resulting in net energy cost savings and positive customer On-Bill cost effectiveness in all cases except Climate Zone 4 with CPAU rates. If the \$3,181 cost to upgrade the main service panel is included in the first cost, the combination of these measures is still cost-effective in most cases (see Figure 11).








Figure 11: Net benefit – min efficiency HPWH at DHW replacement + PV + Panel Upgrade: 1992-2010.

Existing Building Efficiency Upgrade Cost-Effectiveness Study

Climate	14: Sur e Zone	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Uti		PG&E	PG&E			PG&E SCG	SCE	SDG&E	SCE		SCE SDGE	PG&E	PG&E	PG&E	SCE SDGE	SCE	PG&E
								Heat Pur	np at H\	/AC Repl	acement						
	Pre- 1978	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A On-Bill	N/A	N/A	N/A	N/A
2019 TDV	1978- 1991	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A On-Bill	N/A	N/A	N/A	N/A
	1992- 2010	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A On-Bill	N/A	N/A	N/A	N/A
	Pre- 1978	TDV	TDV	TDV	TDV	N/A	N/A	N/A	N/A	TDV	N/A	TDV	TDV Both	TDV	N/A	N/A	N/A
2022 TDV	1978- 1991	TDV	TDV	TDV	TDV	N/A	N/A	N/A	N/A	N/A	N/A	TDV	TDV Both	TDV	N/A	N/A	N/A
	1992- 2010	N/A	TDV	TDV	TDV	N/A	N/A	N/A	N/A	N/A	N/A	TDV	TDV Both	TDV	N/A	N/A	N/A
	-					-		HPWH	l at DHV	/ Replace	ement	-	_		· · · ·		
	Pre- 1978	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A On-Bill	N/A	N/A	N/A	N/A
2019 TDV	1978- 1991	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A On-Bill	N/A	N/A	N/A	N/A
	1992- 2010	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A On-Bill	N/A	N/A	N/A	N/A
	Pre- 1978	N/A	TDV	TDV	TDV	TDV	TDV	TDV	TDV	TDV	TDV	TDV	TDV Both	TDV	TDV	TDV	N/A
2022 TDV	1978- 1991	N/A	TDV	TDV	TDV	TDV	TDV	TDV	TDV	TDV	TDV	TDV	TDV Both	TDV	TDV	TDV	N/A
	1992- 2010	N/A	TDV	TDV	TDV	TDV	TDV	TDV	TDV	TDV	TDV	TDV	TDV Both	TDV	TDV	TDV	N/A

Existing Building Efficiency Upgrade Cost-Effectiveness Study

Climate	e Zone	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Util	lity	PG&E	PG&E	PG&E	PG&E CPAU	PG&E SCG	SCE	SDG&E	SCE	SCE	SCE SDGE	PG&E	PG&E	PG&E	SCE SDGE	SCE	PG&E
				-			Н	eat Pump	+ PV at	HVAC Re	eplaceme	nt	_	-			
	Pre- 1978	N/A	Both	Both	Both TDV	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	N/A
2019 TDV	1978- 1991	N/A	Both	Both	Both TDV	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	N/A
	1992- 2010	On-Bill	Both	Both	Both TDV	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	N/A
	Pre- 1978	TDV	Both	Both	Both TDV	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	N/A
2022 TDV	1978- 1991	TDV	Both	Both	Both TDV	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	N/A
	1992- 2010	Both	Both	Both	Both TDV	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	N/A
	-		-	<u>.</u>			-	HPWH +	PV at DI	HW Repl	acement		-	<u>-</u>	<u> </u>		-
	Pre- 1978	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both
2019 TDV	1978- 1991	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	On-Bill
	1992- 2010	Both	Both	Both	Both TDV	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	On-Bill
	Pre- 1978	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both
2022 TDV	1978- 1991	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both
	1992- 2010	Both	Both	Both	Both TDV	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both	Both

Table 15: Summary of Single Family Equipment Fuel Substitution + PV – On-Bill & TDV – Federal Minimum Efficiency

Existing Building Efficiency Upgrade Cost-Effectiveness Study

PV and Electric Readiness Measures: Electric ready measures do not result in any energy savings, but combining electric ready measures with installation of PV provides a path to finance needed prewiring and service panel upgrades and reduce fuel substitution costs when appliances are replaced at end of useful life (see Figure 12 and Table 16). Upgrading the main service panel and pre-wiring for future space and water heating heat pumps with installation of a PV system is cost-effective On-Bill in all cases except in Climate Zone 4 with CPAU rates and Climate Zone 12 with SMUD rates due to reduced cost effectiveness of PV with those municipal rates. It is cost-effective based on TDV in all climate zones.




Figure 12: Net benefit – PV and Electric Readiness: 1992-2010.

Climate	e Zone	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Util	lity	PG&E	PG&E	PG&E	PG&E CPAU	PG&E SCG	SCE	SDG&E	SCE	SCE	SCE SDGE	PG&E	PG&E SMUD	PG&E	SCE SDGE	SCE	PG&E
	Pre- 1978	Both	Both	Both	Both TDV	Both	Both	Both	Both	Both	Both	Both	Both TDV	Both	Both	Both	Both
2019 TDV	1978- 1991	Both	Both	Both	Both TDV	Both	Both	Both	Both	Both	Both	Both	Both TDV	Both	Both	Both	Both
	1992- 2010	Both	Both	Both	Both TDV	Both	Both	Both	Both	Both	Both	Both	Both TDV	Both	Both	Both	Both

Table 16: Summary of Single Family Electric Ready Measures at PV Install – On-Bill & 2019 TDV

5 Energy Performance Equivalency

For jurisdictions looking to provide flexibility in their reach codes for existing buildings, an approach to energy performance equivalency for retrofit measures and packages was completed. The metric for evaluating equivalency is based on the 2022 Title 24 source energy metric (EDR1). A summary of the results and how this can be applied is described below. Appendix E – Details on Energy Performance Equivalency provides additional background and the point score for all retrofit measures and packages by climate zone.

The results of this analysis presented in Section 4 demonstrate different sets of cost-effective measures based on home vintage. The energy performance equivalency defines value for the building characteristics that are applied in each of the three vintage prototypes and evaluated as upgrades. The values are relative to a typical worst-case scenario (i.e., uninsulated or minimally insulated assemblies, very leaky ducts, old mechanical equipment).

Table 17 presents the energy performance equivalency for the three vintage homes. The pre-1978 vintage generally represents the worst-case scenario and therefore has zero points. These values reflect the assumptions presented in Table 2.

Climate Zone	Pre-1978	1978-1991	1992-2010
1	0	8.8	25.5
2	0	5.3	9.3
3	0	4.1	6.1
4	0	3.7	6.9
5	0	3.9	5.5
6	0	2.1	3.4
7	0	1.6	2.7
8	0	1.8	3.8
9	0	2.3	4.8
10	0	3.0	6.2
11	0	6.0	13.1
12	0	5.1	10.5
13	0	4.3	10.3
14	0	5.8	11.3
15	0	2.3	8.3
16	0	9.9	29.9

Table 17: Energy Performance Equivalency for Each Vintage by Climate Zone

If a jurisdiction adopts an ordinance with different sets of requirements based on home vintage, an applicant could either conform with the requirements based on their home's year of construction or value existing upgrades to the home according to a points menu. A sample points menu for Climate Zone 12 is presented in Table 18. Measures are valued differently according to each of the three prototype vintages evaluated.

As an example, consider a home built in the 1950s in Climate Zone 12 that recently replaced their HVAC system with an 80 AFUE furnace (0.4 points) and 14 SEER air conditioner (1.4 points) and testing confirmed duct leakage of no more than 15 percent (2.1 points). In addition, the home has replaced windows with a U-factor less than or

equal to 0.32 (2.5 points). This combination results in a total of 6.4 points which is greater than the 1978-1991 vintage points of 5.1 but less than the 10.5 points for the 1992-2010 vintage. In this instance the project could be subject to the ordinance retrofit requirements for a 1978-1991 vintage home instead of a pre-1978 vintage home. The existing home characteristics should be verified by a HERS Rater, the building department, or another third party.

Component	Pre-1978	1978-1991	1992-2010
Walls			
R-11 (<=0.110 U-factor)	2.9	0.4	n/a
R-19 (<=0.074 U-factor)	4.2	1.7	1.1
Attic Ceiling Insulation	1		1
R-19	1.4	n/a	n/a
R-30	2.3	0.9	n/a
R-38	2.6	1.2	0.3
≥ R-49	2.9	1.5	0.6
Roof	1		1
Cool roof (aged solar reflectance >=0.25)	0.1	0.1	0.0
Floors	1		1
≥ R-19 raised floor	3.5	1.3	n/a
Windows	1		1
Double non-metal	1.8	1.4	n/a
U-factor <=0.32	2.5	2.1	1.3
Infiltration			
<=10 ACH50	0.8	n/a	n/a
<=7 ACH50	1.3	0.5	n/a
<=5 ACH50	1.7	0.9	0.3
Duct Leakage	1		r
<=15% leakage	2.1	1.1	n/a
<=10% leakage	2.7	1.6	n/a
New ducts ^a	4.5	3.3	1.1
Heating			
80% AFUE	0.4	0.3	0.3
90% AFUE	2.3	1.7	1.3
Heat Pump: 8.2 HSPF	7.8	5.8	4.9
Heat Pump: 9 HSPF	8.4	6.3	5.5
Cooling			

Table 18: Energy Performance Equivalency by Measure for Climate Zone 12

Component	Pre-1978	1978-1991	1992-2010
13 SEER	0.9	0.8	n/a
14 SEER	1.4	1.2	0.2
16+ SEER	1.7	1.4	0.4
Water Heater			
Gas tankless	3.0	3.0	3.0
Condensing gas water heater	3.8	3.8	3.8
2.0 UEF HPWH	7.1	7.2	7.2
NEEA Tier 3 HPWH	7.6	7.7	7.7
PV+Battery			
Solar PV	1.2	1.2	1.2
10 kWh Battery	3.2	3.3	3.4

^a≥R-6+ and <=5% leakage, ducts in conditioned space, or ductless distribution.

The energy performance equivalency approach also provides additional flexibility in allowing applicants the ability to choose upgrades from the points menu that result in equivalent performance to the applicable reach code requirement. Table 19 and Table 20 demonstrate how this could be implemented. As an example, consider a jurisdiction with an ordinance that requires attic insulation, air sealing, and duct sealing package. While not cost-effective in all climate zones and vintages, where cost-effective and if this package was part of an ordinance, there are other measures that provide equal or greater energy performance that could be used as equivalent to the required ordinance. For a pre-1978 home (Table 19), the value for this package is 6.2 in Climate Zone 12. Based on the menu of options (Table 18) there are several alternative individual or packages of measures that provide equal or greater performance that the package. This is because the impact of those insulation and air sealing measures is reduced in a newer home with a better building envelope. Measures like water heating upgrades have a similar impact across vintages because the loads are primarily occupant driven.

Climate Zone	R-49, Air & Duct Sealing Package	80 AFUE/14 SEER	90 AFUE/16 SEER/New Ducts	8.2 HSPF/14 SEER	Condensing Water Heater	NEEA Tier 3 HPWH	NEEA Tier 3 HPWH & PV/Battery	R-13 Wall Insulation & R-49 Attic Insulation
1	9.7	No	No	Yes	No	No	Yes	No
2	5.8	No	No	Yes	No	Yes	Yes	No
3	4.2	No	No	Yes	No	Yes	Yes	Yes
4	4.2	No	No	Yes	No	Yes	Yes	No
5	3.9	No	No	Yes	Yes	Yes	Yes	Yes
6	2.2	No	No	No	Yes	Yes	Yes	Yes
7	1.8	No	No	No	Yes	Yes	Yes	Yes
8	2.1	No	Yes	Yes	Yes	Yes	Yes	Yes
9	2.8	No	Yes	Yes	Yes	Yes	Yes	No
10	3.4	No	Yes	Yes	Yes	Yes	Yes	No
11	7.1	No	Yes	Yes	No	Yes	Yes	No
12	6.2	No	Yes	Yes	No	Yes	Yes	No
13	5.5	No	Yes	Yes	No	Yes	Yes	No
14	6.7	No	Yes	Yes	No	Yes	Yes	No
15	3.5	Yes	Yes	Yes	No	Yes	Yes	No
16	12.8	No	No	Yes	No	No	No	No

Table 19: Performance Equivalency Options – Pre-1978 Home

Climate Zone	R-49, Air & Duct Sealing Package	80 AFUE/14 SEER	90 AFUE/16 SEER/New Ducts	8.2 HSPF/14 SEER	Condensing Water Heater	Minimum Efficiency HPWH	New Construction PV System
1	1.9	No	Yes	Yes	Yes	Yes	No
2	1.2	No	Yes	Yes	Yes	Yes	No
3	0.9	No	Yes	Yes	Yes	Yes	Yes
4	0.9	No	Yes	Yes	Yes	Yes	Yes
5	0.8	No	Yes	Yes	Yes	Yes	Yes
6	0.4	No	Yes	Yes	Yes	Yes	Yes
7	0.3	No	Yes	Yes	Yes	Yes	Yes
8	0.4	No	Yes	Yes	Yes	Yes	Yes
9	0.6	No	Yes	Yes	Yes	Yes	Yes
10	0.7	No	Yes	Yes	Yes	Yes	Yes
11	1.5	No	Yes	Yes	Yes	Yes	No
12	1.3	No	Yes	Yes	Yes	Yes	No
13	1.2	No	Yes	Yes	Yes	Yes	Yes
14	1.4	No	Yes	Yes	Yes	Yes	Yes
15	0.6	Yes	Yes	Yes	Yes	Yes	Yes
16	2.5	No	Yes	Yes	Yes	Yes	No

Table 20: Performance Equivalency Options – 1992-2010 Home

6 Recommendations and Discussion

This analysis evaluated the feasibility and cost effectiveness of retrofit measures in California existing homes built before 2010. The Statewide Reach Codes Team used both On-Bill- and TDV-based LCC approaches to evaluate cost effectiveness and quantify the energy cost savings associated with energy efficiency measures compared to the incremental costs associated with the measures.

6.1 Recommended Efficiency Measures

Based on the analysis, the following cost-effective measures or packages of measures are recommended where they are found to be cost-effective in Section 4. Descriptions of each measure or package and the relevant requirements are provided below. In most cases, exceptions are defined which would exempt a particular project from a measure under certain conditions. These exceptions are based on existing on-site conditions and cost effectiveness.

Attic Insulation: In vented attics, insulation shall be installed to achieve a weighted U-factor of 0.020 or insulation installed at the ceiling level shall result in an installed thermal resistance of R-49 or greater for the insulation alone. Recessed downlight luminaires in the ceiling shall be covered with insulation to the same depth as the rest of the ceiling. Luminaires not rated for insulation contact must be replaced or fitted with a fire-proof cover that allows for insulation to be installed directly over the cover. This measure applies to homes according to vintage and climate zone as defined in Table 2.

<u>Exception 1</u>: Buildings with at least R-38 existing insulation installed at the ceiling level. Buildings with at least R-30 existing insulation installed at the ceiling level are exempt from the recessed downlight luminaire requirements.

Exception 2: Buildings where the alteration would directly cause the disturbance of asbestos unless the alteration is made in conjunction with asbestos abatement.

Exception 3: Buildings with knob and tube wiring located in the vented attic.

<u>Exception 4</u>: Where the accessible space in the attic is not large enough to accommodate the required R-value, the entire accessible space shall be filled with insulation provided such installation does not violate roof ventilation clearance requirements in Section 806.3 of Title 24, Part 2.5.

Exception 5: Where the attic space above the altered dwelling unit is shared with other dwelling units and the attic insulation requirement is not triggered for the other dwelling units.

<u>Air Sealing</u>: Seal all accessible cracks, holes, and gaps in the building envelope at walls, floors, and ceilings. Pay special attention to penetrations including plumbing, electrical, and mechanical vents, recessed can light luminaires, and windows. Weather-strip doors if not already present. Verification shall be conducted following a prescriptive checklist (to be developed) that outlines which building aspects need to be addressed by the permit applicant and verified by an inspector. Compliance can also be demonstrated with blower door testing showing at least a 30 percent reduction from pre-retrofit conditions. This measure applies to homes according to vintage, building type and climate zone as defined in Table 11.

<u>Exception 1</u>: Buildings that can demonstrate blower door test results showing five ACH50 or lower or can otherwise demonstrate that air sealing meeting the requirements of this ordinance was conducted within the last 12 months.

Duct Sealing: Air seal all space conditioning ductwork to meet the requirements of the 2019 Title 24 Section 150.2(b)1E, with the exception that the duct sealing requirements be reduced from the current code requirement of 15 percent to ten percent in alignment with the 2022 Title 24 code change proposal. The duct system must be tested to confirm that the requirements have been met. Cost effectiveness included costs for a third-party HERS Rater to verify the duct sealing. See Appendix C – Standards Sections for additional details on the requirements per Title 24. This measure applies to homes according to vintage, building type and climate zone as defined in Table 11.

Exception 1: All exceptions as stated in the 2019 Title 24 Section 150.2(b)1E are allowed.

Exception 2: Buildings without ductwork or where the ducts are in conditioned space.

<u>New Ducts</u>: Replace existing space conditioning ductwork with new R-8 ducts that meet the requirements of 2019 Title 24 Section 150.0(m)11.

Exception 1: Buildings without ductwork or where the ducts are in conditioned space.

<u>Windows</u>: Replace existing windows with high performance windows with an area weighted average U-factor no greater than 0.32.

Exception 1: All exceptions as stated in the 2019 Title 24 Section 150.1(c)3A are allowed.

Exception 2: Buildings where it is not feasible to meet the performance requirements as a result of historic preservation design guidelines or other reasons as determined by the jurisdiction.

Window upgrades were only found to be cost-effective in Climate Zones 10-15 for the pre-1992 vintage homes and as part of the Advanced Envelope Package in pre-1978 vintage homes. Because the cost requirement for window replacement is significant and the margin for cost effectiveness is lower than many other measures, it is recommended that jurisdictions consider whether a window replacement requirement is appropriate and only require it for large projects where the additional cost is small relative to total cost.

<u>Wall Insulation</u>: Older vintage homes with no insulation in exterior walls shall be insulated to achieve a weighted U-factor of 0.102 or insulation installed in the exterior wall cavity shall result in an installed thermal resistance of R-13 or greater for the insulation alone.

Cool Roof: When replacing a roof, install a roofing product rated by the Cool Roof Rating Council to have an aged solar reflectance equal to or greater than 0.25, and a thermal emittance equal to or greater than 0.75, regardless of the compliance approach (prescriptive or performance). This measure only applies to steep slope roofs (ratio of rise to run greater than 2:12) and to buildings that are installing a new roof as part of the scope of the remodel and where more than 50 percent of the roof is being replaced. This applies only to certain homes according to vintage, building type, and climate zone as defined in Table 11. Low slope roofs (ratio of rise to run of 2:12 or less) shall meet the requirements of Section 150.2(b)11ii of 2019 Title 24, Part 6. See Appendix C – Standards Sections for additional details on the requirements per Title 24.

Exception 1: Projects that are not installing a new roof as part of the scope. Only areas of roof that are to be re-roofed are subject to the cool roof upgrade.

Exception 2: All exceptions as stated in the 2019 Title 24 Section 150.2(b)1li for steep slope roofs and 150.2(b)1lii for low slope roofs are allowed.

Envelope and Duct Packages: From a performance perspective, air sealing of the boundary between the attic and living space should be addressed any time there is significant work in the attic, such as adding attic insulation and sealing or replacing ductwork. When the building shell is being improved, air sealing is an important component to be addressed. The boundary between the living space and vented attics is where a significant amount of building air leakage can occur and sealing these areas prior to covering the attic floor with insulation is both practical and effective. For this reason, several envelope and duct packages were evaluated and are recommended where cost-effective. Detailed requirements and relevant exceptions are listed above for the individual measures.

Attic Insulation, Air Sealing, and Duct Packages: These requirements can be triggered when an entirely new or complete replacement duct system is installed in a vented attic space in alignment with the 2022 Title 24 code change proposal. Addressing air sealing and attic insulation when attic ductwork is being replaced avoids lost opportunities to improve the building shell. While replacing ductwork the contractor accesses most areas of the ceiling and there are efficiencies to be gained with performing air sealing at the same time. Other benefits to addressing air sealing and ceiling insulation when HVAC systems and ductwork are being replaced is the potential ability to downsize equipment by reducing heating and cooling loads.

<u>Advanced Envelope Package</u>: This package only applies to older vintage homes with single-pane windows and no exterior wall insulation where cost-effective as defined in Table 12. Because the incremental cost of this package is significantly higher than other packages, jurisdictions may wish to consider placing a limit on the incremental cost relative to the total project cost, limiting the requirement to large projects.

Water Heating Package: Add exterior insulation meeting a minimum of R-6 to storage water heaters. Insulate all accessible hot water pipes with pipe insulation a minimum of ³/₄ inch thick. This includes insulating the supply pipe leaving the water heater, piping to faucets underneath sinks, and accessible pipes in attic spaces or crawlspaces. Upgrade fittings in sinks and showers to meet current CALGreen (Title 24, Part 11) requirements.

Exception 1: Water heater blanket is not required on water heaters less than 20 gallons.

Exception 2: Water heater blanket not required if application of a water heater blanket voids the warranty on the water heater.

Exception 3: Fixtures with rated or measured flow rates no more than ten percent greater than current CALGreen requirements.

Lighting Measures – LED Lamps and Exterior Photocell Sensors: Replace all interior and exterior screw-in incandescent, halogen, and compact fluorescent lamps with screw-in LED lamps. Install photocell controls on all exterior lighting luminaires.

Installation of PV: Install a PV system that meets the requirements of 2019 Title 24 Section 150.1(c)14. Alternatively, a smaller PV system can be required as analysis found that cost-effectiveness results do not change appreciably with a PV system as small as one kW_{DC} .

Exception 1: All exceptions as stated in the 2019 Title 24 Section 150.1(c)14 are allowed.

Exception 2: A smaller PV system may be installed if the proposed system capacity is larger than the maximum size allowed by the electric utility based on NEM requirements.

Installation of PV and Battery: Install a PV system that meets the requirements of 2019 Title 24 Section 150.1(c)14 and a battery system that meets the requirements of 2019 Title 24 Joint Appendix 12. Combining PV with a battery system is cost-effective both On-Bill and TDV as shown in Table 13; however, battery systems are not cost-effective on their own without the energy savings from the PV system.

Alternatively, instead of requiring a battery system battery-ready measures could be required with a PV installation including locating and reserving a zone for installation of a battery storage system, running conduit for a future battery storage system, and possibly panel upgrades if the main service panel is replaced as part of the scope of work.

Exception 1: All exceptions as stated in the 2019 Title 24 Section 150.1(c)14 are allowed.

6.2 Fuel Substitution Measures

HVAC Heat Pump: Replace an existing ducted natural gas furnace/AC with a ducted heat pump at time of equipment replacement. This measure applies to homes according to climate zone as defined in Table 14, and summarized in Figure 4, Figure 5, and Figure 6. While it is cost-effective based on 2022 TDV in some conditions, replacement of the HVAC equipment with a minimum efficiency heat pump results in higher utility costs in most cases, resulting in negative impact on customer's ability to recover costs. Operating costs are sensitive to utility rate structures and changes in natural gas and electricity rates. As shown in Climate Zone 12 with SMUD rates, installing a heat pump can result in lower utility costs. Installing high-efficiency heat pumps can improve cost-effectiveness and lower operating costs but cannot be used for the basis of a reach code.

Installation of PV in addition to replacing a gas furnace/AC with a heat pump increases first cost but results in reduced utility costs and positive On-Bill cost effectiveness in most cases.

Exception 1: Non-ducted space conditioning systems and systems without central air conditioning.

Exception 2: Ducted space conditioning systems where only the gas furnace is replaced.

<u>Exception 3:</u> The main service panel does not have the capacity or space to accommodate an additional 240 V, 30 A circuit, and the cost to upgrade the main service panel and run required electrical service to the heat pump air handler is prohibitive as determined by the jurisdiction.

HPWH: Replace an existing natural gas storage water heater with a heat pump at time of equipment replacement. This measure applies to homes according to climate zone as defined in Table 15, and summarized in Figure 8, Figure 9, and Figure 10. This measure is cost-effective based on 2022 TDV in all climate zones except 1 and 16, but installation of a HPWH to replace an existing storage tank water heater can result in higher utility costs. Like the space conditioning heat pump, operating costs are sensitive to utility rate structures and future changes in natural gas and electricity rates. Installing a HPWH in Climate Zone 12 with SMUD rates results in lower utility costs. Like space conditioning heat pumps, installing higher efficiency equipment lowers operating costs but cannot be used for the basis of a reach code.

Installation of PV in addition to replacing an existing water heater with a HPWH significantly increases first cost but results in reduced utility costs and positive On-Bill cost effectiveness in all cases except the newest vintage case in Climate Zone 4 and CPAU territory.

This requirement could apply when replacing an existing water heater under the following conditions:

- 1. Electric resistance water heater located in a garage or vented closet with adequate space and ventilation,
- 2. Natural gas or propane water heater located in a garage or vented closet with adequate space and ventilation, and
 - a. there is adequate space in the main service panel for a 240 V, 30 A dedicated breaker.

Exception 1: The proposed location of the new water heater is located within conditioned space.

Exception 2: The proposed location of the replacement water heater is not large enough to accommodate a HPWH equivalent in size and one-hour capacity rating to the existing water heater or the next nominal size available.

<u>Exception 3:</u> The main service panel does not have the capacity or space to accommodate an additional 240 V, 30 A circuit, or the cost to upgrade the main service panel and run required electrical service to the water heater is prohibitive as determined by the jurisdiction.

Exception 4: A solar water heating system is installed meeting the installation criteria specified in Reference Residential Appendix RA4.20 and with a minimum solar savings fraction of 60 percent.

<u>PV and Electric Readiness Measures:</u> Install a PV system and wiring for 240 V power to the furnace location and the water heater location and upgrade the main service panel to allow for installation of electric appliances at a future date. The requirements include the following:

1. Install a dedicated 240 V, 50 A or greater electrical circuit that terminates within three feet of the existing furnace or designated future location of an electric replacement heater with no obstructions into a listed cabinet, box, enclosure, or receptacle labelled "For Future Heat Pump Space Heater".

Exception 1: The building does not have existing central ducted heating or cooling system.

Exception 2: The building already has a heat pump for space heating.

2. Install a dedicated 240 V, 30 A or greater electrical circuit that terminates within three feet of the existing water heater or designated future location of an electric replacement water heater with no obstructions into a listed cabinet, box, enclosure, or receptacle labelled "For Future Heat Pump Water Heater".

Exception 1: The proposed location of the new water heater is located within conditioned space.

<u>Exception 2</u>: The proposed location of the replacement water heater is not large enough to accommodate a HPWH equivalent in size and one-hour capacity rating to the existing water heater or the next nominal size available.

Exception 3: The building already has a HPWH.

3. Upgrade existing main service panel to a minimum 200 A panel to accommodate future connection of electric appliances.

<u>Exception 1:</u> The existing main service panel can be documented by an electrician or engineer to have sufficient capacity for the following electrical appliances: space heating, water heating, cooking, clothes drying, and Level 2 electric vehicle service equipment.

Exception 2: The building already uses electric appliances for space heating, water heating, cooking, and clothes drying.

6.3 Other Considerations

<u>Measure Tradeoffs for Energy Performance Equivalency:</u> Jurisdictions looking to provide flexibility in their reach codes for existing buildings can use the energy performance equivalency results to allow projects to select alternative measures or packages to meet the energy performance of the ordinance. This approach also allows an applicant to value previous upgrades made to the building in determining which ordinance requirements should apply. If tradeoffs are adopted by a jurisdiction, it can also provide flexibility to applicants to choose upgrades from the points menu that result in equivalent performance to the applicable reach code requirement or allow a jurisdiction to encourage installation of fuel substitution measures, such as space conditioning heat pumps or HPWHs as an equivalent alternative path to the adopted reach code measure or package.

<u>HERS Rater Field Verification</u>: HERS Rater field verification applies to duct sealing and new duct measures. It also may be required for other measures depending on the project work scope.

<u>Combustion Appliance Safety and Indoor Air Quality:</u> Implementation of some of the recommended measures will affect the pressure balance of the home which can subsequently impact the safe operation of existing combustion appliances as well as indoor air quality. Buildings with older gas appliances can present serious health and safety problems which may not be addressed in a remodel if the appliances are not being replaced. It is recommended that the building department require inspection and testing of all combustion appliances after completion of the retrofit work. It is also recommended that jurisdictions require combustion safety testing by a certified professional whenever air sealing and insulation measures are applied, and existing combustion appliances are located within the pressure boundary of the building.

Jurisdictions may also want to consider requiring mechanical ventilation in homes where air sealing has been conducted. In older buildings, outdoor air is typically introduced through leaks in the building envelope. After air sealing a building, it may be necessary to forcefully bring in fresh outdoor air using supply and/or exhaust fans to minimize potential issues associated with indoor air quality.

Required Measures Included in Title 24 Performance Simulation: If any of the measures above are included in a performance Title 24 compliance report, it's suggested that trade-offs be allowed as long as all minimum code requirements are met. For example, if a project is installing new windows, a new roof, and insulating the attic and is demonstrating Title 24 compliance with a performance simulation run, it would be acceptable if the installed roof did not meet the requirements listed above as long as this was traded off with either an increase in attic insulation or better performing windows. This would also allow trade-offs for projects that are installing high impact measures, such as solar water heating or whole house fans. This would require two simulation runs; however, it's not expected this approach would be utilized often. Run number one would evaluate the proposed building upgrades. This would also be the report submitted to the building department for the permit application demonstrating compliance with Title 24. Run number two would also be completed with the minimum ordinance requirements modeled for each of the affected building components. To show compliance with the ordinance the applicant would need to demonstrate that the proposed upgrades in run one would result in annual TDV energy use equal to or less than the annual TDV energy use of the case based on the ordinance requirements in run two.

7 References

Barbose, Galen and Darghouth, Naim. 2018. Tracking the Sun. Installed Price Trends for Distributed Photovoltaic Systems in the United States – 2018 Edition. Lawrence Berkeley National Laboratory. September 2018. https://emp.lbl.gov/sites/default/files/tracking the sun 2018 edition final 0.pdf.

California Energy Commission. 2017. Rooftop Solar PV System. Measure number: 2019-Res-PV-D Prepared by Energy and Environmental Economics, Inc. <u>https://efiling.energy.ca.gov/getdocument.aspx?tn=221366.</u>

California Energy Commission. 2018. 2019 Building Energy Efficiency Standards for Residential and Nonresidential Buildings. CEC-400-2018-020-CMF. December 2018. California Energy Commission. https://ww2.energy.ca.gov/2018publications/CEC-400-2018-020/CEC-400-2018-020-CMF.pdf.

California Public Utilities Commission. 2021. DEER2021 Update. Retrieved from Deer Resources website April 13, 2021: <u>http://www.deeresources.com/index.php/deer-versions/deer2021</u>

ConSol. 2010. Water Use in the California Residential Home. January 2010. <u>https://wordpressstorageaccount.blob.core.windows.net/wp-media/wp-content/uploads/sites/833/2018/10/2010-chf_water_use_in_the_California_Residential_Home-.pdf</u>.

Consortium for Energy Efficiency (CEE). 2014. Residential Lighting Controls Market Characterization. January 9, 2014. <u>https://library.cee1.org/content/cee-residential-lighting-controls-market-characterization</u>.

Davis Energy Group (DEG). 2017. Large Scale Residential Retrofit Program. Prepared for the California Energy Commission by Davis Energy Group. January 2017. <u>http://www.energy.ca.gov/2017publications/CEC-500-2017-009/CEC-500-2017-009.pdf.</u>

E Source Companies. 2020. Behind-the-Meter Battery Market Study. Prepared for San Diego Gas & Electric. February 2020. <u>https://www.etcc-ca.com/reports/behind-meter-battery-market-study?dl=1582149166.</u>

Energy & Environmental Economics. 2019. Residential Building Electrification in California. April 2019. https://www.ethree.com/wp-

content/uploads/2019/04/E3 Residential Building Electrification in California April 2019.pdf.

Energy & Environmental Economics. 2020. Time Dependent valuation of Energy for Developing Building Efficiency Standards. 2022 Time Dependent Valuation (TDV) and Source Energy Metric Data Sources and Inputs. Prepared for the California Energy Commission. May 2020. https://efiling.energy.ca.gov/GetDocument.aspx?tn=233345&DocumentContentId=65837.

Horii, B., E. Cutter, N. Kapur, J. Arent, and D. Conotyannis. 2014. "Time Dependent Valuation of Energy for Developing Building Energy Efficiency Standards." <u>http://www.energy.ca.gov/title24/2016standards/prerulemaking/documents/2014-07-</u> 09 workshop/2017 TDV Documents/.

KEMA. 2010. *Final Evaluation Report: Upstream Lighting Program, Vol 1.* KEMA, Inc. February 2010. <u>http://www.energydataweb.com/cpucfiles/18/finalupstreamlightingevaluationreport 2.pdf.</u>

Sacramento Municipal Utility District (SMUD). 2020. SMUD Residential Electrification Project Costs. September 22, 2020. Submitted to California Energy Commission Docket 19-DECARB-01. https://efiling.energy.ca.gov/GetDocument.aspx?tn=234862&DocumentContentId=67717.

Self-Generation Incentive Program (SGIP). 2020. Weekly Statewide Reports. https://www.selfgenca.com/report/weekly_statewide_archives/. Accessed November 2020.

Statewide CASE Team. 2020. Residential Energy Savings and Process Improvements for Additions and Alterations. August 2020. <u>https://title24stakeholders.com/wp-content/uploads/2020/08/SF-Additions-and-Alterations_Final_-CASE-Report_Statewide-CASE-Team.pdf</u>.

Statewide Reach Codes Team. 2019. 2019 Cost-effectiveness Study: Low-Rise Residential New Construction. August 1, 2019. <u>https://localenergycodes.com/download/73/file_path/fieldList/2019%20Res%20NC%20Cost-eff%20Report.pdf</u>.

Statewide Reach Codes Team. 2020. 2019 Cost-Effectiveness Study: Existing Low-rise Residential Building Efficiency Upgrade. February 6, 2020. https://localenergycodes.com/download/96/file_path/fieldList/2019%20Res%20Retrofit%20Cost-

nttps://iocalenergycodes.com/download/96/file_path/fieldList/2019%20Res%20Retrofit%20 eff%20Report.pdf.

TRC. 2016. Palo Alto Electrification Final Report. November 16, 2016.

https://www.cityofpaloalto.org/files/assets/public/development-services/advisory-groups/electrification-taskforce/palo-alto-electrification-study-11162016.pdf

8 Appendices

8.1 Appendix A: Map of California Climate Zones

Climate zone geographical boundaries are depicted in Figure 13. The map in Figure 13 along with a zip-code search directory is available at: <u>https://ww2.energy.ca.gov/maps/renewable/building_climate_zones.html</u>





8.2 Appendix B: Utility Rate Schedules

<u>PG&E</u>

The following pages provide details on the PG&E electricity and natural gas tariffs applied in this study. Table 21 describes the baseline territories that were assumed for each climate zone.

Table 21: PG&E Baseline Territory by Climate Zone

	Baseline Territory
CZ01	V
CZ02	Х
CZ03	Т
CZ04	Х
CZ05	Т
CZ11	R
CZ12	S
CZ13	R
CZ16	Y

The PG&E monthly gas rate in \$/therm was applied on a monthly basis for the 12-month period ending March 2021 according to the rates shown in Table 22.

Month	Procurement	Transportat	ion Charge	<u>Total Cl</u>	narge
Monu	<u>Charge</u>	Baseline	Excess	Baseline	Excess
Jan 2021	\$0.49332	\$1.09586	\$1.53752	\$1.58918	\$2.03084
Feb 2021	\$0.49073	\$1.09586	\$1.53752	\$1.58659	\$2.02825
Mar 2021	\$0.42316	\$1.19868	\$1.68034	\$1.62184	\$2.1035
Apr 2020	\$0.23856	\$1.13126	\$1.64861	\$1.36982	\$1.88717
May 2020	\$0.23187	\$1.13126	\$1.64861	\$1.36313	\$1.88048
June 2020	\$0.24614	\$1.13126	\$1.64861	\$1.3774	\$1.89475
July 2020	\$0.23892	\$1.13126	\$1.64861	\$1.37018	\$1.88753
Aug 2020	\$0.28328	\$1.13126	\$1.64861	\$1.41454	\$1.93189
Sept 2020	\$0.41891	\$1.13126	\$1.64861	\$1.55017	\$2.06752
Oct 2020	\$0.38068	\$1.13416	\$1.65280	\$1.51484	\$2.03348
Nov 2020	\$0.46046	\$1.13416	\$1.65280	\$1.59462	\$2.11326
Dec 2020	\$0.48474	\$1.13416	\$1.65280	\$1.6189	\$2.13754

Table 22: PG&E Monthly Gas Rate (\$/therm)



Cancelling Revised

Cal. P.U.C. Sheet No. 35436-G Cal. P.U.C. Sheet No. 34288-G

GAS SCHEDULE G-1

Sheet 2

RESIDENTIAL SERVICE

BASELINE QUANTITIES: The delivered quantities of gas shown below are billed at the rates for baseline use.

Baseline Territories	BASELINE QUANTITIE Summer (April-October) Effective Apr. 1, 2020		Winter Off-Peak (Nov,Feb,Mar) Effective Nov. 1, 2019		Winter On-Peak (Dec, Jan)		(T) (T)
P	0.39	(R)	1.88	(R)	2.16	(1)	
Q	0.59	(R)	1.55	(R)	2.16	(1)	
R	0.36	(R)	1.28	(R)	1.97	(1)	
S	0.39	(R)	1.38	(R)	2.06	(1)	
Т	0.59	(R)	1.38	(R)	1.81	(1)	
V	0.62	(R)	1.51	(R)	1.84	(1)	
W	0.39	(R)	1.18	(R)	1.84	(1)	
X	0.49	(R)	1.55	(R)	2.16	(1)	
Y	0.69	(R)	2.15	(R)	2.65	(1)	

SEASONAL CHANGES: The summer season is April-October, the winter off-peak season is November, February and March, and the winter on-peak season is December and January. Baseline quantities for bills that include the April 1, November 1 and December 1 seasonal changeover dates will be calculated by multiplying the applicable daily baseline quantity for each season by the number of days in each season for the billing period.



Revised Cancelling Revised Cal. P.U.C. Sheet No. 49113-E Cal. P.U.C. Sheet No. 48199-E

ELECTRIC SCHEDULE E-TOU-C Sheet 2 RESIDENTIAL TIME-OF-USE (PEAK PRICING 4 - 9 p.m. EVERY DAY)

RATES: (Cont'd.)

E-TOU-C TOTAL RATES

Total Energy Rates (\$ per kWh)	PEAK		OFF-PEAK	
Summer Total Usage Baseline Credit (Applied to Baseline Usage Only)	\$0.41813 (\$0.07584)	(I) (R)	\$0.35469 (\$0.07584)	(l) (R)
Winter Total Usage Baseline Credit (Applied to Baseline Usage Only)	\$0.32104 (\$0.07584)	(I) (R)	\$0.30372 (\$0.07584)	(l) (R)
Delivery Minimum Bill Amount (\$ per meter per day)	\$0.32854			
California Climate Credit (per household, per semi- annual payment occurring in the April and October bill cycles)	(\$17.20)			

Total bundled service charges shown on customer's bills are unbundled according to the component rates shown below. Where the delivery minimum bill amount applies, the customer's bill will equal the rates shown below. Where the derivery minimum bill amount applies, the customer's bill will equal the sum of (1) the delivery minimum bill amount plus (2) for bundled service, the generation rate times the number of kWh used. For revenue accounting purposes, the revenues from the delivery minimum bill amount will be assigned to the Transmission, Transmission Rate Adjustments, Reliability Services, Public Purpose Programs, Nuclear Decommissioning, Competition Transition Charges, Energy Cost Recovery Amount, Wildfire Fund Charge, and New System Generation Charges based on kWh usage times the corresponding unbundled rate component per kWh, with any residual revenue assigned to Distribution.

				(Continued)
Advice	6090-E-A	Issued by	Submitted	February 26, 2021
Decision		Robert S. Kenney	Effective	March 1, 2021
		Vice President, Regulatory Affairs	Resolution	



	Revised
Cancelling	Revised

Cal. P.U.C. Sheet No. 46190-E Cal. P.U.C. Sheet No.

43414-E

ELECTRIC SCHEDULE E-TOU-C

(T)

Sheet 4 RESIDENTIAL TIME-OF-USE (PEAK PRICING 4 - 9 p.m. EVERY DAY)

BASELINE (TIER 1) QUANTITIES: The following quantities of electricity are to be used to define usage eligible for the baseline credit (also see Rule 19 for additional allowances for medical needs): SPECIAL 1. CONDITIONS:

	Code B - Bas	ic Quantities	Code H - All-Electri Quantities		
Baseline	Summer Winter		Summer	Winter	
Territory*	Tier	Tier	Tier	Tier	
Р	14.2	12.0	16.0	27.4	
Q	10.3	12.0	8.9	27.4	
R S T	18.6	11.3	20.9	28.1	
S	15.8	11.1	18.7	24.9	
	6.8	8.2	7.5	13.6	
v	7.5	8.8	10.9	16.9	
w	20.2	10.7	23.6	20.0	
x	10.3	10.5	8.9	15.4	
Y	11.0	12.1	12.6	25.3	
Z	6.2	8.1	7.0	16.5	

TIME PERIODS FOR E-TOU-C: Times of the year and times of the day are 2. (T) defined as follows:

Summer (service from June 1 through September 30):

Peak:	4:00 p.m. to 9:00 p.m.	All days
Off-Peak:	All other times	
Winter (service fro	m October 1 through May 31)	c
Peak:	4:00 p.m. to 9:00 p.m.	All days
Off-Peak:	All other times	

. The applicable baseline territory is described in Part A of the Preliminary Statement

Advice 5759-E Submitted February 14, 2020 Issued by March 1, 2020 Decision D.19-07-004 Robert S. Kenney Effective Vice President, Regulatory Affairs Resolution

(Continued)

<u>SCE</u>

The following pages provide details on are the SCE electricity tariffs applied in this study. Table 23 describes the baseline territories that were assumed for each climate zone.

	Baseline	
	<u>Territory</u>	
CZ06	6	
CZ08	8	
CZ09	9	
CZ10	10	
CZ14	14	
CZ15	15	

Table 23: SCE Baseline Territory by Climate Zone

Summer Daily Allocations (June through September)

Baseline Region Number	Daily kWh Allocation	All- Electric Allocation
5	17.2	17.9
6	11.4	8.8
8	12.6	9.8
9	16.5	12.4
10	18.9	15.8
13	22.0	24.6
14	18.7	18.3
15	46.4	24.1
16	14.4	13.5

Baseline Region Number	Daily kWh Allocation	All- Electric Allocation
5	18.7	29.1
6	11.3	13.0
8	10.6	12.7
9	12.3	14.3
10	12.5	17.0
13	12.6	24.3
14	12.0	21.3
15	9.9	18.2
16	12.6	23.1

(T)

Winter Daily Allocations (October through May)

Schedule TOU-D	Sheet 12	(T)
TIME-OF-USE		
DOMESTIC		
(Continued)		

SPECIAL CONDITIONS

1. Applicable rate time periods are defined as follows:

Option 4-9 PM, Option 4-9 PM-CPP, Option PRIME, Option PRIME-CPP :

TOU Period	Weekdays		Weekends and Holidays		
TOU Period	Summer	Winter	Summer	Winter	
On-Peak	4 p.m 9 p.m.	N/A	N/A	N/A	
Mid-Peak	N/A	4 p.m 9 p.m.	4 p.m 9 p.m.	4 p.m 9 p.m.	
Off-Peak	All other hours	9 p.m 8 a.m.	All other hours	9 p.m 8 a.m.	
Super-Off-Peak	N/A	8 a.m 4 p.m.	N/A	8 a.m 4 p.m.	
CPP Event Period	4 p.m 9 p.m.	4 p.m 9 p.m.	N/A	N/A	



Southern California Edison Rosemead, California (U 338-E) Revised Cal. PUC Sheet No. 70277-E Cancelling Revised Cal. PUC Sheet No. 69597-E

Sheet 2

DOMESTIC (Continued)

RATES

Customers receiving service under this Schedule will be charged the applicable rates under Option 4-9 PM, Option 4-9 PM-CPP, Option 5-8 PM, Option 5-8 PM-CPP, Option PRIME, Option PRIME-CPP Option A, Option A-CPP, Option B, or Option B-CPP, as listed below. CPP Event Charges will apply to all energy usage during CPP Event Energy Charge periods and CPP Non-Event Energy Credits will apply as a reduction on CPP Non-Event Energy Credit Periods during Summer Season weekdays, 4:00 p.m. to 9:00 p.m., as described in Special Conditions 1 and 3, below:

Schedule TOU-D

TIME-OF-USE

	Construction of the second	0.0000	
	Delivery Service	Gener	
Option 4-9 PM / Option 4-9 PM-CPP	Total	UG***	DWREC ³
Energy Charge - \$/kWh	1 march march	Then as the second	
Summer Season - On-Peak		0.18143 (R)	
Mid-Peak		and the second second	0.00000 (I)
Off-Peak	0.19495 (I)	0.07403 (R)	0.00000 (I)
Winter Season - Mid-Peak	0.24845 (I)	0.12593 (R)	0.00000 (I)
Off-Peak	0.19495 (I)	0.08893 (R)	0.00000 (1)
Super-Off-Peak	0.18859 (I)	0.06926 (R)	0.00000 (I)
Baseline Credit**** - \$/kWh	(0.07228) (R)	0.00000	
Basic Charge - \$/day	Same State		
Single-Family Residence	0.031		
Multi-Family Residence	0.024		
Minimum Charge** - \$/day			
Single Family Residence	0.346		
Multi-Family Residence			
Minimum Charge (Medical Baseline)** - \$/day	6 1		
Single Family Residence	0.173		
Multi-Family Residence			
water anny residence			
California Climate Credit*	(29.00) (R)		
California Alternate Rates for			
Energy Discount - %	100.00*		
Family Electric Rate Assistance Discount - % Option 4.9 PM-CPP	100.00		
CPP Event Energy Charge - \$/kWh		0.80000	
Summer CPP Non-Event Credit			
On-Peak Energy Credit - S/kWh		(0.15170)	
Maximum Available Credit - 5/kWh*****			
Summer Season	6	(0.58115) (I)	
	and the second second second	Sec. 23	
Represents 100% of the discount percentage as shown in the applicable Speci The Minimum Charge is applicable when the Delivery Service Energy Charge, "The ongoing Competition Transition Charge CTC of (\$0.00002) per kWh is reco "The Baseline Credit applies up to 100% of the Baseline Allocation, regardless of Statement, Part H.	plus the applicable Ba overed in the UG com of Time of Use. The B	sic Charge is less ponent of General laseline Allocation	Bon. Is set forth in Preliminary
"The Maximum Available Credit is the capped credit amount for CPP Customer Total – Total Delivery Service rates are applicable to Bundled Bervice, Direct A Customers, except DA and CCA Service Customers are not subject to the DWI provided by Schedule DA-CRS or Schedule CCA-CRS. Generation – The Gen rates are applicable only to Bundled Service Customers	ccess (DA) and Comr RBC rate component (nunity Choice Ago	regation Service (OCA Service)
DWREC - Department of Water Resources (DWR) Energy Gredit - For more in		R Energy Gredit, s	ee the Billing Calculation Special
Condition of this Schedule. Applied on an equal basis, per household, semi-annually. See the Special Con	ditions of this Schedu	le for more inform	ation.
(Continue	d)		
To be inserted by utility) Issued b		(To be incode	ted by Cal. PUC)
IS DE INSELLEU DY ULIILYT		TTO DE ITSEL	

(To be inserted by utility)	Issued by	(To be inserted b	y Cal. PUC)
Advice 4377-E-A	Carla Peterman	Date Submitted	Jan 11, 2021
Decision	Senior Vice President	Effective	Feb 1, 2021
2011		Resolution	. (in (in)

<u>SoCalGas</u>

Following are the SoCalGas natural gas tariffs applied in this study. Table 24 describes the baseline territories that were assumed for each climate zone.

	<u>Baseline</u> <u>Territory</u>
CZ05	2
CZ06	1
CZ08	1
CZ09	1
CZ10	1
CZ14	2
CZ15	1

Table 24: SoCalGas Baseline Territory by Climate Zone

The SoCalGas monthly gas rate in \$/therm was applied on a monthly basis for the 12-month period ending March 2021 according to the rates shown in Table 25. Historical natural gas rate data was only available for SoCalGas' procurement charges.⁵ To estimate total costs by month, the baseline and excess transmission charges were assumed to be relatively consistence and applied for the entire year based on January 2021 costs.

Month	Procurement	Transportat	ion Charge	<u>Total Cl</u>	narge
wonth	<u>Charge</u>	Baseline	Excess	Baseline	Excess
Jan 2021	\$0.39764	\$0.82358	\$1.21382	\$1.22122	\$1.61146
Feb 2021	\$0.36766	\$0.82358	\$1.21382	\$1.19124	\$1.58148
Mar 2021	\$0.36982	\$0.82358	\$1.21382	\$1.19340	\$1.58364
Apr 2020	\$0.20307	\$0.82358	\$1.21382	\$1.02665	\$1.41689
May 2020	\$0.25654	\$0.82358	\$1.21382	\$1.08012	\$1.47036
June 2020	\$0.2758	\$0.82358	\$1.21382	\$1.09938	\$1.48962
July 2020	\$0.26816	\$0.82358	\$1.21382	\$1.09174	\$1.48198
Aug 2020	\$0.26239	\$0.82358	\$1.21382	\$1.08597	\$1.47621
Sept 2020	\$0.25498	\$0.82358	\$1.21382	\$1.07856	\$1.4688
Oct 2020	\$0.25268	\$0.82358	\$1.21382	\$1.07626	\$1.4665
Nov 2020	\$0.3432	\$0.82358	\$1.21382	\$1.16678	\$1.55702
Dec 2020	\$0.36159	\$0.82358	\$1.21382	\$1.18517	\$1.57541

Table 25: SoCalGas Monthly Gas Rate (\$/therm)

⁵ The SoCalGas procurement and transmission charges were obtained from the following site: <u>https://www.socalgas.com/for-your-business/energy-market-services/gas-prices</u>

SOUTHERN CALIFORNIA GAS COMPANY Rev LOS ANGELES, CALIFORNIA CANCELING Rev		C. SHEET NO. C. SHEET NO.	57456-G 57430-G
	e No. GR <u>AL SERVICE</u> C and GT-R Rate	<u>s)</u>	Sheet 1
APPLICABILITY			
The GR rate is applicable to natural gas procuremen	nt service to indiv	idually meter	ed residential customers.
The GR-C, cross-over rate, is a core procurement of transportation customers with annual consumption of			
The GT-R rate is applicable to Core Aggregation Tr residential customers, as set forth in Special Condition		T) service to	individually metered
The California Alternate Rates for Energy (CARE) the bill, is applicable to income-qualified household as set forth in Schedule No. G-CARE.			
TERRITORY			
Applicable throughout the service territory.			
<u>RATES</u> <u>Customer Charge</u> , per meter per day:	<u>GR</u> 16.438¢	<u>GR-C</u> 16.438¢	<u>GT-R</u> 16.438¢
For "Space Heating Only" customers, a daily Customer Charge applies during the winter period from November 1 through April 30 ^{1/} :	33.149¢	33.149¢	33.149¢

SDG&E

Following are the SDG&E electricity and natural gas tariffs applied in this study. Table 26 describes the baseline territories that were assumed for each climate zone.

Table 26: SDG&E Baseline Territory by Climate Zone

	Baseline
	Territory
CZ07	Coastal
CZ10	Inland
CZ14	Mountain

The SDG&E monthly gas rate in \$/therm was applied on a monthly basis for the 12-month period ending March 2021 according to the rates shown in Table 27. Historical natural gas rate data from SDG&E was reviewed to identify the procurement and transmission charges⁶ used to calculate the monthly total gas rate.

Table 27: SDG&E Monthly Gas Rate (\$/therm)

Month Procurement		Transportation Charge		Total Charge	
<u>Charge</u>	Baseline	Excess	Baseline	Excess	
\$0.39803	\$1.44464	\$1.70732	\$1.84267	\$2.10535	
\$0.28035	\$1.36166	\$1.59166	\$1.64201	\$1.87201	
\$0.22130	\$1.36166	\$1.59166	\$1.58296	\$1.81296	
\$0.20327	\$1.35946	\$1.59125	\$1.56273	\$1.79452	
\$0.25676	\$1.39202	\$1.62888	\$1.64878	\$1.88564	
\$0.27605	\$1.39202	\$1.62888	\$1.66807	\$1.90493	
\$0.2684	\$1.39202	\$1.62888	\$1.66042	\$1.89728	
\$0.26263	\$1.39202	\$1.62888	\$1.65465	\$1.89151	
\$0.25521	\$1.39202	\$1.62888	\$1.64723	\$1.88409	
\$0.2529	\$1.42577	\$1.67181	\$1.67867	\$1.92471	
\$0.34351	\$1.42577	\$1.67181	\$1.76928	\$2.01532	
\$0.36192	\$1.42577	\$1.67181	\$1.78769	\$2.03373	
	Charge \$0.39803 \$0.28035 \$0.22130 \$0.20327 \$0.25676 \$0.27605 \$0.2684 \$0.26263 \$0.25521 \$0.2529 \$0.34351	ChargeBaseline\$0.39803\$1.44464\$0.28035\$1.36166\$0.22130\$1.36166\$0.20327\$1.35946\$0.20327\$1.35946\$0.25676\$1.39202\$0.27605\$1.39202\$0.2684\$1.39202\$0.26263\$1.39202\$0.25521\$1.39202\$0.2529\$1.42577\$0.34351\$1.42577	ChargeBaselineExcess\$0.39803\$1.44464\$1.70732\$0.28035\$1.36166\$1.59166\$0.22130\$1.36166\$1.59166\$0.20327\$1.35946\$1.59125\$0.25676\$1.39202\$1.62888\$0.27605\$1.39202\$1.62888\$0.2684\$1.39202\$1.62888\$0.26263\$1.39202\$1.62888\$0.25521\$1.39202\$1.62888\$0.2529\$1.42577\$1.67181\$0.34351\$1.42577\$1.67181	ChargeBaselineExcessBaseline\$0.39803\$1.44464\$1.70732\$1.84267\$0.28035\$1.36166\$1.59166\$1.64201\$0.22130\$1.36166\$1.59166\$1.58296\$0.20327\$1.35946\$1.59125\$1.56273\$0.25676\$1.39202\$1.62888\$1.64878\$0.25676\$1.39202\$1.62888\$1.66807\$0.2684\$1.39202\$1.62888\$1.66042\$0.26263\$1.39202\$1.62888\$1.65465\$0.25521\$1.39202\$1.62888\$1.64723\$0.25521\$1.39202\$1.62888\$1.64723\$0.2529\$1.42577\$1.67181\$1.67867\$0.34351\$1.42577\$1.67181\$1.76928	

⁶ The SDG&E procurement and transmission charges were obtained from the following sets of documents: <u>http://regarchive.sdge.com/tm2/pdf/GAS_GAS-SCHEDS_GM_2020.pdf</u> <u>http://regarchive.sdge.com/tm2/pdf/GAS_GAS-SCHEDS_GM_2019.pdf</u>

RATES	GR	<u>GR-C</u>	GTC/GTCA1/
Minimum Bill, per day: ^{3/} Non-CARE customers: CARE customers:	 \$0.13151 \$0.10521	\$0.13151 \$0.10521	\$0.13151 \$0.10521

Baseline Usage: The following quantities of gas used in individually metered residences are to be billed at the baseline rates:

All Customers:	Allowance
Summer (May 1 to October 31, inclusive)	0.493
Winter (November 1 to April 30, inclusive)	1.546

SDOF	R	evised Cal. I	P.U.C. Sheet N	o.		33	144-E					
San Diego Gas & Electric Company San Diego, California	Canceling R	evised Cal. I	P.U.C. Sheet N	,		32	930-F					
							eet 2					
SCHEDULE TOU-DR1 Sheet 2 RESIDENTIAL TIME-OF-USE												
	REDIDENTI	AL TIME-OF-	JOE									
RATES												
Total Rates:												
Description – TOU DR1	UDC Total Rate	DWR-BC	EECC Rate +		Total							
	ODC Total Rate	Rate	DWR Credit		Rate	_						
Summer: On-Peak	0.22374	1 0.00580	0.29042	R	0.51996	R						
Off-Peak	0.22374	I 0.00580	0.29042	R	0.51996	R						
Super Off-Peak	0.22374	I 0.00580	0.04743	R	0.27697	R						
Winter:												
On-Peak Off-Peak	0.25734	R 0.00580 R 0.00580	0.07844	R	0.34158	R						
Super Off-Peak	0.25734	R 0.00580	0.06961 0.05981	R	0.32295	R						
Summer Baseline Adjustment Credit up to 130% of Baseline	(0.07506)	1			(0.07506)	I						
Winter Baseline Adjustment Credit up to 130% of Baseline	(0.06833)	1			(0.06833)	I						
Minimum Bill (\$/day)	0.338				0.338							
Note: (1) Total Rates consist of UDC, Sched EECC (Electric Energy Commodity C (2) Total Rates presented are for custon (3) DWR-BC charges do not apply to C (4) As identified in the rates tables, cust 130% of baseline to provide the rate	cost) rates, with the ers that receive of ARE customers. comer bills will als	e EECC rates re ommodity suppl o include line-it	eflecting a DWR ly and delivery s em summer an	Credi service d winte	t. from Utility. er credits for u	isage up						
2C8		(Continued) Issued by		Subm	itte d	Mar	28.20					
Advice Ltr. No. 3514-E	D		Effect			26, 20 or 1, 20						
NUTICE LU. 140. 3014-E		an Skopec		Enect		~	л <u>т, 2</u> 0					
	v	ce riesident										

Time Periods

All time periods listed are applicable to local time. The definition of time will be based upon the date service is rendered.

TOU Periods – Weekdays	Summer	Winter
On-Peak	4:00 p.m. – 9:00 p.m.	4:00 p.m. – 9:00 p.m.
Off-Peak	6:00 a.m. – 4:00 p.m.;	6:00 a.m. – 4:00 p.m.
	9:00 p.m midnight	Excluding 10:00 a.m. – 2:00 p.m. in March and April;
		9:00 p.m midnight
Super Off-Peak	Midnight – 6:00 a.m.	Midnight – 6:00 a.m.
-		10:00 a.m. – 2:00 p.m. in March and April
TOU Period – Weekends and Holidays	Summer	Winter
On-Peak	4:00 p.m. – 9:00 p.m.	4:00 p.m. – 9:00 p.m.
Off-Peak	2:00 p.m. – 4:00 p.m.;	2:00 p.m. – 4:00 p.m.;
	9:00 p.m midnight	9:00 p.m midnight
Super Off-Peak	Midnight – 2:00 p.m.	Midnight – 2:00 p.m.

Seasons:	Summer	June 1 – October 31
	Winter	November 1 – May 31

15. <u>Baseline Usage</u>: The following quantities of electricity are used to calculate the baseline adjustment credit.

	Baseline Allowance For Climatic Zones*						
	Coastal	Inland	Mountain	Desert			
Basic Allowance							
Summer (June 1 to October 31)	9.0	10.4	13.6	15.9			
Winter (November 1 to May 31)	9.2	9.6	12.9	10.9			
All Electric**							
Summer (June 1 to October 31)	6.0	8.7	15,2	17.0			
Winter (November 1 to May 31)	8.8	12.2	22.1	17.1			

Climatic Zones are shown on the Territory Served, Map No. 1.

** All Electric allowances are available upon application to those customers who have permanently installed space heating or who have electric water heating and receive no energy from another source.

<u>SMUD</u>

Following are the SMUD electricity tariffs applied in this study.

П.	Firm Service Rates	
	A. Time-of-Day (5-8 p.m.) Rate	Rate Category RT02
	Effective January 1, 2021	
	Non-Summer Prices*	
	System Infrastructure Fixed Charge per month	\$22.25
	Electricity Usage Charge	
	Peak \$/kWh	\$0.1465
	Off-Peak \$/kWh	\$0.1061
	Summer Prices	
	System Infrastructure Fixed Charge per month	\$22.25
	Electricity Usage Charge	
	Peak \$/kWh	\$0.3105
	Mid-Peak \$/kWh	\$0.1765
	Off-Peak \$/kWh	\$0.1277
	Effective October 1, 2021 Non-Summer Prices*	
	System Infrastructure Fixed Charge per month	\$22.70
	Electricity Usage Charge	
	Peak \$/kWh	\$0.1494
	Off-Peak \$/kWh	\$0.1082
	Summer Prices	
	System Infrastructure Fixed Charge per month	\$22.70
	Electricity Usage Charge	
	Peak \$/kWh	\$0.3167
	Mid-Peak \$/kWh	\$0.1800
	Off-Peak \$/kWh	\$0.1303

* Non-Summer Season includes Fall (Oct 1 - Nov 30), Winter (Dec 1 - Mar 31) and Spring (Apr 1 - May 31) periods.

	Peak	Weekdays between 5:00 p.m. and 8:00 p.m.					
Summer (Jun 1 - Sept 30)	Mid-Peak	Weekdays between noon and midnight except during the Peak hours.					
(,	Off-Peak	All other hours, including weekends and holidays ¹ .					
Non-Summer	Peak	Weekdays between 5:00 p.m. and 8:00 p.m.					
(Oct 1 - May 31)	Off-Peak	All other hours, including weekends and holidays ¹ .					

<u>CPAU</u>

Following are the CPAU electricity and natural gas tariffs applied in this study.

The CPAU monthly gas rate in \$/therm was applied on a monthly basis for the 12-month period ending February 2021 according to the rates shown in Table 28. The distribution charge was \$0.4835/therm for Tier 1 and \$1.0426/therm for Tier 2. The monthly service charge applied was \$10.94 per month per the G-1 tariff in effect at the time of the analysis.

Effective	Effective Commodity Cap and Trade Transportation Carbon G1 Tier 1 G1 Tier 2												
Date	<u>Rate</u>	<u>Compliance</u>	<u>Charge</u>	<u>Offset</u>	Volumetric	<u>Volumetric</u>							
		<u>Charge</u>		<u>Charge</u>	<u>Totals</u>	<u>Totals</u>							
Jan 2021	\$0.3436	\$0.0486	\$0.11104	\$0.040	\$1.04704	\$1.83144							
Feb 2021	\$0.3309	\$0.0486	\$0.11104	\$0.040	\$1.03434	\$1.81874							
Mar 2020	\$0.2416	\$0.033	\$0.09891	\$0.040	\$0.89701	\$1.45611							
Apr 2020	\$0.2066	\$0.033	\$0.09891	\$0.040	\$0.86201	\$1.42111							
May 2020	\$0.2258	\$0.033	\$0.09891	\$0.040	\$0.88121	\$1.44031							
June 2020	\$0.2279	\$0.033	\$0.09891	\$0.040	\$0.88331	\$1.44241							
July 2020	\$0.2186	\$0.033	\$0.09862	\$0.040	\$0.89402	\$1.67842							
Aug 2020	\$0.2257	\$0.033	\$0.09862	\$0.040	\$0.90112	\$1.68552							
Sept 2020	\$0.3203	\$0.033	\$0.09862	\$0.040	\$0.99572	\$1.78012							
Oct 2020	\$0.3724	\$0.033	\$0.09862	\$0.040	\$1.04782	\$1.83222							
Nov 2020	\$0.3749	\$0.033	\$0.09862	\$0.040	\$1.05032	\$1.83472							
Dec 2020	\$0.3446	\$0.033	\$0.09862	\$0.040	\$1.02002	\$1.80442							

Table 28: CPAU Monthly Gas Rate (\$/therm)

RESIDENTIAL ELECTRIC SERVICE

UTILITY RATE SCHEDULE E-1

A. APPLICABILITY:

This Rate Schedule applies to separately metered single-family residential dwellings receiving Electric Service from the City of Palo Alto Utilities.

B. TERRITORY:

This rate schedule applies everywhere the City of Palo Alto provides Electric Service.

C. UNBUNDLED RATES:

Per kilowatt-hour (kWh)	Commodity	Distribution	Public Benefits	<u>Total</u>
Tier 1 usage	\$0.08339	\$0.04971	\$0.00447	\$0.13757
Tier 2 usage Any usage over Tier 1	0.11569	0.07351	0.00447	0.19367
Minimum Bill (\$/day)				0.3283

Escalation Assumptions

The average annual escalation rates in the following table were used in this study and are from E3's 2019 study Residential Building Electrification in California (Energy & Environmental Economics, 2019). These rates are applied to the 2019 rate schedules over a 30-year period beginning in 2020. SDG&E was not covered in the E3 study. The Statewide Reach Code Team reviewed SDG&E's GRC filing and applied the same approach that E3 applied for PG&E and SoCalGas to arrive at average escalation rates between 2020 and 2022.

	Statewide Electric Residential Average	Natu	ıral Gas Residential Core (%/year escalation, real)	Rate
	Rate (%/year, real)	PG&E	<u>SoCalGas</u>	SDG&E
2020	2.0%	1.48%	6.37%	5.00%
2021	2.0%	5.69%	4.12%	3.14%
2022	2.0%	1.11%	4.12%	2.94%
2023	2.0%	4.0%	4.0%	4.0%
2024	2.0%	4.0%	4.0%	4.0%
2025	2.0%	4.0%	4.0%	4.0%
2026	1.0%	1.0%	1.0%	1.0%
2027	1.0%	1.0%	1.0%	1.0%
2028	1.0%	1.0%	1.0%	1.0%
2029	1.0%	1.0%	1.0%	1.0%
2030	1.0%	1.0%	1.0%	1.0%
2031	1.0%	1.0%	1.0%	1.0%
2032	1.0%	1.0%	1.0%	1.0%
2033	1.0%	1.0%	1.0%	1.0%
2034	1.0%	1.0%	1.0%	1.0%
2035	1.0%	1.0%	1.0%	1.0%
2036	1.0%	1.0%	1.0%	1.0%
2037	1.0%	1.0%	1.0%	1.0%
2038	1.0%	1.0%	1.0%	1.0%
2039	1.0%	1.0%	1.0%	1.0%
2040	1.0%	1.0%	1.0%	1.0%
2041	1.0%	1.0%	1.0%	1.0%
2042	1.0%	1.0%	1.0%	1.0%
2043	1.0%	1.0%	1.0%	1.0%
2044	1.0%	1.0%	1.0%	1.0%
2045	1.0%	1.0%	1.0%	1.0%
2046	1.0%	1.0%	1.0%	1.0%
2047	1.0%	1.0%	1.0%	1.0%
2048	1.0%	1.0%	1.0%	1.0%
2049	1.0%	1.0%	1.0%	1.0%

Table 29: Real Utility Rate Escalation Rate Assumptions

8.3 Appendix C – Standards Sections

2019 Building Energy Efficiency Standards Section 150.2(b)11

Roofs. Replacements of the exterior surface of existing roofs, including adding a new surface layer on top of the existing exterior surface, shall meet the requirements of Section 110.8 and the applicable requirements of Subsections i and ii where more than 50 percent of the roof is being replaced.

i. Low-rise residential buildings with steep-sloped roofs, in Climate Zones 10 through 15 shall have a minimum aged solar reflectance of 0.20 and a minimum thermal emittance of 0.75, or a minimum SRI of 16.

EXCEPTION TO 150.2(b)1li: The following shall be considered equivalent to Subsection i:

- a. Air-space of 1.0 inch (25 mm) is provided between the top of the roof deck to the bottom of the roofing product; or
- b. The installed roofing product has a profile ratio of rise to width of 1 to 5 for 50 percent or greater of the width of the roofing product; or
- c. Existing ducts in the attic are insulated and sealed according to Section 150.1(c)9; or
- d. Buildings with at least R-38 ceiling insulation; or
- e. Buildings with a radiant barrier in the attic meeting the requirements of Section 150.1(c)2; or
- f. Buildings that have no ducts in the attic; or
- g. In Climate Zones 10-15, R-2or greater insulation above the roof deck.
- ii. Low-sloped roofs in Climate Zones 13 and 15 shall have a 3-year aged solar reflectance equal or greater than 0.63 and a thermal emittance equal or greater than 0.75, or a minimum SRI of 75.

EXCEPTION 1 to Section 150.2(b)1lii: Buildings with no ducts in the attic.

EXCEPTION 2 to Section 150.2(b)1lii: The aged solar reflectance can be met by using insulation at the roof deck specified in TABLE 150.2-B.

2019 Building Energy Efficiency Standards Section 150.2(b)1E

Altered Space-Conditioning System - Duct Sealing: In all climate zones, when a space-conditioning system serving a single family or multifamily dwelling is altered by the installation or replacement of space-conditioning system equipment, including replacement of the air handler, outdoor condensing unit of a split system air conditioner or heat pump, or cooling or heating coil; the duct system that is connected to the altered space-conditioning system equipment shall be sealed, as confirmed through field verification and diagnostic testing in accordance with the applicable procedures for duct sealing of altered existing duct systems as specified in Reference Residential Appendix RA3.1 and the leakage compliance criteria specified in subsection i, ii, or iii below. Additionally, when altered ducts, air-handling units, cooling or heating coils, or plenums are located in garage spaces, the system shall comply with Section 150.2(b)1Diic regardless of the length of any new or replacement space-conditioning ducts installed in the garage space.

- i. The measured duct leakage shall be equal to or less than 15 percent of system air handler airflow as determined utilizing the procedures in Reference Residential Appendix Section RA3.1.4.3.1; or
- ii. The measured duct leakage to outside shall be equal to or less than 10 percent of system air handler airflow as determined utilizing the procedures in Reference Residential Appendix Section RA3.1.4.3.4; or
- iii. If it is not possible to meet the duct sealing requirements of either Section 150.2(b)1Ei or Section 150.2(b)1Eii, then, all accessible leaks shall be sealed and verified through a visual inspection and a smoke test by a certified HERS Rater utilizing the methods specified in Reference Residential Appendix RA3.1.4.3.5.

EXCEPTION 1 to Section 150.2(b)1E: Duct Sealing. Duct systems that are documented to have been previously sealed as confirmed through field verification and diagnostic testing in accordance with procedures in the Reference Residential Appendix RA3.1.

EXCEPTION 2 to Section 150.2(b)1E: Duct Sealing. Duct systems with less than 40 linear feet as determined by visual inspection.

EXCEPTION 3 to Section 150.2(b)1E: Duct Sealing. Existing duct systems constructed, insulated or sealed with asbestos.

8.4 Appendix D – Measure Cost-Effectiveness Tables

Detailed cost-effectiveness analysis results are summarized by vintage and climate zone in Table 30 through Table 113. Site energy savings, cost savings, measure cost, and cost effectiveness including lifecycle B/C ratio and NPV of savings are provided. For climate zones that are served by multiple utilities, where cost effectiveness may differ based on applicable utility rates, cost-effectiveness results are reported for both applicable utility territories.

Shaded cells in the tables and values in red indicate that the measure is not cost-effective with B/C ratios less than one. Cells with "n/a" reflect lighting and water heating efficiency measures and packages that did not look at TDV cost effectiveness.

<u>Climate Zone 1:</u>

Manager	Vintage	Measure	Electricity	Gas	GHG Savings		v Cost ings	Custom	er On-Bill	2019	TDV	202	2 TDV
Measure	vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(Ib CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$3,332	103	57	593	\$149	\$124	1.00	-\$14	0.91	-\$312	1.19	\$620
R-49 Attic Insulation	1978-1991	\$2,874	78	29	301	\$82	\$68	0.64	-\$1,173	0.57	-\$1,245	0.74	-\$751
	1992-2010	\$1,852	11	13	131	\$30	\$25	0.36	-\$1,330	0.32	-\$1,259	0.44	-\$1,037
_	Pre-1978		29	34	345	\$77	\$65	1.17	\$283	0.93	-\$100	1.42	\$614
Reduced Infiltration	1978-1991	\$1,474	17	20	209	\$47	\$39	0.71	-\$481	0.57	-\$636	0.86	-\$209
	1992-2010		11	13	131	\$29	\$24	0.44	-\$920	0.37	-\$927	0.54	-\$676
	Pre-1978	\$683	77	90	920	\$206	\$173	6.78	\$4,432	6.02	\$3,430	8.29	\$4,977
Duct Sealing	1978-1991	\$683	47	55	562	\$126	\$106	4.14	\$2,410	3.68	\$1,832	5.07	\$2,779
	1992-2010	\$423	9	10	105	\$24	\$20	1.25	\$121	1.13	\$55	1.54	\$228
	Pre-1978		127	147	1,510	\$339	\$285	1.91	\$4,060	1.71	\$2,812	2.33	\$5,309
New Ducts	1978-1991	\$3,986	92	107	1,099	\$247	\$207	1.39	\$1,740	1.25	\$1,009	1.70	\$2,789
	1992-2010		28	32	328	\$74	\$62	0.42	-\$2,613	0.38	-\$2,454	0.51	-\$1,947
	Pre-1978		-14	-18	-186	-\$41	-\$34	0	-\$1,874	0	-\$1,446	0	-\$1,861
Cool Roof	1978-1991	\$778	-10	-14	-139	-\$30	-\$25	0	-\$1,611	0	-\$1,273	0	-\$1,584
	1992-2010		-6	-9	-91	-\$20	-\$17	0	-\$1,345	0	-\$1,121	0	-\$1,305
R-13 Wall Insulation	Pre-1978	\$3,360	86	99	1,019	\$228	\$192	1.52	\$1,973	1.29	\$961	1.84	\$2,836
Mindowo	Pre-1978	\$9,810	68	77	804	\$180	\$151	0.41	-\$6,481	0.38	-\$6,117	0.51	-\$4,804
Windows	1978-1991	\$9,81U	60	69	712	\$159	\$134	0.36	-\$7,002	0.33	-\$6,587	0.45	-\$5,389
LED lamp vs CFL	All	\$2.26	1.2	0	n/a	\$0.33	\$0.26	3.47	\$5.56	n/a	n/a	n/a	n/a
Exterior Photosensor	All	\$42.58	12.1	0	n/a	\$2.88	\$2.27	1.60	\$25.62	n/a	n/a	n/a	n/a

Table 30: CZ 1 - Single Family Efficiency Upgrade Cost-Effectiveness Results

	Minterre	Measure	Electricity	Gas	GHG Savings	Utility Cost Savings		Customer On-Bill		2019 TDV		2022 TDV	
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO2e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$4,806	133	93	954	\$229	\$192	1.07	\$359	0.93	-\$343	1.28	\$1,335
R49 Attic & Air Sealing Package	1978-1991	\$4,348	96	50	514	\$130	\$109	0.67	-\$1,627	0.58	-\$1,821	0.79	-\$929
e camig racitage	1992-2010	\$3,326	22	26	264	\$59	\$50	0.40	-\$2,242	0.34	-\$2,186	0.49	-\$1,702
	Pre-1978	\$4,015	180	147	1,515	\$356	\$298	1.98	\$4,428	1.75	\$3,006	2.40	\$5,603
R49 Attic & Duct Sealing Package	1978-1991	\$3,557	124	83	849	\$205	\$172	1.29	\$1,159	1.15	\$523	1.55	\$1,942
eeunig Fachage	1992-2010	\$2,275	20	23	233	\$53	\$44	0.52	-\$1,229	0.47	-\$1,215	0.64	-\$829
R49 Attic. Air	Pre-1978	\$5,489	206	178	1,831	\$426	\$357	1.74	\$4,553	1.51	\$2,822	2.10	\$6,050
Sealing & Duct	1978-1991	\$5,031	140	102	1,048	\$250	\$209	1.11	\$627	0.97	-\$145	1.33	\$1,681
Sealing Package	1992-2010	\$3,749	30	35	362	\$81	\$68	0.49	-\$2,161	0.43	-\$2,154	0.60	-\$1,517
R49 Attic, Air	Pre-1978	\$8,792	255	235	2,412	\$557	\$467	1.42	\$4,129	1.25	\$2,204	1.72	\$6,322
Sealing & New	1978-1991	\$8,334	184	153	1,572	\$368	\$308	0.99	-\$119	0.88	-\$1,022	1.19	\$1,604
Ducts Package	1992-2010	\$7,312	48	56	575	\$129	\$108	0.40	-\$4,956	0.36	-\$4,708	0.49	-\$3,758
Advanced Envelope Package	Pre-1978	\$18,659	337	328	3,373	\$772	\$647	0.93	-\$1,530	0.81	-\$3,544	1.13	\$2,380
Water Heating Package	All Vintages	\$208	0	15	n/a	\$28	\$26	1.64	\$150	n/a	n/a	n/a	n/a

Table 31: CZ 1 - Single Family Efficiency Packages Cost-Effectiveness Results

Measure	Vintano	Measure	Electricity Savings (kWh)	Gas	GHG Savings (Ib CO ₂ e)	Utility Cost Savings		Customer On-Bill		2019 TDV		2022 TDV		
		Cost (\$)		Savings (therm)		Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV	
	Pre-1978	-,		3,394		208	\$895	\$707	2.33	\$12,094	1.66	\$5,443	1.29	\$2,381
Prescriptive PV System	1978-1991		8,236 3,394	0	208	\$874	\$690	2.27	\$11,577	1.66	\$5,431	1.29	\$2,372	
i v eyetetti	1992-2010		3,394		208	\$822	\$649	2.14	\$10,366	1.66	\$5,414	1.29	\$2,358	
	Pre-1978	\$19,609	3,221		787	\$920	\$726	1.03	\$625	1.00	-\$27	0.75	-\$4,965	
, –	1978-1991		3,222	0	786	\$889	\$702	0.99	-\$109	1.00	-\$59	0.74	-\$5,022	
	1992-2010		3,224		767	\$838	\$662	0.94	-\$1,312	0.99	-\$140	0.73	-\$5,232	

Table 32: CZ 1 - Single Family PV & Battery Cost-Effectiveness Results

Table 33: CZ 1 - Single Family Equipment Fuel Substitution Cost-Effectiveness Results

	Minterra	Measure	Electricity	Gas	GHG Savings	Utility Savi	r Cost ings	Custom	er On-Bill	201	9 TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
Heat Pump at	Pre-1978		-7,493	705	4,052	-\$780	-\$538	0	-\$16,682	0	-\$12,787	3.58	\$1,296
HVAC	1978-1991	\$501	-6,202	568	3,193	-\$658	-\$457	0	-\$14,266	0	-\$11,444	1.24	\$121
Replacement	1992-2010		-3,675	322	1,734	-\$379	-\$266	0	-\$8,530	0	-\$7,550	0	-\$738
High-Effic. Heat	Pre-1978		-6,395	705	4,464	-\$438	-\$268	0	-\$12,105	0	-\$10,343	2.00	\$3,731
Pump at HVAC	1978-1991	\$3,749	-5,308	568	3,529	-\$380	-\$238	0	-\$11,210	0	-\$10,043	1.40	\$1,499
Replacement	1992-2010		-3,190	322	1,917	-\$235	-\$152	0	-\$8,624	0	-\$8,277	0.61	-\$1,474
Heat Pump at	Pre-1978		-4,115	705	4,255	\$206	\$240	0.75	-\$2,452	0.18	-\$7,188	1.43	\$3,714
HVAC Replacement +	1978-1991	\$8,738	-2,818	568	3,398	\$304	\$302	0.94	-\$607	0.33	-\$5,875	1.29	\$2,551
PV	1992-2010		-281	322	1,938	\$519	\$443	1.38	\$3,634	0.87	-\$2,029	1.19	\$1,629
HVAC HP	Pre-1978		-4,115	705	4,255	\$206	\$240	0.54	-\$6,024	0.13	-\$10,369	1.04	\$533
Replacement w/ Panel Upgrade	1978-1991	\$11,919	-2,818	568	3,398	\$304	\$302	0.68	-\$4,179	0.24	-\$9,056	0.95	-\$630
+ PV	1992-2010		-281	322	1,938	\$519	\$443	1.00	\$62	0.56	-\$5,210	0.87	-\$1,552
HPWH at Water	Pre-1978		-1,769	175	1,286	-\$229	-\$161	0	-\$7,728	0	-\$5,359	0.69	-\$802
Heater	1978-1991	\$2,594	-1,776	176	1,301	-\$233	-\$164	0	-\$7,813	0	-\$5,356	0.72	-\$736
Replacement	1992-2010		-1,776	177	1,311	-\$251	-\$180	0	-\$8,285	0	-\$5,342	0.74	-\$681
NEEA Tier 3	Pre-1978		-1,221	172	1,417	-\$54	-\$23	0	-\$3,788	0	-\$2,830	1.55	\$1,537
HPWH at	1978-1991	\$2,775	-1,228	174	1,436	-\$56	-\$25	0	-\$3,835	0	-\$2,864	1.57	\$1,586
Replacement	1992-2010		-1,231	175	1,449	-\$75	-\$40	0	-\$4,301	0	-\$2,827	1.59	\$1,647
HPWH at Water	Pre-1978		1,625	175	1,495	\$767	\$625	1.56	\$6,751	1.03	\$277	1.16	\$1,778
Heater Replacement +	1978-1991	\$10,830	1,618	176	1,509	\$758	\$618	1.55	\$6,546	1.03	\$271	1.17	\$1,838
PV	1992-2010		1,618	177	1,519	\$730	\$595	1.49	\$5,855	1.03	\$274	1.17	\$1,881
HPWH	Pre-1978		1,625	175	1,495	\$767	\$625	1.20	\$3,179	0.79	-\$2,904	0.90	-\$1,403
Replacement w/ Panel Upgrade	1978-1991	\$14,011	1,618	176	1,509	\$758	\$618	1.19	\$2,974	0.79	-\$2,910	0.90	-\$1,343
+ PV	1992-2010		1,618	177	1,519	\$730	\$595	1.15	\$2,283	0.79	-\$2,907	0.91	-\$1,300

	Minterra	Measure	Electricity	Gas	GHG Savings	-	/ Cost ings	Custome	er On-Bill	2019) TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO2e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978		3,394	0	208	\$895	\$707	1.55	\$7,500	1.11	\$1,352	0.86	-\$1,710
PV + Electric Ready Pre-Wire	1978-1991	\$12,327	3,394	0	208	\$874	\$690	1.51	\$6,984	1.11	\$1,340	0.86	-\$1,719
	1992-2010		3,394	0	208	\$822	\$649	1.42	\$5,772	1.11	\$1,323	0.86	-\$1,733

<u>Climate Zone 2:</u>

	Martana	Measure	Electricity	Gas	GHG Savings	Utility Sav	r Cost ings	Custom	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO2e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
-	Pre-1978	\$3,332	505	38	484	\$269	\$217	1.74	\$2,758	1.93	\$3,093	2.12	\$3,743
R-49 Attic Insulation	1978-1991	\$2,874	254	19	247	\$131	\$105	0.98	-\$69	1.28	\$803	1.39	\$1,122
	1992-2010	\$1,852	34	7	85	\$26	\$22	0.31	-\$1,433	0.61	-\$720	0.58	-\$772
_	Pre-1978		21	17	173	\$41	\$35	0.63	-\$616	0.62	-\$555	0.91	-\$135
Reduced Infiltration	1978-1991	\$1,474	12	11	110	\$25	\$21	0.38	-\$1,031	0.41	-\$866	0.66	-\$503
	1992-2010		9	7	73	\$16	\$14	0.25	-\$1,246	0.29	-\$1,053	0.36	-\$938
	Pre-1978	\$683	184	42	466	\$157	\$129	5.03	\$3,090	6.17	\$3,528	8.63	\$5,213
Duct Sealing	1978-1991	\$683	85	24	269	\$80	\$66	2.58	\$1,209	3.59	\$1,768	5.14	\$2,825
	1992-2010	\$423	11	7	74	\$17	\$15	0.92	-\$38	1.19	\$81	1.83	\$352
	Pre-1978		345	72	806	\$280	\$230	1.54	\$2,410	1.89	\$3,529	2.71	\$6,801
New Ducts	1978-1991	\$3,986	205	51	575	\$178	\$147	0.98	-\$78	1.34	\$1,366	2.02	\$4,059
	1992-2010		41	22	232	\$56	\$46	0.31	-\$3,084	0.41	-\$2,356	0.64	-\$1,422
	Pre-1978		177	-8	-48	\$54	\$42	1.48	\$407	1.76	\$593	2.01	\$786
Cool Roof	1978-1991	\$778	101	-6	-37	\$28	\$21	0.76	-\$204	1.37	\$291	1.58	\$452
	1992-2010		23	-5	-41	-\$1	-\$1	0	-\$878	0.54	-\$354	0.46	-\$418
R-13 Wall Insulation	Pre-1978	\$3,360	118	56	589	\$156	\$129	1.03	\$109	1.11	\$359	1.47	\$1,563
Mindawa	Pre-1978	¢0.040	563	21	347	\$260	\$208	0.57	-\$4,776	0.76	-\$2,309	0.82	-\$1,733
Windows	1978-1991	\$9,810	359	16	270	\$174	\$139	0.38	-\$6,839	0.66	-\$3,369	0.66	-\$3,335
LED lamp vs CFL	All	\$2.26	1.2	0	n/a	\$0.37	\$0.29	3.84	\$6.40	n/a	n/a	n/a	n/a
Exterior Photosensor	All	\$42.58	12.1	0	n/a	\$2.88	\$2.27	1.60	\$25.62	n/a	n/a	n/a	n/a

Table 34: CZ 2 - Single Family Efficiency Upgrade Cost-Effectiveness Results

	Martana	Measure	Electricity	Gas	GHG Savings		/ Cost ings	Custom	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO2e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$4,806	533	56	675	\$315	\$256	1.42	\$2,270	1.56	\$2,702	1.77	\$3,686
R49 Attic & Air Sealing Package	1978-1991	\$4,348	270	31	362	\$157	\$127	0.78	-\$1,062	1.00	\$15	1.11	\$498
eessing racinge	1992-2010	\$3,326	42	14	157	\$42	\$35	0.28	-\$2,687	0.48	-\$1,739	0.48	-\$1,716
	Pre-1978	\$4,015	626	79	931	\$398	\$323	2.15	\$5,196	2.55	\$6,239	3.07	\$8,291
R49 Attic & Duct Sealing Package	1978-1991	\$3,557	316	43	499	\$199	\$162	1.22	\$859	1.65	\$2,301	1.97	\$3,449
county r conage	1992-2010	\$2,275	44	14	156	\$43	\$35	0.41	-\$1,497	0.70	-\$685	0.78	-\$501
R49 Attic. Air	Pre-1978	\$5,489	647	94	1,092	\$436	\$356	1.73	\$4,501	2.04	\$5,709	2.47	\$8,079
Sealing & Duct	1978-1991	\$5,031	330	53	603	\$223	\$182	0.96	-\$202	1.28	\$1,409	1.55	\$2,767
Sealing Package	1992-2010	\$3,749	52	21	225	\$58	\$48	0.34	-\$2,776	0.54	-\$1,727	0.61	-\$1,448
R49 Attic. Air	Pre-1978	\$8,792	764	123	1,415	\$536	\$438	1.33	\$3,258	1.62	\$5,439	2.08	\$9,454
Sealing & New	1978-1991	\$8,334	422	78	893	\$308	\$252	0.81	-\$1,796	1.09	\$773	1.44	\$3,675
Ducts Package	1992-2010	\$7,312	78	35	377	\$92	\$76	0.28	-\$5,920	0.42	-\$4,276	0.55	-\$3,294
Advanced Envelope Package	Pre-1978	\$18,659	1,000	178	2,048	\$730	\$596	0.85	-\$3,066	1.12	\$2,264	1.29	\$5,503
Water Heating Package	All Vintages	\$208	0	16	n/a	\$31	\$28	1.82	\$192	n/a	n/a	n/a	n/a

Table 35: CZ 2 - Single Family Efficiency Packages Cost-Effectiveness Results

	Nr. (Measure	Electricity	Gas	GHG Savings	-	r Cost ings	Custom	er On-Bill	2019	9 TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978		3,442		216	\$896	\$707	2.68	\$13,295	1.95	\$6,844	1.55	\$3,946
Prescriptive PV System	1978-1991	\$7,167	3,442	0	216	\$863	\$681	2.58	\$12,505	1.95	\$6,829	1.55	\$3,932
i v cycloin	1992-2010		3,442		216	\$801	\$632	2.39	\$11,030	1.95	\$6,824	1.55	\$3,923
	Pre-1978		3,252		818	\$937	\$739	1.11	\$2,207	0.79	-\$3,814	0.83	-\$3,071
PV + Battery	1978-1991	\$18,539	3,265	0	827	\$875	\$690	1.04	\$733	0.81	-\$3,607	0.88	-\$2,279
	1992-2010		3,256		836	\$823	\$649	0.97	-\$500	0.82	-\$3,299	0.96	-\$816

Table 36: CZ 2 - Single Family PV & Battery Cost-Effectiveness Results

Table 37: CZ 2 - Single Family Equipment Fuel Substitution Cost-Effectiveness Results

Maaaura	Mintono	Measure	Electricity	Gas	GHG Savings	Utility Savi	v Cost ings	Custom	er On-Bill	2019	9 TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
Heat Pump at	Pre-1978		-3,567	322	1,601	-\$443	-\$317	0	-\$10,046	0	-\$3,874	3.90	\$1,454
HVAC	1978-1991	\$501	-2,772	246	1,188	-\$357	-\$258	0	-\$8,279	0	-\$3,189	2.42	\$711
Replacement	1992-2010		-2,400	211	1,035	-\$311	-\$225	0	-\$7,287	0	-\$2,757	2.10	\$550
High-Effic. Heat	Pre-1978		-2,885	322	1,889	-\$227	-\$146	0	-\$8,438	0.34	-\$2,473	1.81	\$3,046
Pump at HVAC	1978-1991	\$3,749	-2,263	246	1,410	-\$199	-\$133	0	-\$8,034	0.21	-\$2,960	1.32	\$1,193
Replacement	1992-2010		-2,009	211	1,206	-\$192	-\$131	0	-\$7,981	0.05	-\$3,571	0.99	-\$54
Heat Pump at	Pre-1978		-125	322	1,817	\$497	\$425	1.51	\$4,280	1.40	\$3,036	1.71	\$5,438
HVAC Replacement +	1978-1991	\$7,668	671	246	1,404	\$556	\$463	1.64	\$5,419	1.48	\$3,695	1.61	\$4,675
PV	1992-2010		1,042	211	1,251	\$581	\$479	1.70	\$5,901	1.54	\$4,136	1.59	\$4,513
HVAC HP	Pre-1978		-125	322	1,817	\$497	\$425	1.06	\$708	0.99	-\$145	1.21	\$2,257
Replacement w/ Panel Upgrade	1978-1991	\$10,849	671	246	1,404	\$556	\$463	1.15	\$1,847	1.05	\$514	1.14	\$1,494
+ PV	1992-2010		1,042	211	1,251	\$581	\$479	1.19	\$2,329	1.09	\$955	1.12	\$1,332
HPWH at Water	Pre-1978		-1,330	164	1,282	-\$132	-\$88	0	-\$5,516	0	-\$3,366	1.42	\$1,087
Heater	1978-1991	\$2,594	-1,345	165	1,288	-\$144	-\$97	0	-\$5,813	0	-\$3,400	1.45	\$1,174
Replacement	1992-2010		-1,349	165	1,291	-\$147	-\$101	0	-\$5,911	0	-\$3,452	1.41	\$1,059
NEEA Tier 3	Pre-1978		-983	163	1,391	-\$23	-\$1	0	-\$3,126	0.34	-\$1,844	1.89	\$2,465
HPWH at	1978-1991	\$2,775	-1,000	164	1,397	-\$35	-\$11	0	-\$3,430	0.33	-\$1,850	1.89	\$2,473
Replacement	1992-2010		-1,010	165	1,400	-\$40	-\$16	0	-\$3,556	0.32	-\$1,876	1.87	\$2,416
HPWH at Water	Pre-1978		2,112	164	1,498	\$859	\$695	1.93	\$10,021	1.38	\$3,677	1.53	\$5,221
Heater Replacement +	1978-1991	\$9,761	2,098	165	1,504	\$814	\$659	1.83	\$8,942	1.37	\$3,628	1.54	\$5,295
PV	1992-2010		2,093	165	1,507	\$778	\$630	1.75	\$8,079	1.37	\$3,573	1.53	\$5,174
HPWH	Pre-1978		2,112	164	1,498	\$859	\$695	1.45	\$6,449	1.04	\$496	1.16	\$2,040
Replacement w/ Panel Upgrade	1978-1991	\$12,942	2,098	165	1,504	\$814	\$659	1.37	\$5,370	1.03	\$447	1.16	\$2,114
+ PV	1992-2010		2,093	165	1,507	\$778	\$630	1.31	\$4,507	1.03	\$392	1.15	\$1,993

	Minterre	Measure	Electricity	Gas	GHG Savings	-	v Cost ings	Custome	er On-Bill	2019) TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978		3,442	0	216	\$896	\$707	1.70	\$8,701	1.24	\$2,753	0.99	-\$145
PV + Electric Ready Pre-Wire	1978-1991	\$11,258	3,442	0	216	\$863	\$681	1.63	\$7,911	1.24	\$2,738	0.99	-\$159
	1992-2010		3,442	0	216	\$801	\$632	1.51	\$6,436	1.24	\$2,733	0.99	-\$168

<u>Climate Zone 3:</u>

Manager	Mintorio	Measure	Electricity	Gas	GHG Savings		r Cost ings	Custom	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$3,332	151	33	359	\$115	\$95	0.76	-\$901	0.65	-\$1,182	1.27	\$902
R-49 Attic Insulation	1978-1991	\$2,874	90	17	184	\$61	\$50	0.47	-\$1,717	0.42	-\$1,672	0.95	-\$138
	1992-2010	\$1,852	6	6	65	\$14	\$12	0.17	-\$1,725	0.19	-\$1,504	0.22	-\$1,438
_	Pre-1978		10	14	143	\$31	\$26	0.47	-\$883	0.47	-\$783	0.63	-\$552
Reduced Infiltration	1978-1991	\$1,474	7	9	90	\$19	\$16	0.29	-\$1,177	0.30	-\$1,030	0.41	-\$869
	1992-2010		4	6	57	\$12	\$10	0.18	-\$1,349	0.20	-\$1,186	0.24	-\$1,114
	Pre-1978	\$683	40	30	315	\$73	\$61	2.40	\$1,070	2.59	\$1,086	3.68	\$1,832
Duct Sealing	1978-1991	\$683	18	17	175	\$39	\$33	1.29	\$220	1.51	\$348	1.97	\$659
	1992-2010	\$423	4	5	48	\$10	\$9	0.56	-\$211	0.69	-\$129	0.72	-\$118
	Pre-1978		77	54	567	\$133	\$111	0.75	-\$1,136	0.81	-\$754	1.20	\$781
New Ducts	1978-1991	\$3,986	43	38	392	\$89	\$74	0.50	-\$2,246	0.58	-\$1,659	0.79	-\$826
	1992-2010		14	16	164	\$35	\$30	0.20	-\$3,585	0.24	-\$3,010	0.26	-\$2,952
	Pre-1978		25	-8	-69	-\$5	-\$5	0	-\$984	0	-\$1,089	0.25	-\$582
Cool Roof	1978-1991	\$778	11	-5	-50	-\$6	-\$5	0	-\$997	0	-\$1,014	0.41	-\$461
	1992-2010		-1	-4	-45	-\$9	-\$7	0	-\$1,068	0	-\$971	0	-\$1,040
R-13 Wall Insulation	Pre-1978	\$3,360	49	44	458	\$102	\$85	0.68	-\$1,221	0.72	-\$955	1.00	\$10
Windows	Pre-1978	\$9,810	100	27	309	\$92	\$76	0.21	-\$8,740	0.20	-\$7,843	0.50	-\$4,916
WINDOWS	1978-1991	φ9,0 IU	57	25	276	\$71	\$59	0.16	-\$9,257	0.17	-\$8,131	0.38	-\$6,071
LED lamp vs CFL	All	\$2.26	1.2	0	n/a	\$0.34	\$0.27	3.55	\$5.76	n/a	n/a	n/a	n/a
Exterior Photosensor	All	\$42.58	12.1	0	n/a	\$2.88	\$2.27	1.60	\$25.62	n/a	n/a	n/a	n/a

Table 38: CZ 3 - Single Family Efficiency Upgrade Cost-Effectiveness Results

		Measure	Electricity	Gas	GHG Savings		v Cost ings	Custom	er On-Bill	201	9 TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$4,806	163	47	511	\$148	\$122	0.68	-\$1,743	0.60	-\$1,902	1.09	\$453
R49 Attic & Air Sealing Package	1978-1991	\$4,348	97	26	276	\$81	\$67	0.41	-\$2,881	0.38	-\$2,691	0.77	-\$987
e calling r achtage	1992-2010	\$3,326	11	12	123	\$27	\$22	0.18	-\$3,066	0.19	-\$2,690	0.23	-\$2,549
	Pre-1978	\$4,015	179	61	651	\$180	\$149	0.99	-\$45	0.96	-\$163	1.60	\$2,405
R49 Attic & Duct Sealing Package	1978-1991	\$3,557	104	33	346	\$97	\$80	0.60	-\$1,587	0.61	-\$1,379	1.08	\$299
e camig r achage	1992-2010	\$2,275	10	11	113	\$24	\$21	0.24	-\$1,938	0.28	-\$1,642	0.31	-\$1,561
R49 Attic. Air	Pre-1978	\$5,489	190	74	788	\$209	\$173	0.84	-\$966	0.82	-\$963	1.34	\$1,856
Sealing & Duct	1978-1991	\$5,031	111	41	430	\$115	\$95	0.51	-\$2,793	0.52	-\$2,435	0.88	-\$604
Sealing Package	1992-2010	\$3,749	15	16	169	\$36	\$30	0.22	-\$3,297	0.24	-\$2,836	0.29	-\$2,681
R49 Attic. Air	Pre-1978	\$8,792	216	97	1,029	\$263	\$219	0.66	-\$3,313	0.68	-\$2,837	1.07	\$598
Sealing & New	1978-1991	\$8,334	131	60	632	\$159	\$132	0.42	-\$5,389	0.46	-\$4,505	0.71	-\$2,427
Ducts Package	1992-2010	\$7,312	24	27	279	\$59	\$49	0.18	-\$6,733	0.22	-\$5,740	0.24	-\$5,552
Advanced Envelope Package	Pre-1978	\$18,659	274	137	1,451	\$359	\$299	0.43	-\$11,982	0.45	-\$10,354	0.74	-\$4,911
Water Heating Package	All Vintages	\$208	0	16	n/a	\$30	\$28	1.78	\$183	n/a	n/a	n/a	n/a

Table 39: CZ 3 - Single Family Efficiency Packages Cost-Effectiveness Results

	Martana	Measure	Electricity	Gas	GHG Savings	-	r Cost ings	Custom	er On-Bill	2019) TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978		3,464		226	\$866	\$684	2.69	\$12,900	1.95	\$6,551	1.59	\$4,080
Prescriptive PV System	1978-1991	\$6,886	3,464	0	226	\$837	\$661	2.60	\$12,212	1.95	\$6,546	1.59	\$4,074
i v cycloin	1992-2010		3,464		226	\$821	\$648	2.55	\$11,829	1.95	\$6,546	1.59	\$4,074
	Pre-1978		3,276		875	\$885	\$698	1.07	\$1,280	1.16	\$2,997	0.92	-\$1,523
PV + Battery	1978-1991	\$18,258	3,277	0	877	\$855	\$675	1.03	\$579	1.16	\$2,991	0.96	-\$806
	1992-2010		3,278		875	\$838	\$662	1.01	\$183	1.16	\$2,991	0.91	-\$1,719

Table 40: CZ 3 - Single Family PV & Battery Cost-Effectiveness Results

Table 41: CZ 3 - Single Family Equipment Fuel Substitution Cost-Effectiveness Results

		Measure	Electricity	Gas	GHG Savings		v Cost ings	Custome	er On-Bill	2019	9 TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
Heat Pump at	Pre-1978		-2,496	241	1,220	-\$238	-\$163	0	-\$5,443	0	-\$5,127	4.10	\$1,555
HVAC	1978-1991	\$501	-1,895	178	861	-\$181	-\$125	0	-\$4,306	0	-\$4,727	2.42	\$714
Replacement	1992-2010		-1,660	154	753	-\$158	-\$110	0	-\$3,846	0	-\$3,321	2.02	\$510
High-Effic. Heat	Pre-1978		-2,063	241	1,418	-\$106	-\$59	0	-\$5,824	0	-\$5,956	1.26	\$989
Pump at HVAC	1978-1991	\$3,749	-1,573	178	1,011	-\$86	-\$50	0	-\$5,564	0	-\$6,224	0.83	-\$627
Replacement	1992-2010		-1,398	154	872	-\$82	-\$50	0	-\$5,544	0	-\$5,092	0.62	-\$1,433
Heat Pump at	Pre-1978		968	241	1,446	\$670	\$554	2.03	\$8,445	1.20	\$1,467	1.77	\$5,661
HVAC Replacement +	1978-1991	\$7,387	1,569	178	1,086	\$710	\$578	2.13	\$9,191	1.25	\$1,850	1.65	\$4,806
PV	1992-2010		1,804	154	979	\$730	\$591	2.17	\$9,572	1.44	\$3,270	1.62	\$4,610
HVAC HP	Pre-1978		968	241	1,446	\$670	\$554	1.42	\$4,873	0.84	-\$1,714	1.23	\$2,480
Replacement w/ Panel Upgrade	1978-1991	\$10,568	1,569	178	1,086	\$710	\$578	1.48	\$5,619	0.87	-\$1,331	1.15	\$1,625
+ PV	1992-2010		1,804	154	979	\$730	\$591	1.51	\$6,000	1.01	\$89	1.14	\$1,429
HPWH at Water	Pre-1978		-1,308	164	1,288	-\$148	-\$101	0	-\$5,927	0	-\$3,565	1.31	\$808
Heater	1978-1991	\$2,594	-1,317	165	1,295	-\$151	-\$103	0	-\$5,990	0	-\$3,542	1.33	\$845
Replacement	1992-2010		-1,320	165	1,296	-\$160	-\$111	0	-\$6,229	0	-\$3,539	1.28	\$727
NEEA Tier 3	Pre-1978		-986	163	1,397	-\$45	-\$20	0	-\$3,681	0.28	-\$1,991	1.81	\$2,249
HPWH at	1978-1991	\$2,775	-990	164	1,409	-\$45	-\$20	0	-\$3,697	0.28	-\$1,986	1.81	\$2,249
Replacement	1992-2010		-993	164	1,410	-\$55	-\$28	0	-\$3,934	0.29	-\$1,963	1.76	\$2,119
HPWH at Water	Pre-1978		2,155	164	1,513	\$844	\$682	1.95	\$9,952	1.34	\$3,186	1.54	\$5,087
Heater Replacement +	1978-1991	\$9,480	2,146	165	1,521	\$834	\$674	1.93	\$9,719	1.34	\$3,206	1.54	\$5,118
PV	1992-2010		2,143	165	1,522	\$821	\$663	1.89	\$9,394	1.34	\$3,209	1.53	\$5,000
HPWH	Pre-1978		2,155	164	1,513	\$844	\$682	1.45	\$6,380	1.00	\$5	1.15	\$1,906
Replacement w/ Panel Upgrade	1978-1991	\$12,661	2,146	165	1,521	\$834	\$674	1.44	\$6,147	1.00	\$25	1.15	\$1,937
+ PV	1992-2010		2,143	165	1,522	\$821	\$663	1.41	\$5,822	1.00	\$28	1.14	\$1,819

		Measure	Electricity	Gas	GHG Savings	Utility Sav	r Cost ings	Custome	er On-Bill	2019	TDV	2022	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978		3,464	0	226	\$866	\$684	1.68	\$8,306	1.22	\$2,460	1.00	-\$11
PV + Electric Ready Pre-Wire	1978-1991	\$10,977	3,464	0	226	\$837	\$661	1.62	\$7,618	1.22	\$2,455	1.00	-\$17
,, ,	1992-2010		3,464	0	226	\$821	\$648	1.59	\$7,235	1.22	\$2,455	1.00	-\$17

Climate Zone 4 PG&E:

	Nr. (Measure	Electricity	Gas	GHG Savings	Utility Sav	v Cost ings	Custom	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO2e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
-	Pre-1978	\$3,332	654	29	409	\$305	\$244	1.96	\$3,579	1.95	\$3,168	1.92	\$3,075
R-49 Attic Insulation	1978-1991	\$2,874	340	15	218	\$156	\$125	1.16	\$511	1.23	\$674	1.18	\$517
	1992-2010	\$1,852	79	6	79	\$39	\$31	0.45	-\$1,138	0.63	-\$691	0.60	-\$740
_	Pre-1978		20	11	111	\$28	\$24	0.43	-\$946	0.59	-\$598	0.84	-\$233
Reduced Infiltration	1978-1991	\$1,474	9	7	74	\$15	\$13	0.23	-\$1,274	0.36	-\$944	0.29	-\$1,051
	1992-2010		8	5	48	\$11	\$9	0.16	-\$1,393	0.23	-\$1,140	0.29	-\$1,051
	Pre-1978	\$683	299	24	314	\$164	\$132	5.17	\$3,201	6.90	\$4,027	7.62	\$4,522
Duct Sealing	1978-1991	\$683	160	13	179	\$88	\$71	2.77	\$1,354	3.79	\$1,904	4.48	\$2,379
	1992-2010	\$423	23	4	45	\$15	\$12	0.79	-\$101	1.17	\$72	1.50	\$214
	Pre-1978		611	43	586	\$324	\$261	1.75	\$3,339	2.38	\$5,482	2.55	\$6,165
New Ducts	1978-1991	\$3,986	430	30	425	\$222	\$178	1.19	\$862	1.79	\$3,140	1.88	\$3,492
	1992-2010		97	12	159	\$59	\$48	0.32	-\$3,050	0.54	-\$1,849	0.58	-\$1,673
	Pre-1978		272	-5	-3	\$96	\$76	2.67	\$1,418	2.80	\$1,403	2.98	\$1,544
Cool Roof	1978-1991	\$778	185	-4	6	\$66	\$52	1.83	\$705	2.09	\$847	2.02	\$792
	1992-2010		75	-3	-8	\$24	\$18	0.65	-\$298	0.99	-\$6	0.89	-\$87
R-13 Wall Insulation	Pre-1978	\$3,360	123	36	394	\$116	\$96	0.76	-\$901	0.90	-\$330	1.07	\$241
) A / ins dia was	Pre-1978	¢0.040	873	6	243	\$354	\$280	0.76	-\$2,601	0.83	-\$1,627	0.87	-\$1,321
Windows	1978-1991	\$9,810	674	5	220	\$273	\$216	0.59	-\$4,534	0.71	-\$2,811	0.67	-\$3,240
LED lamp vs CFL	All	\$2.26	1.2	0	n/a	\$0.40	\$0.31	4.16	\$7.13	n/a	n/a	n/a	n/a
Exterior Photosensor	All	\$42.58	12.1	0	n/a	\$2.88	\$2.27	1.60	\$25.62	n/a	n/a	n/a	n/a

 Table 42: CZ 4 (PG&E) - Single Family Efficiency Upgrade Cost-Effectiveness Results

	N. A.	Measure	Electricity	Gas	GHG Savings		/ Cost ings	Custom	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$4,806	673	41	532	\$335	\$269	1.50	\$2,673	1.54	\$2,582	1.56	\$2,705
R49 Attic & Air Sealing Package	1978-1991	\$4,348	352	22	292	\$172	\$138	0.85	-\$737	0.93	-\$319	0.93	-\$320
e calling r donage	1992-2010	\$3,326	86	10	128	\$50	\$40	0.32	-\$2,530	0.46	-\$1,797	0.46	-\$1,805
	Pre-1978	\$4,015	879	52	699	\$437	\$351	2.34	\$6,022	2.65	\$6,619	2.78	\$7,157
R49 Attic & Duct Sealing Package	1978-1991	\$3,557	473	27	383	\$229	\$184	1.38	\$1,512	1.67	\$2,367	1.67	\$2,389
County P donago	1992-2010	\$2,275	98	9	122	\$53	\$43	0.50	-\$1,278	0.74	-\$596	0.71	-\$665
R49 Attic. Air	Pre-1978	\$5,489	893	62	807	\$461	\$371	1.80	\$4,959	2.05	\$5,741	2.21	\$6,624
Sealing & Duct	1978-1991	\$5,031	482	34	449	\$243	\$195	1.04	\$209	1.27	\$1,371	1.30	\$1,503
Sealing Package	1992-2010	\$3,749	105	14	168	\$62	\$50	0.36	-\$2,697	0.54	-\$1,724	0.52	-\$1,799
R49 Attic. Air	Pre-1978	\$8,792	1,158	80	1,070	\$598	\$481	1.46	\$4,549	1.79	\$6,929	1.90	\$7,942
Sealing & New	1978-1991	\$8,334	724	49	676	\$363	\$291	0.93	-\$629	1.26	\$2,193	1.31	\$2,572
Ducts Package	1992-2010	\$7,312	171	22	276	\$101	\$82	0.30	-\$5,752	0.48	-\$3,795	0.48	-\$3,792
Advanced Envelope Package	Pre-1978	\$18,659	1,501	115	1,502	\$783	\$630	0.90	-\$2,049	1.09	\$1,633	1.13	\$2,418
Water Heating Package	All Vintages	\$208	0	16	n/a	\$32	\$29	1.88	\$205	n/a	n/a	n/a	n/a

Table 43: CZ 4 (PG&E) - Single Family Efficiency Packages Cost-Effectiveness Results

	Martana	Measure	Electricity	Gas	GHG Savings	Utility Savi	r Cost ings	Custome	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
_	Pre-1978		3,562		232	\$980	\$773	3.02	\$15,511	2.02	\$7,090	1.72	\$4,984
Prescriptive PV System	1978-1991	\$6,950	3,562	0	232	\$946	\$746	2.91	\$14,704	2.02	\$7,072	1.71	\$4,958
l v eyetetti	1992-2010		3,562		232	\$883	\$697	2.72	\$13,223	2.02	\$7,061	1.71	\$4,932
	Pre-1978		3,368		822	\$1,020	\$805	1.22	\$4,414	1.20	\$3,650	0.86	-\$2,534
PV + Battery	1978-1991	\$18,322	3,366	0	842	\$987	\$779	1.18	\$3,642	1.24	\$4,310	0.89	-\$2,079
	1992-2010		3,367		870	\$920	\$726	1.10	\$2,045	1.29	\$5,246	0.96	-\$786

Table 44: CZ 4 (PG&E) - Single Family PV & Battery Cost-Effectiveness Results

Table 45: CZ 4 (PG&E) - Single Family Equipment Fuel Substitution Cost-Effectiveness Results

	Markana	Measure	Electricity	Gas	GHG Savings		v Cost ings	Custom	er On-Bill	2019	9 TDV	202:	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO2e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
Heat Pump at	Pre-1978		-2,034	190	917	-\$240	-\$171	0	-\$5,666	0	-\$4,436	2.49	\$749
HVAC	1978-1991	\$501	-1,520	138	633	-\$195	-\$141	0	-\$4,771	0	-\$3,774	1.26	\$132
Replacement	1992-2010		-1,290	117	543	-\$167	-\$121	0	-\$4,167	0	-\$3,647	1.11	\$54
High-Effic. Heat	Pre-1978		-1,446	190	1,150	-\$43	-\$16	0	-\$4,530	0.22	-\$2,908	1.51	\$1,916
Pump at HVAC	1978-1991	\$3,749	-1,084	138	813	-\$50	-\$26	0	-\$4,848	0.13	-\$3,248	1.09	\$329
Replacement	1992-2010		-993	117	675	-\$70	-\$45	0	-\$5,403	0	-\$4,389	0.77	-\$846
Heat Pump at	Pre-1978		1,528	190	1,149	\$746	\$608	2.21	\$9,995	1.36	\$2,691	1.77	\$5,753
HVAC Replacement +	1978-1991	\$7,451	2,042	138	865	\$771	\$622	2.27	\$10,414	1.45	\$3,330	1.69	\$5,105
PV	1992-2010		2,272	117	775	\$763	\$613	2.23	\$10,159	1.46	\$3,457	1.67	\$5,010
HVAC HP	Pre-1978		1,528	190	1,149	\$746	\$608	1.54	\$6,423	0.95	-\$490	1.24	\$2,572
Replacement w/ Panel Upgrade	1978-1991	\$10,632	2,042	138	865	\$771	\$622	1.58	\$6,842	1.01	\$149	1.18	\$1,924
+ PV	1992-2010		2,272	117	775	\$763	\$613	1.56	\$6,587	1.03	\$276	1.17	\$1,829
HPWH at Water	Pre-1978		-1,103	157	1,265	-\$84	-\$51	0	-\$4,427	0	-\$2,761	1.63	\$1,643
Heater	1978-1991	\$2,594	-1,118	157	1,271	-\$104	-\$68	0	-\$4,927	0	-\$2,893	1.52	\$1,338
Replacement	1992-2010		-1,128	158	1,270	-\$110	-\$73	0	-\$5,069	0	-\$2,911	1.57	\$1,473
NEEA Tier 3	Pre-1978		-862	156	1,360	-\$8	\$9	0.09	-\$2,815	0.47	-\$1,461	1.99	\$2,756
HPWH at	1978-1991	\$2,775	-873	157	1,369	-\$26	-\$7	0	-\$3,287	0.49	-\$1,410	1.86	\$2,378
Replacement	1992-2010		-881	157	1,370	-\$31	-\$10	0	-\$3,403	0.46	-\$1,493	1.93	\$2,583
HPWH at Water	Pre-1978		2,459	157	1,497	\$968	\$779	2.21	\$12,793	1.47	\$4,522	1.71	\$6,812
Heater Replacement +	1978-1991	\$9,544	2,444	157	1,503	\$924	\$743	2.11	\$11,729	1.46	\$4,375	1.68	\$6,483
PV	1992-2010		2,434	158	1,502	\$859	\$692	1.96	\$10,188	1.46	\$4,349	1.69	\$6,596
HPWH	Pre-1978		2,459	157	1,497	\$968	\$779	1.65	\$9,221	1.11	\$1,341	1.29	\$3,631
Replacement w/ Panel Upgrade	1978-1991	\$12,725	2,444	157	1,503	\$924	\$743	1.58	\$8,157	1.09	\$1,194	1.26	\$3,302
+ PV	1992-2010		2,434	158	1,502	\$859	\$692	1.47	\$6,616	1.09	\$1,168	1.27	\$3,415

	Minterra	Measure	Electricity	Gas	GHG Savings	-	v Cost ings	Custome	er On-Bill	2019) TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978		3,562	0	232	\$980	\$773	1.89	\$10,917	1.27	\$2,999	1.08	\$893
PV + Electric Ready Pre-Wire	1978-1991	\$11,041	3,562	0	232	\$946	\$746	1.82	\$10,110	1.27	\$2,981	1.08	\$867
	1992-2010		3,562	0	232	\$883	\$697	1.70	\$8,629	1.27	\$2,970	1.08	\$841

<u>Climate Zone 4 CPAU:</u>

	Nr. (Measure	Electricity	Gas	GHG Savings	Utility Sav	v Cost ings	Custom	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO2e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$3,332	654	29	409	\$172	\$138	1.11	\$404	1.95	\$3,168	1.92	\$3,075
R-49 Attic Insulation	1978-1991	\$2,874	340	15	218	\$83	\$66	0.62	-\$1,234	1.23	\$674	1.18	\$517
	1992-2010	\$1,852	79	6	79	\$20	\$16	0.23	-\$1,599	0.63	-\$691	0.60	-\$740
	Pre-1978		20	11	111	\$22	\$18	0.33	-\$1,114	0.59	-\$598	0.84	-\$233
Reduced Infiltration	1978-1991	\$1,474	9	7	74	\$11	\$9	0.17	-\$1,381	0.36	-\$944	0.29	-\$1,051
	1992-2010		8	5	48	\$6	\$5	0.09	-\$1,498	0.23	-\$1,140	0.29	-\$1,051
	Pre-1978	\$683	299	24	314	\$98	\$80	3.13	\$1,631	6.90	\$4,027	7.62	\$4,522
Duct Sealing	1978-1991	\$683	160	13	179	\$49	\$40	1.55	\$419	3.79	\$1,904	4.48	\$2,379
	1992-2010	\$423	23	4	45	\$8	\$7	0.42	-\$274	1.17	\$72	1.50	\$214
	Pre-1978		611	43	586	\$191	\$155	1.04	\$168	2.38	\$5,482	2.55	\$6,165
New Ducts	1978-1991	\$3,986	430	30	425	\$122	\$99	0.66	-\$1,514	1.79	\$3,140	1.88	\$3,492
	1992-2010		97	12	159	\$31	\$25	0.17	-\$3,716	0.54	-\$1,849	0.58	-\$1,673
	Pre-1978		272	-5	-3	\$44	\$35	1.22	\$191	2.80	\$1,403	2.98	\$1,544
Cool Roof	1978-1991	\$778	185	-4	6	\$31	\$24	0.84	-\$135	2.09	\$847	2.02	\$792
	1992-2010		75	-3	-8	\$10	\$8	0.27	-\$615	0.99	-\$6	0.89	-\$87
R-13 Wall Insulation	Pre-1978	\$3,360	123	36	394	\$83	\$69	0.55	-\$1,713	0.90	-\$330	1.07	\$241
Mindawa	Pre-1978	¢0.040	873	6	243	\$183	\$145	0.39	-\$6,666	0.83	-\$1,627	0.87	-\$1,321
Windows	1978-1991	\$9,810	674	5	220	\$137	\$109	0.30	-\$7,758	0.71	-\$2,811	0.67	-\$3,240
LED lamp vs CFL	All	\$2.26	1.2	0	n/a	\$0.18	\$0.14	1.90	\$2.03	n/a	n/a	n/a	n/a
Exterior Photosensor	All	\$42.58	12.1	0	n/a	\$1.66	\$1.31	0.93	-\$3.17	n/a	n/a	n/a	n/a

Table 46: CZ 4 (CPAU) - Single Family Efficiency Upgrade Cost-Effectiveness Results

		Measure	Electricity	Gas	GHG Savings	-	/ Cost ings	Custom	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$4,806	673	41	532	\$195	\$157	0.88	-\$673	1.54	\$2,582	1.56	\$2,705
R49 Attic & Air Sealing Package	1978-1991	\$4,348	352	22	292	\$94	\$76	0.47	-\$2,612	0.93	-\$319	0.93	-\$320
e calling r achage	1992-2010	\$3,326	86	10	128	\$26	\$21	0.17	-\$3,095	0.46	-\$1,797	0.46	-\$1,805
	Pre-1978	\$4,015	879	52	699	\$252	\$204	1.36	\$1,612	2.65	\$6,619	2.78	\$7,157
R49 Attic & Duct Sealing Package	1978-1991	\$3,557	473	27	383	\$124	\$100	0.75	-\$997	1.67	\$2,367	1.67	\$2,389
ocalling r donago	1992-2010	\$2,275	98	9	122	\$27	\$22	0.26	-\$1,891	0.74	-\$596	0.71	-\$665
R49 Attic. Air	Pre-1978	\$5,489	893	62	807	\$270	\$219	1.07	\$405	2.05	\$5,741	2.21	\$6,624
Sealing & Duct	1978-1991	\$5,031	482	34	449	\$134	\$108	0.57	-\$2,414	1.27	\$1,371	1.30	\$1,503
Sealing Package	1992-2010	\$3,749	105	14	168	\$33	\$27	0.19	-\$3,398	0.54	-\$1,724	0.52	-\$1,799
R49 Attic. Air	Pre-1978	\$8,792	1,158	80	1,070	\$345	\$279	0.85	-\$1,489	1.79	\$6,929	1.90	\$7,942
Sealing & New	1978-1991	\$8,334	724	49	676	\$195	\$157	0.50	-\$4,635	1.26	\$2,193	1.31	\$2,572
Ducts Package	1992-2010	\$7,312	171	22	276	\$54	\$44	0.16	-\$6,888	0.48	-\$3,795	0.48	-\$3,792
Advanced Envelope Package	Pre-1978	\$18,659	1,501	115	1,502	\$448	\$363	0.52	-\$10,070	1.09	\$1,633	1.13	\$2,418
Water Heating Package	All Vintages	\$208	0	16	n/a	\$23	\$21	1.36	\$85	n/a	n/a	n/a	n/a

Table 47: CZ 4 (CPAU) - Single Family Efficiency Packages Cost-Effectiveness Results

	Nr. (Measure	Electricity	Gas	GHG Savings	Utility Sav	Cost ings	Custom	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978		3,562		232	\$459	\$362	1.41	\$3,171	2.02	\$7,090	1.72	\$4,984
Prescriptive PV System	1978-1991	\$6,950	3,562	0	232	\$448	\$353	1.38	\$2,918	2.02	\$7,072	1.71	\$4,958
i v cyctom	1992-2010		3,562		232	\$424	\$335	1.31	\$2,355	2.02	\$7,061	1.71	\$4,932
	Pre-1978		3,368		822	\$512	\$404	0.61	-\$7,606	1.20	\$3,650	0.86	-\$2,534
PV + Battery	1978-1991	\$18,322	3,366	0	842	\$491	\$387	0.59	-\$8,118	1.24	\$4,310	0.89	-\$2,079
	1992-2010		3,367		870	\$434	\$342	0.52	-\$9,467	1.29	\$5,246	0.96	-\$786

Table 48: CZ 4 (CPAU) - Single Family PV & Battery Cost-Effectiveness Results

Table 49: CZ 4 (CPAU) - Single Family Equipment Fuel Substitution Cost-Effectiveness Results

•	Minterre	Measure	Electricity	Gas	GHG Savings	Utility Savi	v Cost ings	Custom	er On-Bill	2019	9 TDV	2022	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
Heat Pump at	Pre-1978		-2,034	190	917	-\$161	-\$114	0	-\$3,969	0	-\$4,436	2.49	\$749
HVAC	1978-1991	\$501	-1,520	138	633	-\$140	-\$102	0	-\$3,598	0	-\$3,774	1.26	\$132
Replacement	1992-2010		-1,290	117	543	-\$121	-\$88	0	-\$3,197	0	-\$2,014	1.11	\$54
High-Effic. Heat	Pre-1978		-1,446	190	1,150	-\$47	-\$24	0	-\$4,781	0.22	-\$2,908	1.51	\$1,916
Pump at HVAC	1978-1991	\$3,749	-1,084	138	813	-\$56	-\$35	0	-\$5,121	0.13	-\$3,248	1.09	\$329
Replacement	1992-2010		-993	117	675	-\$64	-\$44	0	-\$5,370	0.27	-\$2,756	0.77	-\$846
Heat Pump at	Pre-1978		1,528	190	1,149	\$318	\$264	0.96	-\$316	1.36	\$2,691	1.77	\$5,753
HVAC Replacement +	1978-1991	\$7,451	2,042	138	865	\$325	\$265	0.97	-\$273	1.45	\$3,330	1.69	\$5,105
PV	1992-2010		2,272	117	775	\$325	\$264	0.96	-\$318	1.46	\$3,457	1.67	\$5,010
HVAC HP	Pre-1978		1,528	190	1,149	\$318	\$264	0.67	-\$3,888	0.95	-\$490	1.24	\$2,572
Replacement w/ Panel Upgrade	1978-1991	\$10,632	2,042	138	865	\$325	\$265	0.67	-\$3,845	1.01	\$149	1.18	\$1,924
+ PV	1992-2010		2,272	117	775	\$325	\$264	0.67	-\$3,890	1.03	\$276	1.17	\$1,829
HPWH at Water	Pre-1978		-1,103	157	1,265	-\$23	-\$8	0	-\$3,125	0	-\$2,761	1.63	\$1,643
Heater	1978-1991	\$2,594	-1,118	157	1,271	-\$50	-\$30	0	-\$3,790	0	-\$2,893	1.52	\$1,338
Replacement	1992-2010		-1,128	158	1,270	-\$55	-\$35	0	-\$3,931	0	-\$2,911	1.57	\$1,473
NEEA Tier 3	Pre-1978		-862	156	1,360	\$22	\$28	0.27	-\$2,241	0.47	-\$1,461	1.99	\$2,756
HPWH at	1978-1991	\$2,775	-873	157	1,369	-\$3	\$7	0.07	-\$2,881	0.49	-\$1,410	1.86	\$2,378
Replacement	1992-2010		-881	157	1,370	-\$8	\$3	0.03	-\$3,006	0.46	-\$1,493	1.93	\$2,583
HPWH at Water	Pre-1978		2,459	157	1,497	\$488	\$395	1.12	\$1,287	1.47	\$4,522	1.71	\$6,812
Heater Replacement +	1978-1991	\$9,544	2,444	157	1,503	\$455	\$368	1.04	\$463	1.46	\$4,375	1.68	\$6,483
PV	1992-2010	1	2,434	158	1,502	\$430	\$348	0.99	-\$138	1.46	\$4,349	1.69	\$6,596
HPWH	Pre-1978		2,459	157	1,497	\$488	\$395	0.84	-\$2,285	1.11	\$1,341	1.29	\$3,631
Replacement w/ Panel Upgrade	1978-1991	\$12,725	2,444	157	1,503	\$455	\$368	0.78	-\$3,109	1.09	\$1,194	1.26	\$3,302
+ PV	1992-2010		2,434	158	1,502	\$430	\$348	0.74	-\$3,710	1.09	\$1,168	1.27	\$3,415

	Minterre	Measure	Electricity	Gas	GHG Savings	Utility Savi	r Cost ings	Custome	er On-Bill	2019) TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978		3,562	0	232	\$459	\$362	0.88	-\$1,423	1.27	\$2,999	1.08	\$893
PV + Electric Ready Pre-Wire	1978-1991	\$11,041	3,562	0	232	\$448	\$353	0.86	-\$1,676	1.27	\$2,981	1.08	\$867
	1992-2010		3,562	0	232	\$424	\$335	0.82	-\$2,239	1.27	\$2,970	1.08	\$841

Climate Zone 5 PG&E:

	Nr. (Measure	Electricity	Gas	GHG Savings		v Cost ings	Custome	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO2e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$3,332	141	31	339	\$106	\$87	0.70	-\$1,125	0.57	-\$1,430	0.97	-\$100
R-49 Attic Insulation	1978-1991	\$2,874	84	16	169	\$56	\$46	0.43	-\$1,853	0.39	-\$1,765	0.60	-\$1,145
	1992-2010	\$1,852	6	6	60	\$13	\$10	0.15	-\$1,766	0.17	-\$1,538	0.22	-\$1,449
	Pre-1978		10	14	141	\$30	\$25	0.45	-\$908	0.55	-\$670	0.59	-\$607
Reduced Infiltration	1978-1991	\$1,474	6	9	87	\$19	\$16	0.28	-\$1,188	0.33	-\$981	0.37	-\$932
initiation	1992-2010		4	6	57	\$12	\$10	0.18	-\$1,365	0.22	-\$1,149	0.24	-\$1,123
	Pre-1978	\$683	32	28	293	\$66	\$55	2.16	\$892	2.70	\$1,160	2.81	\$1,238
Duct Sealing	1978-1991	\$683	15	15	160	\$35	\$30	1.16	\$120	1.55	\$374	1.52	\$354
	1992-2010	\$423	4	5	47	\$10	\$8	0.51	-\$235	0.73	-\$115	0.69	-\$132
	Pre-1978		63	49	517	\$119	\$99	0.66	-\$1,502	0.81	-\$769	0.87	-\$504
New Ducts	1978-1991	\$3,986	35	34	351	\$78	\$65	0.44	-\$2,515	0.57	-\$1,702	0.59	-\$1,647
	1992-2010		13	15	152	\$31	\$26	0.17	-\$3,693	0.25	-\$2,986	0.24	-\$3,035
	Pre-1978		19	-8	-77	-\$8	-\$7	0	-\$1,067	0	-\$1,282	0	-\$1,077
Cool Roof	1978-1991	\$778	5	-6	-56	-\$9	-\$8	0	-\$1,084	0	-\$1,132	0	-\$1,017
	1992-2010		-1	-5	-48	-\$9	-\$8	0	-\$1,080	0	-\$1,072	0	-\$1,043
R-13 Wall Insulation	Pre-1978	\$3,360	44	43	445	\$98	\$82	0.65	-\$1,311	0.79	-\$719	0.85	-\$491
	Pre-1978	¢0.040	72	21	236	\$68	\$56	0.15	-\$9,341	0.15	-\$8,315	0.21	-\$7,759
Windows	1978-1991	\$9,810	38	20	213	\$52	\$43	0.12	-\$9,727	0.14	-\$8,407	0.18	-\$8,018
LED lamp vs CFL	All	\$2.26	1.2	0	n/a	\$0.34	\$0.27	3.54	\$5.72	n/a	n/a	n/a	n/a
Exterior Photosensor	All	\$42.58	12.1	0	n/a	\$2.88	\$2.27	1.60	\$25.62	n/a	n/a	n/a	n/a

Table 50: CZ 5 (PG&E) - Single Family Efficiency Upgrade Cost-Effectiveness Results

		Measure	Electricity	Gas	GHG Savings	-	/ Cost ings	Custom	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$4,806	152	45	484	\$137	\$113	0.63	-\$1,999	0.58	-\$2,032	0.86	-\$675
R49 Attic & Air Sealing Package	1978-1991	\$4,348	91	24	259	\$75	\$62	0.38	-\$3,021	0.38	-\$2,714	0.53	-\$2,061
e calling r achage	1992-2010	\$3,326	11	11	117	\$24	\$20	0.16	-\$3,129	0.19	-\$2,678	0.23	-\$2,569
	Pre-1978	\$4,015	163	56	603	\$164	\$136	0.90	-\$441	0.91	-\$368	1.22	\$874
R49 Attic & Duct Sealing Package	1978-1991	\$3,557	96	30	316	\$88	\$73	0.55	-\$1,806	0.59	-\$1,442	0.75	-\$904
e calling r achage	1992-2010	\$2,275	10	10	105	\$22	\$18	0.21	-\$2,010	0.27	-\$1,656	0.30	-\$1,593
R49 Attic. Air	Pre-1978	\$5,489	173	69	736	\$192	\$160	0.78	-\$1,377	0.80	-\$1,073	1.04	\$226
Sealing & Duct	1978-1991	\$5,031	103	38	398	\$105	\$87	0.46	-\$3,038	0.51	-\$2,447	0.63	-\$1,868
Sealing Package	1992-2010	\$3,749	14	15	160	\$33	\$28	0.20	-\$3,385	0.25	-\$2,813	0.27	-\$2,727
R49 Attic, Air	Pre-1978	\$8,792	190	89	945	\$238	\$198	0.60	-\$3,940	0.66	-\$3,008	0.80	-\$1,769
Sealing & New	1978-1991	\$8,334	117	55	575	\$141	\$117	0.38	-\$5,836	0.45	-\$4,566	0.51	-\$4,065
Ducts Package	1992-2010	\$7,312	23	25	260	\$53	\$44	0.16	-\$6,880	0.22	-\$5,711	0.23	-\$5,662
Advanced Envelope Package	Pre-1978	\$18,659	226	124	1,302	\$313	\$261	0.37	-\$13,126	0.42	- \$10,731	0.50	-\$9,309
Water Heating Package	All Vintages	\$208	0	16	0	\$30	\$28	1.79	\$186	n/a	n/a	n/a	n/a

Table 51: CZ 5 (PG&E) - Single Family Efficiency Packages Cost-Effectiveness Results

		Measure	Electricity	Gas	GHG Savings	Utility Sav	v Cost ings	Custom	er On-Bill	2019) TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978		3,463		259	\$851	\$672	2.82	\$13,000	2.08	\$6,961	1.71	\$4,619
Prescriptive PV System	1978-1991	\$6,467	3,463	0	259	\$828	\$654	2.74	\$12,459	2.08	\$6,955	1.71	\$4,617
i v cycloini	1992-2010		3,463		259	\$818	\$646	2.71	\$12,219	2.08	\$6,955	1.71	\$4,617
	Pre-1978		3,268		921	\$868	\$685	1.07	\$1,350	1.14	\$2,519	0.90	-\$1,802
PV + Battery	1978-1991	\$17,840	3,269	0	923	\$845	\$667	1.04	\$797	1.14	\$2,502	0.91	-\$1,554
	1992-2010		3,270		923	\$834	\$659	1.03	\$554	1.14	\$2,505	0.92	-\$1,358

Table 52: CZ 5 (PG&E) - Single Family PV & Battery Cost-Effectiveness Results

Table 53: CZ 5 (PG&E) - Single Family Equipment Fuel Substitution Cost-Effectiveness Results

	Minterre	Measure	Electricity	Gas	GHG Savings	Utility Savi	r Cost ings	Custom	er On-Bill	2019	9 TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
Heat Pump at	Pre-1978		-2,800	213	797	-\$379	-\$277	0	-\$8,861	0	-\$6,740	0	-\$1,959
HVAC	1978-1991	\$501	-2,205	154	479	-\$319	-\$236	0	-\$7,639	0	-\$6,282	0	-\$2,495
Replacement	1992-2010		-1,828	138	514	-\$238	-\$175	0	-\$5,788	0	-\$4,710	0	-\$1,512
High-Effic. Heat	Pre-1978		-2,469	213	945	-\$280	-\$199	0	-\$10,036	0	-\$7,696	0.08	-\$3,435
Pump at HVAC	1978-1991	\$3,749	-1,968	154	587	-\$248	-\$181	0	-\$9,482	0	-\$7,851	0	-\$4,478
Replacement	1992-2010		-1,624	138	604	-\$177	-\$127	0	-\$7,864	0	-\$6,463	0	-\$3,732
Heat Pump at	Pre-1978		663	213	1,056	\$534	\$443	1.73	\$5,599	1.04	\$264	1.38	\$2,678
HVAC Replacement +	1978-1991	\$6,969	1,258	154	738	\$582	\$474	1.85	\$6,524	1.10	\$705	1.31	\$2,133
PV	1992-2010		1,634	138	773	\$658	\$532	2.07	\$8,271	1.33	\$2,298	1.45	\$3,121
HVAC HP	Pre-1978				1,056	\$534	\$443	1.18	\$2,027	0.71	-\$2,917	0.95	-\$503
Replacement w/ Panel Upgrade	1978-1991	\$10,150			738	\$582	\$474	1.26	\$2,952	0.76	-\$2,476	0.90	-\$1,048
+ PV	1992-2010				773	\$658	\$532	1.42	\$4,699	0.91	-\$883	0.99	-\$60
HPWH at Water	Pre-1978		-1,304	164	1,292	-\$143	-\$97	0	-\$5,796	0	-\$3,945	1.31	\$802
Heater	1978-1991	\$2,594	-1,308	165	1,299	-\$149	-\$102	0	-\$5,942	0	-\$3,879	1.32	\$831
Replacement	1992-2010		-1,309	165	1,301	-\$159	-\$111	0	-\$6,213	0	-\$3,870	1.32	\$819
NEEA Tier 3	Pre-1978		-987	163	1,405	-\$41	-\$17	0	-\$3,586	0.21	-\$2,181	1.81	\$2,254
HPWH at	1978-1991	\$2,775	-990	164	1,415	-\$46	-\$21	0	-\$3,705	0.23	-\$2,147	1.83	\$2,312
Replacement	1992-2010		-992	165	1,416	-\$57	-\$30	0	-\$3,983	0.23	-\$2,124	1.82	\$2,289
HPWH at Water	Pre-1978		2,158	164	1,551	\$849	\$686	2.05	\$10,534	1.36	\$3,227	1.62	\$5,620
Heater Replacement +	1978-1991	\$9,061	2,154	165	1,559	\$838	\$677	2.02	\$10,261	1.36	\$3,290	1.62	\$5,646
PV	1992-2010	1	2,153	165	1,561	\$825	\$666	1.99	\$9,936	1.36	\$3,302	1.62	\$5,635
HPWH	Pre-1978		2,158	164	1,551	\$849	\$686	1.51	\$6,962	1.00	\$46	1.20	\$2,439
Replacement w/ Panel Upgrade	1978-1991	\$12,242	2,154	165	1,559	\$838	\$677	1.49	\$6,689	1.01	\$109	1.20	\$2,465
+ PV	1992-2010		2,153	165	1,561	\$825	\$666	1.47	\$6,364	1.01	\$121	1.20	\$2,454

	Minterre	Measure	Electricity	Gas	GHG Savings	-	v Cost ings	Custome	er On-Bill	2019) TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978		3,463	0	259	\$851	\$672	1.72	\$8,406	1.27	\$2,870	1.05	\$528
PV + Electric Ready Pre-Wire	1978-1991	\$10,558	3,463	0	259	\$828	\$654	1.67	\$7,865	1.27	\$2,864	1.05	\$526
	1992-2010		3,463	0	259	\$818	\$646	1.65	\$7,625	1.27	\$2,864	1.05	\$526

Climate Zone 5 PG&E/SoCalGas:

Note: Values in red and grey rows indicate option is not cost-effective with B/C ratio less than 1. Cells with "n/a" reflect lighting and water heating efficiency measures and packages that did not look at TDV cost effectiveness or GHG impacts.

		Measure	Electricity	Gas	GHG Savings	Utility Sav	v Cost ings	Custom	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$3,332	141	31	339	\$89	\$73	0.58	-\$1,565	0.57	-\$1,430	0.97	-\$100
R-49 Attic Insulation	1978-1991	\$2,874	84	16	169	\$45	\$37	0.34	-\$2,127	0.39	-\$1,765	0.60	-\$1,145
modiation	1992-2010	\$1,852	6	6	60	\$9	\$8	0.11	-\$1,843	0.17	-\$1,538	0.22	-\$1,449
	Pre-1978		10	14	141	\$23	\$19	0.34	-\$1,087	0.55	-\$670	0.59	-\$607
Reduced Infiltration	1978-1991	\$1,474	6	9	87	\$14	\$12	0.21	-\$1,310	0.33	-\$981	0.37	-\$932
miliadion	1992-2010		4	6	57	\$8	\$7	0.13	-\$1,443	0.22	-\$1,149	0.24	-\$1,123
	Pre-1978	\$683	32	28	293	\$52	\$43	1.69	\$531	2.70	\$1,160	2.81	\$1,238
Duct Sealing	1978-1991	\$683	15	15	160	\$26	\$22	0.87	-\$102	1.55	\$374	1.52	\$354
	1992-2010	\$423	4	5	47	\$7	\$6	0.37	-\$298	0.73	-\$115	0.69	-\$132
	Pre-1978		63	49	517	\$94	\$78	0.52	-\$2,134	0.81	-\$769	0.87	-\$504
New Ducts	1978-1991	\$3,986	35	34	351	\$58	\$49	0.33	-\$3,011	0.57	-\$1,702	0.59	-\$1,647
	1992-2010		13	15	152	\$23	\$19	0.13	-\$3,898	0.25	-\$2,986	0.24	-\$3,035
	Pre-1978		19	-8	-77	-\$4	-\$4	0	-\$956	0	-\$1,282	0	-\$1,077
Cool Roof	1978-1991	\$778	5	-6	-56	-\$6	-\$5	0	-\$1,003	0	-\$1,132	0	-\$1,017
	1992-2010		-1	-5	-48	-\$6	-\$5	0	-\$1,009	0	-\$1,072	0	-\$1,043
R-13 Wall Insulation	Pre-1978	\$3,360	44	43	445	\$76	\$63	0.50	-\$1,868	0.79	-\$719	0.85	-\$491
Aliza da sua	Pre-1978	¢0.040	72	21	236	\$57	\$47	0.13	-\$9,605	0.15	-\$8,315	0.21	-\$7,759
Windows	1978-1991	\$9,810	38	20	213	\$41	\$34	0.09	-\$10,007	0.14	-\$8,407	0.18	-\$8,018
LED lamp vs CFL	All	\$2.26	1.2	0	n/a	\$0.28	\$0.22	2.96	\$4.42	n/a	n/a	n/a	n/a
Exterior Photosensor	All	\$42.58	12.1	0	n/a	\$2.88	\$2.27	1.60	\$25.62	n/a	n/a	n/a	n/a

Table 54: CZ 5 (PG&E/SoCalGas) - Single Family Efficiency Upgrade Cost-Effectiveness Results

	N. A.	Measure	Electricity	Gas	GHG Savings	-	v Cost ings	Custome	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$4,806	152	45	484	\$112	\$92	0.51	-\$2,623	0.58	-\$2,032	0.86	-\$675
R49 Attic & Air Sealing Package	1978-1991	\$4,348	91	24	259	\$59	\$49	0.30	-\$3,426	0.38	-\$2,714	0.53	-\$2,061
	1992-2010	\$3,326	11	11	117	\$18	\$15	0.12	-\$3,284	0.19	-\$2,678	0.23	-\$2,569
	Pre-1978	\$4,015	163	56	603	\$133	\$110	0.73	-\$1,211	0.91	-\$368	1.22	\$874
R49 Attic & Duct Sealing Package	1978-1991	\$3,557	96	30	316	\$69	\$57	0.43	-\$2,293	0.59	-\$1,442	0.75	-\$904
e cannig r achaige	1992-2010	\$2,275	10	10	105	\$16	\$14	0.16	-\$2,148	0.27	-\$1,656	0.30	-\$1,593
R49 Attic. Air	Pre-1978	\$5,489	173	69	736	\$155	\$128	0.62	-\$2,316	0.80	-\$1,073	1.04	\$226
Sealing & Duct	1978-1991	\$5,031	103	38	398	\$81	\$67	0.36	-\$3,643	0.51	-\$2,447	0.63	-\$1,868
Sealing Package	1992-2010	\$3,749	14	15	160	\$24	\$20	0.15	-\$3,597	0.25	-\$2,813	0.27	-\$2,727
R49 Attic, Air	Pre-1978	\$8,792	190	89	945	\$189	\$157	0.48	-\$5,173	0.66	-\$3,008	0.80	-\$1,769
Sealing & New	1978-1991	\$8,334	117	55	575	\$108	\$89	0.29	-\$6,682	0.45	-\$4,566	0.51	-\$4,065
Ducts Package	1992-2010	\$7,312	23	25	260	\$39	\$33	0.12	-\$7,231	0.22	-\$5,711	0.23	-\$5,662
Advanced Envelope Package	Pre-1978	\$18,659	226	124	1,302	\$245	\$204	0.29	-\$14,840	0.42	- \$10,731	0.50	-\$9,309
Water Heating Package	All Vintages	\$208	0	16	n/a	\$24	\$22	1.41	\$96	n/a	n/a	n/a	n/a

Table 55: CZ 5 (PG&E/SoCalGas) - Single Family Efficiency Packages Cost-Effectiveness Results

	Martana	Measure	Electricity	Gas	GHG Savings	Utility Sav	r Cost ings	Custome	er On-Bill	2019) TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
_	Pre-1978		3,463		259	\$851	\$672	2.82	\$13,000	2.08	\$6,961	1.71	\$4,619
Prescriptive PV System	1978-1991	\$6,467	3,463	0	259	\$828	\$654	2.74	\$12,459	2.08	\$6,955	1.71	\$4,617
i v cycloini	1992-2010		3,463		259	\$818	\$646	2.71	\$12,219	2.08	\$6,955	1.71	\$4,617
	Pre-1978		3,268		921	\$868	\$685	1.07	\$1,350	1.14	\$2,519	0.90	-\$1,802
PV + Battery	1978-1991	\$17,840	3,269	0	923	\$845	\$667	1.04	\$797	1.14	\$2,502	0.91	-\$1,554
	1992-2010		3,270		923	\$834	\$659	1.03	\$554	1.14	\$2,505	0.92	-\$1,358

Table 56: CZ 5 (PG&E/SoCalGas) - Single Family PV & Battery Cost-Effectiveness Results

Table 57: CZ 5 (PG&E/SoCalGas) - Single Family Equipment Fuel Substitution Cost-Effectiveness Results

		Measure	Electricity	Gas	GHG Savings	Utility Savi	r Cost ings	Custom	er On-Bill	2019	Ð TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
Heat Pump at	Pre-1978		-2,800	213	797	-\$484	-\$366	0	-\$11,529	0	-\$6,740	0	-\$1,959
HVAC	1978-1991	\$501	-2,205	154	479	-\$393	-\$299	0	-\$9,525	0	-\$6,282	0	-\$2,495
Replacement	1992-2010		-1,828	138	514	-\$303	-\$230	0	-\$7,438	0	-\$4,710	0	-\$1,512
High-Effic. Heat	Pre-1978		-2,469	213	945	-\$385	-\$288	0	-\$12,704	0	-\$7,696	0.08	-\$3,435
Pump at HVAC	1978-1991	\$3,749	-1,968	154	587	-\$322	-\$244	0	-\$11,369	0	-\$7,851	0	-\$4,478
Replacement	1992-2010		-1,624	138	604	-\$242	-\$182	0	-\$9,514	0	-\$6,463	0	-\$3,732
Heat Pump at	Pre-1978		663	213	1,056	\$429	\$354	1.38	\$2,931	1.04	\$264	1.38	\$2,678
HVAC Replacement +	1978-1991	\$6,969	1,258	154	738	\$507	\$411	1.60	\$4,637	1.10	\$705	1.31	\$2,133
PV	1992-2010		1,634	138	773	\$593	\$477	1.86	\$6,621	1.33	\$2,298	0.99	-\$60
HVAC HP	Pre-1978		663	213	1,056	\$429	\$354	0.94	-\$641	0.71	-\$2,917	0.95	-\$503
Replacement w/ Panel Upgrade	1978-1991	\$10,150	1,258	154	738	\$507	\$411	1.09	\$1,065	0.76	-\$2,476	0.90	-\$1,048
+ PV	1992-2010		1,634	138	773	\$593	\$477	1.27	\$3,049	0.91	-\$883	0.99	-\$60
HPWH at Water	Pre-1978		-1,304	164	1,292	-\$212	-\$155	0	-\$7,548	0	-\$3,945	1.31	\$802
Heater	1978-1991	\$2,594	-1,308	165	1,299	-\$222	-\$163	0	-\$7,793	0	-\$3,879	1.32	\$831
Replacement	1992-2010		-1,309	165	1,301	-\$228	-\$169	0	-\$7,962	0	-\$3,870	1.32	\$819
NEEA Tier 3	Pre-1978		-987	163	1,405	-\$110	-\$75	0	-\$5,324	0.21	-\$2,181	1.81	\$2,254
HPWH at	1978-1991	\$2,775	-990	164	1,415	-\$118	-\$82	0	-\$5,548	0.23	-\$2,147	1.83	\$2,312
Replacement	1992-2010		-992	165	1,416	-\$125	-\$88	0	-\$5,725	0.23	-\$2,124	1.82	\$2,289
HPWH at Water	Pre-1978		2,158	164	1,551	\$780	\$628	1.87	\$8,783	1.36	\$3,227	1.62	\$5,620
Heater Replacement +	1978-1991	\$9,061	2,154	165	1,559	\$765	\$615	1.84	\$8,410	1.36	\$3,290	1.62	\$5,646
PV	1992-2010		2,153	165	1,561	\$756	\$608	1.82	\$8,187	1.36	\$3,302	1.62	\$5,635
HPWH	Pre-1978		2,158	164	1,551	\$780	\$628	1.38	\$5,211	1.00	\$46	1.20	\$2,439
Replacement w/ Panel Upgrade	1978-1991	\$12,242	2,154	165	1,559	\$765	\$615	1.36	\$4,838	1.01	\$109	1.20	\$2,465
+ PV	1992-2010		2,153	165	1,561	\$756	\$608	1.34	\$4,615	1.01	\$121	1.20	\$2,454

	Minterre	Measure	Electricity	Gas	GHG Savings	-	v Cost ings	Custome	er On-Bill	2019) TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978		3,463	0	259	\$851	\$672	1.72	\$8,406	1.27	\$2,870	1.05	\$528
PV + Electric Ready Pre-Wire	1978-1991	\$10,558	3,463	0	259	\$828	\$654	1.67	\$7,865	1.27	\$2,864	1.05	\$526
	1992-2010		3,463	0	259	\$818	\$646	1.65	\$7,625	1.27	\$2,864	1.05	\$526

Climate Zone 6:

Note: Values in red and grey rows indicate option is not cost-effective with B/C ratio less than 1. Cells with "n/a" reflect lighting and water heating efficiency measures and packages that did not look at TDV cost effectiveness or GHG impacts.

	Minterra	Measure	Electricity	Gas	GHG Savings		v Cost ings	Custom	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$3,332	547	18	273	\$218	\$174	1.40	\$1,489	1.60	\$1,987	1.32	\$1,050
R-49 Attic Insulation	1978-1991	\$2,874	254	7	112	\$97	\$77	0.72	-\$909	0.82	-\$505	0.72	-\$808
modiation	1992-2010	\$1,852	54	3	43	\$21	\$17	0.25	-\$1,567	0.34	-\$1,227	0.36	-\$1,193
	Pre-1978		-12	5	50	\$1	\$1	0.02	-\$1,614	0.23	-\$1,131	0.22	-\$1,146
Reduced Infiltration	1978-1991	\$1,474	-7	3	32	\$1	\$1	0.02	-\$1,625	0.13	-\$1,275	0.15	-\$1,246
initiation	1992-2010		-3	2	20	\$1	\$1	0.03	-\$1,613	0.10	-\$1,324	0.09	-\$1,347
	Pre-1978	\$683	182	8	121	\$78	\$63	2.46	\$1,123	3.30	\$1,572	3.18	\$1,486
Duct Sealing	1978-1991	\$683	98	4	63	\$41	\$33	1.29	\$224	1.72	\$492	1.89	\$610
	1992-2010	\$423	12	1	14	\$5	\$4	0.27	-\$348	0.52	-\$201	0.55	-\$190
	Pre-1978		340	16	229	\$147	\$118	0.79	-\$933	1.08	\$309	1.03	\$133
New Ducts	1978-1991	\$3,986	227	9	147	\$96	\$77	0.52	-\$2,161	0.73	-\$1,083	0.76	-\$944
	1992-2010		41	4	52	\$19	\$15	0.10	-\$4,019	0.20	-\$3,200	0.21	-\$3,145
	Pre-1978		277	0	52	\$104	\$82	2.90	\$1,611	3.71	\$1,566	2.32	\$1,025
Cool Roof	1978-1991	\$778	132	-2	5	\$47	\$37	1.30	\$251	1.51	\$293	1.12	\$92
	1992-2010		54	-2	-2	\$16	\$13	0.45	-\$470	0.50	-\$286	0.54	-\$360
R-13 Wall Insulation	Pre-1978	\$3,360	41	18	185	\$34	\$29	0.23	-\$2,908	0.51	-\$1,643	0.44	-\$1,877
) A / ins dia was	Pre-1978	¢0.040	643	-3	76	\$235	\$185	0.50	-\$5,459	0.48	-\$5,089	0.45	-\$5,440
Windows	1978-1991	\$9,810	521	-3	83	\$192	\$151	0.41	-\$6,472	0.39	-\$5,953	0.44	-\$5,515
LED lamp vs CFL	All	\$2.26	1.2	0	n/a	\$0.31	\$0.25	3.27	\$5.11	n/a	n/a	n/a	n/a
Exterior Photosensor	All	\$42.58	12.1	0	n/a	\$2.00	\$1.58	1.11	\$4.84	n/a	n/a	n/a	n/a

Table 58: CZ 6 - Single Family Efficiency Upgrade Cost-Effectiveness Results

		Measure	Electricity	Gas	GHG Savings	-	/ Cost ings	Custom	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO2e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$4,806	536	24	327	\$220	\$176	0.98	-\$104	1.18	\$876	0.99	-\$64
R49 Attic & Air Sealing Package	1978-1991	\$4,348	245	10	142	\$97	\$78	0.48	-\$2,551	0.59	-\$1,771	0.52	-\$2,083
e camig raciage	1992-2010	\$3,326	52	5	64	\$23	\$19	0.15	-\$3,174	0.24	-\$2,540	0.24	-\$2,540
	Pre-1978	\$4,015	668	25	373	\$272	\$218	1.45	\$2,019	1.75	\$3,029	1.54	\$2,176
R49 Attic & Duct Sealing Package	1978-1991	\$3,557	327	11	165	\$128	\$103	0.77	-\$914	0.94	-\$208	0.88	-\$411
e calling r achage	1992-2010	\$2,275	63	4	56	\$25	\$21	0.24	-\$1,938	0.36	-\$1,460	0.38	-\$1,411
R49 Attic. Air	Pre-1978	\$5,489	657	30	419	\$272	\$219	1.06	\$398	1.34	\$1,875	1.18	\$993
Sealing & Duct	1978-1991	\$5,031	317	13	191	\$127	\$102	0.54	-\$2,580	0.70	-\$1,507	0.66	-\$1,735
Sealing Package	1992-2010	\$3,749	61	6	76	\$27	\$22	0.16	-\$3,546	0.26	-\$2,781	0.26	-\$2,764
R49 Attic. Air	Pre-1978	\$8,792	777	36	511	\$325	\$261	0.79	-\$2,044	1.04	\$346	0.94	-\$510
Sealing & New	1978-1991	\$8,334	428	18	265	\$175	\$140	0.45	-\$5,151	0.61	-\$3,266	0.59	-\$3,396
Ducts Package	1992-2010	\$7,312	86	8	109	\$38	\$31	0.11	-\$7,273	0.20	-\$5,840	0.21	-\$5,777
Advanced Envelope Package	Pre-1978	\$18,659	1,056	52	731	\$445	\$358	0.51	-\$10,204	0.67	-\$6,243	0.62	-\$7,131
Water Heating Package	All Vintages	\$208	0	17	n/a	\$23	\$21	1.38	\$88	n/a	n/a	n/a	n/a

Table 59: CZ 6 - Single Family Efficiency Packages Cost-Effectiveness Results

	Nr. (Measure	Electricity	Gas	GHG Savings	Utility Sav	r Cost ings	Custom	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	ሮፖ ዕድር	3,858		306	\$800	\$631	2.43	\$11,140	1.92	\$6,468	1.81	\$5,708
Prescriptive PV System	1978-1991	\$7,056	3,858	0	306	\$771	\$609	2.34	\$10,455	1.91	\$6,454	1.81	\$5,687
i v cycloin	1992-2010	\$6,963ª	3,806		302	\$724	\$571	2.23	\$9,436	1.91	\$6,445	1.80	\$5,592
	Pre-1978		3,643		992	\$969	\$765	1.16	\$3,099	1.11	\$2,084	0.97	-\$578
PV + Battery	1978-1991	\$18,428	3,641	0	1,016	\$938	\$740	1.12	\$2,356	1.12	\$2,150	0.98	-\$414
	1992-2010		3,640		1,054	\$788	\$622	0.94	-\$1,198	1.10	\$1,853	1.03	\$612

Table 60: CZ 6 - Single Family PV & Battery Cost-Effectiveness Results

^aThe 1992-2010 vintage was evaluated with a 2.18kW PV system instead of a 2.22kWh system in the other vintages to avoid over-generation of PV electricity on an annual basis.

Table 61: CZ 6 - Single Family Equipment Fuel Substitution Cost-Effectiveness Results

		Measure	Electricity	Gas	GHG Savings	Utility Savi	r Cost ings	Custom	er On-Bill	2019	9 TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
Heat Pump at	Pre-1978		-700	67	311	-\$121	-\$87	0	-\$3,158	0	-\$1,377	0.97	-\$18
HVAC	1978-1991	\$501	-435	40	171	-\$76	-\$55	0	-\$2,195	0	-\$1,216	0.33	-\$334
Replacement	1992-2010		-365	34	149	-\$61	-\$44	0	-\$1,865	0	-\$1,034	0.34	-\$329
High-Effic. Heat	Pre-1978		-402	67	417	-\$21	-\$7	0	-\$4,281	0.44	-\$2,087	0.77	-\$852
Pump at HVAC	1978-1991	\$3,749	-240	40	243	-\$9	-\$2	0	-\$4,112	0.28	-\$2,718	0.52	-\$1,802
Replacement	1992-2010		-250	34	198	-\$24	-\$15	0	-\$4,504	0.15	-\$3,185	0.35	-\$2,450
Heat Pump at	Pre-1978		3,158	67	617	\$702	\$563	2.02	\$8,529	1.68	\$5,108	1.75	\$5,693
HVAC Replacement +	1978-1991	\$7,557	3,423	40	478	\$708	\$564	2.03	\$8,582	1.69	\$5,247	1.71	\$5,353
PV	1992-2010		3,493	34	455	\$696	\$554	1.99	\$8,261	1.72	\$5,425	1.71	\$5,336
HVAC HP	Pre-1978		3,158	67	617	\$702	\$563	1.42	\$4,957	1.18	\$1,927	1.23	\$2,512
Replacement w/ Panel Upgrade	1978-1991	\$10,738	3,423	40	478	\$708	\$564	1.42	\$5,010	1.19	\$2,066	1.20	\$2,172
+ PV	1992-2010		3,493	34	455	\$696	\$554	1.39	\$4,689	1.21	\$2,244	1.20	\$2,155
HPWH at Water	Pre-1978		-971	153	1,264	-\$90	-\$52	0	-\$4,451	0.21	-\$2,041	1.68	\$1,764
Heater	1978-1991	\$2,594	-975	153	1,267	-\$88	-\$50	0	-\$4,390	0.20	-\$2,073	1.68	\$1,758
Replacement	1992-2010		-984	154	1,267	-\$84	-\$47	0	-\$4,311	0.18	-\$2,121	1.66	\$1,724
NEEA Tier 3	Pre-1978		-798	153	1,347	-\$34	-\$8	0	-\$3,329	0.59	-\$1,150	1.94	\$2,609
HPWH at	1978-1991	\$2,775	-803	153	1,350	-\$32	-\$6	0	-\$3,272	0.58	-\$1,176	1.94	\$2,612
Replacement	1992-2010		-813	153	1,350	-\$30	-\$4	0	-\$3,223	0.56	-\$1,234	1.93	\$2,568
HPWH at Water	Pre-1978		2,887	153	1,570	\$771	\$627	1.76	\$8,125	1.48	\$4,626	1.79	\$7,656
Heater Replacement +	1978-1991	\$9,650	2,883	153	1,573	\$741	\$604	1.69	\$7,425	1.47	\$4,583	1.79	\$7,630
PV	1992-2010	1	2,874	154	1,573	\$701	\$572	1.61	\$6,478	1.47	\$4,525	1.79	\$7,576
HPWH	Pre-1978		2,887	153	1,570	\$771	\$627	1.32	\$4,553	1.11	\$1,445	1.35	\$4,475
Replacement w/ Panel Upgrade	1978-1991	\$12,831	2,883	153	1,573	\$741	\$604	1.27	\$3,853	1.11	\$1,402	1.35	\$4,449
+ PV	1992-2010		2,874	154	1,573	\$701	\$572	1.20	\$2,906	1.10	\$1,344	1.34	\$4,395

	Minterre	Measure	Electricity	Gas	GHG Savings	-	v Cost ings	Custome	er On-Bill	2019) TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978		3,858	0	306	\$800	\$631	1.53	\$6,546	1.21	\$2,377	1.15	\$1,617
PV + Electric Ready Pre-Wire	1978-1991	\$11,147	3,858	0	306	\$771	\$609	1.47	\$5,861	1.21	\$2,363	1.14	\$1,596
	1992-2010		3,806	0	302	\$724	\$571	1.38	\$4,740	1.21	\$2,354	1.13	\$1,409

Climate Zone 7:

Note: Values in red and grey rows indicate option is not cost-effective with B/C ratio less than 1. Cells with "n/a" reflect lighting and water heating efficiency measures and packages that did not look at TDV cost effectiveness or GHG impacts.

	Minterre	Measure	Electricity	Gas	GHG Savings		v Cost ings	Custom	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO2e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$3,332	515	14	241	\$286	\$228	1.83	\$3,098	1.26	\$856	1.11	\$351
R-49 Attic Insulation	1978-1991	\$2,874	227	5	94	\$124	\$99	0.92	-\$266	0.69	-\$898	0.56	-\$1,277
	1992-2010	\$1,852	49	2	37	\$30	\$24	0.34	-\$1,367	0.36	-\$1,190	0.28	-\$1,337
	Pre-1978		-23	4	30	-\$5	-\$4	0	-\$1,768	0.05	-\$1,393	0.02	-\$1,439
Reduced Infiltration	1978-1991	\$1,474	-12	2	18	-\$3	-\$2	0	-\$1,711	0.02	-\$1,445	0.04	-\$1,422
	1992-2010		-4	2	13	\$0	\$0	0.01	-\$1,642	0.03	-\$1,437	0.04	-\$1,419
	Pre-1978	\$683	149	5	86	\$93	\$74	2.89	\$1,449	1.85	\$579	1.87	\$596
Duct Sealing	1978-1991	\$683	76	2	41	\$48	\$38	1.50	\$381	0.94	-\$41	0.99	-\$9
	1992-2010	\$423	10	1	9	\$7	\$5	0.33	-\$318	0.21	-\$334	0.30	-\$296
	Pre-1978		318	11	176	\$196	\$156	1.05	\$213	0.67	-\$1,324	0.67	-\$1,307
New Ducts	1978-1991	\$3,986	218	6	114	\$136	\$108	0.72	-\$1,241	0.46	-\$2,168	0.49	-\$2,033
	1992-2010		44	2	38	\$28	\$23	0.15	-\$3,796	0.10	-\$3,600	0.14	-\$3,442
	Pre-1978		278	0	57	\$146	\$115	4.07	\$2,607	2.97	\$1,137	2.01	\$783
Cool Roof	1978-1991	\$778	119	-2	11	\$63	\$49	1.74	\$625	1.40	\$232	0.83	-\$136
	1992-2010		51	-1	3	\$25	\$19	0.68	-\$274	0.72	-\$162	0.43	-\$447
R-13 Wall Insulation	Pre-1978	\$3,360	26	14	137	\$35	\$30	0.23	-\$2,887	0.27	-\$2,447	0.28	-\$2,418
) A (inclusion	Pre-1978	¢0.040	541	-6	43	\$279	\$219	0.60	-\$4,439	0.34	-\$6,483	0.29	-\$6,984
Windows	1978-1991	\$9,810	416	-4	63	\$226	\$178	0.49	-\$5,670	0.35	-\$6,328	0.27	-\$7,195
LED lamp vs CFL	All	\$2.26	1.2	0	n/a	\$0.44	\$0.35	4.63	\$8.20	n/a	n/a	n/a	n/a
Exterior Photosensor	All	\$42.58	12.1	0	n/a	\$2.76	\$2.18	1.54	\$22.81	n/a	n/a	n/a	n/a

Table 62: CZ 7 - Single Family Efficiency Upgrade Cost-Effectiveness Results

		Measure	Electricity	Gas	GHG Savings	-	v Cost ings	Custom	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$4,806	500	18	274	\$284	\$227	1.26	\$1,402	0.89	-\$531	0.79	-\$999
R49 Attic & Air Sealing Package	1978-1991	\$4,348	215	8	112	\$121	\$96	0.59	-\$1,993	0.46	-\$2,349	0.38	-\$2,708
eessing racitage	1992-2010	\$3,326	45	4	50	\$30	\$24	0.19	-\$3,008	0.21	-\$2,615	0.17	-\$2,759
	Pre-1978	\$4,015	615	19	310	\$351	\$279	1.86	\$3,869	1.27	\$1,086	1.17	\$702
R49 Attic & Duct Sealing Package	1978-1991	\$3,557	288	7	130	\$162	\$129	0.97	-\$122	0.71	-\$1,045	0.62	-\$1,355
county r conage	1992-2010	\$2,275	57	3	45	\$35	\$28	0.33	-\$1,712	0.32	-\$1,547	0.28	-\$1,644
R49 Attic. Air	Pre-1978	\$5,489	600	22	339	\$348	\$278	1.35	\$2,168	0.94	-\$304	0.88	-\$674
Sealing & Duct	1978-1991	\$5,031	277	9	146	\$159	\$127	0.68	-\$1,835	0.50	-\$2,496	0.45	-\$2,786
Sealing Package	1992-2010	\$3,749	54	4	59	\$36	\$29	0.20	-\$3,349	0.21	-\$2,977	0.18	-\$3,064
R49 Attic. Air	Pre-1978	\$8,792	735	26	414	\$433	\$345	1.05	\$489	0.72	-\$2,461	0.69	-\$2,713
Sealing & New	1978-1991	\$8,334	401	12	209	\$237	\$189	0.61	-\$3,694	0.42	-\$4,820	0.41	-\$4,919
Ducts Package	1992-2010	\$7,312	83	6	84	\$55	\$44	0.16	-\$6,893	0.14	-\$6,304	0.15	-\$6,247
Advanced Envelope Package	Pre-1978	\$18,659	922	37	565	\$552	\$441	0.63	-\$7,734	0.48	-\$9,611	0.43	-\$10,707
Water Heating Package	All Vintages	\$208	0	17	n/a	\$31	\$29	1.86	\$200	n/a	n/a	n/a	n/a

Table 63: CZ 7 - Single Family Efficiency Packages Cost-Effectiveness Results

	Martana	Measure	Electricity	Gas	GHG Savings	Utility Savi	r Cost ings	Custom	er On-Bill	2019	9 TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978		3,425		289	\$1,151	\$909	3.69	\$19,872	2.00	\$6,692	1.67	\$4,494
Prescriptive PV System	1978-1991	\$6,685	3,425	0	289	\$1,192	\$941	3.82	\$20,837	2.00	\$6,683	1.67	\$4,474
i v oyotom	1992-2010		3,425		289	\$1,158	\$914	3.71	\$20,029	2.00	\$6,680	1.67	\$4,457
	Pre-1978		3,237		871	\$1,230	\$971	1.50	\$9,690	1.12	\$2,169	0.88	-\$2,189
PV + Battery	1978-1991	\$18,057	3,237	0	892	\$1,270	\$1,003	1.55	\$10,633	1.13	\$2,302	0.90	-\$1,794
	1992-2010		3,235		923	\$1,174	\$927	1.43	\$8,352	1.12	\$2,100	0.95	-\$844

Table 64: CZ 7 - Single Family PV & Battery Cost-Effectiveness Results

Utility Cost Customer On-Bill 2019 TDV 2022 TDV Electricity Gas Savings Measure **GHG Savings** Measure Vintage Savings Savings Cost (\$) (lb CO₂e) Avg B/C B/C B/C (kWh) (therm) NPV NPV NPV Year 1 Ratio Ratio Annual Ratio Pre-1978 -441 44 212 -\$142 -\$106 0 -\$3.716 0 -\$715 0.91 -\$43 Heat Pump at HVAC 1978-1991 \$501 -258 24 106 -\$100 -\$75 0 -\$2.803 0 -\$703 0.34 -\$331 Replacement 0 1992-2010 -217 21 93 -\$83 -\$63 0 -\$2.428 -\$674 0.33 -\$334 -\$4,250 0.39 -\$2,303 Pre-1978 -194 44 301 -\$16 -\$6 0 0.58 -\$1,580 High-Effic. Heat Pump at HVAC 1978-1991 24 -\$8 0 0.24 \$3,749 -96 167 -\$14 -\$4.300 -\$2.845 0.38 -\$2.335 Replacement -122 21 -\$25 0 0.25 1992-2010 134 -\$35 -\$4.801 0.10 -\$3.363 -\$2.796 Pre-1978 2,984 44 501 \$1.058 \$841 3.18 \$17,298 1.83 \$5,983 1.62 \$4,451 Heat Pump at HVAC 1978-1991 \$7.186 3,168 24 395 \$1,119 \$887 3.35 \$18,661 1.83 \$5,983 1.58 \$4,143 Replacement + ΡV 1992-2010 3.209 21 382 \$1.110 \$879 3.32 \$18.425 1.84 \$6.009 1.57 \$4,125 HVAC HP 2,984 44 501 \$1.058 \$841 2.19 \$13,726 1.27 \$2,802 1.12 \$1,270 Pre-1978 Replacement w/ 24 1.27 1978-1991 \$10,367 3.168 395 \$1.119 \$887 2.31 \$15.089 \$2,802 1.09 \$962 Panel Upgrade + PV 1992-2010 3,209 21 382 \$1,110 \$879 2.29 \$14,853 1.27 \$2,828 1.09 \$944 Pre-1978 -953 153 1,267 -\$92 -\$52 0 -\$4,445 0.18 -\$2,116 1.73 \$1,897 HPWH at Water \$2.594 -961 153 -\$87 -\$48 0 -\$4.327 0.18 1.76 Heater 1978-1991 1.274 -\$2,121 \$1.966 Replacement 1992-2010 -969 153 1,272 -\$85 0 -\$4,273 0.17 -\$2,142 \$1.917 -\$46 1.74 Pre-1978 -777 153 1,352 -\$18 \$7 0.07 -\$2,878 0.56 -\$1,228 1.97 \$2,698 **NEEA Tier 3** HPWH at 1978-1991 \$2.775 -786 153 1,355 \$10 -\$2,791 0.55 -\$1,242 -\$14 0.10 1.97 \$2,686 Replacement 1992-2010 -796 153 1.353 -\$14 \$10 0.10 -\$2.792 0.54 -\$1.265 1.95 \$2.638 Pre-1978 2.472 153 1,556 \$1.047 \$847 2.47 \$15.138 1.51 \$4,766 1.71 \$6,561 HPWH at Water Heater 1978-1991 \$831 \$14,639 \$9,279 2,464 153 1,562 \$1.026 2.42 1.51 \$4,755 1.71 \$6,613 Replacement + ΡV 1992-2010 2.456 153 1.561 \$985 \$798 2.33 \$13.665 1.51 \$4.732 1.71 \$6.549 HPWH Pre-1978 2.472 153 1,556 \$1.047 \$847 1.83 \$11.566 1.13 \$1,585 1.27 \$3.380 Replacement w/ 1978-1991 \$12,460 2,464 153 1,562 \$1.026 \$831 1.80 \$11,067 1.13 \$1,574 1.28 \$3,432 Panel Upgrade + PV 1992-2010 2.456 153 1.561 \$985 \$798 1.73 \$10.093 1.12 \$1.551 1.27 \$3.368

Table 65: CZ 7 - Single Family Equipment Fuel Substitution Cost-Effectiveness Results

	Minterra	Measure	Electricity	Gas	GHG Savings	-	v Cost ings	Custome	er On-Bill	2019) TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978		3,425	0	289	\$1,151	\$909	2.27	\$15,279	1.24	\$2,601	1.04	\$403
PV + Electric Ready Pre-Wire	1978-1991	\$10,776	3,425	0	289	\$1,192	\$941	2.36	\$16,243	1.24	\$2,592	1.04	\$383
	1992-2010		3,425	0	289	\$1,158	\$914	2.29	\$15,435	1.24	\$2,589	1.03	\$366

Climate Zone 8:

Note: Values in red and grey rows indicate option is not cost-effective with B/C ratio less than 1. Cells with "n/a" reflect lighting and water heating efficiency measures and packages that did not look at TDV cost effectiveness or GHG impacts.

	Minterra	Measure	Electricity	Gas	GHG Savings		v Cost ings	Custom	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO2e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$3,332	913	15	246	\$328	\$261	2.09	\$4,075	1.84	\$2,796	2.06	\$3,541
R-49 Attic Insulation	1978-1991	\$2,874	487	7	119	\$176	\$140	1.30	\$973	1.19	\$555	1.38	\$1,099
	1992-2010	\$1,852	124	3	45	\$48	\$39	0.56	-\$921	0.63	-\$694	0.69	-\$568
	Pre-1978		9	4	42	\$7	\$6	0.12	-\$1,463	0.29	-\$1,045	0.34	-\$976
Reduced Infiltration	1978-1991	\$1,474	-1	3	20	\$2	\$2	0.04	-\$1,596	0.22	-\$1,143	0.30	-\$1,030
initiation	1992-2010		1	2	14	\$2	\$2	0.03	-\$1,599	0.15	-\$1,252	0.20	-\$1,174
	Pre-1978	\$683	575	7	151	\$217	\$172	6.74	\$4,402	7.33	\$4,326	9.09	\$5,527
Duct Sealing	1978-1991	\$683	340	3	87	\$130	\$103	4.04	\$2,330	4.55	\$2,422	5.75	\$3,243
	1992-2010	\$423	58	1	21	\$23	\$18	1.16	\$77	1.42	\$179	1.82	\$346
	Pre-1978		1,040	14	280	\$394	\$313	2.09	\$4,901	2.32	\$5,257	2.89	\$7,516
New Ducts	1978-1991	\$3,986	775	8	201	\$298	\$236	1.58	\$2,603	1.82	\$3,276	2.29	\$5,134
	1992-2010		202	3	75	\$82	\$65	0.43	-\$2,533	0.55	-\$1,785	0.67	-\$1,304
	Pre-1978		422	-2	27	\$144	\$113	3.99	\$2,541	4.09	\$1,782	3.94	\$2,284
Cool Roof	1978-1991	\$778	303	-2	28	\$106	\$83	2.95	\$1,656	3.35	\$1,358	2.99	\$1,550
	1992-2010		135	-1	12	\$48	\$38	1.34	\$288	1.68	\$394	1.59	\$461
R-13 Wall Insulation	Pre-1978	\$3,360	151	16	181	\$71	\$58	0.46	-\$2,038	0.69	-\$1,053	0.77	-\$776
Mindawa	Pre-1978	¢0.040	1,105	-2	91	\$375	\$296	0.81	-\$2,147	0.71	-\$2,851	0.82	-\$1,791
Windows	1978-1991	\$9,810	891	-1	94	\$313	\$247	0.67	-\$3,611	0.65	-\$3,479	0.73	-\$2,675
LED lamp vs CFL	All	\$2.26	1.2	0	n/a	\$0.35	\$0.28	3.68	\$6.04	n/a	n/a	n/a	n/a
Exterior Photosensor	All	\$42.58	12.1	0	n/a	\$2.00	\$1.58	1.11	\$4.84	n/a	n/a	n/a	n/a

Table 66: CZ 8 - Single	Family Efficiency	Upgrade (Cost-Effectiveness	Results
-------------------------	-------------------	-----------	---------------------------	---------

	Martana	Measure	Electricity	Gas	GHG Savings		v Cost ings	Custom	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$4,806	916	19	284	\$333	\$265	1.48	\$2,564	1.38	\$1,829	1.58	\$2,810
R49 Attic & Air Sealing Package	1978-1991	\$4,348	485	10	139	\$178	\$142	0.87	-\$624	0.85	-\$639	1.02	\$97
eessing racitage	1992-2010	\$3,326	125	4	59	\$51	\$41	0.33	-\$2,520	0.41	-\$1,961	0.47	-\$1,759
	Pre-1978	\$4,015	1,382	20	385	\$508	\$404	2.69	\$7,605	2.63	\$6,529	3.09	\$8,403
R49 Attic & Duct Sealing Package	1978-1991	\$3,557	772	10	195	\$287	\$228	1.71	\$2,840	1.75	\$2,655	2.13	\$4,025
county r conage	1992-2010	\$2,275	175	3	63	\$69	\$55	0.64	-\$908	0.74	-\$587	0.89	-\$242
R49 Attic. Air	Pre-1978	\$5,489	1,377	24	416	\$510	\$406	1.98	\$6,011	2.01	\$5,533	2.38	\$7,597
Sealing & Duct	1978-1991	\$5,031	779	12	222	\$292	\$232	1.23	\$1,300	1.28	\$1,403	1.55	\$2,767
Sealing Package	1992-2010	\$3,749	177	5	79	\$71	\$57	0.41	-\$2,498	0.51	-\$1,854	0.59	-\$1,523
R49 Attic, Air	Pre-1978	\$8,792	1,820	29	548	\$681	\$542	1.65	\$6,373	1.73	\$6,410	2.08	\$9,462
Sealing & New	1978-1991	\$8,334	1,186	16	330	\$450	\$357	1.15	\$1,360	1.26	\$2,129	1.54	\$4,522
Ducts Package	1992-2010	\$7,312	314	7	131	\$127	\$101	0.37	-\$5,172	0.46	-\$3,928	0.55	-\$3,262
Advanced Envelope Package	Pre-1978	\$18,659	2,129	44	706	\$799	\$636	0.91	-\$1,862	0.98	-\$355	1.13	\$2,444
Water Heating Package	All Vintages	\$208	0	17	n/a	\$23	\$22	1.39	\$90	n/a	n/a	n/a	n/a

Table 67: CZ 8 - Single Family Efficiency Packages Cost-Effectiveness Results

	Martana	Measure	Electricity	Gas	GHG Savings	-	r Cost ings	Custom	er On-Bill	2019) TDV	2022	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978		3,929		312	\$895	\$706	2.57	\$12,934	1.96	\$7,166	1.87	\$6,506
Prescriptive PV System	1978-1991	\$7,458	3,929	0	312	\$886	\$699	2.54	\$12,728	1.96	\$7,140	1.87	\$6,466
i v oyotom	1992-2010		3,929		312	\$813	\$642	2.34	\$11,013	1.95	\$7,111	1.86	\$6,414
	Pre-1978		3,719		873	\$1,070	\$845	1.25	\$5,041	1.09	\$1,787	0.98	-\$284
PV + Battery	1978-1991	\$18,831	3,714	0	906	\$1,067	\$842	1.25	\$4,974	1.12	\$2,294	1.00	-\$42
	1992-2010		3,710		976	\$1,001	\$790	1.17	\$3,391	1.15	\$2,773	1.01	\$238

Table 68: CZ 8 - Single Family PV & Battery Cost-Effectiveness Results

Table 69: CZ 8 - Single Family Equipment Fuel Substitution Cost-Effectiveness Results

	Minterra	Measure	Electricity	Gas	GHG Savings		r Cost ings	Custom	er On-Bill	2019	Ð TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO₂e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
Heat Pump at	Pre-1978		-568	55	250	-\$96	-\$69	0	-\$2,607	0	-\$692	0.81	-\$95
HVAC	1978-1991	\$501	-362	33	145	-\$66	-\$47	0	-\$1,967	0	-\$700	0.33	-\$334
Replacement	1992-2010		-296	27	120	-\$56	-\$40	0.00	-\$1,756	0	-\$660	0.29	-\$355
High-Effic. Heat	Pre-1978		-15	55	401	\$97	\$83	0.62	-\$1,556	1.03	\$108	1.30	\$1,124
Pump at HVAC	1978-1991	\$3,749	66	33	264	\$87	\$73	0.54	-\$1,863	0.81	-\$719	1.01	\$33
Replacement	1992-2010		-9	27	215	\$47	\$40	0.30	-\$2,843	0.56	-\$1,658	0.71	-\$1,079
Heat Pump at	Pre-1978		3,361	55	562	\$807	\$644	2.20	\$10,520	1.81	\$6,486	1.81	\$6,408
HVAC Replacement +	1978-1991	\$7,960	3,567	33	457	\$806	\$640	2.18	\$10,412	1.81	\$6,448	1.77	\$6,128
PV	1992-2010		3,633	27	432	\$771	\$612	2.09	\$9,579	1.81	\$6,465	1.76	\$6,059
HVAC HP	Pre-1978		3,361	55	562	\$807	\$644	1.56	\$6,948	1.30	\$3,305	1.29	\$3,227
Replacement w/ Panel Upgrade	1978-1991	\$11,141	3,567	33	457	\$806	\$640	1.55	\$6,840	1.29	\$3,267	1.26	\$2,947
+ PV	1992-2010		3,633	27	432	\$771	\$612	1.49	\$6,007	1.29	\$3,284	1.26	\$2,878
HPWH at Water	Pre-1978		-888	149	1,239	-\$85	-\$48	0	-\$4,343	0.39	-\$1,580	1.81	\$2,093
Heater	1978-1991	\$2,594	-900	149	1,239	-\$85	-\$49	0	-\$4,347	0.39	-\$1,577	1.83	\$2,147
Replacement	1992-2010		-908	149	1,241	-\$84	-\$48	0	-\$4,326	0.38	-\$1,620	1.78	\$2,032
NEEA Tier 3	Pre-1978		-717	149	1,318	-\$31	-\$6	0	-\$3,260	0.68	-\$882	2.01	\$2,793
HPWH at	1978-1991	\$2,775	-732	149	1,317	-\$32	-\$7	0	-\$3,289	0.69	-\$871	2.04	\$2,894
Replacement	1992-2010		-740	149	1,320	-\$31	-\$6	0	-\$3,264	0.67	-\$926	1.99	\$2,735
HPWH at Water	Pre-1978		3,041	149	1,551	\$861	\$698	1.88	\$9,793	1.57	\$5,776	1.87	\$8,769
Heater Replacement +	1978-1991	\$10,052	3,029	149	1,551	\$850	\$689	1.86	\$9,541	1.57	\$5,758	1.87	\$8,786
PV	1992-2010		3,021	149	1,553	\$794	\$645	1.74	\$8,208	1.57	\$5,689	1.86	\$8,622
HPWH	Pre-1978		3,041	149	1,551	\$861	\$698	1.42	\$6,221	1.20	\$2,595	1.42	\$5,588
Replacement w/ Panel Upgrade	1978-1991	\$13,233	3,029	149	1,551	\$850	\$689	1.41	\$5,969	1.19	\$2,577	1.42	\$5,605
+ PV	1992-2010		3,021	149	1,553	\$794	\$645	1.32	\$4,636	1.19	\$2,508	1.41	\$5,441

	Minterra	Measure	Electricity	Gas	GHG Savings	-	v Cost ings	Custome	er On-Bill	2019) TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978		3,929	0	312	\$895	\$706	1.65	\$8,340	1.27	\$3,075	1.21	\$2,415
PV + Electric Ready Pre-Wire	1978-1991	\$11,549	3,929	0	312	\$886	\$699	1.63	\$8,135	1.26	\$3,049	1.21	\$2,375
	1992-2010		3,929	0	312	\$813	\$642	1.50	\$6,420	1.26	\$3,020	1.20	\$2,323

<u>Climate Zone 9:</u>

Note: Values in red and grey rows indicate option is not cost-effective with B/C ratio less than 1. Cells with "n/a" reflect lighting and water heating efficiency measures and packages that did not look at TDV cost effectiveness or GHG impacts.

	Minterre	Measure	Electricity	Gas	GHG Savings		v Cost ings	Custom	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO2e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$3,332	840	19	289	\$311	\$248	1.99	\$3,702	2.22	\$4,054	2.04	\$3,463
R-49 Attic Insulation	1978-1991	\$2,874	455	9	152	\$167	\$133	1.24	\$762	1.36	\$1,021	1.21	\$603
	1992-2010	\$1,852	115	3	58	\$44	\$36	0.51	-\$1,015	0.73	-\$507	0.66	-\$631
_	Pre-1978		25	6	62	\$15	\$12	0.22	-\$1,283	0.55	-\$665	0.44	-\$826
Reduced Infiltration	1978-1991	\$1,474	12	3	33	\$8	\$7	0.12	-\$1,455	0.29	-\$1,042	0.35	-\$956
	1992-2010		7	2	23	\$5	\$4	0.07	-\$1,534	0.26	-\$1,094	0.21	-\$1,169
	Pre-1978	\$683	544	11	206	\$212	\$168	6.59	\$4,287	10.65	\$6,593	8.86	\$5,372
Duct Sealing	1978-1991	\$683	322	6	123	\$126	\$100	3.91	\$2,230	6.75	\$3,929	5.26	\$2,909
	1992-2010	\$423	54	2	30	\$22	\$17	1.10	\$47	2.38	\$582	1.76	\$320
	Pre-1978		1,018	21	393	\$395	\$315	2.11	\$4,972	3.28	\$9,068	2.79	\$7,144
New Ducts	1978-1991	\$3,986	764	13	290	\$298	\$237	1.59	\$2,633	2.55	\$6,165	2.17	\$4,670
	1992-2010		198	5	109	\$79	\$63	0.42	-\$2,586	0.86	-\$573	0.64	-\$1,437
	Pre-1978		396	-3	20	\$136	\$107	3.77	\$2,350	5.57	\$2,637	3.75	\$2,137
Cool Roof	1978-1991	\$778	284	-2	26	\$100	\$78	2.77	\$1,499	3.92	\$1,687	2.68	\$1,305
	1992-2010		128	-2	13	\$44	\$34	1.21	\$175	2.20	\$690	1.29	\$225
R-13 Wall Insulation	Pre-1978	\$3,360	170	21	238	\$82	\$68	0.54	-\$1,744	1.02	\$62	0.88	-\$393
	Pre-1978	¢0.040	1,141	0	137	\$396	\$313	0.85	-\$1,637	0.94	-\$621	0.82	-\$1,719
Windows	1978-1991	\$9,810	929	0	140	\$330	\$260	0.71	-\$3,210	0.78	-\$2,122	0.70	-\$2,897
LED lamp vs CFL	All	\$2.26	1.2	0	n/a	\$0.34	\$0.27	3.57	\$5.80	n/a	n/a	n/a	n/a
Exterior Photosensor	All	\$42.58	12.1	0	n/a	\$2.00	\$1.58	1.11	\$4.84	n/a	n/a	n/a	n/a

Table 70: CZ 9 - Single Family Efficiency Upgrade Cost-Effectiveness Results

	Minterne	Measure	Electricity	Gas	GHG Savings		/ Cost ings	Custom	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO2e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$4,806	864	25	353	\$325	\$260	1.44	\$2,394	1.70	\$3,358	1.54	\$2,580
R49 Attic & Air Sealing Package	1978-1991	\$4,348	464	13	183	\$174	\$139	0.85	-\$712	1.06	\$244	0.94	-\$243
e camig raciage	1992-2010	\$3,326	121	6	81	\$49	\$39	0.32	-\$2,551	0.55	-\$1,494	0.46	-\$1,808
	Pre-1978	\$4,015	1,294	28	484	\$488	\$389	2.59	\$7,170	3.45	\$9,841	2.96	\$7,887
R49 Attic & Duct Sealing Package	1978-1991	\$3,557	735	14	266	\$277	\$220	1.65	\$2,612	2.26	\$4,497	1.89	\$3,163
ecaning r donage	1992-2010	\$2,275	165	5	88	\$64	\$51	0.60	-\$1,010	1.03	\$58	0.81	-\$438
R49 Attic. Air	Pre-1978	\$5,489	1,303	34	532	\$497	\$397	1.93	\$5,739	2.70	\$9,352	2.31	\$7,188
Sealing & Duct	1978-1991	\$5,031	739	17	295	\$282	\$225	1.19	\$1,086	1.72	\$3,599	1.43	\$2,167
Sealing Package	1992-2010	\$3,749	171	7	110	\$69	\$55	0.39	-\$2,557	0.72	-\$1,062	0.56	-\$1,647
R49 Attic, Air	Pre-1978	\$8,792	1,747	42	719	\$670	\$535	1.62	\$6,166	2.34	\$11,812	2.00	\$8,828
Sealing & New	1978-1991	\$8,334	1,153	24	459	\$444	\$353	1.13	\$1,243	1.71	\$5,939	1.44	\$3,657
Ducts Package	1992-2010	\$7,312	305	11	183	\$122	\$98	0.36	-\$5,270	0.68	-\$2,306	0.54	-\$3,378
Advanced Envelope Package	Pre-1978	\$18,659	2,105	62	932	\$813	\$649	0.93	-\$1,469	1.32	\$5,955	1.15	\$2,881
Water Heating Package	All Vintages	\$208	0	17	n/a	\$23	\$21	1.38	\$88	n/a	n/a	n/a	n/a

Table 71: CZ 9 - Single Family Efficiency Packages Cost-Effectiveness Results

	Martana	Measure	Electricity	Gas	GHG Savings	-	r Cost ings	Custom	er On-Bill	2019	9 TDV	2022	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978		4,154		326	\$927	\$732	2.62	\$13,591	1.99	\$7,507	1.87	\$6,599
Prescriptive PV System	1978-1991	\$7,570	4,154	0	326	\$902	\$712	2.55	\$12,979	1.99	\$7,475	1.87	\$6,568
i v cycloin	1992-2010		4,154		326	\$811	\$640	2.29	\$10,840	1.98	\$7,440	1.86	\$6,513
	Pre-1978		3,931		950	\$1,118	\$883	1.30	\$6,055	1.12	\$2,244	0.97	-\$631
PV + Battery	1978-1991	\$18,942	3,928	0	978	\$1,096	\$865	1.27	\$5,531	1.14	\$2,687	1.00	\$92
	1992-2010		3,926		1,040	\$1,000	\$789	1.16	\$3,247	1.17	\$3,186	1.06	\$1,051

Table 72: CZ 9 - Single Family PV & Battery Cost-Effectiveness Results

Table 73: CZ 9 - Single Family Equipment Fuel Substitution Cost-Effectiveness Results

Maaaura	Mintono	Measure	Electricity	Gas	GHG Savings	Utility Savi	r Cost ings	Custom	er On-Bill	2019	9 TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
Heat Pump at	Pre-1978		-921	86	387	-\$164	-\$118	0	-\$4,092	0	-\$902	1.15	\$78
HVAC .	1978-1991	\$501	-638	57	243	-\$118	-\$85	0	-\$3,108	0	-\$861	0.49	-\$257
Replacement	1992-2010		-525	48	207	-\$93	-\$68	0	-\$2,572	0	-\$778	0.49	-\$257
High-Effic. Heat	Pre-1978		-341	86	567	\$34	\$38	0.28	-\$2,920	1.32	\$1,208	1.33	\$1,240
Pump at HVAC	1978-1991	\$3,749	-189	57	387	\$38	\$38	0.28	-\$2,930	1.05	\$180	1.01	\$50
Replacement	1992-2010		-223	48	319	\$10	\$14	0.10	-\$3,639	0.76	-\$901	0.73	-\$1,004
Heat Pump at	Pre-1978		3,233	86	713	\$772	\$620	2.09	\$9,693	1.82	\$6,625	1.83	\$6,683
HVAC Replacement +	1978-1991	\$8,071	3,516	57	569	\$775	\$619	2.08	\$9,666	1.82	\$6,628	1.78	\$6,311
PV	1992-2010		3,629	48	533	\$747	\$596	2.01	\$8,963	1.83	\$6,683	1.78	\$6,262
HVAC HP	Pre-1978		3,233	86	713	\$772	\$620	1.49	\$6,121	1.31	\$3,444	1.31	\$3,502
Replacement w/ Panel Upgrade	1978-1991	\$11,252	3,516	57	569	\$775	\$619	1.49	\$6,094	1.31	\$3,447	1.28	\$3,130
+ PV	1992-2010		3,629	48	533	\$747	\$596	1.43	\$5,391	1.31	\$3,502	1.27	\$3,081
HPWH at Water	Pre-1978		-913	150	1,246	-\$72	-\$38	0	-\$4,040	0.37	-\$1,626	1.83	\$2,142
Heater	1978-1991	\$2,594	-921	150	1,250	-\$70	-\$36	0	-\$3,984	0.36	-\$1,672	1.82	\$2,121
Replacement	1992-2010		-932	150	1,249	-\$62	-\$30	0	-\$3,796	0.38	-\$1,612	1.82	\$2,136
NEEA Tier 3	Pre-1978		-744	150	1,323	-\$18	\$4	0.04	-\$2,955	0.70	-\$819	2.01	\$2,816
HPWH at	1978-1991	\$2,775	-755	150	1,321	-\$17	\$5	0.05	-\$2,926	0.68	-\$888	2.09	\$3,018
Replacement	1992-2010		-764	150	1,326	-\$10	\$11	0.11	-\$2,762	0.72	-\$767	2.01	\$2,802
HPWH at Water	Pre-1978		3,242	150	1,572	\$893	\$724	1.93	\$10,447	1.60	\$6,077	1.88	\$8,931
Heater Replacement +	1978-1991	\$10,163	3,233	150	1,577	\$872	\$707	1.88	\$9,959	1.59	\$6,005	1.87	\$8,879
PV	1992-2010		3,222	150	1,576	\$788	\$640	1.71	\$7,947	1.59	\$6,030	1.87	\$8,842
HPWH	Pre-1978		3,242	150	1,572	\$893	\$724	1.46	\$6,875	1.22	\$2,896	1.43	\$5,750
Replacement w/ Panel Upgrade	1978-1991	\$13,344	3,233	150	1,577	\$872	\$707	1.43	\$6,387	1.21	\$2,824	1.43	\$5,698
+ PV	1992-2010		3,222	150	1,576	\$788	\$640	1.29	\$4,375	1.21	\$2,849	1.42	\$5,661

	Minterre	Measure	Electricity	Gas	GHG Savings	-	/ Cost ings	Custome	er On-Bill	2019) TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978		4,154	0	326	\$927	\$732	1.69	\$8,997	1.29	\$3,416	1.22	\$2,508
PV + Electric Ready Pre-Wire	1978-1991	\$11,661	4,154	0	326	\$902	\$712	1.65	\$8,385	1.29	\$3,384	1.21	\$2,477
	1992-2010		4,154	0	326	\$811	\$640	1.48	\$6,246	1.29	\$3,349	1.21	\$2,422

Climate Zone 10 SCE/SoCalGas:

Note: Values in red and grey rows indicate option is not cost-effective with B/C ratio less than 1. Cells with "n/a" reflect lighting and water heating efficiency measures and packages that did not look at TDV cost effectiveness or GHG impacts.

	Nr. (Measure	Electricity	Gas	GHG Savings		/ Cost ings	Custome	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO₂e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$3,332	1,013	23	333	\$369	\$295	2.37	\$5,109	2.27	\$4,236	2.01	\$3,357
R-49 Attic Insulation	1978-1991	\$2,874	529	11	148	\$193	\$154	1.43	\$1,397	1.43	\$1,228	1.32	\$920
mediadon	1992-2010	\$1,852	143	4	61	\$54	\$44	0.63	-\$773	0.77	-\$421	0.68	-\$591
	Pre-1978		62	8	88	\$31	\$26	0.47	-\$882	0.63	-\$546	0.62	-\$555
Reduced Infiltration	1978-1991	\$1,474	34	5	47	\$17	\$14	0.26	-\$1,228	0.49	-\$754	0.43	-\$843
initiation	1992-2010		18	3	32	\$10	\$8	0.15	-\$1,401	0.27	-\$1,082	0.27	-\$1,076
	Pre-1978	\$683	796	16	266	\$303	\$242	9.46	\$6,485	11.56	\$7,209	10.04	\$6,175
Duct Sealing	1978-1991	\$683	471	8	154	\$181	\$144	5.64	\$3,558	7.08	\$4,150	6.41	\$3,698
	1992-2010	\$423	82	2	37	\$33	\$27	1.68	\$325	2.61	\$683	2.32	\$559
	Pre-1978		1,400	30	489	\$535	\$427	2.86	\$8,341	3.59	\$10,321	3.09	\$8,334
New Ducts	1978-1991	\$3,986	1,035	20	351	\$400	\$319	2.13	\$5,079	2.78	\$7,107	2.45	\$5,782
	1992-2010		281	8	137	\$113	\$90	0.60	-\$1,778	0.91	-\$377	0.81	-\$751
	Pre-1978		480	-4	14	\$157	\$124	4.37	\$2,861	5.17	\$2,404	3.13	\$1,653
Cool Roof	1978-1991	\$778	337	-3	14	\$114	\$90	3.18	\$1,849	4.05	\$1,762	2.50	\$1,164
	1992-2010		153	-2	5	\$51	\$40	1.41	\$347	2.23	\$707	1.28	\$222
R-13 Wall Insulation	Pre-1978	\$3,360	271	27	311	\$127	\$105	0.83	-\$631	1.21	\$701	1.09	\$295
Mindows	Pre-1978	¢0.940	1,443	3	185	\$491	\$388	1.06	\$623	1.10	\$992	0.86	-\$1,399
Windows	1978-1991	\$9,810	1,141	2	145	\$394	\$312	0.85	-\$1,670	0.90	-\$967	0.71	-\$2,796
LED lamp vs CFL	All	\$2.26	1.2	0	n/a	\$0.35	\$0.27	3.64	\$5.95	n/a	n/a	n/a	n/a
Exterior Photosensor	All	\$42.58	12.1	0	n/a	\$2.00	\$1.58	1.11	\$4.84	n/a	n/a	n/a	n/a

Table 74: CZ 10 (SCE/SoCalGas) - Single Family Efficiency Upgrade Cost-Effectiveness Results

	Martana	Measure	Electricity	Gas	GHG Savings	-	v Cost ings	Custom	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO2e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$4,806	1,072	31	419	\$399	\$320	1.78	\$4,196	1.76	\$3,649	1.61	\$2,908
R49 Attic & Air Sealing Package	1978-1991	\$4,348	564	16	199	\$211	\$169	1.04	\$180	1.11	\$475	1.02	\$82
	1992-2010	\$3,326	160	7	93	\$64	\$52	0.42	-\$2,183	0.56	-\$1,457	0.50	-\$1,661
	Pre-1978	\$4,015	1,682	37	574	\$629	\$502	3.34	\$10,545	3.65	\$10,650	3.28	\$9,149
R49 Attic & Duct Sealing Package	1978-1991	\$3,557	944	19	300	\$354	\$282	2.12	\$4,461	2.42	\$5,065	2.18	\$4,200
eeunig raenage	1992-2010	\$2,275	219	6	99	\$85	\$68	0.80	-\$507	1.09	\$196	0.95	-\$106
R49 Attic. Air	Pre-1978	\$5,489	1,729	45	655	\$653	\$523	2.54	\$9,513	2.83	\$10,052	2.55	\$8,527
Sealing & Duct	1978-1991	\$5,031	970	23	346	\$368	\$294	1.56	\$3,162	1.82	\$4,115	1.65	\$3,279
Sealing Package	1992-2010	\$3,749	234	10	128	\$94	\$76	0.54	-\$1,942	0.76	-\$909	0.68	-\$1,186
R49 Attic. Air	Pre-1978	\$8,792	2,308	57	876	\$878	\$702	2.13	\$11,183	2.51	\$13,313	2.24	\$10,870
Sealing & New	1978-1991	\$8,334	1,511	33	535	\$579	\$462	1.48	\$4,490	1.86	\$7,126	1.65	\$5,426
Ducts Package	1992-2010	\$7,312	423	15	222	\$169	\$136	0.50	-\$4,145	0.72	-\$2,067	0.66	-\$2,513
Advanced Envelope Package	Pre-1978	\$18,659	2,797	82	1,159	\$1,065	\$853	1.22	\$4,641	1.45	\$8,398	1.27	\$5,050
Water Heating Package	All Vintages	\$208	0	17	n/a	\$24	\$22	1.40	\$93	n/a	n/a	n/a	n/a

Table 75: CZ 10 (SCE/SoCalGas) - Single Family Efficiency Packages Cost-Effectiveness Results

	Martana	Measure	Electricity	Gas	GHG Savings	Utility Savi	Cost ngs	Custom	er On-Bill	2019) TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
_	Pre-1978		4,272		340	\$965	\$762	2.65	\$14,223	1.92	\$7,176	1.84	\$6,530
Prescriptive PV System	1978-1991	\$7,803	4,272	0	340	\$940	\$742	2.58	\$13,634	1.92	\$7,141	1.83	\$6,487
i v eyetem	1992-2010		4,272		340	\$855	\$675	2.35	\$11,611	1.91	\$7,101	1.82	\$6,421
	Pre-1978		4,048		939	\$1,151	\$908	1.32	\$6,564	1.17	\$3,192	0.99	-\$236
PV + Battery	1978-1991	\$19,175	4,045	0	972	\$1,135	\$896	1.30	\$6,193	1.19	\$3,667	1.00	-\$23
	1992-2010		4,041		1,046	\$1,048	\$827	1.20	\$4,142	1.22	\$4,200	1.04	\$781

Table 76: CZ 10 (SCE/SoCalGas) - Single Family PV & Battery Cost-Effectiveness Results

Table 77: CZ 10 (SCE/SoCalGas) - Single Family Equipment Fuel Substitution Cost-Effectiveness Results

Maaaa	Vinterre	Measure	Electricity	Gas	GHG Savings		r Cost ings	Custom	er On-Bill	2019	Ð TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
Heat Pump at	Pre-1978		-1,398	123	504	-\$214	-\$152	0	-\$5,105	0	-\$1,469	0.93	-\$35
HVAC	1978-1991	\$501	-986	85	335	-\$151	-\$107	0	-\$3,771	0	-\$1,271	0.41	-\$294
Replacement	1992-2010		-823	71	286	-\$121	-\$86	0	-\$3,122	0	-\$1,150	0.40	-\$303
High-Effic. Heat	Pre-1978		-625	123	739	\$45	\$52	0.39	-\$2,491	1.30	\$1,113	1.53	\$1,994
Pump at HVAC	1978-1991	\$3,749	-385	85	524	\$53	\$53	0.39	-\$2,467	1.05	\$197	1.20	\$750
Replacement	1992-2010		-397	71	440	\$17	\$23	0.17	-\$3,369	0.74	-\$990	0.91	-\$348
Heat Pump at	Pre-1978		2,874	123	843	\$751	\$610	1.99	\$9,118	1.69	\$5,729	1.78	\$6,501
HVAC Replacement +	1978-1991	\$8,304	3,286	85	675	\$776	\$624	2.04	\$9,543	1.71	\$5,888	1.75	\$6,196
PV	1992-2010		3,449	71	625	\$751	\$602	1.97	\$8,890	1.72	\$5,974	1.74	\$6,127
HVAC HP	Pre-1978		2,874	123	843	\$751	\$610	1.44	\$5,546	1.22	\$2,548	1.29	\$3,320
Replacement w/ Panel Upgrade	1978-1991	\$11,485	3,286	85	675	\$776	\$624	1.47	\$5,971	1.24	\$2,707	1.26	\$3,015
+ PV	1992-2010		3,449	71	625	\$751	\$602	1.42	\$5,318	1.24	\$2,793	1.26	\$2,946
HPWH at Water	Pre-1978		-922	149	1,233	-\$69	-\$35	0	-\$3,946	0.41	-\$1,543	1.75	\$1,951
Heater	1978-1991	\$2,594	-935	150	1,232	-\$71	-\$37	0	-\$3,996	0.45	-\$1,427	1.74	\$1,911
Replacement	1992-2010		-946	150	1,232	-\$65	-\$33	0	-\$3,874	0.44	-\$1,456	1.74	\$1,920
NEEA Tier 3	Pre-1978		-734	149	1,319	-\$8	\$13	0.12	-\$2,704	0.70	-\$828	1.95	\$2,623
HPWH at	1978-1991	\$2,775	-752	150	1,310	-\$12	\$10	0.09	-\$2,803	0.74	-\$710	1.95	\$2,643
Replacement	1992-2010		-761	150	1,314	-\$8	\$13	0.12	-\$2,713	0.71	-\$807	1.94	\$2,614
HPWH at Water	Pre-1978		3,350	149	1,572	\$932	\$755	1.97	\$11,140	1.56	\$5,832	1.83	\$8,663
Heater Replacement +	1978-1991	\$10,397	3,337	150	1,572	\$910	\$737	1.92	\$10,605	1.57	\$5,918	1.83	\$8,586
PV	1992-2010		3,326	150	1,571	\$827	\$672	1.75	\$8,634	1.56	\$5,849	1.82	\$8,531
HPWH	Pre-1978		3,350	149	1,572	\$932	\$755	1.50	\$7,568	1.20	\$2,651	1.40	\$5,482
Replacement w/ Panel Upgrade	1978-1991	\$13,578	3,337	150	1,572	\$910	\$737	1.47	\$7,033	1.20	\$2,737	1.40	\$5,405
+ PV	1992-2010		3,326	150	1,571	\$827	\$672	1.34	\$5,062	1.20	\$2,668	1.39	\$5,350

	Minterra	Measure	Electricity	Gas	GHG Savings	-	v Cost ings	Custome	er On-Bill	2019) TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978		4,272	0	340	\$965	\$762	1.73	\$9,630	1.26	\$3,085	1.21	\$2,439
PV + Electric Ready Pre-Wire	1978-1991	\$11,894	4,272	0	340	\$940	\$742	1.68	\$9,040	1.26	\$3,050	1.20	\$2,396
	1992-2010		4,272	0	340	\$855	\$675	1.53	\$7,017	1.25	\$3,010	1.20	\$2,330

<u>Climate Zone 10 SDG&E:</u>

Note: Values in red and grey rows indicate option is not cost-effective with B/C ratio less than 1. Cells with "n/a" reflect lighting and water heating efficiency measures and packages that did not look at TDV cost effectiveness or GHG impacts.

	Martana	Measure	Electricity	Gas	GHG Savings	Utility Sav	v Cost ings	Custome	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO2e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$3,332	1,013	23	333	\$514	\$410	3.29	\$8,569	2.27	\$4,236	2.01	\$3,357
R-49 Attic Insulation	1978-1991	\$2,874	529	11	148	\$272	\$217	2.02	\$3,277	1.43	\$1,228	1.32	\$920
modiation	1992-2010	\$1,852	143	4	61	\$82	\$65	0.94	-\$117	0.77	-\$421	0.68	-\$591
	Pre-1978		62	8	88	\$42	\$35	0.64	-\$599	0.63	-\$546	0.62	-\$555
Reduced Infiltration	1978-1991	\$1,474	34	5	47	\$24	\$20	0.35	-\$1,068	0.49	-\$754	0.43	-\$843
	1992-2010		18	3	32	\$14	\$12	0.22	-\$1,295	0.27	-\$1,082	0.27	-\$1,076
	Pre-1978	\$683	796	16	266	\$432	\$344	13.47	\$9,564	11.56	\$7,209	10.04	\$6,175
Duct Sealing	1978-1991	\$683	471	8	154	\$261	\$208	8.12	\$5,462	7.08	\$4,150	6.41	\$3,698
	1992-2010	\$423	82	2	37	\$50	\$40	2.53	\$725	2.61	\$683	2.32	\$559
	Pre-1978		1,400	30	489	\$764	\$610	4.09	\$13,810	3.59	\$10,321	3.09	\$8,334
New Ducts	1978-1991	\$3,986	1,035	20	351	\$577	\$459	3.08	\$9,304	2.78	\$7,107	2.45	\$5,782
	1992-2010		281	8	137	\$170	\$136	0.91	-\$402	0.91	-\$377	0.81	-\$751
	Pre-1978		480	-4	14	\$221	\$174	6.14	\$4,363	5.17	\$2,404	3.13	\$1,653
Cool Roof	1978-1991	\$778	337	-3	14	\$162	\$127	4.51	\$2,976	4.05	\$1,762	2.50	\$1,164
	1992-2010		153	-2	5	\$77	\$61	2.14	\$967	2.23	\$707	1.28	\$222
R-13 Wall Insulation	Pre-1978	\$3,360	271	27	311	\$178	\$146	1.16	\$613	1.21	\$701	1.09	\$295
	Pre-1978	¢0.040	1,443	3	185	\$686	\$542	1.48	\$5,258	1.10	\$992	0.86	-\$1,399
Windows	1978-1991	\$9,810	1,141	2	145	\$558	\$441	1.20	\$2,215	0.90	-\$967	0.71	-\$2,796
LED lamp vs CFL	All	\$2.26	1.2	0	n/a	\$0.51	\$0.40	5.33	\$9.76	n/a	n/a	n/a	n/a
Exterior Photosensor	All	\$42.58	12.1	0	n/a	\$2.76	\$2.18	1.54	\$22.81	n/a	n/a	n/a	n/a

Table 78: CZ 10 (SDG&E) - Single Family Efficiency Upgrade Cost-Effectiveness Results

	Martana	Measure	Electricity	Gas	GHG Savings	-	v Cost ings	Custom	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO2e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$4,806	1,072	31	419	\$555	\$445	2.47	\$7,948	1.76	\$3,649	1.61	\$2,908
R49 Attic & Air Sealing Package	1978-1991	\$4,348	564	16	199	\$296	\$237	1.46	\$2,226	1.11	\$475	1.02	\$82
eeunig Paenage	1992-2010	\$3,326	160	7	93	\$96	\$77	0.62	-\$1,414	0.56	-\$1,457	0.50	-\$1,661
	Pre-1978	\$4,015	1,682	37	574	\$888	\$709	4.72	\$16,754	3.65	\$10,650	3.28	\$9,149
R49 Attic & Duct Sealing Package	1978-1991	\$3,557	944	19	300	\$504	\$402	3.02	\$8,062	2.42	\$5,065	2.18	\$4,200
eeunig raenage	1992-2010	\$2,275	219	6	99	\$128	\$103	1.20	\$522	1.09	\$196	0.95	-\$106
R49 Attic. Air	Pre-1978	\$5,489	1,729	45	655	\$922	\$737	3.59	\$15,957	2.83	\$10,052	2.55	\$8,527
Sealing & Duct	1978-1991	\$5,031	970	23	346	\$524	\$418	2.22	\$6,899	1.82	\$4,115	1.65	\$3,279
Sealing Package	1992-2010	\$3,749	234	10	128	\$142	\$114	0.81	-\$797	0.76	-\$909	0.68	-\$1,186
R49 Attic. Air	Pre-1978	\$8,792	2,308	57	876	\$1,248	\$996	3.03	\$20,022	2.51	\$13,313	2.24	\$10,870
Sealing & New	1978-1991	\$8,334	1,511	33	535	\$833	\$664	2.13	\$10,576	1.86	\$7,126	1.65	\$5,426
Ducts Package	1992-2010	\$7,312	423	15	222	\$258	\$207	0.76	-\$2,004	0.72	-\$2,067	0.66	-\$2,513
Advanced Envelope Package	Pre-1978	\$18,659	2,797	82	1,159	\$1,512	\$1,210	1.73	\$15,344	1.45	\$8,398	1.27	\$5,050
Water Heating Package	All Vintages	\$208	0	17	n/a	\$32	\$29	1.88	\$206	n/a	n/a	n/a	n/a

Table 79: CZ 10 (SDG&E) - Single Family Efficiency Packages Cost-Effectiveness Results

	Martana	Measure	Electricity	Gas	GHG Savings	Utility Sav	Cost ings	Custome	er On-Bill	2019) TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978		4,272		340	\$1,520	\$1,199	4.17	\$27,356	1.92	\$7,176	1.84	\$6,530
Prescriptive PV System	1978-1991	\$7,803	4,272	0	340	\$1,507	\$1,190	4.14	\$27,064	1.92	\$7,141	1.83	\$6,487
i v eyetem	1992-2010		4,272		340	\$1,479	\$1,168	4.06	\$26,402	1.91	\$7,101	1.82	\$6,421
	Pre-1978		4,048		939	\$1,702	\$1,343	1.95	\$19,620	1.17	\$3,192	0.99	-\$236
PV + Battery	1978-1991	\$19,175	4,045	0	972	\$1,706	\$1,346	1.95	\$19,708	1.19	\$3,667	1.00	-\$23
	1992-2010		4,041		1,046	\$1,682	\$1,328	1.93	\$19,152	1.22	\$4,200	1.04	\$781

Table 80: CZ 10 (SDG&E) - Single Family PV & Battery Cost-Effectiveness Results

Table 81: CZ 10 (SDG&E) - Single Family Equipment Fuel Substitution Cost-Effectiveness Results

	Ninte no	Measure	Electricity	Gas	GHG Savings	Utility Sav	v Cost ings	Custom	er On-Bill	2019	9 TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
Heat Pump at	Pre-1978		-1,398	123	504	-\$323	-\$231	0	-\$7,467	0	-\$1,469	0.93	-\$35
HVAC	1978-1991	\$501	-986	85	335	-\$232	-\$167	0	-\$5,544	0	-\$1,271	0.41	-\$294
Replacement	1992-2010		-823	71	286	-\$191	-\$137	0.00	-\$4,665	0	-\$1,150	0.40	-\$303
High-Effic. Heat	Pre-1978		-625	123	739	\$49	\$63	0.46	-\$2,178	1.30	\$1,113	1.53	\$1,994
Pump at HVAC	1978-1991	\$3,749	-385	85	524	\$64	\$67	0.49	-\$2,052	1.05	\$197	1.20	\$750
Replacement	1992-2010		-397	71	440	\$20	\$29	0.21	-\$3,187	0.74	-\$990	0.91	-\$348
Heat Pump at	Pre-1978		2,874	123	843	\$1,251	\$1,012	3.31	\$21,173	1.69	\$5,729	1.78	\$6,501
HVAC Replacement +	1978-1991	\$8,304	3,286	85	675	\$1,352	\$1,083	3.54	\$23,321	1.71	\$5,888	1.75	\$6,196
PV	1992-2010		3,449	71	625	\$1,348	\$1,078	3.52	\$23,157	1.72	\$5,974	1.74	\$6,127
HVAC HP	Pre-1978		2,874	123	843	\$1,251	\$1,012	2.38	\$17,601	1.22	\$2,548	1.29	\$3,320
Replacement w/ Panel Upgrade	1978-1991	\$11,485	3,286	85	675	\$1,352	\$1,083	2.55	\$19,749	1.24	\$2,707	1.26	\$3,015
+ PV	1992-2010		3,449	71	625	\$1,348	\$1,078	2.54	\$19,585	1.24	\$2,793	1.26	\$2,946
HPWH at Water	Pre-1978		-922	149	1,233	-\$87	-\$40	0	-\$4,083	0.41	-\$1,543	1.75	\$1,951
Heater	1978-1991	\$2,594	-935	150	1,232	-\$88	-\$42	0	-\$4,139	0.45	-\$1,427	1.74	\$1,911
Replacement	1992-2010		-946	150	1,232	-\$85	-\$39	0	-\$4,069	0.44	-\$1,456	1.74	\$1,920
NEEA Tier 3	Pre-1978		-734	149	1,319	-\$9	\$22	0.21	-\$2,444	0.70	-\$828	1.95	\$2,623
HPWH at	1978-1991	\$2,775	-752	150	1,310	-\$13	\$18	0.17	-\$2,553	0.74	-\$710	1.95	\$2,643
Replacement	1992-2010		-761	150	1,314	-\$10	\$20	0.20	-\$2,485	0.71	-\$807	1.94	\$2,614
HPWH at Water	Pre-1978		3,350	149	1,572	\$1,402	\$1,135	2.96	\$22,534	1.56	\$5,832	1.83	\$8,663
Heater Replacement +	1978-1991	\$10,397	3,337	150	1,572	\$1,382	\$1,119	2.91	\$22,046	1.57	\$5,918	1.83	\$8,586
PV	1992-2010		3,326	150	1,571	\$1,352	\$1,095	2.85	\$21,341	1.56	\$5,849	1.82	\$8,531
HPWH	Pre-1978		3,350	149	1,572	\$1,402	\$1,135	2.26	\$18,962	1.20	\$2,651	1.40	\$5,482
Replacement w/ Panel Upgrade	1978-1991	\$13,578	3,337	150	1,572	\$1,382	\$1,119	2.22	\$18,475	1.20	\$2,737	1.40	\$5,405
+ PV	1992-2010		3,326	150	1,571	\$1,352	\$1,095	2.18	\$17,769	1.20	\$2,668	1.39	\$5,350

	Minterre	Measure	Electricity	Gas	GHG Savings	-	v Cost ings	Custome	er On-Bill	2019	O TDV	2022	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978		4,272	0	340	\$1,520	\$1,199	2.72	\$22,762	1.26	\$3,085	1.21	\$2,439
PV + Electric Ready Pre-Wire	1978-1991	\$11,894	4,272	0	340	\$1,507	\$1,190	2.70	\$22,470	1.26	\$3,050	1.20	\$2,396
	1992-2010		4,272	0	340	\$1,479	\$1,168	2.65	\$21,808	1.25	\$3,010	1.20	\$2,330

<u>Climate Zone 11:</u>

Note: Values in red and grey rows indicate option is not cost-effective with B/C ratio less than 1. Cells with "n/a" reflect lighting and water heating efficiency measures and packages that did not look at TDV cost effectiveness or GHG impacts.

	Mindana	Measure	Electricity	Gas	GHG Savings		v Cost ings	Custom	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO2e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$3,332	1,031	47	610	\$479	\$384	3.08	\$7,766	3.13	\$7,085	2.73	\$5,757
R-49 Attic Insulation	1978-1991	\$2,874	559	23	293	\$256	\$205	1.90	\$2,908	2.10	\$3,165	1.71	\$2,053
	1992-2010	\$1,852	161	9	116	\$78	\$63	0.90	-\$199	1.08	\$152	0.91	-\$176
	Pre-1978		100	17	194	\$73	\$60	1.08	\$132	1.11	\$168	1.21	\$306
Reduced Infiltration	1978-1991	\$1,474	63	11	117	\$45	\$36	0.66	-\$562	1.04	\$56	0.76	-\$356
	1992-2010		35	7	73	\$27	\$22	0.40	-\$1,000	0.40	-\$881	0.51	-\$719
	Pre-1978	\$683	1,087	43	608	\$506	\$405	15.83	\$11,373	19.66	\$12,746	16.28	\$10,438
Duct Sealing	1978-1991	\$683	669	24	357	\$308	\$246	9.61	\$6,607	12.99	\$8,189	10.24	\$6,311
	1992-2010	\$423	129	7	94	\$64	\$51	3.23	\$1,060	4.28	\$1,386	3.90	\$1,227
	Pre-1978		1,837	74	1,052	\$858	\$686	4.60	\$16,105	5.71	\$18,793	4.79	\$15,103
New Ducts	1978-1991	\$3,986	1,387	52	774	\$643	\$513	3.44	\$10,926	4.39	\$13,530	3.72	\$10,837
	1992-2010		406	21	304	\$201	\$161	1.08	\$350	1.41	\$1,640	1.28	\$1,135
	Pre-1978		475	-5	6	\$170	\$133	4.71	\$3,148	6.76	\$3,323	3.37	\$1,843
Cool Roof	1978-1991	\$778	343	-4	6	\$124	\$98	3.46	\$2,086	6.04	\$2,911	2.63	\$1,270
	1992-2010		164	-3	3	\$59	\$46	1.62	\$529	2.52	\$875	1.35	\$273
R-13 Wall Insulation	Pre-1978	\$3,360	448	55	647	\$281	\$228	1.81	\$3,067	2.03	\$3,472	2.05	\$3,516
) A / in day to	Pre-1978	¢0.040	1,779	34	605	\$738	\$586	1.60	\$6,574	1.61	\$5,960	1.39	\$3,838
Windows	1978-1991	\$9,810	1,453	26	480	\$601	\$477	1.30	\$3,299	1.32	\$3,161	1.13	\$1,237
LED lamp vs CFL	All	\$2.26	1.2	0	n/a	\$0.44	\$0.35	4.65	\$8.23	n/a	n/a	n/a	n/a
Exterior Photosensor	All	\$42.58	12.1	0	n/a	\$2.88	\$2.27	1.60	\$25.62	n/a	n/a	n/a	n/a

Table 82: CZ 11 - Single Family Efficiency Upgrade Cost-Effectiveness Results

		Measure	Electricity	Gas	GHG Savings	-	v Cost ings	Custome	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$4,806	1,135	65	805	\$554	\$445	2.47	\$7,956	2.55	\$7,458	2.28	\$6,155
R49 Attic & Air Sealing Package	1978-1991	\$4,348	626	35	420	\$302	\$243	1.49	\$2,397	1.59	\$2,558	1.39	\$1,696
e cannig r achaige	1992-2010	\$3,326	196	16	189	\$105	\$85	0.68	-\$1,187	0.74	-\$878	0.75	-\$835
	Pre-1978	\$4,015	2,012	87	1,182	\$938	\$751	5.00	\$18,017	5.77	\$19,166	4.86	\$15,501
R49 Attic & Duct Sealing Package	1978-1991	\$3,557	1,172	46	643	\$540	\$431	3.24	\$8,943	3.92	\$10,374	3.23	\$7,917
County P donago	1992-2010	\$2,275	281	15	205	\$138	\$111	1.30	\$772	1.57	\$1,302	1.46	\$1,037
R49 Attic, Air	Pre-1978	\$5,489	2,095	103	1,355	\$1,002	\$803	3.91	\$17,922	4.47	\$19,071	3.87	\$15,741
Sealing & Duct	1978-1991	\$5,031	1,228	56	755	\$580	\$464	2.47	\$8,282	2.92	\$9,667	2.49	\$7,486
Sealing Package	1992-2010	\$3,749	316	22	282	\$164	\$132	0.94	-\$244	1.16	\$612	1.05	\$185
R49 Attic, Air	Pre-1978	\$8,792	2,851	133	1,811	\$1,356	\$1,086	3.30	\$22,705	3.85	\$25,061	3.37	\$20,806
Sealing & New	1978-1991	\$8,334	1,928	82	1,157	\$906	\$724	2.32	\$12,371	2.81	\$15,114	2.46	\$12,156
Ducts Package	1992-2010	\$7,312	581	36	479	\$296	\$238	0.87	-\$1,078	1.08	\$592	1.03	\$185
Advanced Envelope Package	Pre-1978	\$18,659	3,636	197	2,570	\$1,768	\$1,418	2.03	\$21,602	2.27	\$23,651	2.05	\$19,546
Water Heating Package	All Vintages	\$208	0	16	n/a	\$32	\$29	1.88	\$207	n/a	n/a	n/a	n/a

Table 83: CZ 11 - Single Family Efficiency Packages Cost-Effectiveness Results

		Measure	Electricity	Gas	GHG Savings	-	r Cost ings	Custom	er On-Bill	2019	9 TDV	2022	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978		4,408		283	\$1,260	\$995	3.00	\$19,886	2.05	\$9,439	1.58	\$5,236
Prescriptive PV System	1978-1991	\$9,005	4,408	0	283	\$1,235	\$975	2.94	\$19,296	2.04	\$9,390	1.58	\$5,190
i v oyotom	1992-2010		4,408		283	\$1,159	\$915	2.76	\$17,493	2.04	\$9,324	1.57	\$5,113
	Pre-1978		4,191		901	\$1,304	\$1,029	1.40	\$8,869	1.42	\$8,612	0.92	-\$1,562
PV + Battery	1978-1991	\$20,377	4,187	0	926	\$1,284	\$1,014	1.38	\$8,395	1.43	\$8,822	0.93	-\$1,389
	1992-2010		4,184		973	\$1,215	\$959	1.31	\$6,748	1.45	\$9,254	0.95	-\$1,046

Table 84: CZ 11 - Single Family PV & Battery Cost-Effectiveness Results

Table 85: CZ 11 - Single Family Equipment Fuel Substitution Cost-Effectiveness Results

•	Minterre	Measure	Electricity	Gas	GHG Savings	Utility Sav	r Cost ings	Custom	er On-Bill	2019	9 TDV	2022	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
Heat Pump at	Pre-1978		-3,496	328	1,615	-\$237	-\$152	0	-\$5,114	0	-\$3,889	5.15	\$2,079
HVAC	1978-1991	\$501	-2,597	244	1,186	-\$162	-\$102	0	-\$3,621	0	-\$3,128	3.73	\$1,371
Replacement	1992-2010		-2,122	199	986	-\$132	-\$84	0	-\$3,064	0	-\$2,581	3.19	\$1,097
High-Effic. Heat	Pre-1978		-2,236	328	2,046	\$187	\$182	1.35	\$1,408	1.66	\$2,487	2.92	\$7,185
Pump at HVAC	1978-1991	\$3,749	-1,610	244	1,528	\$172	\$161	1.19	\$771	1.37	\$1,384	2.30	\$4,872
Replacement	1992-2010		-1,389	199	1,258	\$104	\$102	0.75	-\$1,004	1.01	\$56	1.79	\$2,974
Heat Pump at	Pre-1978		912	328	1,898	\$997	\$821	2.35	\$14,141	1.59	\$5,622	1.77	\$7,362
HVAC Replacement +	1978-1991	\$9,506	1,811	244	1,469	\$1,037	\$843	2.41	\$14,796	1.66	\$6,313	1.69	\$6,593
PV	1992-2010		2,285	199	1,270	\$1,000	\$809	2.31	\$13,774	1.72	\$6,815	1.66	\$6,259
HVAC HP	Pre-1978		912	328	1,898	\$997	\$821	1.75	\$10,569	1.19	\$2,441	1.33	\$4,181
Replacement w/ Panel Upgrade	1978-1991	\$12,687	1,811	244	1,469	\$1,037	\$843	1.80	\$11,224	1.25	\$3,132	1.27	\$3,412
+ PV	1992-2010		2,285	199	1,270	\$1,000	\$809	1.72	\$10,202	1.29	\$3,634	1.24	\$3,078
HPWH at Water	Pre-1978		-1,079	151	1,207	-\$61	-\$32	0	-\$3,855	0.03	-\$2,510	1.50	\$1,306
Heater	1978-1991	\$2,594	-1,092	152	1,213	-\$66	-\$37	0	-\$3,997	0.04	-\$2,487	1.50	\$1,300
Replacement	1992-2010		-1,101	152	1,214	-\$73	-\$42	0	-\$4,154	0	-\$2,634	1.50	\$1,303
NEEA Tier 3	Pre-1978		-829	150	1,292	\$17	\$29	0.28	-\$2,210	0.45	-\$1,516	1.85	\$2,361
HPWH at	1978-1991	\$2,775	-844	151	1,298	\$11	\$24	0.24	-\$2,361	0.48	-\$1,438	1.85	\$2,349
Replacement	1992-2010		-855	152	1,301	\$5	\$19	0.18	-\$2,522	0.44	-\$1,548	1.84	\$2,329
HPWH at Water	Pre-1978		3,328	151	1,490	\$1,263	\$1,012	2.36	\$17,525	1.61	\$7,116	1.58	\$6,727
Heater Replacement +	1978-1991	\$11,598	3,316	152	1,496	\$1,240	\$994	2.32	\$16,983	1.61	\$7,096	1.58	\$6,678
PV	1992-2010		3,306	152	1,497	\$1,165	\$934	2.18	\$15,184	1.59	\$6,885	1.57	\$6,609
HPWH	Pre-1978		3,328	151	1,490	\$1,263	\$1,012	1.85	\$13,953	1.27	\$3,935	1.24	\$3,546
Replacement w/ Panel Upgrade	1978-1991	\$14,779	3,316	152	1,496	\$1,240	\$994	1.82	\$13,411	1.26	\$3,915	1.24	\$3,497
+ PV	1992-2010		3,306	152	1,497	\$1,165	\$934	1.71	\$11,612	1.25	\$3,704	1.23	\$3,428

	Minterre	Measure	Electricity	Gas	GHG Savings	-	/ Cost ings	Custome	er On-Bill	2019) TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978		4,408	0	283	\$1,260	\$995	2.05	\$15,292	1.41	\$5,348	1.09	\$1,145
PV + Electric Ready Pre-Wire	1978-1991	\$13,096	4,408	0	283	\$1,235	\$975	2.01	\$14,702	1.40	\$5,299	1.08	\$1,099
	1992-2010		4,408	0	283	\$1,159	\$915	1.89	\$12,899	1.40	\$5,233	1.08	\$1,022

Climate Zone 12 PG&E:

Note: Values in red and grey rows indicate option is not cost-effective with B/C ratio less than 1. Cells with "n/a" reflect lighting and water heating efficiency measures and packages that did not look at TDV cost effectiveness or GHG impacts.

	Martana	Measure	Electricity	Gas	GHG Savings	Utility Savi	v Cost ings	Custome	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO2e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$3,332	886	41	545	\$421	\$337	2.70	\$6,372	2.61	\$5,372	2.55	\$5,152
R-49 Attic Insulation	1978-1991	\$2,874	482	20	282	\$224	\$179	1.66	\$2,144	1.61	\$1,745	1.57	\$1,644
	1992-2010	\$1,852	126	8	106	\$60	\$48	0.69	-\$643	0.84	-\$291	0.84	-\$294
	Pre-1978		52	14	146	\$48	\$40	0.72	-\$468	0.76	-\$359	0.97	-\$42
Reduced Infiltration	1978-1991	\$1,474	31	9	97	\$29	\$24	0.43	-\$938	0.50	-\$739	0.58	-\$616
initiation	1992-2010		18	6	60	\$18	\$15	0.27	-\$1,212	0.23	-\$1,131	0.44	-\$820
	Pre-1978	\$683	619	38	509	\$321	\$258	10.07	\$6,958	13.77	\$8,719	12.40	\$7,788
Duct Sealing	1978-1991	\$683	358	22	299	\$185	\$148	5.80	\$3,679	8.59	\$5,182	7.73	\$4,597
	1992-2010	\$423	60	6	77	\$34	\$28	1.75	\$355	2.57	\$663	2.83	\$775
	Pre-1978		1,094	66	888	\$562	\$451	3.03	\$9,068	4.19	\$12,715	3.77	\$11,030
New Ducts	1978-1991	\$3,986	795	47	662	\$407	\$326	2.19	\$5,316	3.23	\$8,898	2.91	\$7,605
	1992-2010		203	19	251	\$114	\$92	0.62	-\$1,708	1.02	\$84	1.01	\$38
	Pre-1978		389	-5	14	\$142	\$111	3.93	\$2,486	5.48	\$2,588	3.28	\$1,771
Cool Roof	1978-1991	\$778	276	-3	18	\$101	\$80	2.82	\$1,542	4.41	\$1,969	2.51	\$1,172
	1992-2010		121	-3	2	\$39	\$30	1.07	\$62	1.88	\$509	1.30	\$233
R-13 Wall Insulation	Pre-1978	\$3,360	247	49	550	\$192	\$157	1.25	\$934	1.55	\$1,859	1.58	\$1,940
	Pre-1978	¢0.040	1,242	25	473	\$532	\$423	1.15	\$1,680	1.27	\$2,662	1.05	\$499
Windows	1978-1991	\$9,810	1,011	21	408	\$435	\$346	0.94	-\$647	1.05	\$456	0.89	-\$1,094
LED lamp vs CFL	All	\$2.26	1.2	0	n/a	\$0.43	\$0.34	4.48	\$7.85	n/a	n/a	n/a	n/a
Exterior Photosensor	All	\$42.58	12.1	0	n/a	\$2.88	\$2.27	1.60	\$25.62	n/a	n/a	n/a	n/a

Table 86: CZ 12 (PG&E) - Single Family Efficiency Upgrade Cost-Effectiveness Results

		Measure	Electricity	Gas	GHG Savings	-	v Cost ings	Custome	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$4,806	938	57	713	\$471	\$378	2.10	\$5,956	2.16	\$5,571	2.05	\$5,046
R49 Attic & Air Sealing Package	1978-1991	\$4,348	513	30	377	\$254	\$204	1.25	\$1,225	1.27	\$1,181	1.27	\$1,175
e cannig r achaige	1992-2010	\$3,326	145	14	170	\$78	\$63	0.51	-\$1,842	0.60	-\$1,319	0.64	-\$1,212
	Pre-1978	\$4,015	1,396	77	1,026	\$694	\$557	3.71	\$12,205	4.34	\$13,393	4.04	\$12,223
R49 Attic & Duct Sealing Package	1978-1991	\$3,557	789	41	563	\$386	\$310	2.32	\$5,291	2.85	\$6,578	2.65	\$5,863
County P donago	1992-2010	\$2,275	179	14	181	\$91	\$74	0.87	-\$343	1.22	\$493	1.17	\$398
R49 Attic. Air	Pre-1978	\$5,489	1,439	90	1,169	\$736	\$591	2.88	\$11,568	3.38	\$13,089	3.17	\$11,899
Sealing & Duct	1978-1991	\$5,031	817	49	655	\$413	\$331	1.76	\$4,294	2.20	\$6,020	2.02	\$5,141
Sealing Package	1992-2010	\$3,749	197	19	241	\$109	\$88	0.63	-\$1,568	0.88	-\$460	0.88	-\$466
R49 Attic, Air	Pre-1978	\$8,792	1,884	117	1,548	\$964	\$774	2.35	\$13,357	2.96	\$17,240	2.74	\$15,342
Sealing & New	1978-1991	\$8,334	1,222	73	1,005	\$621	\$498	1.60	\$5,591	2.15	\$9,587	1.97	\$8,083
Ducts Package	1992-2010	\$7,312	330	32	411	\$184	\$149	0.54	-\$3,753	0.83	-\$1,275	0.80	-\$1,482
Advanced Envelope Package	Pre-1978	\$18,659	2,410	169	2,174	\$1,262	\$1,015	1.45	\$9,508	1.76	\$14,200	1.63	\$11,725
Water Heating Package	All Vintages	\$208	0	16	n/a	\$32	\$29	1.89	\$208	n/a	n/a	n/a	n/a

Table 87: CZ 12 (PG&E) - Single Family Efficiency Packages Cost-Effectiveness Results

	Martana	Measure	Electricity	Gas	GHG Savings		v Cost ings	Custome	er On-Bill	2019) TDV	2022	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978		3,876		237	\$1,077	\$850	2.99	\$16,979	2.01	\$7,783	1.62	\$4,738
Prescriptive PV System	1978-1991	\$7,697	3,876	0	237	\$1,046	\$826	2.91	\$16,264	2.01	\$7,754	1.61	\$4,704
i v eyetetti	1992-2010		3,876		237	\$958	\$756	2.66	\$14,167	2.00	\$7,719	1.61	\$4,666
	Pre-1978		3,673		854	\$1,123	\$887	1.29	\$6,038	1.28	\$5,337	0.87	-\$2,389
PV + Battery	1978-1991	\$19,069	3,670	0	878	\$1,095	\$864	1.26	\$5,368	1.30	\$5,789	0.88	-\$2,236
	1992-2010		3,671		908	\$1,006	\$794	1.16	\$3,254	1.33	\$6,342	0.90	-\$1,864

Table 88: CZ 12 (PG&E) - Single Family PV & Battery Cost-Effectiveness Results

Table 89: CZ 12 (PG&E) - Single Family Equipment Fuel Substitution Cost-Effectiveness Results

•	Minterre	Measure	Electricity	Gas	GHG Savings	Utility Sav	v Cost ings	Custom	er On-Bill	2019	9 TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
Heat Pump at	Pre-1978		-3,101	293	1,419	-\$236	-\$156	0	-\$5,224	0	-\$2,541	4.12	\$1,567
HVAC	1978-1991	\$501	-2,361	222	1,058	-\$177	-\$117	0	-\$4,068	0	-\$2,083	2.93	\$968
Replacement	1992-2010		-1,955	184	899	-\$145	-\$96	0	-\$3,427	0	-\$1,841	2.63	\$815
High-Effic. Heat	Pre-1978		-2,198	293	1,769	\$59	\$78	0.57	-\$1,729	1.44	\$1,666	2.28	\$4,794
Pump at HVAC	1978-1991	\$3,749	-1,669	222	1,334	\$50	\$62	0.46	-\$2,198	1.17	\$632	1.78	\$2,907
Replacement	1992-2010		-1,459	184	1,110	\$11	\$27	0.20	-\$3,262	0.81	-\$725	1.37	\$1,395
Heat Pump at	Pre-1978		776	293	1,657	\$800	\$662	2.19	\$10,809	1.65	\$5,302	1.77	\$6,334
HVAC Replacement +	1978-1991	\$8,198	1,515	222	1,295	\$823	\$672	2.23	\$11,116	1.70	\$5,720	1.69	\$5,697
PV	1992-2010		1,921	184	1,136	\$818	\$664	2.20	\$10,859	1.73	\$5,945	1.67	\$5,516
HVAC HP	Pre-1978		776	293	1,657	\$800	\$662	1.57	\$7,237	1.19	\$2,121	1.28	\$3,153
Replacement w/ Panel Upgrade	1978-1991	\$11,379	1,515	222	1,295	\$823	\$672	1.60	\$7,544	1.22	\$2,539	1.22	\$2,516
+ PV	1992-2010		1,921	184	1,136	\$818	\$664	1.58	\$7,287	1.24	\$2,764	1.21	\$2,335
HPWH at Water	Pre-1978		-1,146	157	1,243	-\$79	-\$46	0	-\$4,279	0	-\$2,957	1.48	\$1,257
Heater	1978-1991	\$2,594	-1,154	158	1,248	-\$85	-\$51	0	-\$4,423	0	-\$3,009	1.48	\$1,252
Replacement	1992-2010		-1,161	158	1,250	-\$81	-\$48	0	-\$4,335	0	-\$3,061	1.47	\$1,211
NEEA Tier 3	Pre-1978		-868	156	1,340	\$8	\$22	0.21	-\$2,428	0.43	-\$1,571	1.90	\$2,508
HPWH at	1978-1991	\$2,775	-881	157	1,346	\$1	\$17	0.16	-\$2,593	0.45	-\$1,530	1.90	\$2,511
Replacement	1992-2010		-892	157	1,348	\$3	\$18	0.17	-\$2,553	0.41	-\$1,649	1.88	\$2,445
HPWH at Water	Pre-1978		2,731	157	1,481	\$1,065	\$857	2.25	\$14,302	1.49	\$5,016	1.60	\$6,186
Heater Replacement +	1978-1991	\$10,291	2,722	158	1,485	\$1,036	\$833	2.19	\$13,602	1.48	\$4,938	1.60	\$6,151
PV	1992-2010		2,716	158	1,488	\$954	\$769	2.02	\$11,660	1.47	\$4,855	1.59	\$6,076
HPWH	Pre-1978		2,731	157	1,481	\$1,065	\$857	1.72	\$10,730	1.14	\$1,835	1.22	\$3,005
Replacement w/ Panel Upgrade	1978-1991	\$13,472	2,722	158	1,485	\$1,036	\$833	1.67	\$10,030	1.13	\$1,757	1.22	\$2,970
+ PV	1992-2010		2,716	158	1,488	\$954	\$769	1.54	\$8,088	1.12	\$1,674	1.21	\$2,895

	Minterre	Measure	Electricity	Gas	GHG Savings	-	v Cost ings	Custome	er On-Bill	2019) TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978		3,876	0	237	\$1,077	\$850	1.95	\$12,385	1.31	\$3,692	1.05	\$647
PV + Electric Ready Pre-Wire	1978-1991	\$11,788	3,876	0	237	\$1,046	\$826	1.89	\$11,670	1.31	\$3,663	1.05	\$613
	1992-2010		3,876	0	237	\$958	\$756	1.73	\$9,574	1.31	\$3,628	1.05	\$575

Climate Zone 12 SMUD/PG&E:

Note: Values in red and grey rows indicate option is not cost-effective with B/C ratio less than 1. Cells with "n/a" reflect lighting and water heating efficiency measures and packages that did not look at TDV cost effectiveness or GHG impacts.

			-	-		-							
	Mintorio	Measure	Electricity	Gas	GHG Savings		/ Cost ings	Custom	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO₂e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$3,332	886	41	545	\$249	\$201	1.61	\$2,295	2.61	\$5,372	2.55	\$5,152
R-49 Attic Insulation	1978-1991	\$2,874	482	20	282	\$131	\$106	0.99	-\$47	1.61	\$1,745	1.57	\$1,644
modulion	1992-2010	\$1,852	126	8	106	\$39	\$32	0.46	-\$1,124	0.84	-\$291	0.84	-\$294
	Pre-1978		52	14	146	\$38	\$32	0.57	-\$706	0.76	-\$359	0.97	-\$42
Reduced Infiltration	1978-1991	\$1,474	31	9	97	\$23	\$19	0.34	-\$1,084	0.50	-\$739	0.58	-\$616
minutation	1992-2010		18	6	60	\$15	\$13	0.23	-\$1,280	0.23	-\$1,131	0.44	-\$820
	Pre-1978	\$683	619	38	509	\$199	\$162	6.33	\$4,091	13.77	\$8,719	12.40	\$7,788
Duct Sealing	1978-1991	\$683	358	22	299	\$115	\$93	3.65	\$2,034	8.59	\$5,182	7.73	\$4,597
	1992-2010	\$423	60	6	77	\$24	\$20	1.25	\$120	2.57	\$663	2.83	\$775
	Pre-1978		1,094	66	888	\$348	\$283	1.90	\$4,006	4.19	\$12,715	3.77	\$11,030
New Ducts	1978-1991	\$3,986	795	47	662	\$252	\$205	1.37	\$1,660	3.23	\$8,898	2.91	\$7,605
	1992-2010		203	19	251	\$80	\$66	0.44	-\$2,510	1.02	\$84	1.01	\$38
	Pre-1978		389	-5	14	\$65	\$51	1.79	\$668	5.48	\$2,588	3.28	\$1,771
Cool Roof	1978-1991	\$778	276	-3	18	\$47	\$37	1.30	\$254	4.41	\$1,969	2.51	\$1,172
	1992-2010		121	-3	2	\$19	\$15	0.52	-\$408	1.88	\$509	1.30	\$233
R-13 Wall Insulation	Pre-1978	\$3,360	247	49	550	\$144	\$119	0.95	-\$202	1.55	\$1,859	1.58	\$1,940
	Pre-1978	¢0.040	1,242	25	473	\$289	\$231	0.63	-\$4,084	1.27	\$2,662	1.05	\$499
Windows	1978-1991	\$9,810	1,011	21	408	\$239	\$191	0.52	-\$5,282	1.05	\$456	0.89	-\$1,094
LED lamp vs CFL	All	\$2.26	1.2	0	n/a	\$0.24	\$0.19	2.54	\$3.48	n/a	n/a	n/a	n/a
Exterior Photosensor	All	\$42.58	12.1	0	n/a	\$1.44	\$1.14	0.80	-\$8.38	n/a	n/a	n/a	n/a

Table 90: CZ 12 (SMUD/PG&E) - Single Family Efficiency Upgrade Cost-Effectiveness Results

		Measure	Electricity	Gas	GHG Savings		v Cost ings	Custom	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO2e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$4,806	938	57	713	\$289	\$234	1.30	\$1,635	2.16	\$5,571	2.05	\$5,046
R49 Attic & Air Sealing Package	1978-1991	\$4,348	513	30	377	\$155	\$126	0.77	-\$1,103	1.27	\$1,181	1.27	\$1,175
	1992-2010	\$3,326	145	14	170	\$54	\$45	0.36	-\$2,399	0.60	-\$1,319	0.64	-\$1,212
	Pre-1978	\$4,015	1,396	77	1,026	\$423	\$343	2.28	\$5,779	4.34	\$13,393	4.04	\$12,223
R49 Attic & Duct Sealing Package	1978-1991	\$3,557	789	41	563	\$235	\$190	1.43	\$1,701	2.85	\$6,578	2.65	\$5,863
oouning r uonugo	1992-2010	\$2,275	179	14	181	\$62	\$51	0.59	-\$1,039	1.22	\$493	1.17	\$398
R49 Attic. Air	Pre-1978	\$5,489	1,439	90	1,169	\$456	\$370	1.80	\$4,938	3.38	\$13,089	3.17	\$11,899
Sealing & Duct	1978-1991	\$5,031	817	49	655	\$256	\$207	1.10	\$573	2.20	\$6,020	2.02	\$5,141
Sealing Package	1992-2010	\$3,749	197	19	241	\$77	\$63	0.45	-\$2,329	0.88	-\$460	0.88	-\$466
R49 Attic, Air	Pre-1978	\$8,792	1,884	117	1,548	\$598	\$485	1.47	\$4,682	2.96	\$17,240	2.74	\$15,342
Sealing & New	1978-1991	\$8,334	1,222	73	1,005	\$385	\$312	1.00	\$12	2.15	\$9,587	1.97	\$8,083
Ducts Package	1992-2010	\$7,312	330	32	411	\$129	\$105	0.39	-\$5,050	0.83	-\$1,275	0.80	-\$1,482
Advanced Envelope Package	Pre-1978	\$18,659	2,410	169	2,174	\$797	\$649	0.93	-\$1,489	1.76	\$14,200	1.63	\$11,725
Water Heating Package	All Vintages	\$208	0	16	n/a	\$32	\$29	1.89	\$208	n/a	n/a	n/a	n/a

Table 91: CZ 12 (SMUD/PG&E) - Single Family Efficiency Packages Cost-Effectiveness Results

	Martana	Measure	Electricity	Gas	GHG Savings	Utility Savi	r Cost ings	Custome	er On-Bill	2019) TDV	2022	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
-	Pre-1978		3,876		237	\$493	\$389	1.37	\$3,157	2.01	\$7,783	1.62	\$4,738
Prescriptive PV System	1978-1991	\$7,697	3,876	0	237	\$493	\$389	1.37	\$3,157	2.01	\$7,754	1.61	\$4,704
i v eyetem	1992-2010		3,876		237	\$493	\$389	1.37	\$3,157	2.00	\$7,719	1.61	\$4,666
	Pre-1978		3,673		854	\$559	\$441	0.64	-\$7,321	1.28	\$5,337	0.87	-\$2,389
PV + Battery	1978-1991	\$19,069	3,670	0	878	\$562	\$444	0.65	-\$7,252	1.30	\$5,789	0.88	-\$2,236
	1992-2010		3,671		908	\$557	\$440	0.64	-\$7,363	1.33	\$6,342	0.90	-\$1,864

Table 92: CZ 12 (SMUD/PG&E) - Single Family PV & Battery Cost-Effectiveness Results

Table 93: CZ 12 (SMUD/PG&E) - Single Family Equipment Fuel Substitution Cost-Effectiveness Results

		Measure	Electricity	Gas	GHG Savings		v Cost ings	Custom	er On-Bill	2019	9 TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
Heat Pump at	Pre-1978		-3,101	293	1,419	\$202	\$190	10.45	\$5,158	0	-\$2,541	4.12	\$1,567
HVAC	1978-1991	\$501	-2,361	222	1,058	\$138	\$132	7.24	\$3,406	0	-\$2,083	2.93	\$968
Replacement	1992-2010		-1,955	184	899	\$107	\$103	5.65	\$2,537	0	-\$1,841	2.63	\$815
High-Effic. Heat	Pre-1978		-2,198	293	1,769	\$334	\$295	2.18	\$4,780	1.44	\$1,666	2.28	\$4,794
Pump at HVAC	1978-1991	\$3,749	-1,669	222	1,334	\$241	\$213	1.57	\$2,327	1.17	\$632	1.78	\$2,907
Replacement	1992-2010		-1,459	184	1,110	\$178	\$159	1.17	\$699	0.81	-\$725	1.37	\$1,395
Heat Pump at	Pre-1978		776	293	1,657	\$695	\$579	1.92	\$8,315	1.65	\$5,302	1.77	\$6,334
HVAC Replacement +	1978-1991	\$8,198	1,515	222	1,295	\$631	\$521	1.72	\$6,563	1.70	\$5,720	1.69	\$5,697
PV	1992-2010		1,921	184	1,136	\$600	\$492	1.63	\$5,694	1.73	\$5,945	1.67	\$5,516
HVAC HP	Pre-1978		776	293	1,657	\$695	\$579	1.38	\$4,743	1.19	\$2,121	1.28	\$3,153
Replacement w/ Panel Upgrade	1978-1991	\$11,379	1,515	222	1,295	\$631	\$521	1.24	\$2,991	1.22	\$2,539	1.22	\$2,516
+ PV	1992-2010		1,921	184	1,136	\$600	\$492	1.17	\$2,122	1.24	\$2,764	1.21	\$2,335
HPWH at Water	Pre-1978		-1,146	157	1,243	\$145	\$130	1.35	\$1,009	0	-\$2,957	1.48	\$1,257
Heater	1978-1991	\$2,594	-1,154	158	1,248	\$139	\$126	1.30	\$879	0	-\$3,009	1.48	\$1,252
Replacement	1992-2010		-1,161	158	1,250	\$136	\$123	1.28	\$805	0	-\$3,061	1.47	\$1,211
NEEA Tier 3	Pre-1978		-868	156	1,340	\$176	\$154	1.50	\$1,541	0.43	-\$1,571	1.90	\$2,508
HPWH at	1978-1991	\$2,775	-881	157	1,346	\$170	\$150	1.46	\$1,408	0.45	-\$1,530	1.90	\$2,511
Replacement	1992-2010		-892	157	1,348	\$167	\$147	1.43	\$1,329	0.41	-\$1,649	1.88	\$2,445
HPWH at Water	Pre-1978		2,731	157	1,481	\$637	\$519	1.37	\$4,165	1.49	\$5,016	1.60	\$6,186
Heater Replacement +	1978-1991	\$10,291	2,722	158	1,485	\$632	\$515	1.35	\$4,036	1.48	\$4,938	1.60	\$6,151
PV	1992-2010	1	2,716	158	1,488	\$629	\$512	1.35	\$3,962	1.47	\$4,855	1.59	\$6,076
HPWH	Pre-1978		2,731	157	1,481	\$637	\$519	1.04	\$594	1.14	\$1,835	1.22	\$3,005
Replacement w/ Panel Upgrade	1978-1991	\$13,472	2,722	158	1,485	\$632	\$515	1.03	\$464	1.13	\$1,757	1.22	\$2,970
+ PV	1992-2010		2,716	158	1,488	\$629	\$512	1.03	\$390	1.12	\$1,674	1.21	\$2,895

	Minterre	Measure	Electricity	Gas	GHG Savings	-	r Cost ings	Custome	er On-Bill	2019) TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978		3,876	0	237	\$493	\$389	0.89	-\$1,437	1.31	\$3,692	1.05	\$647
PV + Electric Ready Pre-Wire	1978-1991	\$11,788	3,876	0	237	\$493	\$389	0.89	-\$1,437	1.31	\$3,663	1.05	\$613
	1992-2010		3,876	0	237	\$493	\$389	0.89	-\$1,437	1.31	\$3,628	1.05	\$575

Climate Zone 13:

Note: Values in red and grey rows indicate option is not cost-effective with B/C ratio less than 1. Cells with "n/a" reflect lighting and water heating efficiency measures and packages that did not look at TDV cost effectiveness or GHG impacts.

	Mindana	Measure	Electricity	Gas	GHG Savings		v Cost ings	Custom	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO2e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$3,332	1,329	29	454	\$545	\$434	3.48	\$9,266	2.80	\$6,001	3.09	\$6,969
R-49 Attic Insulation	1978-1991	\$2,874	714	15	223	\$294	\$234	2.18	\$3,796	1.86	\$2,458	2.01	\$2,907
inculation	1992-2010	\$1,852	207	5	86	\$90	\$71	1.03	\$59	0.97	-\$58	1.01	\$23
	Pre-1978		107	12	132	\$64	\$52	0.94	-\$104	0.99	-\$19	1.12	\$171
Reduced Infiltration	1978-1991	\$1,474	70	7	72	\$42	\$34	0.62	-\$636	0.71	-\$428	0.92	-\$112
minudion	1992-2010		41	5	60	\$24	\$20	0.36	-\$1,064	0.37	-\$932	0.29	-\$1,051
	Pre-1978	\$683	1,409	27	475	\$593	\$471	18.42	\$13,362	17.50	\$11,271	19.77	\$12,821
Duct Sealing	1978-1991	\$683	873	15	299	\$368	\$292	11.43	\$8,001	11.78	\$7,365	12.43	\$7,806
	1992-2010	\$423	174	4	79	\$77	\$61	3.86	\$1,357	4.37	\$1,426	4.39	\$1,435
	Pre-1978		2,409	47	853	\$1,016	\$808	5.41	\$19,752	5.20	\$16,745	5.68	\$18,660
New Ducts	1978-1991	\$3,986	1,839	34	679	\$777	\$617	4.13	\$14,030	4.23	\$12,876	4.29	\$13,127
	1992-2010		551	13	266	\$242	\$193	1.29	\$1,313	1.43	\$1,706	1.38	\$1,524
	Pre-1978		631	-5	26	\$225	\$177	6.27	\$4,472	4.23	\$2,512	5.29	\$3,338
Cool Roof	1978-1991	\$778	460	-3	31	\$167	\$131	4.64	\$3,087	3.69	\$2,094	3.95	\$2,293
	1992-2010		220	-3	18	\$79	\$62	2.19	\$1,007	1.86	\$671	1.79	\$613
R-13 Wall Insulation	Pre-1978	\$3,360	550	38	464	\$281	\$226	1.80	\$3,012	1.82	\$2,758	2.02	\$3,429
Mindawa	Pre-1978	¢0.040	1,991	21	451	\$781	\$619	1.68	\$7,542	1.41	\$4,048	1.52	\$5,116
Windows	1978-1991	\$9,810	1,617	18	388	\$640	\$507	1.38	\$4,203	1.21	\$2,063	1.24	\$2,357
LED lamp vs CFL	All	\$2.26	1.2	0	n/a	\$0.44	\$0.35	4.67	\$8.27	n/a	n/a	n/a	n/a
Exterior Photosensor	All	\$42.58	12.1	0	n/a	\$2.88	\$2.27	1.60	\$25.62	n/a	n/a	n/a	n/a

Table 94: CZ 13 - Single Family Efficiency Upgrade Cost-Effectiveness Results

		Measure	Electricity	Gas	GHG Savings		/ Cost ings	Custom	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$4,806	1,444	42	598	\$613	\$489	2.72	\$9,271	2.26	\$6,048	2.50	\$7,195
R49 Attic & Air Sealing Package	1978-1991	\$4,348	785	22	318	\$336	\$268	1.64	\$3,146	1.46	\$2,006	1.51	\$2,200
e camig raciage	1992-2010	\$3,326	248	10	149	\$114	\$91	0.73	-\$995	0.71	-\$973	0.69	-\$1,042
	Pre-1978	\$4,015	2,592	55	932	\$1,082	\$860	5.73	\$21,304	5.19	\$16,820	5.57	\$18,341
R49 Attic & Duct Sealing Package	1978-1991	\$3,557	1,508	29	527	\$631	\$501	3.76	\$11,043	3.62	\$9,316	3.72	\$9,685
County P donago	1992-2010	\$2,275	370	10	166	\$162	\$129	1.51	\$1,312	1.56	\$1,273	1.58	\$1,314
R49 Attic. Air	Pre-1978	\$5,489	2,686	66	1,055	\$1,141	\$908	4.42	\$21,080	4.07	\$16,832	4.40	\$18,641
Sealing & Duct	1978-1991	\$5,031	1,574	36	616	\$669	\$532	2.83	\$10,316	2.75	\$8,792	2.77	\$8,908
Sealing Package	1992-2010	\$3,749	409	14	226	\$185	\$148	1.05	\$227	1.10	\$358	1.06	\$214
R49 Attic. Air	Pre-1978	\$8,792	3,687	86	1,451	\$1,567	\$1,246	3.79	\$27,518	3.60	\$22,815	3.80	\$24,651
Sealing & New	1978-1991	\$8,334	2,512	53	973	\$1,068	\$849	2.72	\$16,119	2.72	\$14,335	2.77	\$14,736
Ducts Package	1992-2010	\$7,312	772	23	402	\$345	\$275	1.00	\$38	1.11	\$793	1.06	\$407
Advanced Envelope Package	Pre-1978	\$18,659	4,436	128	1,955	\$1,924	\$1,533	2.20	\$25,042	2.09	\$20,426	2.17	\$21,881
Water Heating Package	All Vintages	\$208	0	16	n/a	\$33	\$30	1.94	\$220	n/a	n/a	n/a	n/a

Table 95: CZ 13 - Single Family Efficiency Packages Cost-Effectiveness Results

	Martana	Measure	Electricity	Gas	GHG Savings	Utility Savi	r Cost ings	Custom	er On-Bill	2019) TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
_	Pre-1978		4,855		309	\$1,394	\$1,101	3.13	\$22,473	1.94	\$8,973	1.66	\$6,326
Prescriptive PV System	1978-1991	\$9,534	4,855	0	309	\$1,376	\$1,086	3.09	\$22,042	1.94	\$8,921	1.66	\$6,262
l' v oyotom	1992-2010		4,855		309	\$1,312	\$1,035	2.95	\$20,511	1.93	\$8,843	1.65	\$6,167
	Pre-1978		4,634		911	\$1,432	\$1,131	1.50	\$11,321	1.31	\$6,412	0.94	-\$1,201
PV + Battery	1978-1991	\$20,907	4,629	0	942	\$1,422	\$1,122	1.49	\$11,067	1.35	\$7,333	0.96	-\$913
	1992-2010		4,622		1,002	\$1,367	\$1,079	1.43	\$9,771	1.42	\$8,802	0.97	-\$556

Table 96: CZ 13 - Single Family PV & Battery Cost-Effectiveness Results

Table 97: CZ 13 - Single Family Equipment Fuel Substitution Cost-Effectiveness Results

•	Minterre	Measure	Electricity	Gas	GHG Savings	Utility Savi	v Cost ings	Custom	er On-Bill	2019	9 TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO2e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
Heat Pump at	Pre-1978		-2,305	214	991	-\$120	-\$72	0	-\$2,717	0	-\$2,757	2.65	\$826
HVAC	1978-1991	\$501	-1,711	159	730	-\$75	-\$43	0	-\$1,846	0	-\$2,163	1.93	\$466
Replacement	1992-2010		-1,396	130	605	-\$60	-\$35	0	-\$1,598	0.97	-\$58	1.65	\$325
High-Effic. Heat	Pre-1978		-1,039	214	1,388	\$316	\$272	2.01	\$4,099	1.90	\$3,362	2.63	\$6,102
Pump at HVAC	1978-1991	\$3,749	-700	159	1,054	\$278	\$235	1.74	\$2,996	1.60	\$2,265	2.12	\$4,186
Replacement	1992-2010		-647	130	865	\$190	\$162	1.20	\$808	0.37	-\$932	1.63	\$2,357
Heat Pump at	Pre-1978		2,550	214	1,300	\$1,224	\$988	2.67	\$18,562	1.63	\$6,279	1.72	\$7,181
HVAC Replacement +	1978-1991	\$10,036	3,144	159	1,039	\$1,247	\$1,000	2.71	\$18,924	1.68	\$6,806	1.67	\$6,746
PV	1992-2010		3,459	130	914	\$1,203	\$962	2.60	\$17,775	4.37	\$1,426	1.65	\$6,527
HVAC HP	Pre-1978		2,550	214	1,300	\$1,224	\$988	2.02	\$14,990	1.23	\$3,098	1.30	\$4,000
Replacement w/ Panel Upgrade	1978-1991	\$13,217	3,144	159	1,039	\$1,247	\$1,000	2.05	\$15,352	1.27	\$3,625	1.27	\$3,565
+ PV	1992-2010		3,459	130	914	\$1,203	\$962	1.97	\$14,203	1.43	\$1,706	1.25	\$3,346
HPWH at Water	Pre-1978		-952	148	1,205	-\$36	-\$14	0	-\$3,297	0.12	-\$2,286	1.67	\$1,735
Heater	1978-1991	\$2,594	-964	149	1,205	-\$36	-\$14	0	-\$3,311	0.10	-\$2,338	1.72	\$1,871
Replacement	1992-2010		-976	149	1,210	-\$48	-\$24	0	-\$3,605	0.07	-\$2,401	1.64	\$1,663
NEEA Tier 3	Pre-1978		-736	147	1,295	\$32	\$40	0.39	-\$1,884	0.54	-\$1,283	1.90	\$2,494
HPWH at	1978-1991	\$2,775	-747	148	1,293	\$32	\$40	0.39	-\$1,881	0.55	-\$1,260	1.97	\$2,704
Replacement	1992-2010		-759	148	1,306	\$21	\$30	0.30	-\$2,176	0.47	-\$1,458	1.83	\$2,315
HPWH at Water	Pre-1978		3,904	148	1,514	\$1,406	\$1,125	2.51	\$20,306	1.57	\$6,874	1.68	\$8,243
Heater Replacement +	1978-1991	\$12,128	3,891	149	1,514	\$1,396	\$1,117	2.49	\$20,066	1.56	\$6,776	1.69	\$8,320
PV	1992-2010		3,879	149	1,519	\$1,326	\$1,061	2.37	\$18,400	1.55	\$6,635	1.66	\$8,024
HPWH	Pre-1978		3,904	148	1,514	\$1,406	\$1,125	1.98	\$16,734	1.24	\$3,693	1.33	\$5,062
Replacement w/ Panel Upgrade	1978-1991	\$15,309	3,891	149	1,514	\$1,396	\$1,117	1.97	\$16,494	1.23	\$3,595	1.34	\$5,139
+ PV	1992-2010		3,879	149	1,519	\$1,326	\$1,061	1.87	\$14,828	1.23	\$3,454	1.32	\$4,843

	Minterre	Measure	Electricity	Gas	GHG Savings	-	v Cost ings	Custome	er On-Bill	2019	O TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978		4,855	0	309	\$1,394	\$1,101	2.18	\$17,880	1.36	\$4,882	1.16	\$2,235
PV + Electric Ready Pre-Wire	1978-1991	\$13,625	4,855	0	309	\$1,376	\$1,086	2.15	\$17,448	1.35	\$4,830	1.16	\$2,171
	1992-2010		4,855	0	309	\$1,312	\$1,035	2.05	\$15,917	1.35	\$4,752	1.15	\$2,076

Climate Zone 14 SCE/SoCalGas:

Note: Values in red and grey rows indicate option is not cost-effective with B/C ratio less than 1. Cells with "n/a" reflect lighting and water heating efficiency measures and packages that did not look at TDV cost effectiveness or GHG impacts.

	Martana	Measure	Electricity	Gas	GHG Savings		v Cost ings	Custome	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO2e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$3,332	936	48	564	\$374	\$303	2.43	\$5,358	2.75	\$5,816	2.83	\$6,086
R-49 Attic Insulation	1978-1991	\$2,874	504	23	274	\$201	\$162	1.51	\$1,634	1.76	\$2,180	1.75	\$2,154
	1992-2010	\$1,852	139	9	105	\$61	\$50	0.72	-\$588	0.96	-\$75	0.92	-\$141
	Pre-1978		111	19	201	\$63	\$52	0.95	-\$86	1.26	\$378	1.30	\$444
Reduced Infiltration	1978-1991	\$1,474	69	11	120	\$38	\$31	0.57	-\$714	0.80	-\$290	0.72	-\$420
initiation	1992-2010		36	7	74	\$22	\$19	0.34	-\$1,100	0.40	-\$889	0.51	-\$728
	Pre-1978	\$683	939	44	567	\$388	\$314	12.27	\$8,641	17.18	\$11,049	15.61	\$9,980
Duct Sealing	1978-1991	\$683	560	24	321	\$233	\$188	7.36	\$4,876	10.91	\$6,766	9.68	\$5,928
	1992-2010	\$423	104	7	88	\$47	\$38	2.43	\$679	3.74	\$1,158	3.40	\$1,017
	Pre-1978		1,650	73	960	\$681	\$550	3.68	\$12,009	5.01	\$15,981	4.76	\$14,976
New Ducts	1978-1991	\$3,986	1,230	50	692	\$511	\$411	2.76	\$7,865	3.91	\$11,586	3.60	\$10,382
	1992-2010		349	21	279	\$157	\$128	0.86	-\$647	1.27	\$1,092	1.21	\$839
	Pre-1978		432	-7	-43	\$136	\$106	3.75	\$2,335	3.97	\$2,307	4.06	\$2,382
Cool Roof	1978-1991	\$778	306	-5	-14	\$99	\$78	2.74	\$1,478	3.17	\$1,685	2.75	\$1,362
	1992-2010		141	-4	-17	\$46	\$35	1.25	\$216	1.49	\$383	1.34	\$268
R-13 Wall Insulation	Pre-1978	\$3,360	389	57	641	\$210	\$175	1.39	\$1,482	1.84	\$2,810	1.90	\$3,032
) A (inclusion	Pre-1978	¢0.040	1,571	17	363	\$554	\$440	1.20	\$2,183	1.38	\$3,725	1.12	\$1,150
Windows	1978-1991	\$9,810	1,281	9	272	\$452	\$358	0.98	-\$269	1.11	\$1,116	0.89	-\$1,125
LED lamp vs CFL	All	\$2.26	1.2	0	n/a	\$0.35	\$0.28	3.66	\$6.01	n/a	n/a	n/a	n/a
Exterior Photosensor	All	\$42.58	12.1	0	n/a	\$2.00	\$1.58	1.11	\$4.84	n/a	n/a	n/a	n/a

Table 98: CZ 14 (SCE/SoCalGas) - Single Family Efficiency Upgrade Cost-Effectiveness Results

		Measure	Electricity	Gas	GHG Savings		v Cost ings	Custom	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$4,806	1,051	67	761	\$439	\$357	1.99	\$5,326	2.35	\$6,467	2.40	\$6,726
R49 Attic & Air Sealing Package	1978-1991	\$4,348	573	35	397	\$240	\$195	1.20	\$964	1.43	\$1,864	1.44	\$1,913
e calling r achage	1992-2010	\$3,326	173	16	183	\$83	\$68	0.54	-\$1,704	0.70	-\$993	0.73	-\$904
	Pre-1978	\$4,015	1,764	88	1,094	\$726	\$587	3.91	\$13,105	5.04	\$16,222	4.83	\$15,366
R49 Attic & Duct Sealing Package	1978-1991	\$3,557	1,006	45	579	\$413	\$334	2.51	\$6,017	3.39	\$8,517	3.12	\$7,554
e calling r achage	1992-2010	\$2,275	235	15	191	\$106	\$86	1.01	\$21	1.39	\$887	1.34	\$778
R49 Attic. Air	Pre-1978	\$5,489	1,851	105	1,277	\$777	\$630	3.07	\$12,751	4.01	\$16,508	3.80	\$15,373
Sealing & Duct	1978-1991	\$5,031	1,063	56	698	\$446	\$361	1.92	\$5,183	2.59	\$8,019	2.39	\$6,976
Sealing Package	1992-2010	\$3,749	267	22	265	\$126	\$103	0.73	-\$1,120	1.04	\$157	1.01	\$21
R49 Attic. Air	Pre-1978	\$8,792	2,558	132	1,671	\$1,072	\$868	2.64	\$16,165	3.45	\$21,550	3.33	\$20,481
Sealing & New	1978-1991	\$8,334	1,711	80	1,054	\$716	\$579	1.85	\$7,997	2.55	\$12,880	2.37	\$11,425
Ducts Package	1992-2010	\$7,312	502	35	447	\$232	\$189	0.69	-\$2,538	1.00	\$16	0.98	-\$180
Advanced Envelope Package	Pre-1978	\$18,659	3,187	188	2,319	\$1,350	\$1,096	1.57	\$11,940	2.04	\$19,495	1.90	\$16,726
Water Heating Package	All Vintages	\$208	0	16	n/a	\$24	\$22	1.43	\$100	n/a	n/a	n/a	n/a

Table 99: CZ 14 (SCE/SoCalGas) - Single Family Efficiency Packages Cost-Effectiveness Results

	Martana	Measure	Electricity	Gas	GHG Savings	Utility Savi	r Cost ings	Custom	er On-Bill	2019) TDV	2022	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
-	Pre-1978		4,697		377	\$1,043	\$823	2.82	\$15,923	2.22	\$9,650	1.99	\$7,867
Prescriptive PV System	1978-1991	\$7,929	4,697	0	377	\$1,022	\$806	2.76	\$15,421	2.21	\$9,610	1.99	\$7,821
l v eyetem	1992-2010		4,697		377	\$954	\$753	2.58	\$13,814	2.20	\$9,546	1.98	\$7,746
	Pre-1978		4,467		1,019	\$1,218	\$962	1.39	\$8,029	1.27	\$5,234	1.09	\$1,705
PV + Battery	1978-1991	\$19,302	4,463	0	1,041	\$1,209	\$954	1.37	\$7,795	1.28	\$5,404	1.10	\$1,968
	1992-2010		4,456		1,105	\$1,154	\$911	1.31	\$6,509	1.31	\$6,009	1.16	\$3,166

Table 100: CZ 14 (SCE/SoCalGas) - Single Family PV & Battery Cost-Effectiveness Results

Table 101: CZ 14 (SCE/SoCalGas) - Single Family Equipment Fuel Substitution Cost-Effectiveness Results

Maaaaaa	Mintone	Measure	Electricity	Gas	GHG Savings		r Cost ings	Custom	er On-Bill	2019	Ð TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO2e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
Heat Pump at	Pre-1978		-3,788	306	1,144	-\$549	-\$387	0	-\$12,159	0	-\$4,914	0	-\$729
HVAC	1978-1991	\$501	-2,810	222	785	-\$409	-\$291	0	-\$9,269	0	-\$3,895	0	-\$1,011
Replacement	1992-2010		-2,358	189	701	-\$338	-\$240	0	-\$7,756	0	-\$3,246	0	-\$712
High-Effic. Heat	Pre-1978		-2,606	306	1,569	-\$178	-\$94	0	-\$6,890	1.21	\$776	1.99	\$3,717
Pump at HVAC	1978-1991	\$3,749	-1,884	222	1,124	-\$118	-\$61	0	-\$5,873	1.02	\$64	1.52	\$1,942
Replacement	1992-2010		-1,662	189	976	-\$123	-\$70	0	-\$6,157	0.73	-\$1,022	1.19	\$718
Heat Pump at	Pre-1978		909	306	1,522	\$521	\$457	1.47	\$4,401	1.57	\$4,840	1.85	\$7,187
HVAC Replacement +	1978-1991	\$8,431	1,887	222	1,162	\$639	\$536	1.73	\$6,776	1.69	\$5,790	1.81	\$6,841
PV	1992-2010		2,339	189	1,078	\$665	\$552	1.78	\$7,243	1.76	\$6,404	1.84	\$7,089
HVAC HP	Pre-1978		909	306	1,522	\$521	\$457	1.06	\$829	1.14	\$1,659	1.35	\$4,006
Replacement w/ Panel Upgrade	1978-1991	\$11,612	1,887	222	1,162	\$639	\$536	1.25	\$3,204	1.22	\$2,609	1.32	\$3,660
+ PV	1992-2010		2,339	189	1,078	\$665	\$552	1.28	\$3,671	1.28	\$3,223	1.34	\$3,908
HPWH at Water	Pre-1978		-1,144	153	1,195	-\$127	-\$79	0	-\$5,271	0.06	-\$2,441	1.47	\$1,217
Heater	1978-1991	\$2,594	-1,160	153	1,193	-\$128	-\$80	0	-\$5,290	0.05	-\$2,453	1.48	\$1,243
Replacement	1992-2010		-1,168	154	1,198	-\$127	-\$79	0	-\$5,266	0.02	-\$2,545	1.43	\$1,110
NEEA Tier 3	Pre-1978		-873	152	1,288	-\$43	-\$13	0	-\$3,477	0.53	-\$1,312	1.83	\$2,306
HPWH at	1978-1991	\$2,775	-891	153	1,287	-\$44	-\$14	0	-\$3,500	0.54	-\$1,289	1.84	\$2,324
Replacement	1992-2010		-902	153	1,292	-\$43	-\$13	0	-\$3,487	0.50	-\$1,392	1.79	\$2,203
HPWH at Water	Pre-1978		3,553	153	1,572	\$982	\$796	2.05	\$12,218	1.71	\$7,425	1.88	\$9,300
Heater Replacement +	1978-1991	\$10,523	3,537	153	1,571	\$961	\$780	2.01	\$11,738	1.70	\$7,376	1.88	\$9,286
PV	1992-2010	1	3,529	154	1,576	\$897	\$729	1.88	\$10,205	1.69	\$7,223	1.86	\$9,081
HPWH	Pre-1978		3,553	153	1,572	\$982	\$796	1.57	\$8,646	1.31	\$4,244	1.45	\$6,119
Replacement w/ Panel Upgrade	1978-1991	\$13,704	3,537	153	1,571	\$961	\$780	1.54	\$8,166	1.31	\$4,195	1.45	\$6,105
+ PV	1992-2010		3,529	154	1,576	\$897	\$729	1.44	\$6,633	1.29	\$4,042	1.43	\$5,900

	Minterre	Measure	Electricity	Gas	GHG Savings	-	v Cost ings	Custome	er On-Bill	2019) TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO2e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978		4,697	0	377	\$1,043	\$823	1.85	\$11,329	1.46	\$5,559	1.31	\$3,776
PV + Electric Ready Pre-Wire	1978-1991	\$12,020	4,697	0	377	\$1,022	\$806	1.81	\$10,827	1.46	\$5,519	1.31	\$3,730
	1992-2010		4,697	0	377	\$954	\$753	1.69	\$9,221	1.45	\$5,455	1.30	\$3,655

<u>Climate Zone 14 SDG&E:</u>

Note: Values in red and grey rows indicate option is not cost-effective with B/C ratio less than 1. Cells with "n/a" reflect lighting and water heating efficiency measures and packages that did not look at TDV cost effectiveness or GHG impacts.

	Martana	Measure	Electricity	Gas	GHG Savings		/ Cost ings	Custome	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO2e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$3,332	936	48	564	\$506	\$409	3.28	\$8,541	2.75	\$5,816	2.83	\$6,086
R-49 Attic Insulation	1978-1991	\$2,874	504	23	274	\$272	\$219	2.04	\$3,354	1.76	\$2,180	1.75	\$2,154
	1992-2010	\$1,852	139	9	105	\$86	\$70	1.01	\$17	0.96	-\$75	0.92	-\$141
	Pre-1978		111	19	201	\$85	\$71	1.28	\$467	1.26	\$378	1.30	\$444
Reduced Infiltration	1978-1991	\$1,474	69	11	120	\$50	\$42	0.76	-\$397	0.80	-\$290	0.72	-\$420
initiation	1992-2010		36	7	74	\$30	\$25	0.46	-\$892	0.40	-\$889	0.51	-\$728
	Pre-1978	\$683	939	44	567	\$540	\$436	17.05	\$12,306	17.18	\$11,049	15.61	\$9,980
Duct Sealing	1978-1991	\$683	560	24	321	\$326	\$263	10.27	\$7,112	10.91	\$6,766	9.68	\$5,928
	1992-2010	\$423	104	7	88	\$68	\$55	3.45	\$1,166	3.74	\$1,158	3.40	\$1,017
	Pre-1978		1,650	73	960	\$948	\$764	5.12	\$18,435	5.01	\$15,981	4.76	\$14,976
New Ducts	1978-1991	\$3,986	1,230	50	692	\$717	\$576	3.86	\$12,814	3.91	\$11,586	3.60	\$10,382
	1992-2010		349	21	279	\$226	\$183	1.23	\$1,007	1.27	\$1,092	1.21	\$839
	Pre-1978		432	-7	-43	\$189	\$148	5.22	\$3,585	3.97	\$2,307	4.06	\$2,382
Cool Roof	1978-1991	\$778	306	-5	-14	\$137	\$107	3.80	\$2,375	3.17	\$1,685	2.75	\$1,362
	1992-2010		141	-4	-17	\$66	\$51	1.81	\$690	1.49	\$383	1.34	\$268
R-13 Wall Insulation	Pre-1978	\$3,360	389	57	641	\$285	\$237	1.89	\$3,352	1.84	\$2,810	1.90	\$3,032
Mindawa	Pre-1978	¢0.040	1,571	17	363	\$752	\$597	1.63	\$6,901	1.38	\$3,725	1.12	\$1,150
Windows	1978-1991	\$9,810	1,281	9	272	\$618	\$490	1.33	\$3,673	1.11	\$1,116	0.89	-\$1,125
LED lamp vs CFL	All	\$2.26	1.2	0	n/a	\$0.50	\$0.39	5.23	\$9.55	n/a	n/a	n/a	n/a
Exterior Photosensor	All	\$42.58	12.1	0	n/a	\$2.76	\$2.18	1.54	\$22.81	n/a	n/a	n/a	n/a

Table 102: CZ 14 (SDG&E) - Single Family Efficiency Upgrade Cost-Effectiveness Results

		Measure	Electricity	Gas	GHG Savings	-	v Cost ings	Custom	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$4,806	1,051	67	761	\$593	\$482	2.68	\$9,064	2.35	\$6,467	2.40	\$6,726
R49 Attic & Air Sealing Package	1978-1991	\$4,348	573	35	397	\$324	\$263	1.62	\$3,021	1.43	\$1,864	1.44	\$1,913
e cannig r achaige	1992-2010	\$3,326	173	16	183	\$115	\$94	0.76	-\$901	0.70	-\$993	0.73	-\$904
	Pre-1978	\$4,015	1,764	88	1,094	\$995	\$804	5.35	\$19,623	5.04	\$16,222	4.83	\$15,366
R49 Attic & Duct Sealing Package	1978-1991	\$3,557	1,006	45	579	\$571	\$461	3.46	\$9,823	3.39	\$8,517	3.12	\$7,554
County P donago	1992-2010	\$2,275	235	15	191	\$150	\$121	1.42	\$1,083	1.39	\$887	1.34	\$778
R49 Attic. Air	Pre-1978	\$5,489	1,851	105	1,277	\$1,064	\$862	4.20	\$19,699	4.01	\$16,508	3.80	\$15,373
Sealing & Duct	1978-1991	\$5,031	1,063	56	698	\$615	\$497	2.64	\$9,267	2.59	\$8,019	2.39	\$6,976
Sealing Package	1992-2010	\$3,749	267	22	265	\$177	\$145	1.03	\$133	1.04	\$157	1.01	\$21
R49 Attic, Air	Pre-1978	\$8,792	2,558	132	1,671	\$1,479	\$1,196	3.63	\$26,004	3.45	\$21,550	3.33	\$20,481
Sealing & New	1978-1991	\$8,334	1,711	80	1,054	\$1,000	\$806	2.58	\$14,825	2.55	\$12,880	2.37	\$11,425
Ducts Package	1992-2010	\$7,312	502	35	447	\$333	\$271	0.99	-\$92	1.00	\$16	0.98	-\$180
Advanced Envelope Package	Pre-1978	\$18,659	3,187	188	2,319	\$1,851	\$1,501	2.15	\$24,087	2.04	\$19,495	1.90	\$16,726
Water Heating Package	All Vintages	\$208	0	16	n/a	\$31	\$29	1.85	\$198	n/a	n/a	n/a	n/a

Table 103: CZ 14 (SDG&E) - Single Family Efficiency Packages Cost-Effectiveness Results

	Martana	Measure	Electricity	Gas	GHG Savings		v Cost ings	Custome	er On-Bill	2019	9 TDV	2022	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
_	Pre-1978		4,697		377	\$1,651	\$1,303	4.46	\$30,316	2.22	\$9,650	1.99	\$7,867
Prescriptive PV System	1978-1991	\$7,929	4,697	0	377	\$1,771	\$1,398	4.78	\$33,158	2.21	\$9,610	1.99	\$7,821
i v eyetem	1992-2010		4,697		377	\$1,726	\$1,362	4.66	\$32,106	2.20	\$9,546	1.98	\$7,746
	Pre-1978		4,467		1,019	\$1,810	\$1,429	2.06	\$22,037	1.27	\$5,234	1.09	\$1,705
PV + Battery	1978-1991	\$19,302	4,463	0	1,041	\$1,822	\$1,438	2.07	\$22,311	1.28	\$5,404	1.10	\$1,968
	1992-2010		4,456		1,105	\$1,846	\$1,457	2.10	\$22,892	1.31	\$6,009	1.16	\$3,166

Table 104: CZ 14 (SDG&E) - Single Family PV & Battery Cost-Effectiveness Results

Table 105: CZ 14 (SDG&E) - Single Family Equipment Fuel Substitution Cost-Effectiveness Results

	Minterra	Measure	Electricity	Gas	GHG Savings	Utility Sav	r Cost ings	Custom	er On-Bill	2019	Ð TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
Heat Pump at	Pre-1978		-3,788	306	1,144	-\$733	-\$515	0	-\$15,998	0	-\$4,914	0	-\$729
HVAC	1978-1991	\$501	-2,810	222	785	-\$519	-\$364	0	-\$11,456	0	-\$3,895	0	-\$1,011
Replacement	1992-2010		-2,358	189	701	-\$410	-\$285	0	-\$9,110	0	-\$3,246	0	-\$712
High-Effic. Heat	Pre-1978		-2,606	306	1,569	-\$210	-\$102	0	-\$7,128	1.21	\$776	1.99	\$3,717
Pump at HVAC	1978-1991	\$3,749	-1,884	222	1,124	-\$102	-\$34	0	-\$5,091	1.02	\$64	1.52	\$1,942
Replacement	1992-2010		-1,662	189	976	-\$108	-\$47	0	-\$5,471	0.73	-\$1,022	1.19	\$718
Heat Pump at	Pre-1978		909	306	1,522	\$1,009	\$860	2.77	\$16,491	1.57	\$4,840	1.85	\$7,187
HVAC Replacement +	1978-1991	\$8,431	1,887	222	1,162	\$1,195	\$989	3.19	\$20,356	1.69	\$5,790	1.81	\$6,841
PV	1992-2010		2,339	189	1,078	\$1,282	\$1,050	3.38	\$22,193	1.76	\$6,404	1.84	\$7,089
HVAC HP	Pre-1978		909	306	1,522	\$1,009	\$860	2.00	\$12,919	1.14	\$1,659	1.35	\$4,006
Replacement w/ Panel Upgrade	1978-1991	\$11,612	1,887	222	1,162	\$1,195	\$989	2.30	\$16,784	1.22	\$2,609	1.32	\$3,660
+ PV	1992-2010		2,339	189	1,078	\$1,282	\$1,050	2.45	\$18,621	1.28	\$3,223	1.34	\$3,908
HPWH at Water	Pre-1978		-1,144	153	1,195	-\$130	-\$73	0	-\$5,075	0.06	-\$2,441	1.47	\$1,217
Heater	1978-1991	\$2,594	-1,160	153	1,193	-\$121	-\$66	0	-\$4,870	0.05	-\$2,453	1.48	\$1,243
Replacement	1992-2010		-1,168	154	1,198	-\$118	-\$63	0	-\$4,791	0.02	-\$2,545	1.43	\$1,110
NEEA Tier 3	Pre-1978		-873	152	1,288	-\$27	\$8	0.08	-\$2,851	0.53	-\$1,312	1.83	\$2,306
HPWH at	1978-1991	\$2,775	-891	153	1,287	-\$22	\$12	0.12	-\$2,727	0.54	-\$1,289	1.84	\$2,324
Replacement	1992-2010		-902	153	1,292	-\$25	\$10	0.10	-\$2,777	0.50	-\$1,392	1.79	\$2,203
HPWH at Water	Pre-1978		3,553	153	1,572	\$1,487	\$1,203	3.10	\$24,444	1.71	\$7,425	1.88	\$9,300
Heater Replacement +	1978-1991	\$10,523	3,537	153	1,571	\$1,478	\$1,197	3.08	\$24,239	1.70	\$7,376	1.88	\$9,286
PV	1992-2010	1	3,529	154	1,576	\$1,472	\$1,192	3.07	\$24,096	1.69	\$7,223	1.86	\$9,081
HPWH	Pre-1978		3,553	153	1,572	\$1,487	\$1,203	2.37	\$20,872	1.31	\$4,244	1.45	\$6,119
Replacement w/ Panel Upgrade	1978-1991	\$13,704	3,537	153	1,571	\$1,478	\$1,197	2.36	\$20,667	1.31	\$4,195	1.45	\$6,105
+ PV	1992-2010		3,529	154	1,576	\$1,472	\$1,192	2.35	\$20,524	1.29	\$4,042	1.43	\$5,900

	Minterre	Measure	Electricity	Gas	GHG Savings	Utility Savi	v Cost ings	Custome	er On-Bill	2019	O TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978		4,697	0	377	\$1,651	\$1,303	2.92	\$25,722	1.46	\$5,559	1.31	\$3,776
PV + Electric Ready Pre-Wire	1978-1991	\$12,020	4,697	0	377	\$1,771	\$1,398	3.14	\$28,564	1.46	\$5,519	1.31	\$3,730
	1992-2010		4,697	0	377	\$1,726	\$1,362	3.06	\$27,512	1.45	\$5,455	1.30	\$3,655

Climate Zone 15:

Note: Values in red and grey rows indicate option is not cost-effective with B/C ratio less than 1. Cells with "n/a" reflect lighting and water heating efficiency measures and packages that did not look at TDV cost effectiveness or GHG impacts.

	Nr. (Measure	Electricity	Gas	GHG Savings		v Cost ings	Custom	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO2e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$3,332	1,824	10	257	\$584	\$463	3.71	\$10,135	3.33	\$7,766	3.26	\$7,518
R-49 Attic Insulation	1978-1991	\$2,874	996	5	140	\$320	\$253	2.35	\$4,368	2.12	\$3,206	1.98	\$2,803
modiation	1992-2010	\$1,852	296	2	44	\$97	\$77	1.10	\$218	1.09	\$167	1.03	\$60
	Pre-1978		219	3	38	\$71	\$57	1.02	\$40	1.15	\$214	1.12	\$179
Reduced Infiltration	1978-1991	\$1,474	142	2	42	\$47	\$37	0.67	-\$546	0.79	-\$313	0.56	-\$642
minutuon	1992-2010		84	1	22	\$27	\$22	0.39	-\$1,006	0.51	-\$728	0.38	-\$918
	Pre-1978	\$683	2,634	4	325	\$866	\$684	26.77	\$19,763	27.36	\$18,002	25.02	\$16,407
Duct Sealing	1978-1991	\$683	1,696	1	243	\$566	\$447	17.49	\$12,645	18.21	\$11,758	16.21	\$10,389
	1992-2010	\$423	356	0	63	\$119	\$94	5.95	\$2,352	6.99	\$2,532	5.97	\$2,100
	Pre-1978		4,230	7	577	\$1,401	\$1,107	7.42	\$28,727	7.53	\$26,043	6.90	\$23,514
New Ducts	1978-1991	\$3,986	3,252	4	486	\$1,093	\$863	5.78	\$21,413	6.01	\$19,985	5.40	\$17,537
	1992-2010		1,016	1	178	\$342	\$270	1.81	\$3,633	2.08	\$4,324	1.84	\$3,356
	Pre-1978		883	-1	56	\$280	\$221	7.82	\$5,788	6.20	\$4,044	6.13	\$3,992
Cool Roof	1978-1991	\$778	659	-1	65	\$214	\$169	5.96	\$4,209	4.85	\$2,996	4.58	\$2,785
	1992-2010		311	0	26	\$102	\$81	2.85	\$1,568	2.52	\$1,184	2.61	\$1,250
R-13 Wall Insulation	Pre-1978	\$3,360	1,020	10	259	\$337	\$267	2.13	\$4,245	2.40	\$4,717	2.02	\$3,432
) A (inclusive	Pre-1978	¢0.040	3,358	2	347	\$1,067	\$842	2.29	\$14,248	2.15	\$11,315	1.88	\$8,668
Windows	1978-1991	\$9,810	2,702	2	284	\$864	\$682	1.86	\$9,453	1.71	\$6,989	1.52	\$5,108
LED lamp vs CFL	All	\$2.26	1.2	0	n/a	\$0.36	\$0.28	3.73	\$6.17	n/a	n/a	n/a	n/a
Exterior Photosensor	All	\$42.58	12.1	0	n/a	\$2.00	\$1.58	1.11	\$4.84	n/a	n/a	n/a	n/a

Table 106: CZ 15 - Single Family Efficiency Upgrade Cost-Effectiveness Results

		Measure	Electricity	Gas	GHG Savings	-	v Cost ings	Custome	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$4,806	2,056	13	322	\$660	\$523	2.91	\$10,289	2.70	\$8,167	2.55	\$7,450
R49 Attic & Air Sealing Package	1978-1991	\$4,348	1,133	6	154	\$365	\$289	1.77	\$3,777	1.64	\$2,764	1.57	\$2,469
	1992-2010	\$3,326	379	3	67	\$124	\$98	0.79	-\$795	0.83	-\$564	0.74	-\$881
	Pre-1978	\$4,015	4,283	13	617	\$1,401	\$1,107	7.37	\$28,712	7.23	\$25,008	6.65	\$22,669
R49 Attic & Duct Sealing Package	1978-1991	\$3,557	2,574	6	374	\$850	\$672	5.05	\$16,159	5.06	\$14,449	4.54	\$12,581
	1992-2010	\$2,275	636	2	108	\$211	\$167	1.96	\$2,450	2.15	\$2,627	1.89	\$2,019
R49 Attic. Air	Pre-1978	\$5,489	4,496	15	676	\$1,471	\$1,163	5.66	\$28,734	5.64	\$25,467	5.12	\$22,592
Sealing & Duct	1978-1991	\$5,031	2,706	7	408	\$894	\$706	3.75	\$15,536	3.81	\$14,138	3.38	\$11,986
Sealing Package	1992-2010	\$3,749	710	3	123	\$236	\$186	1.33	\$1,383	1.50	\$1,862	1.31	\$1,159
R49 Attic. Air	Pre-1978	\$8,792	6,122	18	920	\$2,023	\$1,599	4.86	\$38,098	4.90	\$34,297	4.49	\$30,658
Sealing & New	1978-1991	\$8,334	4,241	8	648	\$1,417	\$1,120	3.59	\$24,236	3.71	\$22,585	3.32	\$19,312
Ducts Package	1992-2010	\$7,312	1,353	3	242	\$450	\$356	1.30	\$2,464	1.49	\$3,607	1.31	\$2,285
Advanced Envelope Package	Pre-1978	\$18,659	7,579	28	1,156	\$2,482	\$1,963	2.81	\$37,936	2.87	\$34,978	2.55	\$28,977
Water Heating Package	All Vintages	\$208	0	17	n/a	\$24	\$22	1.43	\$101	n/a	n/a	n/a	n/a

Table 107: CZ 15 - Single Family Efficiency Packages Cost-Effectiveness Results

	Minterra	Measure	Electricity	Gas	GHG Savings	Utility Savi	r Cost ings	Custome	er On-Bill	2019	9 TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
_	Pre-1978		7,104		584	\$1,705	\$1,346	2.82	\$26,069	2.03	\$13,265	1.84	\$10,897
Prescriptive PV System	1978-1991	\$12,933	7,104	0	584	\$1,683	\$1,328	2.79	\$25,539	2.01	\$13,124	1.83	\$10,736
i v oyotom	1992-2010		7,104		584	\$1,533	\$1,210	2.54	\$21,996	2.00	\$12,942	1.81	\$10,494
	Pre-1978		6,850		1,082	\$1,885	\$1,487	1.69	\$18,268	1.34	\$8,172	1.11	\$2,564
PV + Battery	1978-1991	\$24,305	6,832	0	1,157	\$1,882	\$1,485	1.69	\$18,199	1.38	\$9,324	1.13	\$3,085
	1992-2010		6,821		1,273	\$1,769	\$1,396	1.59	\$15,539	1.43	\$10,341	1.17	\$4,102

Table 108: CZ 15 - Single Family PV & Battery Cost-Effectiveness Results

Table 109: CZ 15 - Single Family Equipment Fuel Substitution Cost-Effectiveness Results

	NP 4	Measure	Electricity	Gas	GHG Savings		v Cost ings	Custom	er On-Bill	2019	9 TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
Heat Pump at	Pre-1978		-308	28	120	-\$150	-\$115	0	-\$3,985	0	-\$709	0.21	-\$398
HVAC	1978-1991	\$501	-163	14	52	-\$140	-\$109	0	-\$3,813	0	-\$668	0	-\$524
Replacement	1992-2010		-112	9	29	-\$137	-\$107	0	-\$3,753	0	-\$643	0	-\$553
High-Effic. Heat	Pre-1978		1,349	28	466	\$394	\$315	2.33	\$5,379	3.14	\$8,029	2.80	\$6,753
Pump at HVAC	1978-1991	\$3,749	1,212	14	350	\$314	\$250	1.85	\$3,441	2.64	\$6,165	2.32	\$4,950
Replacement	1992-2010		929	9	284	\$212	\$169	1.25	\$1,004	2.08	\$4,065	1.80	\$3,011
Heat Pump at	Pre-1978		6,796	28	704	\$1,479	\$1,171	2.37	\$20,288	1.93	\$12,516	1.78	\$10,433
HVAC Replacement +	1978-1991	\$13,434	6,941	14	636	\$1,460	\$1,154	2.33	\$19,787	1.92	\$12,426	1.76	\$10,159
PV	1992-2010		6,992	9	613	\$1,420	\$1,122	2.27	\$18,814	1.92	\$12,300	1.74	\$9,932
HVAC HP	Pre-1978		6,796	28	704	\$1,479	\$1,171	1.91	\$16,716	1.56	\$9,335	1.44	\$7,252
Replacement w/ Panel Upgrade	1978-1991	\$16,615	6,941	14	636	\$1,460	\$1,154	1.88	\$16,215	1.56	\$9,245	1.42	\$6,978
+ PV	1992-2010		6,992	9	613	\$1,420	\$1,122	1.83	\$15,242	1.55	\$9,119	1.41	\$6,751
HPWH at Water	Pre-1978		-613	127	1,086	-\$33	-\$10	0	-\$3,189	0.64	-\$926	1.77	\$2,006
Heater	1978-1991	\$2,594	-622	127	1,089	-\$35	-\$12	0	-\$3,243	0.65	-\$917	1.75	\$1,943
Replacement	1992-2010		-633	127	1,089	-\$36	-\$13	0	-\$3,273	0.62	-\$981	1.73	\$1,903
NEEA Tier 3	Pre-1978		-504	127	1,131	\$1	\$17	0.16	-\$2,589	0.81	-\$531	1.85	\$2,358
HPWH at	1978-1991	\$2,775	-513	127	1,134	-\$1	\$15	0.15	-\$2,640	0.80	-\$566	1.84	\$2,324
Replacement	1992-2010		-524	127	1,132	-\$3	\$13	0.13	-\$2,687	0.77	-\$626	1.82	\$2,272
HPWH at Water	Pre-1978		6,491	127	1,670	\$1,708	\$1,364	2.38	\$23,723	1.81	\$12,503	1.84	\$13,047
Heater Replacement +	1978-1991	\$15,527	6,482	127	1,673	\$1,684	\$1,345	2.35	\$23,150	1.80	\$12,376	1.83	\$12,828
PV	1992-2010		6,471	127	1,672	\$1,541	\$1,232	2.15	\$19,781	1.78	\$12,137	1.81	\$12,552
HPWH	Pre-1978		6,491	127	1,670	\$1,708	\$1,364	1.97	\$20,151	1.50	\$9,322	1.53	\$9,866
Replacement w/ Panel Upgrade	1978-1991	\$18,708	6,482	127	1,673	\$1,684	\$1,345	1.94	\$19,578	1.49	\$9,195	1.52	\$9,647
+ PV	1992-2010		6,471	127	1,672	\$1,541	\$1,232	1.78	\$16,209	1.48	\$8,956	1.50	\$9,371

	Minterre	Measure	Electricity	Gas	GHG Savings	-	v Cost ings	Custome	er On-Bill	2019) TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978		7,104	0	584	\$1,705	\$1,346	2.14	\$21,475	1.54	\$9,174	1.40	\$6,806
PV + Electric Ready Pre-Wire	1978-1991	\$17,024	7,104	0	584	\$1,683	\$1,328	2.11	\$20,945	1.53	\$9,033	1.39	\$6,645
	1992-2010		7,104	0	584	\$1,533	\$1,210	1.92	\$17,402	1.52	\$8,851	1.38	\$6,403

Climate Zone 16:

Note: Values in red and grey rows indicate option is not cost-effective with B/C ratio less than 1. Cells with "n/a" reflect lighting and water heating efficiency measures and packages that did not look at TDV cost effectiveness or GHG impacts.

		Measure	Electricity	Gas	GHG Savings		/ Cost ings	Custom	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO₂e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$3,332	470	79	891	\$338	\$276	2.21	\$4,545	1.83	\$2,757	2.06	\$3,532
R-49 Attic Insulation	1978-1991	\$2,874	261	40	450	\$178	\$145	1.35	\$1,127	1.12	\$346	1.25	\$715
	1992-2010	\$1,852	68	16	182	\$59	\$48	0.70	-\$630	0.61	-\$729	0.71	-\$545
	Pre-1978		29	33	342	\$76	\$64	1.16	\$271	1.02	\$30	1.46	\$683
Reduced Infiltration	1978-1991	\$1,474	17	20	208	\$46	\$39	0.71	-\$487	0.64	-\$538	0.89	-\$166
initiation	1992-2010		10	13	137	\$30	\$25	0.45	-\$908	0.42	-\$858	0.58	-\$621
	Pre-1978	\$683	263	121	1,277	\$343	\$285	11.15	\$7,787	9.74	\$5,968	12.45	\$7,820
Duct Sealing	1978-1991	\$683	151	76	799	\$209	\$174	6.80	\$4,446	6.02	\$3,427	7.72	\$4,591
	1992-2010	\$423	34	16	167	\$44	\$36	2.29	\$612	2.12	\$473	2.63	\$689
	Pre-1978		505	192	2,053	\$581	\$481	3.22	\$9,953	2.83	\$7,277	3.49	\$9,918
New Ducts	1978-1991	\$3,986	367	142	1,521	\$425	\$352	2.36	\$6,095	2.10	\$4,370	2.58	\$6,294
	1992-2010		123	46	499	\$139	\$115	0.77	-\$1,020	0.72	-\$1,114	0.85	-\$593
	Pre-1978		165	-12	-86	\$42	\$32	1.12	\$106	0.69	-\$239	0	-\$792
Cool Roof	1978-1991	\$778	114	-9	-64	\$28	\$21	0.75	-\$211	0.49	-\$401	0	-\$815
	1992-2010		63	-7	-48	\$13	\$9	0.33	-\$572	0.24	-\$594	0	-\$873
R-13 Wall Insulation	Pre-1978	\$3,360	139	108	1,121	\$267	\$223	1.77	\$2,919	1.56	\$1,880	2.13	\$3,795
) A (inclusion	Pre-1978	¢0.040	416	114	1,235	\$388	\$319	0.87	-\$1,436	0.73	-\$2,618	0.89	-\$1,071
Windows	1978-1991	\$9,810	311	93	1,018	\$307	\$253	0.69	-\$3,417	0.59	-\$4,017	0.72	-\$2,710
LED lamp vs CFL	All	\$2.26	1.2	0	n/a	\$0.37	\$0.30	3.93	\$6.61	n/a	n/a	n/a	n/a
Exterior Photosensor	All	\$42.58	12.1	0	n/a	\$2.88	\$2.27	1.60	\$25.62	n/a	n/a	n/a	n/a

Table 110: CZ 16 - Single Family Efficiency Upgrade Cost-Effectiveness Results

	N. A.	Measure	Electricity	Gas	GHG Savings	-	v Cost ings	Custome	er On-Bill	2019	TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978	\$4,806	501	114	1,248	\$419	\$344	1.91	\$4,922	1.61	\$2,931	1.90	\$4,314
R49 Attic & Air Sealing Package	1978-1991	\$4,348	277	61	662	\$225	\$185	1.14	\$660	0.97	-\$151	1.13	\$566
	1992-2010	\$3,326	78	30	321	\$89	\$74	0.59	-\$1,526	0.53	-\$1,566	0.65	-\$1,154
	Pre-1978	\$4,015	691	198	2,140	\$660	\$544	3.62	\$11,813	3.11	\$8,486	3.75	\$11,059
R49 Attic & Duct Sealing Package	1978-1991	\$3,557	392	113	1,223	\$375	\$309	2.32	\$5,272	2.01	\$3,595	2.43	\$5,090
eeunig raenage	1992-2010	\$2,275	99	31	343	\$100	\$83	0.97	-\$66	0.88	-\$271	1.04	\$92
R49 Attic. Air	Pre-1978	\$5,489	715	229	2,457	\$730	\$603	2.93	\$11,923	2.54	\$8,473	3.11	\$11,566
Sealing & Duct	1978-1991	\$5,031	408	132	1,418	\$418	\$345	1.83	\$4,703	1.60	\$2,997	1.96	\$4,837
Sealing Package	1992-2010	\$3,749	108	44	475	\$129	\$107	0.76	-\$1,000	0.69	-\$1,148	0.85	-\$555
R49 Attic, Air	Pre-1978	\$8,792	933	301	3,240	\$959	\$792	2.41	\$13,894	2.09	\$9,600	2.55	\$13,641
Sealing & New	1978-1991	\$8,334	606	197	2,127	\$625	\$516	1.65	\$6,128	1.46	\$3,813	1.77	\$6,414
Ducts Package	1992-2010	\$7,312	194	74	798	\$220	\$182	0.66	-\$2,752	0.61	-\$2,825	0.74	-\$1,900
Advanced Envelope Package	Pre-1978	\$18,659	1,189	418	4,487	\$1,288	\$1,065	1.53	\$11,008	1.33	\$6,171	1.65	\$12,076
Water Heating Package	All Vintages	\$208	0	15	n/a	\$28	\$26	1.68	\$159	n/a	n/a	n/a	n/a

Table 111: CZ 16 - Single Family Efficiency Packages Cost-Effectiveness Results

		Measure	Electricity	Gas	GHG Savings	Utility Sav	r Cost ings	Custome	er On-Bill	2019	9 TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978 3,694		260	\$988	\$780	3.02	\$15,645	2.03	\$7,235	1.71	\$4,986		
Prescriptive	1978-1991	\$7,003	3,694	0	260	\$952	\$751	2.91	\$14,793	2.03	\$7,209	1.71	\$4,963
i v oyotom	1992-2010		3,694		260	\$915	\$722	2.80	\$13,917	2.03	\$7,186	1.71	\$4,940
	Pre-1978		3,500		922	\$1,024	\$808	1.23	\$4,457	1.10	\$1,872	0.90	-\$1,908
PV + Battery	1978-1991	\$18,375	3,499	0	933	\$990	\$782	1.18	\$3,653	1.11	\$1,993	0.90	-\$1,882
	1992-2010		3,498		930	\$954	\$753	1.14	\$2,783	1.11	\$2,010	0.89	-\$1,985

Table 112: CZ 16 - Single Family PV & Battery Cost-Effectiveness Results

Table 113: CZ 16 - Single Family Equipment Fuel Substitution Cost-Effectiveness Results

	Nr. ()	Measure	Electricity	Gas	GHG Savings	Utility Savi	v Cost ings	Custom	er On-Bill	2019	9 TDV	202	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO ₂ e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
Heat Pump at	Pre-1978		-10,697	878	4,463	-\$1,361	-\$979	0	-\$29,912	0	-\$28,001	0	-\$11,165
HVAC	1978-1991	\$501	-8,906	715	3,546	-\$1,154	-\$835	0	-\$25,586	0	-\$23,948	0	-\$10,272
Replacement	1992-2010		-5,719	448	2,155	-\$731	-\$532	0	-\$16,498	0	-\$14,907	0	-\$7,270
High-Effic. Heat	Pre-1978		-9,151	878	5,042	-\$879	-\$598	0	-\$22,010	0	-\$21,556	0	-\$5,639
Pump at HVAC	1978-1991	\$3,749	-7,682	715	4,007	-\$774	-\$534	0	-\$20,088	0	-\$18,854	0	-\$6,572
Replacement	1992-2010		-4,830	448	2,502	-\$453	-\$312	0	-\$13,416	0	-\$12,690	0	-\$5,342
Heat Pump at	Pre-1978		-7,016	878	4,718	-\$328	-\$164	0	-\$13,209	0	-\$20,538	0.19	-\$6,081
HVAC Replacement +	1978-1991	\$7,504	-5,221	715	3,802	-\$136	-\$32	0	-\$9,235	0	-\$16,520	0.31	-\$5,197
PV	1992-2010		-2,025	448	2,411	\$281	\$267	0.97	-\$277	0	-\$7,530	0.70	-\$2,250
HVAC HP	Pre-1978		-7,016	878	4,718	-\$328	-\$164	0	-\$16,781	0	-\$23,719	0.13	-\$9,262
Replacement w/ Panel Upgrade	1978-1991	\$10,685	-5,221	715	3,802	-\$136	-\$32	0	-\$12,807	0	-\$19,701	0.22	-\$8,378
+ PV	1992-2010		-2,025	448	2,411	\$281	\$267	0.68	-\$3,849	0	-\$10,711	0.49	-\$5,431
HPWH at Water	Pre-1978		-1,925	176	1,219	-\$276	-\$199	0	-\$8,870	0	-\$7,338	0.10	-\$2,326
Heater	1978-1991	\$2,594	-1,959	177	1,211	-\$284	-\$205	0	-\$9,055	0	-\$7,447	0.02	-\$2,531
Replacement	1992-2010		-1,973	177	1,209	-\$288	-\$209	0	-\$9,171	0	-\$7,485	0.01	-\$2,579
NEEA Tier 3	Pre-1978		-1,501	174	1,310	-\$144	-\$95	0	-\$5,939	0	-\$5,817	0.79	-\$586
HPWH at	1978-1991	\$2,775	-1,559	176	1,302	-\$157	-\$106	0	-\$6,260	0	-\$6,067	0.67	-\$903
Replacement	1992-2010		-1,572	176	1,304	-\$161	-\$109	0	-\$6,351	0	-\$6,125	0.65	-\$966
HPWH at Water	Pre-1978		1,769	176	1,479	\$825	\$670	1.89	\$9,458	1.01	\$111	1.30	\$2,882
Heater Replacement +	1978-1991	\$9,597	1,735	177	1,470	\$792	\$644	1.82	\$8,689	1.00	-\$19	1.28	\$2,657
PV	1992-2010	1	1,721	177	1,469	\$754	\$614	1.73	\$7,772	0.99	-\$77	1.27	\$2,588
HPWH	Pre-1978		1,769	176	1,479	\$825	\$670	1.41	\$5,886	0.76	-\$3,070	0.98	-\$299
Replacement w/ Panel Upgrade	1978-1991	\$12,778	1,735	177	1,470	\$792	\$644	1.36	\$5,117	0.75	-\$3,200	0.96	-\$524
+ PV	1992-2010		1,721	177	1,469	\$754	\$614	1.30	\$4,200	0.75	-\$3,258	0.95	-\$593

	Minterra	Measure	Electricity	Gas	GHG Savings	-	/ Cost ings	Custome	er On-Bill	2019	O TDV	2022	2 TDV
Measure	Vintage	Cost (\$)	Savings (kWh)	Savings (therm)	(lb CO₂e)	Year 1	Avg Annual	B/C Ratio	NPV	B/C Ratio	NPV	B/C Ratio	NPV
	Pre-1978		3,694	0	260	\$988	\$780	1.90	\$11,051	1.28	\$3,144	1.08	\$895
PV + Electric Ready Pre-Wire	1978-1991	\$11,094	3,694	0	260	\$952	\$751	1.83	\$10,199	1.28	\$3,118	1.08	\$872
	1992-2010		3,694	0	260	\$915	\$722	1.76	\$9,323	1.28	\$3,095	1.08	\$849

8.5 Appendix E – Details on Energy Performance Equivalency

Jurisdictions adopting a retrofit reach code that want flexibility in implementation can apply all or portions of the following approach.

- 1. Identify the appropriate home vintage based on one of the following two methods.
 - a. Year of construction.
 - b. Appraisal of existing conditions of home using the points menu for a pre-1978 home (Table 114) and the relevant climate zone. The sum of the eligible points is compared to the energy performance value for each vintage (Table 17). If the sum is greater than the threshold for any vintage, the requirements for that vintage may be applied in place of those based on the year of construction. Verification should be conducted by a third party such as a HERS Rater or the building department.
- 2. Identify the relevant reach code requirements per the ordinance.
- 3. Demonstrate compliance with the reach code in one of the following ways.
 - a. Install the prescriptive reach code requirements.
 - b. Install individual measures or a package of measures that result in equivalent energy performance as the prescriptive reach code requirement.
 - i. Determine the value for the reach code requirement. For individual measures refer to Table 114, Table 115, or Table 116. For packages of measures refer to Table 117. Use the values for the appropriate vintage home determined in Step 1.
 - ii. Determine the value for the proposed upgrades using Table 114, Table 115, or Table 116 for the appropriate vintage home determined in Step 1.
 - iii. If the sum of the value for the proposed upgrades is greater than or equal to the value of the reach code requirement then the proposed upgrades are an acceptable alternative.

Component	CZ1	CZ2	CZ3	CZ4	CZ5	CZ6	CZ7	CZ8	CZ9	CZ10	CZ11	CZ12	CZ13	CZ14	CZ15	CZ16
Walls	•											•		•		
R-11 to R-13	5.4	3.1	2.4	2.1	2.3	1.0	0.7	0.9	1.2	1.6	3.4	2.9	2.4	3.3	1.3	5.9
R-19	7.7	4.5	3.5	3.0	3.4	1.4	1.0	1.4	1.8	2.4	4.9	4.2	3.6	4.7	1.9	8.3
Ceiling																
R-19	1.6	1.3	0.9	1.1	0.8	0.8	0.7	0.6	0.7	0.9	1.6	1.4	1.1	1.5	0.8	2.3
R-30	2.5	2.0	1.5	1.7	1.3	1.2	1.0	1.0	1.2	1.4	2.5	2.3	1.9	2.3	1.2	3.6
R-38	2.8	2.3	1.7	1.9	1.6	1.3	1.1	1.1	1.4	1.5	2.9	2.6	2.1	2.7	1.3	4.2
>R-38	3.2	2.6	1.9	2.2	1.8	1.4	1.2	1.3	1.5	1.7	3.2	2.9	2.4	2.9	1.3	4.6
Roof									-							
Cool roof	0.0	0.0	0.0	0.0	0.0	0.3	0.3	0.1	0.1	0.1	0.0	0.1	0.1	0.0	0.3	0.0
<u>Floors</u>									-							
R-19+ insulation in raised floor	10.9	4.1	4.7	2.8	4.0	1.0	0.5	0.5	1.0	1.7	5.1	3.5	2.8	5.2	1.4	10.0
<u>Windows</u>									-							
Double non-metal	2.6	1.6	1.0	1.1	0.8	0.4	0.2	0.4	0.6	0.8	2.3	1.8	1.5	1.8	1.0	3.8
<=0.32 U-factor	4.3	1.8	1.6	1.3	1.2	0.4	0.2	0.5	0.7	0.9	3.2	2.5	2.3	1.9	1.8	6.4
Infiltration	-								-							
<=10 ACH50	1.8	0.9	0.8	0.6	0.7	0.3	0.1	0.2	0.3	0.5	1.0	0.8	0.7	1.1	0.2	1.8
<=7 ACH50	3.0	1.5	1.2	1.0	1.2	0.4	0.3	0.3	0.5	0.8	1.7	1.3	1.1	1.7	0.4	2.9
<=5 ACH50	3.7	1.9	1.6	1.3	1.6	0.6	0.3	0.4	0.6	0.9	2.1	1.7	1.4	2.1	0.5	3.6
Duct Leakage																
<=15% leakage	3.7	1.9	1.3	1.3	1.2	0.5	0.3	0.6	0.8	1.1	2.5	2.1	1.9	2.2	1.3	5.1
<=10% leakage	4.9	2.5	1.7	1.7	1.5	0.6	0.4	0.8	1.1	1.4	3.2	2.7	2.5	3.0	1.7	6.7
R-6+ & <=5% leakage (or ductless)	7.7	4.1	2.9	2.9	2.6	1.1	0.9	1.4	1.9	2.4	5.3	4.5	4.2	4.8	2.9	10.4
Heating																
80% AFUE	1.0	0.5	0.4	0.3	0.3	0.1	0.1	0.1	0.1	0.2	0.5	0.4	0.3	0.5	0.0	1.3
90% AFUE	5.6	2.6	1.9	1.5	1.7	0.5	0.3	0.4	0.7	1.0	2.6	2.3	1.7	2.4	0.2	6.9
8.2 HSPF	21.9	8.7	6.6	5.0	4.4	1.7	1.1	1.3	2.1	2.7	8.8	7.8	5.4	6.1	0.6	23.7
9 HSPF	23.0	9.3	7.3	5.5	5.6	1.8	1.3	1.4	2.2	2.8	9.2	8.3	5.7	6.8	0.6	25.9

Table 114: Energy Performance Equivalency by Measure for the Pre-1978 Vintage Home

Component	CZ1	CZ2	CZ3	CZ4	CZ5	CZ6	CZ7	CZ8	CZ9	CZ10	CZ11	CZ12	CZ13	CZ14	CZ15	CZ16
Cooling																
13 SEER	0.0	0.3	0.0	0.6	0.0	0.3	0.4	0.8	0.9	1.1	1.5	0.9	1.9	1.2	3.0	0.4
14 SEER	0.0	0.4	0.0	0.8	0.0	0.4	0.4	1.2	1.3	1.6	2.2	1.4	2.9	1.8	4.5	0.5
16+ SEER	0.0	0.5	0.1	1.0	0.0	0.5	0.6	1.5	1.6	2.0	2.8	1.7	3.5	2.2	5.6	0.6
Water Heater																
Tankless	3.1	3.0	3.0	3.0	3.0	2.9	2.9	2.9	2.9	2.9	2.9	3.0	2.9	2.9	2.7	3.1
Condensing water heater	4.1	3.9	3.9	3.8	3.9	3.7	3.7	3.6	3.6	3.6	3.7	3.8	3.7	3.7	3.3	4.0
НРШН	7.4	7.3	7.4	7.2	7.4	7.1	7.1	6.9	7.0	6.9	6.9	7.1	6.9	6.7	6.1	6.9
NEEA HPWH	8.0	7.9	7.9	7.7	8.0	7.5	7.5	7.3	7.4	7.4	7.3	7.6	7.3	7.2	6.4	7.4
PV+Battery																
NC PV	1.1	1.1	1.2	1.2	1.3	1.6	1.5	1.6	1.7	1.7	1.5	1.2	1.6	1.9	3.0	1.3
10kWh Battery	3.0	3.1	3.3	3.0	3.4	3.5	3.0	2.9	3.2	3.1	3.2	3.2	3.1	3.3	2.6	3.4

Component	CZ1	CZ2	CZ3	CZ4	CZ5	CZ6	CZ7	CZ8	CZ9	CZ10	CZ11	CZ12	CZ13	CZ14	CZ15	CZ16
Walls																
R-11 to R-13	0.8	0.4	0.3	0.3	0.3	0.1	0.1	0.1	0.2	0.2	0.4	0.4	0.3	0.4	0.2	0.8
R-19	3.0	1.8	1.4	1.2	1.3	0.6	0.4	0.6	0.7	0.9	1.9	1.7	1.5	1.9	0.8	3.2
Ceiling																
R-19	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
R-30	0.9	0.8	0.6	0.7	0.5	0.3	0.3	0.3	0.4	0.5	0.9	0.9	0.7	0.8	0.5	1.4
R-38	1.3	1.1	0.8	0.9	0.7	0.5	0.4	0.5	0.6	0.6	1.2	1.2	1.0	1.2	0.6	1.9
>R-38	1.6	1.3	1.0	1.2	0.9	0.6	0.5	0.6	0.8	0.8	1.5	1.5	1.2	1.4	0.7	2.3
<u>Roof</u>																
Cool roof	0.0	0.0	0.0	0.0	0.0	0.0	0.1	0.2	0.1	0.1	0.0	0.1	0.2	0.0	0.3	0.0
<u>Floors</u>																
R-19+ insulation in raised floor	4.0	1.5	1.8	1.1	1.5	0.3	0.2	0.2	0.4	0.6	1.8	1.3	1.0	1.9	0.6	3.7
<u>Windows</u>													-			
Double non-metal	2.2	1.4	0.9	0.9	0.7	0.3	0.2	0.3	0.5	0.6	1.6	1.4	1.2	1.4	0.7	2.8
<=0.32 U-factor	3.8	1.4	1.5	1.1	1.1	0.4	0.3	0.5	0.7	0.8	2.5	2.1	2.0	1.4	1.5	5.3
Infiltration													-			
<=10 ACH50	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
<=7 ACH50	1.1	0.6	0.5	0.4	0.5	0.2	0.1	0.1	0.2	0.3	0.6	0.5	0.4	0.6	0.2	1.1
<=5 ACH50	1.8	1.0	0.8	0.7	0.8	0.3	0.2	0.2	0.3	0.4	1.0	0.9	0.8	1.1	0.3	1.8
Duct Leakage	1							l	l							
<=15% leakage	2.0	1.0	0.6	0.6	0.6	0.2	0.1	0.3	0.4	0.5	1.2	1.1	1.1	1.1	0.9	2.9
<=10% leakage	3.0	1.4	0.9	0.9	0.8	0.3	0.2	0.5	0.6	0.8	1.9	1.6	1.6	1.7	1.3	4.2
R-6+ & <=5% leakage (or ductless)	5.5	2.9	2.0	2.1	1.8	0.7	0.5	1.0	1.4	1.7	3.8	3.3	3.3	3.4	2.4	7.6
Heating																
80% AFUE	0.8	0.4	0.3	0.2	0.2	0.1	0.0	0.0	0.1	0.1	0.4	0.3	0.2	0.3	0.0	1.0
90% AFUE	4.3	1.9	1.4	1.1	1.2	0.3	0.2	0.3	0.4	0.7	1.9	1.7	1.2	1.7	0.1	5.4
8.2 HSPF	17.3	6.5	4.7	3.5	2.7	0.9	0.6	0.8	1.3	1.8	6.5	5.8	4.0	4.2	0.3	18.8
9 HSPF	18.6	7.1	5.3	4.0	4.0	1.1	0.7	0.8	1.4	1.9	6.9	6.3	4.3	4.9	0.2	21.2

Table 115: Energy Performance Equivalency by Measure for the 1978-1991 Vintage Home

Component	CZ1	CZ2	CZ3	CZ4	CZ5	CZ6	CZ7	CZ8	CZ9	CZ10	CZ11	CZ12	CZ13	CZ14	CZ15	CZ16
Cooling																
13 SEER	0.0	0.2	0.0	0.5	0.0	0.3	0.3	0.7	0.8	0.9	1.3	0.8	1.7	1.1	2.7	0.3
14 SEER	0.0	0.3	0.0	0.6	0.0	0.3	0.3	1.0	1.1	1.3	1.9	1.2	2.4	1.6	4.0	0.4
16+ SEER	0.0	0.3	0.0	0.8	0.0	0.4	0.5	1.3	1.4	1.7	2.3	1.4	3.0	1.9	4.9	0.5
Water Heater																
Tankless	3.1	3.0	3.0	3.0	3.0	2.9	2.9	2.9	2.9	2.9	2.9	3.0	2.9	2.9	2.7	3.1
Condensing water heater	4.1	3.9	3.9	3.8	3.9	3.7	3.7	3.6	3.6	3.6	3.7	3.8	3.7	3.7	3.3	4.0
НРШН	7.4	7.4	7.4	7.3	7.4	7.1	7.1	7.0	7.0	6.9	6.9	7.2	6.9	6.7	6.2	6.9
NEEA HPWH	8.1	7.9	8.0	7.8	8.0	7.5	7.5	7.4	7.4	7.3	7.4	7.7	7.3	7.2	6.4	7.3
PV+Battery																
NC PV	1.1	1.1	1.2	1.2	1.3	1.6	1.5	1.6	1.7	1.7	1.5	1.2	1.6	1.9	3.0	1.3
10kWh Battery	3.0	3.1	3.3	3.1	3.4	3.6	3.1	3.1	3.3	3.2	3.3	3.3	3.3	3.4	2.9	3.5

Component	CZ1	CZ2	CZ3	CZ4	CZ5	CZ6	CZ7	CZ8	CZ9	CZ10	CZ11	CZ12	CZ13	CZ14	CZ15	CZ16
Walls																
R-11 to R-13	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
R-19	2.0	1.2	0.9	0.8	0.9	0.4	0.3	0.4	0.5	0.6	1.3	1.1	1.0	1.3	0.4	2.2
Ceiling																
R-19	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
R-30	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
R-38	0.4	0.3	0.2	0.2	0.2	0.1	0.1	0.1	0.2	0.2	0.3	0.3	0.2	0.3	0.1	0.5
>R-38	0.7	0.4	0.3	0.4	0.3	0.2	0.2	0.2	0.3	0.3	0.6	0.6	0.4	0.6	0.2	1.0
Roof																
Cool roof	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.1	0.1	0.0	0.0	0.0	0.1	0.0	0.1	0.0
<u>Floors</u>																
R-19+ insulation in raised floor	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
<u>Windows</u>																
Double non-metal	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
<=0.32 U-factor	3.6	1.1	1.7	0.8	1.7	0.3	0.2	0.3	0.5	0.6	1.4	1.3	1.1	1.1	0.6	2.5
Infiltration																
<=10 ACH50	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
<=7 ACH50	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
<=5 ACH50	0.7	0.4	0.3	0.3	0.3	0.1	0.1	0.1	0.1	0.2	0.4	0.3	0.3	0.4	0.1	0.7
Duct Leakage							Γ									
<=15% leakage	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
<=10% leakage	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
R-6+ & <=5% leakage (or ductless)	1.5	1.1	0.7	0.7	0.7	0.2	0.2	0.3	0.5	0.6	1.4	1.1	1.2	1.3	0.8	2.3
Heating																
80% AFUE	0.4	0.3	0.2	0.2	0.2	0.0	0.0	0.0	0.1	0.1	0.3	0.3	0.2	0.3	0.0	0.6
90% AFUE	2.3	1.5	1.1	0.8	1.0	0.2	0.1	0.2	0.3	0.5	1.4	1.3	0.9	1.3	0.1	3.2
8.2 HSPF	9.4	5.7	4.1	3.0	2.9	0.8	0.5	0.6	1.1	1.5	5.4	4.9	3.3	3.8	0.2	11.5
9 HSPF	10.7	6.5	4.9	3.6	3.9	0.9	0.6	0.7	1.3	1.8	5.9	5.5	3.7	4.5	0.2	13.5

Table 116: Energy Performance Equivalency by Measure for the 1992-2010 Vintage Home

Component	CZ1	CZ2	CZ3	CZ4	CZ5	CZ6	CZ7	CZ8	CZ9	CZ10	CZ11	CZ12	CZ13	CZ14	CZ15	CZ16
Cooling																
13 SEER	n/a	n/a	n/a	n/a	n/a	n/a	n/a									
14 SEER	0.0	0.0	0.0	0.1	0.0	0.0	0.0	0.3	0.3	0.3	0.4	0.2	0.6	0.4	1.1	0.1
16+ SEER	0.0	0.1	0.0	0.2	0.0	0.1	0.1	0.4	0.4	0.6	0.8	0.4	1.1	0.7	1.8	0.2
Water Heater																
Tankless	3.1	3.0	3.0	3.0	3.0	2.9	2.9	2.9	2.9	2.9	2.9	3.0	2.9	2.9	2.7	3.1
Condensing water heater	4.1	3.9	3.9	3.8	3.9	3.7	3.7	3.6	3.6	3.6	3.7	3.8	3.7	3.7	3.3	4.0
НРШН	7.5	7.4	7.4	7.2	7.4	7.1	7.1	7.0	7.0	6.9	6.9	7.2	6.9	6.7	6.1	6.8
NEEA HPWH	8.2	7.9	8.0	7.8	8.0	7.5	7.5	7.4	7.4	7.4	7.4	7.7	7.4	7.2	6.4	7.3
<u>PV+Battery</u>																
NC PV	1.1	1.1	1.2	1.2	1.3	1.6	1.5	1.6	1.7	1.7	1.5	1.2	1.6	1.9	3.0	1.3
5kWh Battery	2.9	3.2	3.3	3.3	3.4	3.9	3.3	3.4	3.7	3.6	3.5	3.4	3.6	3.7	3.5	3.4

Table 117: Energy Performance Equivalency for Packages for all Vintages

Component	Vintage	CZ1	CZ2	CZ3	CZ4	CZ5	CZ6	CZ7	CZ8	CZ9	CZ10	CZ11	CZ12	CZ13	CZ14	CZ15	CZ16
	Pre-1978	5.1	3.6	2.7	2.8	2.5	1.7	1.4	1.5	1.8	2.2	4.2	3.8	3.1	4.0	1.7	6.5
	1978-1991	2.7	1.9	1.4	1.5	1.4	0.7	0.6	0.7	0.9	1.0	2.2	2.0	1.7	2.1	0.8	3.5
R-49 & Air Sealing	1992-2010	1.4	0.8	0.7	0.7	0.6	0.3	0.3	0.3	0.4	0.5	1.0	0.9	0.8	1.0	0.3	1.7
	Pre-1978	8.0	4.9	3.4	3.7	3.2	1.9	1.6	2.0	2.5	3.0	6.2	5.4	4.9	5.7	3.2	11.2
	1978-1991	4.5	2.6	1.8	2.0	1.7	0.9	0.7	1.0	1.4	1.6	3.4	3.0	2.8	3.0	1.9	6.4
R-49 & Duct Sealing	1992-2010	1.2	0.8	0.6	0.6	0.6	0.3	0.2	0.3	0.5	0.5	1.1	0.9	0.9	1.0	0.6	1.8
	Pre-1978	9.7	5.8	4.2	4.2	3.9	2.2	1.8	2.1	2.8	3.4	7.1	6.2	5.5	6.7	3.5	12.8
R-49, Air & Duct	1978-1991	5.5	3.2	2.3	2.4	2.1	1.0	0.8	1.2	1.5	1.8	4.0	3.4	3.2	3.6	2.1	7.4
Sealing	1992-2010	1.9	1.2	0.9	0.9	0.8	0.4	0.3	0.4	0.6	0.7	1.5	1.3	1.2	1.4	0.6	2.5
	Pre-1978	12.8	7.5	5.4	5.6	5.0	2.7	2.1	2.8	3.7	4.6	9.5	8.1	7.6	8.7	4.7	16.9
R-49, Air Sealing &	1978-1991	8.3	4.7	3.3	3.6	3.0	1.4	1.1	1.7	2.4	2.8	6.1	5.3	5.1	5.5	3.3	11.1
New Ducts	1992-2010	3.0	2.0	1.5	1.5	1.4	0.6	0.4	0.7	0.9	1.2	2.5	2.2	2.1	2.3	1.3	4.2
Advanced Envelope	Pre-1978	17.8	10.8	7.7	7.9	6.9	3.8	2.9	3.6	4.8	6.0	13.5	11.4	10.2	12.1	5.9	23.4